

1 Identification

- **Product identifier**
 - *Product number* PL80
 - *Trade name:* **SATIN WHITE ACRYLIC URETHANE**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - 1.3.2 Importer
Name I.C. & S. DISTRIBUTING CO.
Address P.O. BOX 10845
LANCASTER. PA
USA
E-Mail: nelson@ics-company.com
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/MSDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Product number PL80
Trade name: SATIN WHITE ACRYLIC URETHANE

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word Danger**

· **Hazard-determining components of labeling:**

xylene
isobutyl acetate
toluene
ethylbenzene
methyl methacrylate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

(Contd. on page 3)

Product number PL80
Trade name: SATIN WHITE ACRYLIC URETHANE

(Contd. of page 2)

· Dangerous components:		
110-19-0	isobutyl acetate ⚠ Flam. Liq. 2, H225 ⚠ STOT SE 3, H336	20-24.99%
1330-20-7	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	10-12.49%
78-93-3	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	10-12.49%
123-86-4	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	5-9.99%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332 Aquatic Chronic 3, H412	1-2.49%
108-88-3	toluene ⚠ Flam. Liq. 2, H225 ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412	1-2.49%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	0.5-1%
80-62-6	methyl methacrylate ⚠ Flam. Liq. 2, H225 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

(Contd. on page 4)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, refer to Section 11.
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:** Alcohol resistant foam, CO, powder, water spray/mist.
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-I:		
110-19-0	isobutyl acetate	450 ppm
1330-20-7	xylene	130 ppm
78-93-3	butanone	200 ppm
123-86-4	n-butyl acetate	5 ppm
100-41-4	ethylbenzene	33 ppm
108-88-3	toluene	67 ppm

(Contd. on page 5)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 4)

100-41-4	ethylbenzene	33 ppm
9002-84-0	Polytetrafluoroethylene	12 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
9002-88-4	Polyethylene low density	16 mg/m
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
80-62-6	methyl methacrylate	17 ppm

· PAC-2:

110-19-0	isobutyl acetate	1300* ppm
1330-20-7	xylene	920* ppm
78-93-3	butanone	2700* ppm
123-86-4	n-butyl acetate	200 ppm
100-41-4	ethylbenzene	1100* ppm
108-88-3	toluene	560 ppm
100-41-4	ethylbenzene	1100* ppm
9002-84-0	Polytetrafluoroethylene	130 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
9002-88-4	Polyethylene low density	170 mg/m
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
80-62-6	methyl methacrylate	120 ppm

· PAC-3:

110-19-0	isobutyl acetate	7500** ppm
1330-20-7	xylene	2500* ppm
78-93-3	butanone	4000* ppm
123-86-4	n-butyl acetate	3000* ppm
100-41-4	ethylbenzene	1800* ppm
108-88-3	toluene	3700* ppm
100-41-4	ethylbenzene	1800* ppm
9002-84-0	Polytetrafluoroethylene	790 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
9002-88-4	Polyethylene low density	1,000 mg/m
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
80-62-6	methyl methacrylate	570 ppm

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 6)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 5)

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

- At this time, the other constituents have no known exposure limits.

110-19-0 isobutyl acetate

PEL (USA)	Long-term value: 700 mg/m , 150 ppm
REL (USA)	Long-term value: 700 mg/m , 150 ppm
TLV (USA)	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

78-93-3 butanone

PEL (USA)	Long-term value: 590 mg/m , 200 ppm
REL (USA)	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV (USA)	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm BEI

123-86-4 n-butyl acetate

PEL (USA)	Long-term value: 710 mg/m , 150 ppm
REL (USA)	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV (USA)	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

100-41-4 ethylbenzene

PEL (USA)	Long-term value: 435 mg/m , 100 ppm
REL (USA)	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV (USA)	Long-term value: 87 mg/m , 20 ppm BEI

(Contd. on page 7)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 6)

80-62-6 methyl methacrylate

PEL (USA)	Long-term value: 410 mg/m , 100 ppm
REL (USA)	Long-term value: 410 mg/m , 100 ppm
TLV (USA)	Short-term value: 410 mg/m , 100 ppm Long-term value: 205 mg/m , 50 ppm
	DSEN

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

78-93-3 butanone

BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----------	---

100-41-4 ethylbenzene

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

108-88-3 toluene

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 8)

ICS

Product number PL80
Trade name: SATIN WHITE ACRYLIC URETHANE

(Contd. of page 7)

100-41-4 ethylbenzene

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

Product number PL80
Trade name: SATIN WHITE ACRYLIC URETHANE

(Contd. of page 8)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

79 °C (174.2 °F)

· Flash point:

-4 °C (24.8 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

370 °C (698 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

1 Vol %

· Upper:

11.5 Vol %

· Vapor pressure at 20 °C (68 °F):

105 hPa (78.8 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F):

1.237 g/cm (10.323 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

40 s (ISO 4 mm)

· Oxidising properties:

N.A.

· Solvent content:

· VOC content:

53.75 %

664.9 g/l / 5.55 lb/gal

· Solids content:

46.2 %

· Other information (HAPS)

No further relevant information available.

1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	1-2.49%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	0.5-1%
80-62-6	methyl methacrylate	≥0.1-<0.5%

(Contd. on page 10)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 9)

108-31-6 maleic anhydride

<0.01%

Other information

No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

11 Toxicological information**Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****110-19-0 isobutyl acetate**

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4h.	27.571 mg/l (mouse)

78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
------	------	---------------------

(Contd. on page 11)

Product number PL80
Trade name: SATIN WHITE ACRYLIC URETHANE

(Contd. of page 10)

Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	78 mg/l (mouse)

- **Primary irritant effect:**
 - *on the skin:* Irritant to skin and mucous membranes.
 - *on the eye:* Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 - Irritant
 - Causes skin irritation.
 - Causes serious eye irritation.
 - May cause drowsiness or dizziness.
 - May cause damage to the hearing organs through prolonged or repeated exposure.
 - May be fatal if swallowed and enters airways.
 - Contains methyl methacrylate. May produce an allergic reaction.
- **Carcinogenic categories**
 - Titanium dioxide
 - IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."
 - Ethylbenzene
 - From IARC MONOGRAPHS VOLUME 77/2000
 - Human carcinogenicity data
 - Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.
 - Evaluation
 - There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)
None of the ingredients is listed.

(Contd. on page 12)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 11)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

110-19-0 isobutyl acetate

EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

1330-20-7 xylene

EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)

78-93-3 butanone

EC50	2,029 mg/l (algae) (96 h)
	308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)

123-86-4 n-butyl acetate

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

100-41-4 ethylbenzene

EC50	75 mg/l (daphnia) (48 h)
------	--------------------------

108-88-3 toluene

EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)

100-41-4 ethylbenzene

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

80-62-6 methyl methacrylate

EC50	170 mg/l (algae) (72 h)
LC50 (96h)	191 mg/l (Fish)

· Persistence and degradability

Data refers to the substance Toluene CAS No. 108-88-3

Readily biodegradable (according to OECD criteria and/or EU RAR)

· Substances Easily biodegradable

110-19-0	isobutyl acetate	.
1330-20-7	xylene	.
78-93-3	butanone	.
123-86-4	n-butyl acetate	.

(Contd. on page 13)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 12)

100-41-4	ethylbenzene	.
108-88-3	toluene	.
100-41-4	ethylbenzene	.

- **Behavior in environmental systems:**

- *Bioaccumulative potential* No further relevant information available.
- *Mobility in soil* No further relevant information available.

- **Additional ecological information:**

- *General notes:*

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- *Recommendation:*

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- *DOT* NA1263
- *IMDG, IATA* UN1263

- **UN proper shipping name**

- *DOT* Paint
- *IMDG, IATA* PAINT

- **Transport hazard class(es)**

- *DOT*



- *Class* 3 Flammable liquids
- *Label* 3
- *Class* 3 Flammable liquids
- *Label* 3

- *IMDG, IATA*



- *Class* 3 Flammable liquids

(Contd. on page 14)

Product number PL80
Trade name: SATIN WHITE ACRYLIC URETHANE

(Contd. of page 13)

· Label	3
· Packing group	II
· DOT, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

1330-20-7	xylene	10-12.49%
78-93-3	butanone	10-12.49%
100-41-4	ethylbenzene	1-2.49%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	0.5-1%
80-62-6	methyl methacrylate	≥0.1-<0.5%
108-31-6	maleic anhydride	<0.01%

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
100-41-4	ethylbenzene
80-62-6	methyl methacrylate
108-31-6	maleic anhydride

(Contd. on page 15)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 14)

· **Proposition 65**· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	25-29.99%
100-41-4	ethylbenzene	*	1-2.49%
100-41-4	ethylbenzene	*	0.5-1%

· **Chemicals known to cause reproductive toxicity for females:**

70657-70-4	2-methoxypropyl acetate		<0.01%
------------	-------------------------	--	--------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene		1-2.49%
----------	---------	--	---------

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	10-12.49%
78-93-3	butanone	I	10-12.49%
100-41-4	ethylbenzene	D	1-2.49%
108-88-3	toluene	II	1-2.49%
100-41-4	ethylbenzene	D	0.5-1%
80-62-6	methyl methacrylate	E, NL	≥0.1-<0.5%

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
80-62-6	methyl methacrylate	A4
108-31-6	maleic anhydride	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	25-29.99%
------------	---	-----------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl· **Contact:** See emergency phone· **Date of preparation / last revision** 07/19/2019 / 8· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 16)

Product number PL80**Trade name: SATIN WHITE ACRYLIC URETHANE**

(Contd. of page 15)

ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 2: Flammable liquids . Category 2
 Flam. Liq. 3: Flammable liquids . Category 3
 Acute Tox. 4: Acute toxicity . Category 4
 Skin Irrit. 2: Skin corrosion/irritation . Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A
 Skin Sens. 1: Skin sensitisation . Category 1
 Carc. 2: Carcinogenicity . Category 2
 Repr. 2: Reproductive toxicity . Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) . Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2
 Asp. Tox. 1: Aspiration hazard . Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• * **Data compared to the previous version altered.**