

Printing date 09/14/2022

Version number 4

Reviewed on 08/19/2022

1 Identification

- · Product identifier
 - · Product number WMM5A036
 - · Trade name: WB WHITE SELF-SEALER 10 SH
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

2-methyl-2H-isothiazol-3-one

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray P261

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Classification system:
 - · NFPA ratings (scale 0 4)



Health = 0Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 1Reactivity = 0



Printing date 09/14/2022 Version number 4 Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

111-76-2	2-butoxyethanol	1-2.49%
777702	Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	1 2.4370
34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	1-<5%
2682-20-4	2-methyl-2H-isothiazol-3-one ♦ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ♦ Skin Corrosion 1B, H314; Eye Damage 1, H318 ↑ Sensitization - Skin 1, H317	≥0.0015-<0.01%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CÓ)

(Contd. on page 3)



Printing date 09/14/2022

Version number 4

Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 2)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
13463-67-7	1-67-7 Titanium dioxide C.I. 77891 Pigment white 6	
7631-86-9	7631-86-9 silicon dioxide, chemically prepared	
111-76-2	2-butoxyethanol	60 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m³
· PAC-2:		·
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m³
7631-86-9	silicon dioxide, chemically prepared	740 mg/m³
111-76-2	2-butoxyethanol	120 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m³
· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m³
111-76-2	2-butoxyethanol	700 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m³



Printing date 09/14/2022

Version number 4

Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 3)

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 20 ppm

BEL A3

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm

Skin

REL Short-term value: 900 mg/m³, 150 ppm

Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Long-term value: NIC-50 ppm

(Skin)

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Printing date 09/14/2022 Version number 4 Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 4)

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
 - · Breathing equipment:

Not required.

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

nformation on basic physical and · General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
-	Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)

(Contd. on page 6)



Printing date 09/14/2022 Version number 4 Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

	(0	Contd. of page
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard	
· Explosion limits:		
Lower:	0.6 Vol %	
· Upper:	20.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.234 g/cm³ (10.298 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water	·): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	45 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	<i>4</i> 8.9 %	
· VOC content:	4.81 %	
	59.4 g/l / 0.50 lb/gal	
· Solids content:	46.2 %	
Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		<0.19
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

. I D/I C50 value	s that are relevan	t for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 66,262 mg/kg

(Contd. on page 7)



Printing date 09/14/2022

Version number 4

Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

		(Contd. of page 6)
Dermal	LD50	60,740 mg/kg (rab)
Inhalative	LC50/4 h	607 mg/l (mouse)
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
2682-20-4	2-methyl-	-2H-isothiazol-3-one
Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)
Desire	nam irritan	4 offers

- · Primary irritant effect:
 - on the skin: No irritant effect. on the eve: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

May cause an allergic skin reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or

· Carcinogenic categories

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)	
13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic t	oxicity:
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	(Contd. on page 8)



Printing date 09/14/2022 Version number 4 Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 7)

1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

· Persistence and degradability No further relevant information available.

Substances Easily biodegradable
 111-76-2 2-butoxyethanol
 34590-94-8 (2-methoxymethylethoxy)propanol

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

• Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Marine pollutant: Special precautions for user Transport in bulk according to Annex	Not applicable.
MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)



Printing date 09/14/2022

Version number 4

Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 8)

· UN "Model Regulation":

Not applicable

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Various regulations
 - · SARA

· S	ection 355 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· S	ection 313 (Specific toxic chemical listings) :	
111-76-2	2-butoxyethanol	1-2.49%
112-34-5	2-(2-butoxyethoxy)ethanol	<0.1%
1336-21-6	ammonia	<0.01%
· TSC	A (Toxic Substances Control Act):	

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
 - · Chemicals known to cause cancer:

Titanium dioxide only in bound form

13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	20-24.99%
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
~· · · · · · · · · · · · · · · · · · ·		

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
111-76-2 2-butoxyethanol	NL	1-2.49%
· TLV (Threshold Limit Value)		
13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6		A4
111-76-2 2-butoxyethanol		АЗ
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6	20)-24.99%

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 09/14/2022

Version number 4

Reviewed on 08/19/2022

Product number WMM5A036

Trade name: WB WHITE SELF-SEALER 10 SH

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 09/14/2022 / 3
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* Data compared to the previous version altered.

US