

Printing date 09/07/2022 Version number 21 Reviewed on 09/07/2022

1 Identification

· Product identifier

- · Product number TE2303
- · Trade name: CLEAR SB UV SEALER
 - · Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV) Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling:

Hexanedioic acid, polymer with(chloromethyl)oxirane, 2-ethyl-2-(hydroxymethyl)-1,3-propanediol,

4,4'-(1-methylethylidene)bis[phenol] and oxirane, 2-propenoate

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

Trimethylolpropane, ethoxylated, esters with acrylic acid mequinol

· Hazard statements

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 2)



Printing date 09/07/2022

Version number 21

Reviewed on 09/07/2022

Product number TE2303

Trade name: **CLEAR SB UV SEALER**

(Contd. of page 1)

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 1Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: Mixture: consisting of the following components.

184181-05-3	Hexanedioic acid, polymer with(chloromethyl)oxirane, 2-ethyl-2-	75-100%
	(hydroxymethyl)-1,3-propanediol,	
	4,4'-(1-methylethylidene)bis[phenol] and oxirane, 2-propenoate	
	💠 Sensitization - Skin 1, H317	
55818-57-0	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	≥2.5-<25%
	🕸 Aquatic Chronic 2, H411	
	Sensitization - Skin 1, H317	
	Aquatic Acute 2, H401	
28961-43-5	Trimethylolpropane, ethoxylated, esters with acrylic acid	1-2.49%
	Eye Irritation 2A, H319; Sensitization - Skin 1B, H317 Aquatic Chronic 3, H412	
123-86-4	n-butyl acetate	1-2.49%
	Flammable Liquids 3, H226Specific Target Organ Toxicity - Single Exposure 3, H336	
150-76-5	mequinol	≥0.5-<1%
	Acute Toxicity - Oral 4, H302; Eye Irritation 2A, H319; Sensitization - Skin 1, H317 Aquatic Chronic 3, H412	
84434-11-7	PHENYL ETHYL PHOSPHATE	≥0.1-<0.25%
	Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Sensitization - Skin 1B, H317	
142-16-5	Bis(2-ethylhexyl) maleate	≥0.025-<0.25%
	Specific Target Organ Toxicity - Repeated Exposure 2, H373 Aquatic Chronic 1, H410	

4 First-aid measures

- · Description of first aid measures
 - · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) (Contd. on page 3)



Printing date 09/07/2022 Version number 21 Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

(Contd. of page 2)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

123-86-4 n-butyl acetate

5 ppm

(Contd. on page 4)



Printing date 09/07/2022

Version number 21

Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

150-76-5	mequinol	(Contd. of page 3) 15 mg/m³
· PAC-2		
	n-butyl acetate	200 ppm
150-76-5	mequinol	49 mg/m³
· PAC-3		
123-86-4	n-butyl acetate	3000* ppm
150-76-5	mequinol	320 mg/m³

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits

7	t this time, the other constituents have no known exposure limits.
123-8	86-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm
	Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 150 ppm
	Long-term value: 50 ppm
150-7	76-5 mequinol
REL	Long-term value: 5 mg/m³
TLV	Long-term value: 5 mg/m³
	Additional information: The lists that were valid during the creation were used as basis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures: Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)



Printing date 09/07/2022 Version number 21 Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

(Contd. of page 4)

Wash hands before breaks and at the end of work.

· Breathing equipment: Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

9 r nysicai and chemicai prope				
Information on basic physical and chemical properties				
· General Information				
\cdot Appearance:				
· Form:	Fluid			
· Color:	According to product specification			
· Odor:	Characteristic			
· Odor threshold:	Not determined.			
· pH-value:	Mixture is non-polar/aprotic.			
· Change in condition				
· Melting point/Melting range:	Undetermined.			
· Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)			
· Flash point:	100 °C (212 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	370 °C (698 °F)			
· Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits:				
· Lower:	1.2 Vol %			

(Contd. on page 6)



Printing date 09/07/2022 Version number 21 Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

		(Contd. of page
· Upper:	7.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.173 g/cm³ (9.789 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water	·): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	2.46 %	
	28.9 g/l / 0.24 lb/gal	
· Solids content:	97.5 %	
· Other information (HAPS)		
79-10-7 acrylic acid		<0.19
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· Acute i	oxicity:			
· LD/	LC50 valu	es that are relevant for classification:		
184181-0	184181-05-3 Hexanedioic acid, polymer with(chloromethyl)oxirane, 2-ethyl-2 (hydroxymethyl)-1,3-propanediol, 4,4'-(1-methylethylidene)bis[phenol] and oxirane, 2-propenoate			
Oral	LD50	2,001 mg/kg (mouse)		
55818-57	55818-57-0 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, esters with acrylic acid			
Oral	LD50	2,001 mg/kg (mouse)		
Dermal	LD50	2,001 mg/kg (rabbit)		
		(Contd. on page 7)		



Printing date 09/07/2022 Version number 21

Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

		(Contd. of page 6
28961-43-	5 Trimeth	ylolpropane, ethoxylated, esters with acrylic acid
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	13,201 mg/kg (rabbit)
123-86-4	n-butyl ac	etate
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
150-76-5 I	mequinol	
Oral	LD50	1,650 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

May cause an allergic skin reaction.

· Carcinogenic categories

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

•	, , , , , , , , , , , , , , , , , , , ,		
· IA	RC (International Agency for Research on Cancer - Cl. 1 and 2)		
14808-60-7	Quartz (SiO2)	1	
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	2	
$\cdot N$	TP (National Toxicology Program)		
14808-60-7	Quartz (SiO2)	<0.19	
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the	ingredients is listed.		

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid
EC50	105 mg/l (algae) (72h)
	101 mg/l (daphnia) (48h)
LC50 (96h)	101 mg/l (Fish)
28961-43-5	Trimethylolpropane, ethoxylated, esters with acrylic acid
EC50	70.7 mg/l (daphnia) 48H
LC50 (96h)	1.95 mg/l (Fish)

(Contd. on page 8)



Printing date 09/07/2022 Version number 21 Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

	(Contd. of page				
123-86-4 n-	123-86-4 n-butyl acetate				
EC50	397 mg/l (algae) (72 h)				
	44 mg/l (daphnia) (48 h)				
LC50 (96h)	18 mg/l (Fish)				
150-76-5 m	equinol				
EC50	54.7 mg/l (algae) (72 h)				
LC50 48h	3 mg/l (daphnia)				
LC50 (96h)	28.5 mg/l (Fish)				
64742-95-6	Solvent naphtha (petroleum), light arom.				
EC50	1 mg/l (algae) (72 h)				
	1 mg/l (daphnia) (48 h)				
LC50 (96h)	1 mg/l (Fish)				

- · Persistence and degradability No further relevant information available.
 - · Substances Easily biodegradable

123-86-4 n-butyl acetate .

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
· UN proper shipping name	
· DOT, IMDG, IATA	Not applicable



Printing date 09/07/2022

Version number 21

Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

(Contd. of page 8) · Transport hazard class(es) · DOT, ADR, ADN, IMDG, IATA Not applicable · Class · Packing group · DOT, IMDG, IATA Not applicable · Environmental hazards: · Marine pollutant: No · Special precautions for user Not applicable. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": Not applicable

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Various regulations
 - · SARA

5/101	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings) :	
79-10-7 acrylic acid	<0.1%
110-82-7 cyclohexane	<0.01%
· TSCA (Toxic Substances Control Act):	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3 epoxypropane, esters with acrylic acid	- ACTIVE
Trimethylolpropane, ethoxylated, esters with acrylic acid	ACTIVE
n-butyl acetate	ACTIVE
mequinol	ACTIVE
PHENYL ETHYL PHOSPHATE	ACTIVE
Bis(2-ethylhexyl) maleate	ACTIVE
· Hazardous Air Pollutants	
79-10-7 acrylic acid	

- · Proposition 65
 - · Chemicals known to cause cancer: Quartz (SiO2) only in bound form

14808-60-7 Quartz (SiO2)	*	<0.1%
15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate	*	<0.01%

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 10)

<0.1%



Safety Data Sheet acc. to OSHA HCS

Printing date 09/07/2022

Version number 21

Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

))	Contd. of p	page 9)	
· Ch	emicals known to cause developmental toxicity:			
None of the	ingredients is listed.			
· Carcii	nogenic categories			
· EP	A (Environmental Protection Agency)			
110-82-7 cy	vclohexane	<i>I</i> <0.	01%	
· TL	V (Threshold Limit Value)			
14807-96-6	Talc (Mg3H2(SiO3)4)		A4	
14808-60-7	Quartz (SiO2)		A2	
79-10-7	acrylic acid		A4	
· NIOSH-Ca (National Institute for Occupational Safety and Health)				

· National regulations:

14808-60-7 Quartz (SiO2)

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 09/07/2022 / 20
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

LD50: Letnal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

·Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site



Printing date 09/07/2022

Version number 21

Reviewed on 09/07/2022

Product number TE2303

Trade name: CLEAR SB UV SEALER

(Contd. of page 10)

INRS Fiche Toxicologique
IARC International agency for research on cancer

* Data compared to the previous version altered.

US