


1 Identification

- **Product identifier**
 - *Product number* PN4B
 - *Trade name:* **WB EXT SEALER WHITE**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Carcinogenicity 1A H350 May cause cancer. Route of exposure: Inhalation.
 - **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*
- 

GHS08
- *Signal word* Danger
 - *Hazard-determining components of labeling:*
Quartz (SiO₂)
 - *Hazard statements*
H350 May cause cancer. Route of exposure: Inhalation.
 - *Precautionary statements*
 - P201 Obtain special instructions before use.
 - P202 Do not handle until all safety precautions have been read and understood.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P308+P313 IF exposed or concerned: Get medical advice/attention.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- *NFPA ratings (scale 0 - 4)*



- *HMIS-ratings (scale 0 - 4)*



Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 1)

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· *Description:* Mixture: consisting of the following components.

· **Dangerous components:**

34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	1-<5%
57-55-6	propane-1,2-diol	1-2.49%
14808-60-7	Quartz (SiO ₂) ☠ Carcinogenicity 1A, H350	≥0.1-<0.5%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ☠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ☠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ☠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ☠ Sensitization - Skin 1A, H317	≥0.00025-<0.0015%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ☠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ☠ Skin Corrosion 1B, H314 ☠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ☠ Sensitization - Skin 1A, H317	<0.00025%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

US

(Contd. on page 3)

Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
57-55-6	propane-1,2-diol	30 mg/m
546-93-0	Magnesite	45 mg/m
124-68-5	2-amino-2-methylpropanol	17 mg/m
14808-60-7	Quartz (SiO ₂)	0.075 mg/m

· PAC-2:

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
57-55-6	propane-1,2-diol	1,300 mg/m
546-93-0	Magnesite	260 mg/m
124-68-5	2-amino-2-methylpropanol	190 mg/m

(Contd. on page 4)

Product number PN4B
Trade name: WB EXT SEALER WHITE

		(Contd. of page 3)
14808-60-7	Quartz (SiO ₂)	33 mg/m
· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
57-55-6	propane-1,2-diol	7,900 mg/m
546-93-0	Magnesite	1,600 mg/m
124-68-5	2-amino-2-methylpropanol	570 mg/m
14808-60-7	Quartz (SiO ₂)	200 mg/m

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Keep respiratory protective device available.

· Information about protection against explosions and fires:

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m , 100 ppm
Skin

REL Short-term value: 900 mg/m , 150 ppm
Long-term value: 600 mg/m , 100 ppm
Skin

TLV Long-term value: NIC-50 ppm
(Skin)

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m

(Contd. on page 5)

Product number PN4B**Trade name: WB EXT SEALER WHITE**

(Contd. of page 4)

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m *respirable particulate matter, A2

· *Additional information:* The lists that were valid during the creation were used as basis.

- **Exposure controls**

- *Personal protective equipment:*

- *General protective and hygienic measures:*

- Keep away from foodstuffs, beverages and feed.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.

- *Breathing equipment:*

- Short term filter device:



Suitable respiratory protective device recommended.

Filter A

- *Protection of hands:*



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- *Material of gloves*

- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- *Penetration time of glove material*

- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- *Eye protection:*



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- *General Information*

- *Appearance:*

- *Form:*

Fluid

(Contd. on page 6)

US

Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 5)

· Color:	According to product specification	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic. Range: 7 - 9	
· Change in condition		
· Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	94 °C (201.2 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	270 °C (518 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
· Lower:	1.1 Vol %	
· Upper:	14 Vol %	
· Vapor pressure at 20 °C (68 °F):	0.4 hPa (0.3 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.2 g/cm (10.014 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	40.2 %	
· VOC content:	4.07 % 48.9 g/l / 0.41 lb/gal	
· Solids content:	55.3 %	
· Other information (HAPS)		
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
50-00-0	formaldehyde	<0.01%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended

(Contd. on page 7)

Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:**
 No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)

57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

· Primary irritant effect:

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

May cause cancer. Route of exposure: Inhalation.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· Carcinogenic categories

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
14808-60-7	Quartz (SiO ₂)	1

· NTP (National Toxicology Program)

14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%
------------	----------------------------	------------

· OSHA-Ca (Occupational Safety & Health Administration)

50-00-0	formaldehyde	<0.01%
---------	--------------	--------

US

(Contd. on page 8)

Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 7)

12 Ecological information

· Toxicity

· Aquatic toxicity:

34590-94-8 (2-methoxymethylethoxy)propanol

EC50	970 mg/l (algae) (72 h) 1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)

57-55-6 propane-1,2-diol

EC50	19,000 mg/l (algae) (48 h) 18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50	0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50	0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable

34590-94-8	(2-methoxymethylethoxy)propanol	.
57-55-6	propane-1,2-diol	.

· Behavior in environmental systems:

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 8)

· *Recommended cleansing agent: Water, if necessary with cleansing agents.*

14 Transport information

- | | |
|--|--|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | Not applicable |
| · Note | Check viscosity and flash point at section 9 |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | Not applicable |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Not applicable |
| · Packing group | |
| · DOT, IMDG, IATA | Not applicable |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Not applicable |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- **Various regulations**
 · SARA

· **Section 355 (extremely hazardous substances):**

50-00-0	formaldehyde	<0.01%
---------	--------------	--------

· **Section 313 (Specific toxic chemical listings) :**

143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
111-76-2	2-butoxyethanol	<0.01%
71-36-3	butan-1-ol	<0.01%
50-00-0	formaldehyde	<0.01%

· **TSCA (Toxic Substances Control Act):**

(2-methoxymethylethoxy)propanol	ACTIVE
propane-1,2-diol	ACTIVE
Quartz (SiO ₂)	ACTIVE
a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	ACTIVE

· **Hazardous Air Pollutants**

50-00-0	formaldehyde
---------	--------------

(Contd. on page 10)

Product number PN4B
Trade name: WB EXT SEALER WHITE

(Contd. of page 9)

· **Proposition 65**

- **Chemicals known to cause cancer:**
 Titanium dioxide only in bound form
 Quartz (SiO₂) only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	5-9.99%
14808-60-7	Quartz (SiO ₂)	*	≥0.1-<0.5%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	<0.01%
67-64-1	acetone	I	<0.01%
71-36-3	butan-1-ol	D	<0.01%
50-00-0	formaldehyde	B1	<0.01%

· **TLV (Threshold Limit Value)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
14808-60-7	Quartz (SiO ₂)	A2
111-76-2	2-butoxyethanol	A3
67-64-1	acetone	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	5-9.99%
14808-60-7	Quartz (SiO ₂)	≥0.1-<0.5%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
 · **Contact:** See emergency phone
 · **Date of preparation / last revision** 08/15/2022 / 63

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Product number PN4B**Trade name: WB EXT SEALER WHITE**

(Contd. of page 10)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 3: Acute toxicity . Category 3

Acute Toxicity - Dermal 2: Acute toxicity . Category 2

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Eye Damage 1: Serious eye damage/eye irritation . Category 1

Sensitization - Skin 1A: Skin sensitisation . Category 1A

Carcinogenicity 1A: Carcinogenicity . Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- * Data compared to the previous version altered.