ILVA TECHNICAL DATA SHEET

PRODUCT CODE: TO800 DESCRIPTION: NEUTRAL SATIN POLYURETHANE BASE USES: Polyurethane neutral tint base used to made deep tone finish colors. See Page 72 for PZ3 colorants and acceptable tint loads. **PRODUCT PREPARATION:** Parts by weight Parts by volume (ounces) TO800 Neutral Satin Polyurethane Base 100 128 TX24* Hardener 50 64 30 TZ13 30 Thinner *TX50 for slightly faster cure and hardness. **APPLICATION SYSTEM:** Air Assisted, Conventional, or Electrostatic Spray QUANTITY: 130-160 per coat (gr. sq. mt.) (5.2-6.4 wet mils) COATS: One **GENERAL PROPERTIES:** Specific Gravity, gr/cc 1.00 +/-0.030 Viscosity* 70 +/-5 sec Solids by Weight, %, as supplied 46.4 +/-2 Solids by Weight %, catalyzed 39 +/-2 Pot Life, hours at 20°C/68°F 3 hours *EN ISO 2431 Iso Cup 6 @20°C/68°F DRYING TIME: Dust free: 10 mins Dry to touch: 30 mins To handle: 12 Hours AVAILABLE SHEENS: TO800 20 Sheen **TYPICAL SYSTEMS:** Substrate: Various woods Sealer: Tomted polyrethane sealers or primers 1-2 coats TO800 Neutral Satin Polyurethane Base tinted to color Finish: SHELF LIFE: 18 Months STORAGE: Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture and foreign material. DATE OF ISSUANCE: 07-20, 12-20

IC & S, P.O. BOX 10845, LANCASTER, PA 17605 (800) 220-4035

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL. INCLUDING FOR EXAMPLE. THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARANTY, EX-PRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.