

Printing date 08/27/2014

Reviewed on 08/27/2014

1 Identification

- · Product identifier
 - · Product number PD1/001
 - · Trade name: LEMON YELLOW ANTIQUING STAIN
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

toluene

Distillates (petroleum), hydrotreated light naphthenic

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H350 May cause cancer.

(Contd. on page 2)



Printing date 08/27/2014

Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

(Contd. of page 1)

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 3 Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	is components:	
64-17-5	ethanol ⑤ Flam. Lig. 2, H225	50-74.9%
108-88-3	¥	15-19.9%
67-64-1	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	5-9.99%
78-93-3	butanone ♦ Flam. Liq. 2, H225 ♦ Eye Irrit. 2, H319; STOT SE 3, H336	1-2.49%
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic Carc. 1B, H350	1-2.49%
8042-47-5	White mineral oil	1-2.49%

4 First-aid measures

- · Description of first aid measures
 - · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



Printing date 08/27/2014

Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

(Contd. of page 2)

· After skin contact:

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Most important symptoms and effects, both acute and delayed For symptoms and effects caused by substances, refer to Section 11.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
 - For safety reasons unsuitable extinguishing agents:

 Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



Printing date 08/27/2014 Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

(Contd. of page 3)

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm REL Long-term value: 1900 mg/m³, 1000 ppm TLV Short-term value: 1880 mg/m³, 1000 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm

BEI

(Contd. on page 5)



Printing date 08/27/2014

Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

(Contd. of page 4)

· Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Printing date 08/27/2014 Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

(Contd. of page 5)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical prope	erties
Information on basic physical and	chemical properties
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	55 °C (131 °F)
· Flash point:	-17 °C (1 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explos air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	1.2 Vol %
· Upper:	15.0 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)
· Density at 20 °C (68 °F):	0.845 g/cm³ (7.052 lbs/gal)
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)

(Contd. on page 7)



Printing date 08/27/2014

Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

		(Contd. of page 6
· Solvent content: · VOC content:	79.9 % 675.3 g/l / 5.64 lb/gl	
· Solids content:	12.1 %	
· Other information (HA	PS)	
108-88-3 toluene	·	15-19.9%
1330-20-7 xylene		0.1-<0.5%
100-41-4 ethylbenzene	9	<0.1%

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions
- Reacts with strong acids and oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

$\cdot LD/$	LC50 value	rs that are relevant for classification:
64-17-5 et	hanol	
Oral	LD50	7060 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	20000 mg/kg (Con)
Inhalative	LC50/4 h	20000 mg/l (rat/szczur/mouse/souris/Maus/ratón)
108-88-3 1	oluene	
Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	5320 mg/l (mouse) (4 h)
67-64-1 ad	cetone	
Oral	LD50	5800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	20000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	76 mg/l (rat/szczur/mouse/souris/Maus/ratón)
78-93-3 b	utanone	
Oral	LD50	3300 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
		(Contd. on pag



Printing date 08/27/2014 Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

(Contd. of page 7

			(Conta. or page 7)
8042-47-5 White mineral oil			
Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Inhalative	LC50/4 h	4.5 mg/l (rat/szczur/mouse/souris/Maus/ratón)	

- · Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Causes skin irritation.

May cause cancer.

Suspected of damaging the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Only professional use

· Carcinogenic categories

· Carcinogenic calegories		
· IARC (International Agency for Researc	ch on Cancer)	
108-88-3 toluene	3	
1330-20-7 xylene	3	
100-41-4 ethylbenzene	2B	
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Heal	th Administration)	
None of the ingredients is listed.		

12 Ecological information

· Toxicity

· Aquatic t	· Aquatic toxicity:		
108-88-3 to	luene		
EC50	134 mg/l (algae)		
	3.78 mg/l (invertebrates)		
67-64-1 ace	67-64-1 acetone		
EC50	8800 mg/l (daphnia)		
LC50 (96h)	5540 mg/l (Fish)		
8042-47-5 V	8042-47-5 White mineral oil		
LC50 48h	100 mg/l (daphnia)		

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
 - · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.



Printing date 08/27/2014 Reviewed on 08/27/2014

Product number PD1/001

Trade name: **LEMON YELLOW ANTIQUING STAIN**

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number · DOT	NA1263
· IMDG, IATA	UN1263
UN proper shipping name	
· DOT	Paint PAINT
· IMDG, IATA	PAINI
Transport hazard class(es)	
· DOT	
FLAMMABLE LOUD	
3	
· Class	3 Flammable liquids
· Label · Class	3 3 Elemmoble liquido
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
3	
· Class	3 Flammable liquids
· Label	3
Packing group	
· DOT, IMDG, IATA	II .
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33 5 5 5
· EMS Number:	F-E, <u>S-E</u>

(Contd. on page 10)



Printing date 08/27/2014

Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

	(Contd. of page 9)
· Transport/Additional information:	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1263, Paint, special provision 640D, 3, II

4 = -				4.0
15 KA	aulat	orv II	nforma	ntion
10110	guiut	OI y II	11011110	

· Safety, health and environmental regulations/legislation specific for the substance or

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings): 108-88-3 toluene

78-93-3 butanone 1330-20-7 xylene

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

70657-70-4 2-methoxypropyl acetate

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

108-88-3 toluene

· Care	inogenic categories	
· E	SPA (Environmental Protection Agency)	
108-88-3	toluene	- II
67-64-1	acetone	1
	butanone	1
1330-20-7	xylene	1
	LV (Threshold Limit Value established by ACGIH)	
64-17-5	ethanol	АЗ

(Contd. on page 11)



Printing date 08/27/2014

Reviewed on 08/27/2014

Product number PD1/001

Trade name: LEMON YELLOW ANTIQUING STAIN

		(Con	td. of page 10)
	108-88-3	toluene	A4
	67-64-1	acetone	A4
	1330-20-7		A4
	100-41-4	ethylbenzene	A3
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
None of the ingredients is listed.			

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 08/27/2014 / 6
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Toy 3: Acute toxicity, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Carc. 1B: Carcinogenicity, Hazard Category 1B

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer