

Printing date 08/08/2022

Version number 53

Reviewed on 08/08/2022

1 Identification

- · Product identifier
 - · Product number HMM5034
 - Trade name: <u>CLEAR WB SELF SEALER 20SH</u> • Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

 Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 1.3.2 Importer

Name I.C.& S. DISTRIBUTING CO. Address P.O.BOX 10845 LANCASTER. PA USA E-Mail: nelson@ics-company.com

- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585. 001 813-248-0585

2 Hazard(s) identification

• Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).

· Label elements

- · GHS label elements Not applicable
 - · Hazard pictograms Not applicable
 - · Signal word Not applicable
 - · Hazard statements Not applicable
- · Classification system:

· NFPA ratings (scale 0 - 4)




· HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.





Reviewed on 08/08/2022

Printing date 08/08/2022

Version number 53

Product number HMM5034 Trade name: CLEAR WB SELF SEALER 20SH

	(Con	td. of page 1)
34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%
	Flammable Liquids 4, H227	
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
	Optimization 2A, H319	

4 First-aid measures

· Description of first aid measures

- · General information:
- No special measures required.
- personal protective equipment for first aid responders is recommended. (please see section 8) • After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

• Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx) Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Reference to other sections
 No dangerous substances are released.
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

(Contd. on page 3)

US



Version number 53

Reviewed on 08/08/2022

Printing date 08/08/2022

Product number HMM5034 Trade name: CLEAR WB SELF SEALER 20SH

		(Contd. of page
	13 for disposal information.	
	Action Criteria for Chemicals	
• PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppn
7631-86-9	silicon dioxide, chemically prepared	18 mg/n
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/n
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppi
7631-86-9	silicon dioxide, chemically prepared	740 mg/n
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/n
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppr
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/n
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:
 - Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
 - In cases where there is no reported expiration date , it means that the product must be used within 8 months.
 - Take on temperature greater than 5 ° C
 - · Information about storage in one common storage facility: Not required.
 - \cdot Further information about storage conditions: None.
- Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm Skin

(Contd. on page 4)

US



Reviewed on 08/08/2022

Printing date 08/08/2022

Product number HMM5034

Version number 53

REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3
3459	0-94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)
112-	34-5 2-(2-butoxyethoxy)ethanol
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
	· Ingredients with biological limit values:
111-	76-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
	• Additional information: The lists that were valid during the creation were used as basis.
	 osure controls ersonal protective equipment: General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Breathing equipment: Not required. Protection of hands: Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion
	and the degradation The glove material has to be impermeable and resistant to the product .

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

\cdot Information on basic physical and chemical properties

· General Information

• Appearance: • Form:

· Form: · Color:

· Odor:

Fluid According to product specification Characteristic

(Contd. on page 5)

⁻ US



Printing date 08/08/2022

Version number 53

Reviewed on 08/08/2022

Product number HMM5034 Trade name: CLEAR WB SELF SEALER 20SH

	· · · ·	ntd. of page
· Odor threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic.	
	Range: 7 - 9	
· Change in condition		
 Melting point/Melting range: 	Undetermined.	
• Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	100 °C (212 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>370 °C (>698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
· Lower:	0.6 Vol %	
· Upper:	20.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)	
• Density (+/- 0,03) at 20 °C (68 °F):	1.026 g/cm³ (8.562 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• Kinematic at 20 •C (68 •F):	60 s (ISO 6 mm)	
• Oxidising properties:	N.A.	
· Solvent content:		
· Water:	61.4 %	
· VOC content:	6.54 %	
	67.1 g/l / 0.56 lb/gal	
· Solids content:	32.1 %	
Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		<0.5%
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

• **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:

- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- \cdot Incompatible materials: Acids, alkalis and oxidizing agents

(Contd. on page 6)

US



Version number 53

Reviewed on 08/08/2022

Printing date 08/08/2022

Product number HMM5034 Trade name: CLEAR WB SELF SEALER 20SH

(Contd. of page 5) • Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE	(Acute	Toxicity	Estimate)
-----	--------	----------	-----------

Oral	LD50	49,444 mg/kg
Dermal	LD50	45,323 mg/kg (rab)
Inhalative	LC50/4 h	453 mg/l (mouse)

111-76-2	2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
	a (a) /	

34590-94	-8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5.135 ma/ka (mouse)

Ulai	LDSU	S, ISS ING/Kg (Induse)
Dermal	LD50	19,020 mg/kg (rabbit)
112-34-5 2	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)

Dermal LD50 2,764 mg/kg (rabbit)

• Primary irritant effect: • on the skin: No irritant effect.

• on the eve: No irritating effect.

Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us. Safety data sheet available on request.

· Carcinogenic categories

• IARC (International Agency for Research on Cancer - Cl. 1 and 2) None of the ingredients is listed.

ione of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

111-76-2 2-butoxyethanol

EC50 101 mg/l (daphnia) (24 h)

(Contd. on page 7)

US



Version number 53

Reviewed on 08/08/2022

Printing date 08/08/2022

Product number HMM5034 Trade name: CLEAR WB SELF SEALER 20SH

			(Contd. of page 6)
LC50 (96h)	101 mg/l (Fish)		
34590-94-8	(2-methoxymethylethoxy)propan	ol	
EC50	970 mg/l (algae) (72 h)		
	1,919 mg/l (daphnia) (48 h)		
LC50 (96h)	1,001 mg/l (Fish)		
112-34-5 2-	(2-butoxyethoxy)ethanol		
EC50	1,001 mg/l (daphnia) (48 h)		
LC50 (96h)	1,300 mg/l (Leuciscus idus melano	tus)	
· Persistence	e and degradability No further rele	vant information available.	
· Substanc	es Easily biodegradable		
111-76-2	2-butoxyethanol		
34590-94-8	(2-methoxymethylethoxy)propanol		

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- · Recommendation:
- Smaller quantities can be disposed of with household waste.
- Hand over to hazardous waste disposers.
- Dispose of contents and container in accordance with local state and federal regulations.
- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable



Printing date 08/08/2022

Version number 53

Product number HMM5034 Trade name: **CLEAR WB SELF SEALER 20SH**

		(Contd. of page 7)
• Environmental hazards: • Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		
· UN "Model Regulation":	Not applicable	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Various regulations · SARA · Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings) : 111-76-2 2-butoxyethanol 1-2.49% 112-34-5 2-(2-butoxyethoxy)ethanol <0.5% 1336-21-6 ammonia <0.01% · TSCA (Toxic Substances Control Act): All components have the value ACTIVE. · Hazardous Air Pollutants None of the ingredients is listed. · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed.

Carcinogonic categories

· Carcinogenic categories			
· EPA (Environmental Protection Agency)			
111-76-2 2-butoxyethanol	NL	1-2.4	19%
· TLV (Threshold Limit Value)			
111-76-2 2-butoxyethanol			A3
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
None of the ingredients is listed.			

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

บร



Version number 53

Reviewed on 08/08/2022

Product number HMM5034 Trade name: CLEAR WB SELF SEALER 20SH

(Contd. of page 8)

16 Other information

Printing date 08/08/2022

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 08/08/2022 / 52 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Irrititation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer •* Data compared to the previous version altered.

US-