

ILVA TECHNICAL DATA SHEET

PRODUCT CODE: WES5A07

DESCRIPTION: DRY WATER GLAZE

USES: Antiquing and Decape effect on mobile in style, doors and frames for painting

PRODUCT PREPARATION: WES5A07 Dry Glaze 100 parts by weight 128 parts by volume
May be tinted to color using ILVA PZ5xx series water-base pigmented pastes.
May be diluted with water if needed.

APPLICATION SYSTEM: By spray and wipe. Allow to air dry 15-45 minutes. Moving ambient air is best for drying conditions.
After drying, remove the antiquing glaze with scotch brite or cloth to desired effect.

GENERAL PROPERTIES: Specific gravity: 1.02 +/-0.02 gr/m;
Solids content: 8.45% +/- 1% by weight
Viscosity (at 20°C): 50+/-3 (iso 6)

TYPICAL SYSTEM: PT410 1 coat-dry 2-3 hours and sand
PW710/10 with 5% TXW08/TXW13 1 coat-dry 2- 3 hours and then very lightly sand with scotch brite
WES5A07 tinted with PZ5xxseries apply by cloth-allow to dry 45 minutes
remove with scotch brite or cloth
TW34/series final clear coat

SHELF LIFE: 12 Months

STORAGE: Store in a tightly closed container at room temperatures (18 -25°C/64 -75°F) and protect from moisture and foreign material. Do not store at temperatures below 7°C (45°F)

DATE OF ISSUANCE: 4-13, 11-21

**IC & S, P.O. BOX 10845, LANCASTER, PA 17605
(800) 220-4035**

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL, INCLUDING FOR EXAMPLE, THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.