ILVA TECHNICAL DATA SHEET

PRODUCT SERIES: ILVANOL

PRODUCT CODE: PU2419

DESCRIPTION: WHITE HI HIDE 2K POLY PRIMER

USES: Flat panels and mouldings suitable even for polyurethane foam.

PRODUCT PREPARATION: PU2419 Parts by weight 100 128

PU2419 100 128 TX19 40 64 TZ33 Thinner 10 - 20 10 - 30

APPLICATION SYSTEM: Spray, curtain coater

QUANTITY(grsq mt): 120 - 140 per coat (4.8 - 5.6 wet mils)

COATS: One to four

GENERAL PROPERTIES: Specific Gravity, gr/cc 1.395+/-0.05

Viscosity* 36+/-2 sec.

Appl.Viscosity** 15+/-2 sec.

Solids by Weight, %, as supplied 70+/-2

Solids by Weight, %, ready to use 58+/-2

Pot Life, hours at 20°C/68°F 5 hours

* DIN 53211 Nr.6 at 20°C/68°F ** DIN 53211 Nr.4 at 20°C/68°F

DRYING TIME: 1- 6 hours between coats (at 20°C/68°F) 24 hours before sanding

TYPICAL SYSTEMS: SYSTEM NR 1

Substrate: various woods

Sealer: PU2419 - three or four coats - 1 day drying-sanding-120 gr/sqmt/coat

Finish: PL - white pgimented matt finish

PM - white pigmented glossy finish

SYSTEM NR 2

Substrate: MDF

Sealer: PU2419-three or four coats- 1 day drying-sanding-120 gr/sqmt per coat

Finish: PL - white pigmented glossy ginish

SHELF LIFE: One year

STORAGE: Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture

and foreign material.

DATE OF ISSUANCE: 06-16, Revised 3-21

IC & S, P.O. BOX 10845, LANCASTER, PA 17605 (800) 220-4035