

## 1 Identification

- **Product identifier**
  - *Product number* PD1/009
  - *Trade name:* **SB PAT ANTIQUING BLACK**
    - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
  - *Manufacturer/Supplier:*  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
  - *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3H336	May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the central nervous system, the lung and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.

### · Label elements

- *GHS label elements*  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger
- *Hazard-determining components of labeling:*  
toluene  
acetone  
Distillates (petroleum), hydrotreated light paraffinic  
xylene
- *Hazard statements*  
H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361 Suspected of damaging fertility or the unborn child.

(Contd. on page 2)

**Product number PD1/009****Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system, the lung and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3









Reactivity = 0

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

· Description: Mixture: consisting of the following components.

**Dangerous components:**

64-17-5	ethanol  Flammable Liquids 2, H225  Eye Irritation 2A, H319	50-74.99%
108-88-3	toluene  Flammable Liquids 2, H225  Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304  Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	12.5-15%
1333-86-4	Carbon black  Carcinogenicity 2, H351	5-9.99%
67-64-1	acetone  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%

(Contd. on page 3)

**Product number PD1/009****Trade name: SB PAT ANTIQUING BLACK**

		(Contd. of page 2)
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic ⚠️ Aspiration Hazard 1, H304	0.5-1%
67-63-0	propan-2-ol ⚠️ Flammable Liquids 2, H225 ⚠️ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	0.5-1%
78-93-3	butanone ⚠️ Flammable Liquids 2, H225 ⚠️ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	0.5-1%
108-65-6	2-methoxy-1-methylethyl acetate ⚠️ Flammable Liquids 3, H226 ⚠️ Specific Target Organ Toxicity - Single Exposure 3, H336	<0.5%
1330-20-7	xylene ⚠️ Flammable Liquids 3, H226 ⚠️ Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠️ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	<0.5%
123-86-4	n-butyl acetate ⚠️ Flammable Liquids 3, H226 ⚠️ Specific Target Organ Toxicity - Single Exposure 3, H336	<0.5%

#### 4 First-aid measures

##### · Description of first aid measures

###### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

###### · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

###### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

###### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

###### · After swallowing: Do not induce vomiting; immediately call for medical help.

###### · Information for doctor:

###### · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

###### · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

US

(Contd. on page 4)

**Product number PD1/009**
**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 3)

## 5 Fire-fighting measures

### · Extinguishing media

#### · Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

#### · For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

### · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

 Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

#### · Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

### · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### · Protective Action Criteria for Chemicals

· PAC-I:		
64-17-5	ethanol	1,800 ppm
108-88-3	toluene	67 ppm
1333-86-4	Carbon black	9 mg/m
67-64-1	acetone	200 ppm
67-63-0	propan-2-ol	400 ppm
78-93-3	butanone	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm

(Contd. on page 5)

**Product number PD1/009****Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 4)

· PAC-2:		
64-17-5	ethanol	3300* ppm
108-88-3	toluene	560 ppm
1333-86-4	Carbon black	99 mg/m
67-64-1	acetone	3200* ppm
67-63-0	propan-2-ol	2000* ppm
78-93-3	butanone	2700* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm

· PAC-3:		
64-17-5	ethanol	15000* ppm
108-88-3	toluene	3700* ppm
1333-86-4	Carbon black	590 mg/m
67-64-1	acetone	5700* ppm
67-63-0	propan-2-ol	12000** ppm
78-93-3	butanone	4000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm

## 7 Handling and storage

### · Handling:

#### · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

### · Conditions for safe storage, including any incompatibilities

#### · Storage:

##### · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

##### · Information about storage in one common storage facility: Not required.

##### · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 6)

**Product number PD1/009**
**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 5)

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
  - **Components with limit values that require monitoring at the workplace:**  
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
 At this time, the other constituents have no known exposure limits.

### 64-17-5 ethanol

PEL	Long-term value: 1900 mg/m , 1000 ppm
REL	Long-term value: 1900 mg/m , 1000 ppm
TLV	Short-term value: 1000 ppm A3

### 108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m , 1000 ppm
REL	Long-term value: 590 mg/m , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

### 67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m , 400 ppm
REL	Short-term value: 1225 mg/m , 500 ppm Long-term value: 980 mg/m , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

### 78-93-3 butanone

PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

(Contd. on page 7)



**Product number PD1/009**  
**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 6)

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

**· Ingredients with biological limit values:****108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**67-64-1 acetone**

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**67-63-0 propan-2-ol**

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

**78-93-3 butanone**

BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
-----	---

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 8)

**Product number PD1/009**

**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 7)

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

**· Breathing equipment:**

- Short term filter device:
- Filter AX



Suitable respiratory protective device recommended.

**· Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

**· Information on basic physical and chemical properties**

**· General Information**

**· Appearance:**

- Form:** Fluid
- Color:** According to product specification
- Odor:** Characteristic
- Odor threshold:** Not determined.

**· pH-value:** Mixture is non-polar/aprotic.

**· Change in condition**

- Melting point/Melting range:** Undetermined.

(Contd. on page 9)



**Product number PD1/009**  
**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 8)

· <b>Boiling point/Boiling range:</b>	56 °C (132.8 °F)	
· <b>Flash point:</b>	-17 °C (1.4 °F)	
· <b>Flammability (solid, gaseous):</b>	Not applicable.	
· <b>Ignition temperature:</b>	425 °C (797 °F)	
· <b>Decomposition temperature:</b>	Not determined.	
· <b>Auto igniting:</b>	Product is not selfigniting.	
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· <b>Explosion limits:</b>		
· <b>Lower:</b>	1.2 Vol %	
· <b>Upper:</b>	50 Vol %	
· <b>Vapor pressure at 20 °C (68 °F):</b>	233 hPa (174.8 mm Hg)	
· <b>Density (+/- 0,03) at 20 °C (68 °F):</b>	0.86 g/cm (7.177 lbs/gal)	
· <b>Relative density</b>	Not determined.	
· <b>Vapor density</b>	Not determined.	
· <b>Evaporation rate</b>	Not determined.	
· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>	Not determined.	
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.	
· <b>Viscosity:</b>		
· <b>Dynamic:</b>	Not determined.	
· <b>Kinematic at 20 °C (68 °F):</b>	29 s (ISO 3 mm)	
· <b>Oxidising properties:</b>	N.A.	
· <b>Solvent content:</b>		
· <b>Water:</b>	0.1 %	
· <b>VOC content:</b>	80.83 % 695.1 g/l / 5.80 lb/gal	
· <b>Solids content:</b>	10.1 %	
· <b>Other information (HAPS)</b>		
108-88-3	toluene	12.5-15%
1330-20-7	xylene	<0.5%
100-41-4	ethylbenzene	<0.1%
· <b>Other information</b>	No further relevant information available.	

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**  
in case of possible formation of combustion:

(Contd. on page 10)

Product number PD1/009

Trade name: SB PAT ANTIQUING BLACK

Carbon monoxide and carbon dioxide

(Contd. of page 9)

## 11 Toxicological information

### · Information on toxicological effects

#### · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

#### 64-17-5 ethanol

Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	124.7 mg/l (mouse)

#### 108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

#### 1333-86-4 Carbon black

Oral	LD50	5,001 mg/kg (mouse)
------	------	---------------------

#### 67-64-1 acetone

Oral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (mouse)

#### 67-63-0 propan-2-ol

Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)

#### 78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)

#### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

#### 1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)

#### 123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

#### · Primary irritant effect:

· on the skin: Irritant to skin and mucous membranes.

(Contd. on page 11)

US

**Product number PD1/009****Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 10)

- *on the eye:* Irritating effect.
- *Sensitization:* No sensitizing effects known.
- *Additional toxicological information:*  
*Irritant*  
*Causes skin irritation.*  
*Causes serious eye irritation.*  
*Suspected of damaging fertility or the unborn child.*  
*May cause drowsiness or dizziness.*  
*May cause damage to the central nervous system, the lung and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.*  
*May be fatal if swallowed and enters airways.*  
*Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.*

- *Carcinogenic categories*

- *Carbon Black*

- *IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to carbon black but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as paint."*

- *Ethylbenzene*

- *From IARC MONOGRAPHS VOLUME 77/2000*

- *Human carcinogenicity data*

- *Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.*

- *Evaluation*

- *There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.*

- *IARC (International Agency for Research on Cancer - Cl. 1 and 2)*

64-17-5	ethanol	1 in alcoholic beverages
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B

- *NTP (National Toxicology Program)*

- *None of the ingredients is listed.*

- *OSHA-Ca (Occupational Safety & Health Administration)*

- *None of the ingredients is listed.*

## 12 Ecological information

- *Toxicity*

- *Aquatic toxicity:*

- **64-17-5 ethanol**

EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)

- **108-88-3 toluene**

EC50	134 mg/l (algae) (96 h)
------	-------------------------

(Contd. on page 12)

**Product number PD1/009****Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 11)

LC50 (96h)	3.78 mg/l (daphnia) (48 h) 5.5 mg/l (Fish)
<b>1333-86-4 Carbon black</b>	
EC50	10,001 mg/l (algae) (72h) 5,601 mg/l (daphnia) (24h)
LC50 (96h)	1,000 mg/l (Fish)
<b>67-64-1 acetone</b>	
EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)
<b>67-63-0 propan-2-ol</b>	
EC50	1,001 mg/l (algae) (72 h) 10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)
<b>78-93-3 butanone</b>	
EC50	2,029 mg/l (algae) (96 h) 308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
EC50	1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)
<b>1330-20-7 xylene</b>	
EC50	2.2 mg/l (algae)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
<b>123-86-4 n-butyl acetate</b>	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

64-17-5	ethanol	.
108-88-3	toluene	.
67-64-1	acetone	.
67-63-0	propan-2-ol	.
78-93-3	butanone	.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 13)

US

**Product number PD1/009**  
**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 12)

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport information

· **UN-Number**

· DOT, IMDG, IATA

UN1263

· Note

Check viscosity and flash point at section 9

· **UN proper shipping name**

· DOT

Paint

· IMDG, IATA

PAINT

· **Transport hazard class(es)**

· DOT



· Class

3 Flammable liquids

· Label

3

· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· **Packing group**

· DOT, IMDG, IATA

II

· **Environmental hazards:**

· Marine pollutant:

No

· **Special precautions for user**

Warning: Flammable liquids

· Hazard identification number (Kemler code):

33

· EMS Number:

F-E, S-E

(Contd. on page 14)

**Product number PD1/009**  
**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 13)

· <i>Stowage Category</i>	B
· <i>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</i>	Not applicable.
· <i>Transport/Additional information:</i>	
· <i>IMDG</i>	
· <i>Limited quantities (LQ)</i>	5L
· <i>Excepted quantities (EQ)</i>	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· <i>UN "Model Regulation":</i>	UN 1263 PAINT, 3, II

## 15 Regulatory information

### · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- *Various regulations*
- *SARA*

· <i>Section 355 (extremely hazardous substances):</i>		
None of the ingredients is listed.		
· <i>Section 313 (Specific toxic chemical listings) :</i>		
108-88-3	toluene	12.5-15%
67-63-0	propan-2-ol	0.5-1%
1330-20-7	xylene	<0.5%
100-41-4	ethylbenzene	<0.1%
· <i>TSCA (Toxic Substances Control Act):</i>		
All components have the value ACTIVE.		
· <i>Hazardous Air Pollutants</i>		
108-88-3	toluene	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· <i>Proposition 65</i>		
· <i>Chemicals known to cause cancer:</i>		
Carbon black only in bound form		
1333-86-4	Carbon black	* 5-9.99%
100-41-4	ethylbenzene	* <0.1%
· <i>Chemicals known to cause reproductive toxicity for females:</i>		
None of the ingredients is listed.		
· <i>Chemicals known to cause reproductive toxicity for males:</i>		
None of the ingredients is listed.		
· <i>Chemicals known to cause developmental toxicity:</i>		
108-88-3	toluene	12.5-15%

(Contd. on page 15)



**Product number PD1/009****Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 14)

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II	12.5-15%
67-64-1	acetone	I	5-9.99%
78-93-3	butanone	I	0.5-1%
1330-20-7	xylene	I	<0.5%
100-41-4	ethylbenzene	D	<0.1%

· **TLV (Threshold Limit Value)**

64-17-5	ethanol	A3
108-88-3	toluene	A4
1333-86-4	Carbon black	A4
67-64-1	acetone	A4
67-63-0	propan-2-ol	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black	5-9.99%
-----------	--------------	---------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
  - **Date of preparation / last revision** 08/15/2022 / 77
  - **Abbreviations and acronyms:**
    - IMDG: International Maritime Code for Dangerous Goods
    - DOT: US Department of Transportation
    - IATA: International Air Transport Association
    - EINECS: European Inventory of Existing Commercial Chemical Substances
    - ELINCS: European List of Notified Chemical Substances
    - CAS: Chemical Abstracts Service (division of the American Chemical Society)
    - NFPA: National Fire Protection Association (USA)
    - HMIS: Hazardous Materials Identification System (USA)
    - VOC: Volatile Organic Compounds (USA, EU)
    - LC50: Lethal concentration, 50 percent
    - LD50: Lethal dose, 50 percent
    - NIOSH: National Institute for Occupational Safety
    - OSHA: Occupational Safety & Health
    - TLV: Threshold Limit Value
    - PEL: Permissible Exposure Limit
    - REL: Recommended Exposure Limit
    - BEI: Biological Exposure Limit
    - Flammable Liquids 2: Flammable liquids . Category 2
    - Flammable Liquids 3: Flammable liquids . Category 3
    - Acute Toxicity - Dermal 4: Acute toxicity . Category 4
    - Skin Irritation 2: Skin corrosion/irritation . Category 2
    - Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
    - Carcinogenicity 2: Carcinogenicity . Category 2
    - Toxic to Reproduction 2: Reproductive toxicity . Category 2
    - Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

(Contd. on page 16)

**Product number PD1/009**

**Trade name: SB PAT ANTIQUING BLACK**

(Contd. of page 15)

*Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2*

*Aspiration Hazard 1: Aspiration hazard . Category 1*

*Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3*

• **Sources**

**REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments**

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• \* **Data compared to the previous version altered.**