


1 Identification

- **Product identifier**
 - Product number WBS5AA2
 - Trade name: **WB SEALER BLACK**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - **Information department:**
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - **Emergency telephone number:**
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
 - **Label elements**
 - **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms
- 

GHS08
- **Signal word** Warning
 - **Hazard-determining components of labeling:**
Carbon black
 - **Hazard statements**
H351 Suspected of causing cancer. Route of exposure: Inhalation.
 - **Precautionary statements**
 - P201 Obtain special instructions before use.
 - P202 Do not handle until all safety precautions have been read and understood.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P308+P313 IF exposed or concerned: Get medical advice/attention.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 1)

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irritation 2A, H319	1-2.49%
107-98-2	1-methoxy-2-propanol ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	1-2.49%
5131-66-8	3-butoxypropan-2-ol ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	0.5-1%
57-55-6	propane-1,2-diol	0.5-1%
1333-86-4	Carbon black ⚠ Carcinogenicity 2, H351	≥0.1-<0.5%
34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	<1%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 3)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 2)

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation
 Keep away from ignition sources

· **Environmental precautions:**

Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to Section 13.

· **Reference to other sections**

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

471-34-1	calcium carbonate	45 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
57-55-6	propane-1,2-diol	30 mg/m
1333-86-4	Carbon black	9 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm

· **PAC-2:**

471-34-1	calcium carbonate	210 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
57-55-6	propane-1,2-diol	1,300 mg/m
1333-86-4	Carbon black	99 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm

· **PAC-3:**

471-34-1	calcium carbonate	1,300 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
107-98-2	1-methoxy-2-propanol	660 ppm
57-55-6	propane-1,2-diol	7,900 mg/m
1333-86-4	Carbon black	590 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Open and handle receptacle with care.
 Keep respiratory protective device available.

(Contd. on page 4)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 3)

- **Information about protection against explosions and fires:**
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
 Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
 In cases where there is no reported expiration date, it means that the product must be used within 8 months.
 Take on temperature greater than 5 ° C
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep receptacle tightly sealed.
 - **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

112-34-5 2-(2-butoxyethoxy)ethanol

TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
-----	---

107-98-2 1-methoxy-2-propanol

REL	Short-term value: 540 mg/m , 150 ppm Long-term value: 360 mg/m , 100 ppm
TLV	Short-term value: 100 ppm Long-term value: 50 ppm A4

57-55-6 propane-1,2-diol

WEEL	Long-term value: 10 mg/m
------	--------------------------

34590-94-8 (2-methoxymethylethoxy)propanol

PEL	Long-term value: 600 mg/m , 100 ppm Skin
REL	Short-term value: 900 mg/m , 150 ppm Long-term value: 600 mg/m , 100 ppm Skin
TLV	Long-term value: 50 ppm

- **Regulatory information**

- TLV: Guide to Occupational Exposure Values (TLV)
- REL: Guide to Occupational Exposure Values (NIOSH RELs)
- WEEL: Guide to Occupational Exposure Values (AIHA WEELs)
- PEL: Guide to Occupational Exposure Values (OSHA PELs)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**
 - **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 4)

Wash hands before breaks and at the end of work.
Store protective clothing separately.

- **Breathing equipment:**
Not required.



Suitable respiratory protective device recommended.

Filter A

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

- **pH-value:** Mixture is non-polar/aprotic.
Range: 7 - 9

· Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 100 °C (212 °F)

- **Flash point:** 100 °C (212 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto igniting:** 225 °C (437 °F)

- **Decomposition temperature:** Not determined.

- **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

- **Lower:** 0.9 Vol %
- **Upper:** ~20 Vol %

(Contd. on page 6)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 5)

· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)	
· Vapor pressure at 50 °C (122 °F):	5.3 hPa (4 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.376 g/cm (11.483 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	35.9 %	
· VOC content:	5.47 %	
	75.3 g/l / 0.63 lb/gal	
· Solids content:	58.7 %	
· Other information (HAPS)		
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
107-98-2 1-methoxy-2-propanol		
Oral	LD50	4,016 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	5,001 mg/l (mouse)

(Contd. on page 7)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 6)

5131-66-8 3-butoxypropan-2-ol

Oral	LD50	3,300 mg/kg (mouse)
Dermal	LD50	8,001 mg/kg (mouse)

57-55-6 propane-1,2-diol

Oral	LD50	20,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

1333-86-4 Carbon black

Oral	LD50	5,001 mg/kg (mouse)
------	------	---------------------

34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	9,510 mg/kg (rabbit)

· **Primary irritant effect:**

- *on the skin:* No irritant effect.
- *on the eye:* No irritating effect.

· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

Suspected of causing cancer. Route of exposure: Inhalation.
 Safety data sheet available on request.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

1333-86-4	Carbon black	2B
-----------	--------------	----

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information· **Toxicity**· **Aquatic toxicity:****112-34-5 2-(2-butoxyethoxy)ethanol**

EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	1,300 mg/l (Leuciscus idus melanotus)

107-98-2 1-methoxy-2-propanol

EC50	21,100 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	6,812 mg/l (Fish)

5131-66-8 3-butoxypropan-2-ol

EC50	1,001 mg/l (algae) (96 h)
	1,001 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	1,000 mg/l (Fish)

57-55-6 propane-1,2-diol

EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	40,613 mg/l (Fish)

(Contd. on page 8)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 7)

1333-86-4 Carbon black

EC50	10,001 mg/l (algae) (72h)
	5,601 mg/l (daphnia) (24h)
LC50 (96 ore/h/saat)	1,000 mg/l (Fish)

34590-94-8 (2-methoxymethylethoxy)propanol

EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	1,001 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

112-34-5	2-(2-butoxyethoxy)ethanol	.
107-98-2	1-methoxy-2-propanol	.
5131-66-8	3-butoxypropan-2-ol	.
57-55-6	propane-1,2-diol	.

· **Behavior in environmental systems:**

· **Bioaccumulative potential**

112-34-5	2-(2-butoxyethoxy)ethanol	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1
107-98-2	1-methoxy-2-propanol	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 0,37
5131-66-8	3-butoxypropan-2-ol	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1,2

· **Mobility in soil**

112-34-5	2-(2-butoxyethoxy)ethanol	Il prodotto ha potenziale di mobilità molto alto.
----------	---------------------------	---

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

Not applicable

· **Note**

Check viscosity and flash point at section 9

(Contd. on page 9)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 8)

- | | |
|---|--------------------|
| · UN proper shipping name
· DOT, IMDG, IATA | Not applicable |
| · Transport hazard class(es)
· DOT, ADR/RID, ADN, IMDG, IATA
· Class | Not applicable |
| · Packing group
· DOT, IMDG, IATA | Not applicable |
| · Environmental hazards:
· Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT
· Remarks: | > 450 l: 3 F1, III |
| · IMDG
· Remarks: | > 30 l: 3, III |
| · UN "Model Regulation": | Not applicable |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Various regulations
 · SARA

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings) :**

112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

1333-86-4	Carbon black	* ≥0.1-<0.5%
-----------	--------------	--------------

- **Chemicals known to cause reproductive toxicity for females:**

1589-47-5	2-methoxypropanol	<0.01%
-----------	-------------------	--------

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 10)

Product number WBS5AA2
Trade name: WB SEALER BLACK

(Contd. of page 9)

· **Carcinogenic categories**

· EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value)		
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1333-86-4	Carbon black	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
1333-86-4	Carbon black	≥0.1-<0.5%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

- **Date of preparation / last revision** 02/12/2024

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids . Category 3

Flammable Liquids 4: Flammable liquids . Category 4

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Carcinogenicity 2: Carcinogenicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- *** Data compared to the previous version altered.**