

## 1 Identification

- **Product identifier**
  - Product number HMM5037
  - Trade name: **CLEAR WB SELF SEALER 5SH**
    - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
  - **Information department:**  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - **Emergency telephone number:**  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
- **Label elements**
  - **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
    - Hazard pictograms



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**  
adipohydrazide
- **Hazard statements**  
H317 May cause an allergic skin reaction.
- **Precautionary statements**
  - P261 Avoid breathing dust/fume/gas/mist/vapors/spray
  - P280 Wear protective gloves.
  - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
  - P321 Specific treatment (see on this label).
  - P363 Wash contaminated clothing before reuse.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
  - **NFPA ratings (scale 0 - 4)**



Health = 0  
Fire = 1  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0  
Fire = 1  
Reactivity = 0

**Product number HMM5037**  
**Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 1)

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· *Description: Mixture: consisting of the following components.*

· **Dangerous components:**

34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	1-<5%
5131-66-8	3-butoxypropan-2-ol ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	1-2.49%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irritation 2A, H319	0.5-1%
1071-93-8	adipohydrazide ⚠ Aquatic Chronic 2, H411 ⚠ Sensitization - Skin 1, H317 ⚠ Aquatic Acute 2, H401	≥0.5-<1%

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 3)

**Product number HMM5037****Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 2)

**· Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

**· Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

**· Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

**· Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals****· PAC-1:**

112945-52-5	Silicon dioxide, chemically prepared	18 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/m

**· PAC-2:**

112945-52-5	Silicon dioxide, chemically prepared	100 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m

**· PAC-3:**

112945-52-5	Silicon dioxide, chemically prepared	630 mg/m
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m

## 7 Handling and storage

**· Handling:****· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

**· Information about protection against explosions and fires: No special measures required.**

(Contd. on page 4)

**Product number HMM5037****Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** None.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

### 34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m<sup>3</sup>, 100 ppm

Skin

REL Short-term value: 900 mg/m<sup>3</sup>, 150 ppm

Long-term value: 600 mg/m<sup>3</sup>, 100 ppm

Skin

TLV Long-term value: 50 ppm

### 112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10\* ppm

\*Inhalable fraction and vapor

- **Regulatory information**

PEL: Guide to Occupational Exposure Values (OSHA PELs)

REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

(Contd. on page 5)

US

**Product number HMM5037****Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 4)

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.  
Range: 7 - 9

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

100 °C (212 °F)

- **Flash point:**

100 °C (212 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Auto igniting:**

270 °C (518 °F)

- **Decomposition temperature:**

Not determined.

- **Danger of explosion:**

Product does not present an explosion hazard.

- **Explosion limits:**

- **Lower:**

0.6 Vol %

- **Upper:**

20.4 Vol %

- **Vapor pressure at 20 °C (68 °F):**

1.3 hPa (1 mm Hg)

- **Vapor pressure at 50 °C (122 °F):**

5.3 hPa (4 mm Hg)

- **Density (+/- 0,03) at 20 °C (68 °F):**

1.05 g/cm (8.762 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Fully miscible.

(Contd. on page 6)

**Product number HMM5037**  
**Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 5)

· <i>Partition coefficient (n-octanol/water):</i> Not determined.		
· <i>Viscosity:</i>		
· <i>Dynamic:</i>	Not determined.	
· <i>Kinematic at 20 °C (68 °F):</i>	60 s (ISO 6 mm)	
· <i>Oxidising properties:</i>	N.A.	
· <i>Solvent content:</i>		
· <i>Water:</i>	59.9 %	
· <i>VOC content:</i>	6.17 %	
	64.8 g/l / 0.54 lb/gal	
· <i>Solids content:</i> 33.9 %		
· <b>Other information (HAPS)</b>		
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
80-62-6	methyl methacrylate	<0.01%

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

### · Information on toxicological effects

#### · Acute toxicity:

· *LD/LC50 values that are relevant for classification:*

<b>34590-94-8 (2-methoxymethylethoxy)propanol</b>		
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	9,510 mg/kg (rabbit)
<b>5131-66-8 3-butoxypropan-2-ol</b>		
Oral	LD50	3,300 mg/kg (mouse)
Dermal	LD50	8,001 mg/kg (mouse)
<b>112-34-5 2-(2-butoxyethoxy)ethanol</b>		
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
<b>1071-93-8 adipohydrazide</b>		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

#### · Primary irritant effect:

- *on the skin:* No irritant effect.
- *on the eye:* No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 7)

**Product number HMM5037**  
**Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 6)

- **Additional toxicological information:**  
Irritant  
May cause an allergic skin reaction.  
Safety data sheet available on request.

- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer - Cl. 1 and 2)</b>	
None of the ingredients is listed.	
· <b>NTP (National Toxicology Program)</b>	
None of the ingredients is listed.	
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>	
None of the ingredients is listed.	

## 12 Ecological information

- **Toxicity**

· <b>Aquatic toxicity:</b>	
<b>34590-94-8 (2-methoxymethylethoxy)propanol</b>	
EC50	970 mg/l (algae) (72 h) 1,919 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	1,001 mg/l (Fish)
<b>5131-66-8 3-butoxypropan-2-ol</b>	
EC50	1,001 mg/l (algae) (96 h) 1,001 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	1,000 mg/l (Fish)
<b>112-34-5 2-(2-butoxyethoxy)ethanol</b>	
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	1,300 mg/l (Leuciscus idus melanotus)
<b>1071-93-8 adipohidrazide</b>	
EC50	9.19 mg/l (algae) (72 h) 101 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	101 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

· <b>Substances Easily biodegradable</b>	
34590-94-8	(2-methoxymethylethoxy)propanol .
5131-66-8	3-butoxypropan-2-ol .
112-34-5	2-(2-butoxyethoxy)ethanol .

- **Behavior in environmental systems:**

· <b>Bioaccumulative potential</b>		
34590-94-8	(2-methoxymethylethoxy)propanol	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 0,01
5131-66-8	3-butoxypropan-2-ol	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1,2
112-34-5	2-(2-butoxyethoxy)ethanol	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1

(Contd. on page 8)

**Product number HMM5037**  
**Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 7)

· <b>Mobility in soil</b>	
34590-94-8	(2-methoxymethylethoxy)propanol
112-34-5	2-(2-butoxyethoxy)ethanol

*Il prodotto ha potenziale di mobilità molto alto.*  
*Il prodotto ha potenziale di mobilità molto alto.*

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

· <b>UN-Number</b>	
· DOT, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
· <b>UN proper shipping name</b>	
· DOT, IMDG, IATA	Not applicable
· <b>Transport hazard class(es)</b>	
· DOT, ADR/RID, ADN, IMDG, IATA	
· Class	Not applicable
· <b>Packing group</b>	
· DOT, IMDG, IATA	Not applicable
· <b>Environmental hazards:</b>	
· Marine pollutant:	No
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	Not applicable

US

(Contd. on page 9)



**Product number HMM5037**

**Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 8)

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
80-62-6	methyl methacrylate	<0.01%
1336-21-6	ammonia	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

80-62-6	methyl methacrylate
---------	---------------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

80-62-6	methyl methacrylate	E, NL	<0.01%
---------	---------------------	-------	--------

· **TLV (Threshold Limit Value)**

112945-52-5	Silicon dioxide, chemically prepared	A4
80-62-6	methyl methacrylate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
  - **Date of preparation / last revision** 02/13/2024
  - **Abbreviations and acronyms:**  
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

**Product number HMM5037**
**Trade name: CLEAR WB SELF SEALER 5SH**

(Contd. of page 9)

DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Flammable Liquids 4: Flammable liquids . Category 4  
 Skin Irritation 2: Skin corrosion/irritation . Category 2  
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A  
 Sensitization - Skin 1: Skin sensitisation . Category 1  
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• \* Data compared to the previous version altered.