

*Printing date 08/08/2022* 

Version number 1

Reviewed on 08/08/2022

# **1** Identification

- · Product identifier
  - · Product number HUM5AA36
  - · Trade name: SELF SEALER WB UV CLEAR 20 GL
    - $\cdot$  Application of the substance / the mixture For professional use

# · Details of the supplier of the safety data sheet

 Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 1.3.2 Importer

- Name I.C.& S. DISTRIBUTING CO. Address P.O.BOX 10845 LANCASTER. PA USA E-Mail: nelson@ics-company.com
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585. 001 813-248-0585

# 2 Hazard(s) identification

# · Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling:
- Trimethylolpropane, ethoxylated, esters with acrylic acid
- Glycerol, propoxylated, esters with acrylic acid
- 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid
- · Hazard statements
- H317 May cause an allergic skin reaction.
- · Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

(Contd. on page 2)

<sup>—</sup> US




Version number 1

Reviewed on 08/08/2022

# Printing date 08/08/2022

Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL





Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

# Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

		(Contd. of page 2)
34590-94-8	(2-methoxymethylethoxy)propanol	<1%
	Flammable Liquids 4, H227	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	<ul> <li>Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330</li> <li>Skin Corrosion 1B, H314; Eye Damage 1, H318</li> <li>Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)</li> <li>Sensitization - Skin 1A, H317</li> </ul>	

# 4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation*:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
  - Most important symptoms and effects, both acute and delayed Allergic reactions
  - For symptoms and effects caused by substances, refer to Section 11.
  - Indication of any immediate medical attention and special treatment needed
  - No further relevant information available.

# 5 Fire-fighting measures

# · Extinguishing media

- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.

# · Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

# Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

# · Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

(Contd. on page 4)

US



Printing date 08/08/2022

# Version number 1

Reviewed on 08/08/2022

Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 3)

	ecautions, protective equipment and emergency procedures	
	juate ventilation	
	rom ignition sources ntal precautions:	
	lenty of water.	
Do not allow	to enter sewers/ surface or ground water.	
	d material for containment and cleaning up:	a a wal wat
	liquid-binding material (sand, diatomite, acid binders, universal binders, taminated material as waste according to Section 13.	sawdust).
	juate ventilation.	
Reference t	o other sections	
	7 for information on safe handling.	
	8 for information on personal protection equipment. 13 for disposal information.	
	Action Criteria for Chemicals	
· PAC-1:		
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
111-90-0	Diethylene glycol monoethyl ether	75 ppm
111-76-2	2-butoxyethanol	60 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/n
121-44-8	triethylamine	1 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/n
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
· PAC-2:		
7631-86-9	silicon dioxide, chemically prepared	740 mg/n
111-90-0	Diethylene glycol monoethyl ether	100 ppm
111-76-2	2-butoxyethanol	120 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m <sup>3</sup>
121-44-8	triethylamine	170 ppm
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m <sup>3</sup>
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppi
· PAC-3:		
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/n
111-90-0	Diethylene glycol monoethyl ether	450 ppm
111-76-2	2-butoxyethanol	700 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m <sup>3</sup>
	triethylamine	1,000 ppm
	c16-18 alcohols ethoxylated	250 mg/m <sup>3</sup>
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm

(Contd. on page 5)



Version number 1

Reviewed on 08/08/2022

Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 4)

# 7 Handling and storage

## · Handling:

Printing date 08/08/2022

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.

## · Conditions for safe storage, including any incompatibilities

- · Storage:
  - Requirements to be met by storerooms and receptacles:
  - Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
  - In cases where there is no reported expiration date , it means that the product must be used within 8 months.
  - Take on temperature greater than 5 ° C
  - · Information about storage in one common storage facility: Not required.
  - · Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

# 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

### · Control parameters

- · Components with limit values that require monitoring at the workplace:
  - The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-9	0-0 Diethylene glycol monoethyl ether	
WEEL	Long-term value: 25 ppm	
111-7	6-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin	
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 20 ppm BEI, A3	
112-34	4-5 2-(2-butoxyethoxy)ethanol	
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor	
121-4	4-8 triethylamine	
PEL	Long-term value: 100 mg/m <sup>3</sup> , 25 ppm	
TLV	Short-term value: 1 ppm Long-term value: 0.5 ppm Skin, A4	
34590	-94-8 (2-methoxymethylethoxy)propanol	
PEL	Long-term value: 600 mg/m³, 100 ppm Skin	
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin	
		(Contd. on page



Version number 1

Reviewed on 08/08/2022

# Product number HUM5AA36

Printing date 08/08/2022

· Color: · Odor:

· Odor threshold:

Trade name: SELF SEALER WB UV CLEAR 20 GL

		(Contd. of page
TLV	<pre>/ Long-term value: NIC-50 ppm (Skin)</pre>	
	· Ingredients with biological limit val	lues:
111	-76-2 2-butoxyethanol	
BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (1	
	· Additional information: The lists that	were valid during the creation were used as basis.
-	osure controls Personal protective equipment:	
_	• General protective and hygienic measu	res:
	Immediately remove all soiled and co	
	Wash hands before breaks and at th • Breathing equipment:	e end of work.
	Short term filter device:	
	Suitable respiratory protect	tive device recommended.
	Filter A • Protection of hands:	
	Protective gloves	
		ation to the glove material can be given for the product onsideration of the penetration times, rates of diffusion
	The glove material has to be imperm	eable and resistant to the product .
	The selection of the suitable glo further marks of quality and varie a preparation of several substa	ves does not only depend on the material, but also des from manufacturer to manufacturer. As the product nces, the resistance of the glove material can not be refore to be checked prior to the application.
	• •	s to be found out by the manufacturer of the protecti
	gloves and has to be observed.	
	· Eye protection: Goggles recommended	ed during refilling.
9 Phy	ysical and chemical properties	
· Info	rmation on basic physical and chem	nical properties
	General Information	
	· Appearance:	
	· Form:	Fluid

(Contd. on page 7)

According to product specification

Characteristic

Not determined.

US



Printing date 08/08/2022

# Safety Data Sheet acc. to OSHA HCS

Version number 1

Reviewed on 08/08/2022

# Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

		(Contd. of page
· pH-value:	Mixture is non-polar/aprotic. Range: 7 - 9	
• Change in condition • Melting point/Melting range: • Boiling point/Boiling range:	Undetermined. 100 °C (212 °F)	
· Flash point:	100 °C (212 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	>370 °C (>698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion	hazard.
• Explosion limits: • Lower: • Upper:	Not determined. Not determined.	
· Vapor pressure at 20 °C (68 °F):	0 hPa	
• Density (+/- 0,03) at 20 °C (68 °F) • Relative density • Vapor density • Evaporation rate	): 1.031 g/cm <sup>3</sup> (8.604 lbs/gal) Not determined. Not determined. Not determined.	
• Solubility in / Miscibility with • Water:	Fully miscible.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic at 20 °C (68 °F):</li> <li>Oxidising properties:</li> <li>Solvent content:</li> </ul>	Not determined. 60 s (ISO 6 mm) N.A.	
• Water: • VOC content:	56.9 % 3.31 % 34.2 g/l / 0.29 lb/gal	
· Solids content:	39.7 %	
Other information (HAPS)		
111-90-0 Diethylene glycol monoe	•	0.5-1%
112-34-5 2-(2-butoxyethoxy)ethan	ol	0.5-1%
121-44-8 triethylamine		<0.5%
110-80-5 2-ethoxyethanol		<0.019

# 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
  - No decomposition if used and stored according to specifications.

(Contd. on page 8)

US

(Contd. of page 7)

# Safety Data Sheet acc. to OSHA HCS

Version number 1

Reviewed on 08/08/2022

Product number HUM5AA36

Printing date 08/08/2022

Chemicals

gs & polymers technologies

Trade name: SELF SEALER WB UV CLEAR 20 GL

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

· Information on toxicological effects	
• Acute toxicity:	

	LC50 value	es that are relevant for classification:
ATE (Acu	te Toxicit	y Estimate)
Oral	LD50	48,754 mg/kg
Dermal	LD50	333,333 mg/kg (rabbit)
Inhalative	LC50/4 h	6,264 mg/l (mouse)
28961-43-	5 Trimeth	ylolpropane, ethoxylated, esters with acrylic acid
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	13,201 mg/kg (rabbit)
7473-98-5	2-hydrox	y-2-methylpropiophenone
Oral	LD50	1,694 mg/kg (mouse)
Dermal	LD50	6,929 mg/kg (mouse)
111 <b>-90-</b> 0	Diethylene	e glycol monoethyl ether
Oral	LD50	6,031 mg/kg (mouse)
Dermal	LD50	9,143 mg/kg (rabbit)
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
112-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
55818-57-		propylidenediphenol, oligomeric reaction products with 1-chloro-2, ropane, esters with acrylic acid
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
121-44-8	triethylam	ine
Oral	LD50	730 mg/kg (mouse)
Dermal	LD50	580 mg/kg (rabbit)
Inhalative	LC50/4 h	10.9 mg/l (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
· 0		No irritant effect.
• 6	on the eye:	No irritating effect.

· Sensitization: Sensitization possible through skin contact.

(Contd. on page 9)



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

### Product number HUM5AA36 SELF SEALER WB UV CLEAR 20 GL Trade name:

(Contd. of page 8)

3

• Additional toxicological information:	
Irritant	
May cause an allergic skin reaction.	

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

# · Toxicity

· Aquatic t	Trimethylolpropane, ethoxylated, esters with acrylic acid
EC50	70.7 mg/l (daphnia)
1 CEO (06h)	48H
	1.95 mg/l (Fish) <b>-hydroxy-2-methylpropiophenone</b>
EC50	119 mg/l (daphnia) (48h)
	160 mg/l (Fish)
, ,	,
	ethylene glycol monoethyl ether
	1,982 mg/l (daphnia)
• •	101 mg/l (Fish)
	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
. ,	101 mg/l (Fish)
	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
52408-84-1	Glycerol, propoxylated, esters with acrylic acid
EC50	12.2 mg/l (algae) (72 h)
	91.4 mg/l (daphnia) (48 h)
LC50 (96h)	5.74 mg/l (Fish)
55818-57-0	<i>4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,</i> epoxypropane, esters with acrylic acid
EC50	105 mg/l (algae) (72h)
	101 mg/l (daphnia) (48h)
LC50 (96h)	101 mg/l (Fish)
121-44-8 tri	ethylamine
EC50	8 mg/l (algae) (72 h)
	17 mg/l (daphnia) (48 h)
LC50 (96h)	36 mg/l (Fish)
. ,	(Contd. on page



*Printing date 08/08/2022* 

Version number 1

Reviewed on 08/08/2022

# Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

	8 (2-methoxymethylethoxy)propanol	
EC50	970 mg/l (algae) (72 h)	
	1,919 mg/l (daphnia) (48 h)	
. ,	n) 1,001 mg/l (Fish)	
55965-84-9	9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	] and
EC50	0.027 mg/l (algae) (72 h)	
	0.16 mg/l (daphnia) (48 h)	
LC50 (96h)	n) 0.19 mg/l (Fish)	
· Persistend	ce and degradability No further relevant information available.	
· Substan	nces Easily biodegradable	
111-90-0	Diethylene glycol monoethyl ether .	
111-76-2	2-butoxyethanol .	
112-34-5	2-(2-butoxyethoxy)ethanol .	
<ul> <li>Bioaccu</li> <li>Mobility</li> <li>Additional</li> <li>General</li> <li>Water H</li> <li>Do not</li> <li>sewage</li> </ul>	<i>in environmental systems:</i> <i>umulative potential</i> No further relevant information available. <i>y in soil</i> No further relevant information available. <i>In ecological information:</i> <i>I notes:</i> <i>hazard class 1 (Self-assessment): slightly hazardous for water</i> <i>allow undiluted product or large quantities of it to reach ground water, water</i> <i>e system.</i> <i>yerse effects</i> No further relevant information available.	course
-	I considerations	
. Waste trea	atment methods	

sewage system. Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

# · Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

# 14 Transport information · UN-Number · DOT, ADN, IMDG, IATA · Note · Note Check viscosity and flash point at section 9 · UN proper shipping name · DOT, ADN, IMDG, IATA · DOT, ADN, IMDG, IATA Not applicable · Transport hazard class(es) · DOT, ADR, ADN, IMDG, IATA · Class Not applicable



Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

### Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

		(Contd. of page 10
• Packing group • DOT, IMDG, IATA	Not applicable	
• Environmental hazards: • Marine pollutant:	No	
· Special precautions for user	Not applicable.	
<ul> <li>Transport in bulk according to Anne&gt; MARPOL73/78 and the IBC Code</li> </ul>	<b>( Il of</b> Not applicable.	
· UN "Model Regulation":	Not applicable	

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Various regulations

· SARA

	Section 355 (extremely hazardous substances):	
None of t	he ingredients is listed.	
	Section 313 (Specific toxic chemical listings) :	
111-90-0	Diethylene glycol monoethyl ether	0.5-1%
111-76-2	2-butoxyethanol	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
121-44-8	triethylamine	<0.5%
110-80-5	2-ethoxyethanol	<0.01%
52-51-7	bronopol (INN)	<0.01%
· TSO	CA (Toxic Substances Control Act):	
All compo	nents have the value ACTIVE.	
•	Hazardous Air Pollutants	
121-44-8	triethylamine	
	position 65	
	Chemicals known to cause cancer:	
None of t	he ingredients is listed.	
	Chemicals known to cause reproductive toxicity for females:	
None of t	he ingredients is listed.	
	Chemicals known to cause reproductive toxicity for males:	
110-80-5	2-ethoxyethanol	<0.01%
	Chemicals known to cause developmental toxicity:	
110-80-5	2-ethoxyethanol	<0.01%
· Car	cinogenic categories	
•	EPA (Environmental Protection Agency)	
111-76-2	2-butoxyethanol	NL 0.5-1%
	TLV (Threshold Limit Value)	· ·
111-76-2	2-butoxyethanol	A3
		(Contd. on page 12

# ivm Chemicals

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/08/2022

Version number 1

Reviewed on 08/08/2022

Product number HUM5AA36 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 11)

A4

121-44-8 triethylamine

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

IARC International agency for research on cancer • \* Data compared to the previous version altered.

· Contact: See emergency phone

· Date of preparation / last revision 08/08/2022 / -· Abbreviations and acronvms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids - Category 2 Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 4: Acute toxicity - Category 4 Acute Toxicity - Dermal 2: Acute toxicity - Category 2 Acute Toxicity - Dermal 3: Acute toxicity - Category 3 Skin Corrosion 1A: Skin corrosion/irritation - Category 1A Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Skin Irrititation 2: Skin corrosion/irritation - Category 2 Eye Damage 1: Serious eye damage/eye irritation - Category 1 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1A: Skin sensitisation - Category 1A Sensitization - Skin 1B: Skin sensitisation - Category 1B Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Sources REGULATION (EC) № 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site **INRS Fiche Toxicologique**