

1 Identification

- **Product identifier**

- **Product number** TV17

- **Trade name:** **SPEED DRY FOR 2K PU @ 0.5-2.0%**

- **Application of the substance / the mixture** For professional use

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

- IVM Chemicals Srl

- Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

- 1.3.2 Importer

- Name I.C. & S. DISTRIBUTING CO.

- Address P.O. BOX 10845

- LANCASTER. PA

- USA

- E-Mail: nelson@ics-company.com

- **Information department:**

- Environmental Health and safety office

- hseoffice@ivmchemicals.com

- **Emergency telephone number:**

- ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

- 001 813-248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2

H225 Highly flammable liquid and vapor.

Specific Target Organ Toxicity - Single Exposure 2H371 May cause damage to organs.

Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

- The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS08

GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

- isobutyl acetate

- bis(neodecanoyloxy)dioctylstannane

- **Hazard statements**

- H225 Highly flammable liquid and vapor.

- H371 May cause damage to organs.

- H336 May cause drowsiness or dizziness.

- **Precautionary statements**

- P210

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

- P241

- Use explosion-proof electrical/ventilating/lighting/equipment.

- P260

- Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 2)

Product number TV17

Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%

(Contd. of page 1)

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 3
Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

110-19-0	isobutyl acetate	75-100%
	<ul style="list-style-type: none"> Flammable Liquids 2, H225 Specific Target Organ Toxicity - Single Exposure 3, H336 	
68299-15-0	bis(neodecanoyloxy)dioctylstannane	5-9.99%
	<ul style="list-style-type: none"> Specific Target Organ Toxicity - Single Exposure 2, H371 	

4 First-aid measures

Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

· **Suitable extinguishing agents:**

Alcohol resistant foam

(Contd. on page 3)

Product number TV17**Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%**

(Contd. of page 2)

Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

110-19-0	isobutyl acetate	450 ppm
----------	------------------	---------

· **PAC-2:**

110-19-0	isobutyl acetate	1300* ppm
----------	------------------	-----------

· **PAC-3:**

110-19-0	isobutyl acetate	7500** ppm
----------	------------------	------------

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Product number TV17**Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%**

(Contd. of page 3)

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility: Not required.**

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

- The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

- At this time, the remaining constituent has no known exposure limits.

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing.

- Wash hands before breaks and at the end of work.

- **Breathing equipment:**

- Short term filter device:



Suitable respiratory protective device recommended.

Filter A

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Product number TV17**Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%**

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

117.2 °C (243 °F)

- **Flash point:**

18 °C (64.4 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

405 °C (761 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

- **Lower:**

2.4 Vol %

- **Upper:**

10.5 Vol %

- **Vapor pressure at 20 °C (68 °F):**

20 hPa (15 mm Hg)

- **Density (+/- 0,03) at 20 °C (68 °F):**

0.89 g/cm (7.427 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

Product number TV17**Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%**

(Contd. of page 5)

- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic at 20 °C (68 °F):** 40 s (ISO 4 mm)
- **Oxidising properties:** N.A.

- **Solvent content:**
 - **VOC content:** 91.50 %
814.4 g/l / 6.80 lb/gal

- **Solids content:** 8.5 %

- **Other information (HAPS)**

None of the ingredients is listed.

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

68299-15-0 bis(neodecanoyloxy)dioctylstannane

Oral	LD50	2,300 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
Inhalative	LC50/6 h	101 ppm (Fish)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:** May cause damage to organs.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 7)

Product number TV17
Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

110-19-0 isobutyl acetate

EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

68299-15-0 bis(neodecanoyloxy)dioctylstannane

EC50	101 mg/l (algae) (72h)
	24.12 mg/l (daphnia) (48h)

 · **Persistence and degradability** No further relevant information available.

· Substances Easily biodegradable

110-19-0	isobutyl acetate	.
----------	------------------	---

· Behavior in environmental systems:

 · **Bioaccumulative potential** No further relevant information available.

 · **Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

 · **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, IMDG, IATA

UN1263

· Note

Check viscosity and flash point at section 9

· UN proper shipping name

· DOT

Paint

(Contd. on page 8)

Product number TV17

Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%

(Contd. of page 7)

· IMDG, IATA

PAINT

· Transport hazard class(es)

· DOT


 · Class
 · Label
 · Class
 · Label

 3 Flammable liquids
 3
 3 Flammable liquids
 3

· IMDG, IATA


 · Class
 · Label

 3 Flammable liquids
 3

· Packing group

· DOT, IMDG, IATA

III

· Environmental hazards:

· Marine pollutant:

No

· Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler code): -

· EMS Number:

F-E, S-E

· Stowage Category

A

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Remarks:

> 450 l: 3 F1, II

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Remarks:

> 450 l: 3, II

· IATA

· Remarks:

> 30 l: 3, II

· UN "Model Regulation":

UN 1263 PAINT, 3, III

US

(Contd. on page 9)

Product number TV17
Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%

(Contd. of page 8)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
 - **Date of preparation / last revision** 09/14/2022 / 66
 - **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association

(Contd. on page 10)

Product number TV17**Trade name: SPEED DRY FOR 2K PU @ 0.5-2.0%**

(Contd. of page 9)

*EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Flammable Liquids 2: Flammable liquids . Category 2**Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) . Category 2**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3***• Sources****REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments**

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• * Data compared to the previous version altered.