

Printing date 02/07/2017

Reviewed on 02/07/2017

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Product number** PLM5623
- **Trade name:** **WHITE SATIN ACRY EXT SELFSEAL**
- **Application of the substance / the preparation** Professional use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italia tel +39 038425441
- **Information department:** Environmental Health and safety office
hseoffice@ivmchemicals.com Emergency phone number : 001 813-248-0585

Name I.C. & S. DISTRIBUTING CO.
Address P.O.BOX 10845
LANCASTER, PA USA
E-Mail: nelson@ics-company.com

2 Hazards identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

toluene

- **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

(Contd. on page 2)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 1)

Ground/bond container and receiving equipment.
Keep container tightly closed.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Specific treatment (see on this label).
Take off contaminated clothing and wash before reuse.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use for extinction: CO2, powder or water spray.
IF ON SKIN: Wash with plenty of soap and water.
Store locked up.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**





| | | |
|-----------|--|-----------|
| 1330-20-7 | xylene ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 12.5-19% |
| 123-86-4 | n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 | 10-12.49% |
| 110-19-0 | isobutyl acetate ⚠ Flam. Liq. 2, H225 | 2.5-4.99% |
| 78-93-3 | butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 2.5-4.99% |
| 108-88-3 | toluene ⚠ Flam. Liq. 2, H225 ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 0-50% |

(Contd. on page 3)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number **PLM5623** Trade name: **WHITE SATIN ACRY EXT SELFSEAL**

| | | (Contd. of page 2) |
|----------|--|--------------------|
| 100-41-4 | ethylbenzene <ul style="list-style-type: none">  Flam. Liq. 2, H225  Acute Tox. 4, H332 | 1-2.49% |
| 141-78-6 | ethyl acetate <ul style="list-style-type: none">  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336 | 1-2.49% |

4 First aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, see chap. 11th
- **Indication of any immediate medical attention and special treatment needed**
Medical supervision for at least 48 hours.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

USA

(Contd. on page 4)

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

| | |
|-----|--|
| PEL | 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI |

123-86-4 n-butyl acetate

| | |
|-----|---|
| PEL | 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm |

110-19-0 isobutyl acetate

| | |
|-----|---------------------------------|
| PEL | 700 mg/m ³ , 150 ppm |
| REL | 700 mg/m ³ , 150 ppm |
| TLV | 713 mg/m ³ , 150 ppm |

78-93-3 butanone

| | |
|-----|--|
| PEL | 590 mg/m ³ , 200 ppm |
| REL | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm |
| TLV | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI |

(Contd. on page 5)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 4)

108-88-3 toluene

PEL Short-term value: C 300; 500* ppm
Long-term value: 200 ppm
*10-min peak per 8-hr shift
REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
TLV 75 mg/m³, 20 ppm
BEI

100-41-4 ethylbenzene

PEL 435 mg/m³, 100 ppm
REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV Short-term value: 543 mg/m³, 125 ppm
Long-term value: 87 mg/m³, 20 ppm
BEI

141-78-6 ethyl acetate

PEL 1400 mg/m³, 400 ppm
REL 1400 mg/m³, 400 ppm
TLV 1440 mg/m³, 400 ppm

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: MEK

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 6)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623

Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 5)

100-41-4 ethylbenzene

| | |
|-----|---|
| BEI | 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| - | Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product and in accordance with EN 374 and Directive 89/686/EEC.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Color: According to product specification

(Contd. on page 7)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 6)

| | |
|---|--|
| · Odor: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 77 °C (171 °F) |
| · Flash point: | -4 °C (25 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 370 °C (698 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7.5 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 10.7 hPa (8 mm Hg) |
| · Density at 20 °C (68 °F): | 1.233 g/cm ³ (10.289 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic at 20 °C (68 °F): | 101 s (ISO 6 mm) |
| · Solvent content: | |
| Organic solvents: | 45.3 % |
| VOC content: | 45.5 % |
| | 560.6 g/l / 4.68 lb/gl |
| · Solids content: | 53.7 % |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects** Suspected of damaging fertility or the unborn child.

(Contd. on page 8)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 7)

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

| | | |
|--------|------|---------------------|
| Oral | LD50 | 4300 mg/kg (rat) |
| Dermal | LD50 | 2000 mg/kg (rabbit) |

108-88-3 toluene

| | | |
|------------|----------|----------------------|
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 12124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5320 mg/l (mouse) |

· **Primary irritant effect:**

- **on the skin:** Causes skin irritation.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Harmful
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|--------------------------------------|----|
| 1330-20-7 | xylene | 3 |
| | silicon dioxide, chemically prepared | 3 |
| 108-88-3 | toluene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| | silicon dioxide, chemically prepared | 3 |
| | silicon dioxide, chemically prepared | 3 |
| | silicon dioxide, chemically prepared | 3 |
| | titanium dioxide | 2B |
| 80-62-6 | methyl methacrylate | 3 |
| | ASDSDADSA | 3 |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 9)

Printing date 02/07/2017

Reviewed on 02/07/2017


Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 8)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT, IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **Class** 3 Flammable liquids
- **Label** 3

- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3

- **Packing group**
- **DOT, IMDG, IATA** III

- **Environmental hazards:**
- **Marine pollutant:** No

- **Special precautions for user** Warning: Flammable liquids
- **Danger code (Kemler):** 33
- **EMS Number:** F-E,S-E

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **UN "Model Regulation":** UN1263, PAINT, special provision 640H, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
None of the ingredients is listed.

(Contd. on page 10)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 9)

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

| | |
|-----------|---------------------|
| 1330-20-7 | xylene |
| 78-93-3 | butanone |
| 108-88-3 | toluene |
| 100-41-4 | ethylbenzene |
| 80-62-6 | methyl methacrylate |

· TSCA (Toxic Substances Control Act):

Solid content
BT RKB6 SFUSO
xylene
n-butyl acetate
silicon dioxide, chemically prepared
isobutyl acetate
butanone
toluene
ethylbenzene
silicon dioxide, chemically prepared
ethyl acetate
silicon dioxide, chemically prepared
silicon dioxide, chemically prepared
titanium dioxide
methyl methacrylate

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene
64-17-5 ethanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

| | | |
|-----------|---------------------|----|
| 1330-20-7 | xylene | I |
| 78-93-3 | butanone | I |
| 108-88-3 | toluene | II |
| 100-41-4 | ethylbenzene | D |
| 80-62-6 | methyl methacrylate | NL |

· TLV (Threshold Limit Value established by ACGIH)

| | | |
|-----------|---------|----|
| 1330-20-7 | xylene | A4 |
| 108-88-3 | toluene | A4 |

(Contd. on page 11)

Printing date 02/07/2017

Reviewed on 02/07/2017

Product number PLM5623 Trade name: WHITE SATIN ACRY EXT SELFSEAL

(Contd. of page 10)

| | | |
|----------|----------------------|----|
| 100-41-4 | ethylbenzene | A3 |
| | titanium dioxide | A4 |
| 80-62-6 | methyl methacrylate | A4 |
| 64-17-5 | ethanol | A3 |
| 77-58-7 | dibutyltin dilaurate | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

titanium dioxide

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered.**