

Printing date 08/08/2022

Version number 6

Reviewed on 07/26/2022

1 Identification

- · Product identifier
 - · Product number HUM5AA14
 - Trade name: SELF SEALER WB UV CLEAR 20 GL
 - \cdot Application of the substance / the mixture For professional use

\cdot Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* IVM Chemicals Srl Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441 1.3.2 Importer

- Name I.C.& S. DISTRIBUTING CO. Address P.O.BOX 10845 LANCASTER. PA USA E-Mail: nelson@ics-company.com
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585. 001 813-248-0585

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling:
- Trimethylolpropane, ethoxylated, esters with acrylic acid
- Glycerol, propoxylated, esters with acrylic acid
- 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid
- · Hazard statements
- H317 May cause an allergic skin reaction.
- · Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

(Contd. on page 2)

[—] US

Chemicals

Printing date 08/08/2022


Safety Data Sheet acc. to OSHA HCS

Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 1)



< Skin Corrosion 1A. H314 🔥 Acute Toxicity - Oral 4, H302

us



Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14

Printing date 08/08/2022

Trade name: SELF SEALER WB UV CLEAR 20 GL

| | | | (Contd. of page 2) |
|------|---------|---|--------------------|
| 6843 | 39-49-6 | c16-18 alcohols ethoxylated | <0.5% |
| | | Acute Toxicity - Oral 3, H301 Eye Damage 1, H318 | |
| 5596 | 65-84-9 | a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) | ≥0.00025-<0.0015% |
| | | Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 Skin Corrosion 1B, H314; Eye Damage 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Sensitization - Skin 1A, H317 | |

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) \cdot *After inhalation:*

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed Allergic reactions
 - For symptoms and effects caused by substances, refer to Section 11.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture
- In case of fire, the following can be released: Nitrogen oxides (NOx)
- Carbon monoxide (CO) • Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)

Version number 6

Reviewed on 07/26/2022

Printing date 08/08/2022

Chemicals

vis technole

Product number HUM5AA14

Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 3)

```
· Protective equipment:
```

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources · Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation.

· Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| • PAC-1: | | |
|------------|--------------------------------------|---------------------------------------|
| 7631-86-9 | silicon dioxide, chemically prepared | 18 mg/m³ |
| 111-90-0 | D Diethylene glycol monoethyl ether | |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 30 ppm |
| 111-76-2 | 2-butoxyethanol | 60 ppm |
| 68439-49-6 | c16-18 alcohols ethoxylated | 3.8 mg/m ³ |
| 121-44-8 | triethylamine | 1 ppm |
| 68439-49-6 | c16-18 alcohols ethoxylated | 3.8 mg/m [:] |
| · PAC-2: | | · · · · · · · · · · · · · · · · · · · |
| 7631-86-9 | silicon dioxide, chemically prepared | 740 mg/m |
| 111-90-0 | Diethylene glycol monoethyl ether | 100 ppm |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 33 ppm |
| 111-76-2 | 2-butoxyethanol | 120 ppm |
| 68439-49-6 | c16-18 alcohols ethoxylated | 42 mg/m ³ |
| 121-44-8 | triethylamine | 170 ppm |
| 68439-49-6 | 6 c16-18 alcohols ethoxylated 42 r | |
| • PAC-3: | | |
| 7631-86-9 | silicon dioxide, chemically prepared | 4,500 mg/m |
| 111-90-0 | Diethylene glycol monoethyl ether | 450 ppm |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 200 ppm |
| 111-76-2 | 2-butoxyethanol | 700 ppm |
| 68439-49-6 | c16-18 alcohols ethoxylated | 250 mg/m ³ |
| 121-44-8 | triethylamine | 1,000 ppm |
| 68439-49-6 | c16-18 alcohols ethoxylated | 250 mg/m ³ |

(Contd. on page 5)



Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14

Printing date 08/08/2022

Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 4)

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - Requirements to be met by storerooms and receptacles:
 - Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
 - In cases where there is no reported expiration date , it means that the product must be used within 8 months.
 - Take on temperature greater than 5 ° C
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

- · Components with limit values that require monitoring at the workplace:
- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

| | 90-0 Diethylene glycol monoethyl ether |
|-------|---|
| WEE | L Long-term value: 25 ppm |
| 112-: | 34-5 2-(2-butoxyethoxy)ethanol |
| TLV | Long-term value: 10* ppm *Inhalable fraction and vapor |
| 111- | 76-2 2-butoxyethanol |
| PEL | Long-term value: 240 mg/m³, 50 ppm Skin |
| REL | Long-term value: 24 mg/m³, 5 ppm Skin |
| TLV | Long-term value: 20 ppm BEI, A3 |
| 121-4 | 44-8 triethylamine |
| PEL | Long-term value: 100 mg/m³, 25 ppm |
| TLV | Short-term value: 1 ppm Long-term value: 0.5 ppm Skin, A4 |
| | · Ingredients with biological limit values: |
| 111- | 76-2 2-butoxyethanol |
| BEI | 200 mg/g creatinine |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: Butoxyacetic acid (BAA) (with hydrolysis) |
| L | (Contd. on page 6) |

Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 5)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- Breathing equipment: Short term filter device:



Suitable respiratory protective device recommended.

Filter A • Protection of hands:



Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

| Information on basic physical and | chemical properties | |
|-----------------------------------|------------------------------------|--|
| · General Information | | |
| · Appearance: · Form: | Fluid | |
| · Color: | According to product specification | |
| · Odor: | Characteristic | |
| · Odor threshold: | Not determined. | |
| · pH-value: | Mixture is non-polar/aprotic. | |
| r · · · · · · · · · · · · | Range: 7 - 9 | |
| · Change in condition | | |
| • Melting point/Melting range: | Undetermined. | |
| · Boiling point/Boiling range: | 100 °C (212 °F) | |
| · Flash point: | 100 °C (212 °F) | |
| · Flammability (solid, gaseous): | Not applicable. | |
| · Ignition temperature: | >370 °C (>698 °F) | |

iVM Chemicals

Printing date 08/08/2022



Printing date 08/08/2022

Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

| | | (Contd. of page 6 |
|---|--|-------------------|
| · Decomposition temperature: | Not determined. | |
| · Auto igniting: | Product is not selfigniting. | |
| · Danger of explosion: | Product does not present an explosion haze | ard. |
| · Explosion limits: | | |
| - Lower: | Not determined. | |
| · Upper: | Not determined. | |
| · Vapor pressure at 20 °C (68 °F): | 0 hPa | |
| • Density (+/- 0,03) at 20 °C (68 °F): | 1.04 g/cm³ (8.679 lbs/gal) | |
| · Relative density | Not determined. | |
| · Vapor density | Not determined. | |
| • Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| • Water: | Fully miscible. | |
| · Partition coefficient (n-octanol/water |): Not determined. | |
| · Viscosity: | | |
| · Dynamic: | Not determined. | |
| • <i>Kinematic at 20</i> • <i>C</i> (68 • <i>F</i>): | 60 s (ISO 6 mm) | |
| · Oxidising properties: | N.A. | |
| · Solvent content: | | |
| · Water: | 57.3 % | |
| · VOC content: | 3.07 % | |
| | 31.9 g/l / 0.27 lb/gal | |
| · Solids content: | 39.6 % | |
| · Other information (HAPS) | | |
| 111-90-0 Diethylene glycol monoethyl | lether | 0.5-1% |
| 112-34-5 2-(2-butoxyethoxy)ethanol | | 0.5-1% |
| 121-44-8 triethylamine | | <0.5% |
| 110-80-5 2-ethoxyethanol | | <0.01% |
| • Other information | No further relevant information available. | • |

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

us



Version number 6 Re

Reviewed on 07/26/2022

Printing date 08/08/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 7)

| | | cological effects |
|------------------------|------------------------------|--|
| · Acute to | | |
| | | es that are relevant for classification: |
| | | y Estimate) |
| Oral | LD50 | 48,754 mg/kg |
| Dermal | LD50 | 333,333 mg/kg (rabbit) |
| | | 6,264 mg/l (mouse) |
| 28961-43- | | ylolpropane, ethoxylated, esters with acrylic acid |
| Oral | LD50 | 2,001 mg/kg (mouse) |
| Dermal | LD50 | 13,201 mg/kg (rabbit) |
| | | y-2-methylpropiophenone |
| Oral | LD50 | 1,694 mg/kg (mouse) |
| Dermal | LD50 | 6,929 mg/kg (mouse) |
| | - | e glycol monoethyl ether |
| Oral | LD50 | 6,031 mg/kg (mouse) |
| Dermal | LD50 | 9,143 mg/kg (rabbit) |
| | • | yethoxy)ethanol |
| Oral | LD50 | 6,600 mg/kg (mouse) |
| Dermal | LD50 | 2,764 mg/kg (rabbit) |
| | 2-butoxye | |
| Oral | LD50 | 1,200 mg/kg (ATE) |
| | | 1,480 mg/kg (mouse) |
| Dermal | LD50 | 1,100 mg/kg (rab) |
| | | 11 mg/l (mouse) |
| | ерохур | propylidenediphenol, oligomeric reaction products with 1-chloro-2, ropane, esters with acrylic acid |
| Oral | LD50 | 2,001 mg/kg (mouse) |
| Dermal | LD50 | 2,001 mg/kg (rabbit) |
| 121-44-8 1 | triethylam | ine |
| Oral | LD50 | 730 mg/kg (mouse) |
| Dermal | LD50 | 580 mg/kg (rabbit) |
| | | 10.9 mg/l (mouse) |
| | nary irritan on the skin: | t effect: No irritant effect. |
| | | No irritating effect. |
| | | Sensitization possible through skin contact. |
| • Addition Irritant | nal toxicolo | ogical information: |
| | ause an alle | ergic skin reaction. |
| - | cinogenic c | - |
| | - | rnational Agency for Research on Cancer - Cl. 1 and 2) |
| | hiald (D) | B-epoxypropoxy)phenyl]propane |



Reviewed on 07/26/2022

Printing date 08/08/2022

Version number 6

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 8)

·NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

| | Trimethylolpropane, ethoxylated, esters with acrylic acid |
|---|--|
| EC50 | 70.7 mg/l (daphnia) 48H |
| LC50 (96h) | 1.95 mg/l (Fish) |
| 7473-98-52 | 2-hydroxy-2-methylpropiophenone |
| EC50 | 119 mg/l (daphnia) (48h) |
| LC50 (96h) | 160 mg/l (Fish) |
| 111-90-0 D | iethylene glycol monoethyl ether |
| LC50 48h | 1,982 mg/l (daphnia) |
| LC50 (96h) | 101 mg/l (Fish) |
| 112-34-5 2- | (2-butoxyethoxy)ethanol |
| EC50 | 1,001 mg/l (daphnia) (48 h) |
| LC50 (96h) | 1,300 mg/l (Leuciscus idus melanotus) |
| 111-76-2 2- | butoxyethanol |
| EC50 | 101 mg/l (daphnia) (24 h) |
| LC50 (96h) | 101 mg/l (Fish) |
| 52408-84-1 | Glycerol, propoxylated, esters with acrylic acid |
| EC50 | 12.2 mg/l (algae) (72 h) |
| | 91.4 mg/l (daphnia) (48 h) |
| LC50 (96h) | 5.74 mg/l (Fish) |
| 55818-57-0 | 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2, |
| | epoxypropane, esters with acrylic acid |
| EC50 | epoxypropane, esters with acrylic acid 105 mg/l (algae) (72h) |
| | |
| EC50 | 105 mg/l (algae) (72h) |
| EC50 LC50 (96h) | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) |
| EC50 LC50 (96h) | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) 101 mg/l (Fish) |
| EC50 LC50 (96h) 121-44-8 tr | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) 101 mg/l (Fish) iethylamine |
| EC50 LC50 (96h) 121-44-8 tr EC50 | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) 101 mg/l (Fish) iethylamine 8 mg/l (algae) (72 h) |
| EC50 LC50 (96h) 121-44-8 tr EC50 LC50 (96h) | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) 101 mg/l (Fish) iethylamine 8 mg/l (algae) (72 h) 17 mg/l (daphnia) (48 h) 36 mg/l (Fish) |
| EC50 LC50 (96h) 121-44-8 tr EC50 LC50 (96h) | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) 101 mg/l (Fish) iethylamine 8 mg/l (algae) (72 h) 17 mg/l (daphnia) (48 h) 36 mg/l (Fish) a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and |
| EC50 LC50 (96h) 121-44-8 tr EC50 LC50 (96h) 55965-84-9 | 105 mg/l (algae) (72h)101 mg/l (daphnia) (48h)101 mg/l (Fish)iethylamine8 mg/l (algae) (72 h)17 mg/l (daphnia) (48 h)36 mg/l (Fish)a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] andmethyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) |
| EC50 LC50 (96h) 121-44-8 tr EC50 LC50 (96h) 55965-84-9 EC50 LC50 (96h) | 105 mg/l (algae) (72h) 101 mg/l (daphnia) (48h) 101 mg/l (Fish) iethylamine 8 mg/l (algae) (72 h) 17 mg/l (daphnia) (48 h) 36 mg/l (Fish) a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) 0.027 mg/l (algae) (72 h) |



Printing date 08/08/2022

Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 9)

| · Substa | nces Easily biodegradable | |
|----------|-----------------------------------|--|
| 111-90-0 | Diethylene glycol monoethyl ether | |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | |
| 111-76-2 | 2-butoxyethanol | |

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

| · UN-Number | |
|--|--|
| · DOT, ADN, IMDG, IATA | Not applicable |
| · Note | Check viscosity and flash point at section 9 |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | Not applicable |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Not applicable |
| · Packing group | |
| · DOT, IMDĠ, IATA | Not applicable |
| · Environmental hazards: | |
| • Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex | ː ll of |
| MARPOL73/78 and the IBC Code | Not applicable. |
| | (Contd. on page |

(Contd. of page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/08/2022

Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

· UN "Model Regulation":

Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Various regulations

| | Section 355 (extremely hazardous substances): | |
|-----------|---|-----------|
| None of t | he ingredients is listed. | |
| | Section 313 (Specific toxic chemical listings) : | |
| | Diethylene glycol monoethyl ether | 0.5-1% |
| | 2-(2-butoxyethoxy)ethanol | 0.5-1% |
| | 2-butoxyethanol | 0.5-1% |
| | triethylamine | <0.5% |
| 110-80-5 | 2-ethoxyethanol | <0.01% |
| 52-51-7 | bronopol (INN) | <0.01% |
| · TSO | CA (Toxic Substances Control Act): | |
| All compo | onents have the value ACTIVE. | |
| • | Hazardous Air Pollutants | |
| 121-44-8 | triethylamine | |
| · Pro | position 65 | |
| | Chemicals known to cause cancer: | |
| None of t | he ingredients is listed. | |
| | Chemicals known to cause reproductive toxicity for females: | |
| None of t | he ingredients is listed. | |
| | Chemicals known to cause reproductive toxicity for males: | |
| 110-80-5 | 2-ethoxyethanol | <0.01% |
| | Chemicals known to cause developmental toxicity: | |
| 110-80-5 | 2-ethoxyethanol | <0.01% |
| · Car | cinogenic categories | |
| | EPA (Environmental Protection Agency) | |
| | 2-butoxyethanol | NL 0.5-19 |
| | TLV (Threshold Limit Value) | |
| | 2-butoxyethanol | A |
| | triethylamine | A |
| | NIOSH-Ca (National Institute for Occupational Safety and He | alth) |
| | he ingredients is listed. | , |

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 12)



Version number 6

Reviewed on 07/26/2022

Product number HUM5AA14 Trade name: SELF SEALER WB UV CLEAR 20 GL

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Printing date 08/08/2022

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

| Department issuing SDS: IVM Chemicals Srl |
|--|
| • Contact: See emergency phone |
| · Date of preparation / last revision 08/08/2022 / 5 |
| · Abbreviations and acronyms: |
| IMDG: International Maritime Code for Dangerous Goods |
| DOT: US Department of Transportation |
| IATA: International Air Transport Association |
| EINECS: European Inventory of Existing Commercial Chemical Substances |
| ELINCS: European List of Notified Chemical Substances |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) |
| NFPA: National Fire Protection Association (USA) |
| HMIS: Hazardous Materials Identification System (USA) |
| VOC: Volatile Organic Compounds (USA, EU) |
| LC50: Lethal concentration, 50 percent |
| LD50: Lethal dose, 50 percent |
| NIOSH: National Institute for Occupational Safety |
| OSHA: Occupational Safety & Health |
| TLV: Threshold Limit Value |
| PEL: Permissible Exposure Limit |
| REL: Recommended Exposure Limit |
| BEI: Biological Exposure Limit |
| Flammable Liquids 2: Flammable liquids – Category 2 |
| Flammable Liquids 4: Flammable liquids – Category 4 |
| Acute Toxicity - Oral 4: Acute toxicity – Category 4 |
| Acute Toxicity - Dermal 2: Acute toxicity – Category 2 |
| Acute Toxicity - Dermal 3: Acute toxicity – Category 3 |
| Skin Corrosion 1A: Skin corrosion/irritation – Category 1A |
| Skin Corrosion 1B: Skin corrosion/irritation – Category 1B |
| Skin Irrititation 2: Skin corrosion/irritation – Category 2 |
| Eye Damage 1: Serious eye damage/eye irritation – Category 1 |
| Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A |
| Sensitization - Skin 1: Skin sensitisation – Category 1 |
| Sensitization - Skin 1A: Skin sensitisation – Category 1A |
| Sensitization - Skin 1B: Skin sensitisation – Category 1B Agustic Agustic Agustic I: Hozordovo to the agustic agustic agustic bozord – Category 1 |
| Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2 |
| Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3 |
| Aquatic Acute 5. Hazardous to the aquatic environment - acute aquatic hazard – Category 5 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 |
| Aquatic Onronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 |
| Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 |
| · Sources |
| |
| REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE |
| COUNCIL and following amendments |
| Agency ECHA web site |
| |
| INRS Fiche Toxicologique |
| IARC International agency for research on cancer |

IARC International agency for research on cancer * Data compared to the previous version altered.

US -