

1 Identification

- **Product identifier**
 - *Product number* TJ1831
 - *Trade name:* **CLEAR UV SEALER**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 4	H227 Combustible liquid. Flam. Liq. 4
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.
Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Single Exposure 3H335	May cause respiratory irritation.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Oral.
Aquatic Acute 1	H400 Very toxic to aquatic life.
Aquatic Chronic 1	H410 Very toxic to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07 GHS08 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

hexamethylene diacrylate
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate
benzophenone
2,2-dimethoxy-1,2-diphenylethan-1-one
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid
Reaction product of 2-{2-[2-(acryloyloxy)-1-methylethoxy]-1-methylethoxy}-1-methylethyl acrylate and N-ethylethanamine

· Hazard statements

H227 Combustible liquid. Flam. Liq. 4

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 1)

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H335 May cause respiratory irritation.
 H373 May cause damage to the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Oral.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from flames and hot surfaces. . No smoking.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**





HEALTH	2	Health = 2
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

13048-33-4	hexamethylene diacrylate 	≥25-<50%
55818-57-0	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid 	25-<50%
42978-66-5	(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate 	15-19.99%
111497-86-0	Reaction product of 2-[2-[2-(acryloyloxy)-1-methylethoxy]-1-methylethoxy]-1-methylethyl acrylate and N-ethylethanamine 	5-9.99%

(Contd. on page 3)

Product number TJ1831
Trade name: CLEAR UV SEALER

		(Contd. of page 2)
24650-42-8	2,2-dimethoxy-1,2-diphenylethan-1-one ⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373 ⚠ Acute Toxicity - Oral 4, H302 Aquatic Chronic 3, H412	2.5-4.99%
119-61-9	benzophenone ⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<10%
7473-98-5	2-hydroxy-2-methylpropiophenone ⚠ Acute Toxicity - Oral 4, H302 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	2.5-<25%
142-16-5	Bis(2-ethylhexyl) maleate ⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373 ⚠ Aquatic Chronic 1, H410	≥0.025-<0.25%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 3)

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

13048-33-4	hexamethylene diacrylate	3 mg/m
119-61-9	benzophenone	1.5 mg/m

· **PAC-2:**

13048-33-4	hexamethylene diacrylate	170 mg/m
119-61-9	benzophenone	90 mg/m

· **PAC-3:**

13048-33-4	hexamethylene diacrylate	990 mg/m
119-61-9	benzophenone	310 mg/m

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Keep respiratory protective device available.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

(Contd. on page 5)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 4)

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

13048-33-4 hexamethylene diacrylate

WEEL	Long-term value: 1 mg/m
	DSEN

119-61-9 benzophenone

WEEL	Long-term value: 0.5 mg/m
------	---------------------------

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

(Contd. on page 6)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 5)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

250 °C (482 °F)

- **Flash point:**

89 °C (192.2 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

235 °C (455 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Not determined.

- **Explosion limits:**

- **Lower:**

Not determined.

- **Upper:**

Not determined.

- **Vapor pressure at 25 °C (77 °F):**

0 hPa

- **Density (+/- 0,03) at 20 °C (68 °F):**

1.079 g/cm (9.004 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:**

Not determined.

(Contd. on page 7)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 6)

· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	0.62 % 6.7 g/l / 0.06 lb/gal
· Solids content:	99.4 %
· Other information (HAPS)	
79-10-7 acrylic acid	<0.1%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	28,436 mg/kg (mouse)
13048-33-4 hexamethylene diacrylate		
Oral	LD50	5,001 mg/kg (mouse)
Dermal	LD50	3,601 mg/kg (rab)
55818-57-0 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
42978-66-5 (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
111497-86-0 Reaction product of 2-{2-[2-(acryloyloxy)-1-methylethoxy]-1-methylethoxy}-1-methylethyl acrylate and N-ethylethanamine		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
24650-42-8 2,2-dimethoxy-1,2-diphenylethan-1-one		
Oral	LD50	1,470 mg/kg (mouse)
Dermal	LD50	7,101 mg/kg (mouse)

(Contd. on page 8)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 7)

119-61-9 benzophenone

Oral	LD50	2,985 mg/kg (mouse)
Dermal	LD50	3,535 mg/kg (rabbit)

7473-98-5 2-hydroxy-2-methylpropiophenone

Oral	LD50	1,694 mg/kg (mouse)
Dermal	LD50	6,929 mg/kg (mouse)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)

· **Primary irritant effect:**

- *on the skin:* Irritant to skin and mucous membranes.
- *on the eye:* Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Oral.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

119-61-9 benzophenone	2B
-----------------------	----

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information· **Toxicity** Very toxic to aquatic life with long lasting effects.· **Aquatic toxicity:****13048-33-4 hexamethylene diacrylate**

EC50	1.5 mg/l (algae) (72 h)
LC50 48h	2.6 mg/l (daphnia)
LC50 (96h)	10 mg/l (Fish)

55818-57-0 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

EC50	105 mg/l (algae) (72h)
	101 mg/l (daphnia) (48h)
LC50 (96h)	101 mg/l (Fish)

42978-66-5 (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

EC50	29 mg/l (algae) (72 h)
------	------------------------

(Contd. on page 9)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 8)

LC50 (96h)	88.7 mg/l (daphnia) (48h) 10 mg/l (Fish)
111497-86-0 Reaction product of 2-{2-[2-(acryloyloxy)-1-methylethoxy]-1-methylethoxy}-1-methylethyl acrylate and N-ethylethanamine	
EC50	101 mg/l (algae) (72 h) 101 mg/l (daphnia) (48 h)
LC50 (96h)	101 mg/l (Leuciscus idus melanotus)
24650-42-8 2,2-dimethoxy-1,2-diphenylethan-1-one	
EC50	20 mg/l (algae) (72 h) 18 mg/l (daphnia) (48 h)
LC50 (96h)	30 mg/l (Fish)
119-61-9 benzophenone	
EC50	3.5 mg/l (algae) (72 h) 6,784 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)
7473-98-5 2-hydroxy-2-methylpropiophenone	
EC50	119 mg/l (daphnia) (48h)
LC50 (96h)	160 mg/l (Fish)
64742-95-6 Solvent naphtha (petroleum), light arom.	
EC50	1 mg/l (algae) (72 h) 1 mg/l (daphnia) (48 h)
LC50 (96h)	1 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

13048-33-4 hexamethylene diacrylate .

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Very toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.


(Contd. on page 10)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 9)

- **Uncleaned packagings:**
- *Recommendation: Disposal must be made according to official regulations.*

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA · Note 	<p>UN3082</p> <p>Check viscosity and flash point at section 9</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA 	<p>Environmentally hazardous substance, liquid, n.o.s. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid)</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate, 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid, (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate, benzophenone), MARINE POLLUTANT</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (hexamethylene diacrylate, 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid)</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, IMDG, IATA 	 <ul style="list-style-type: none"> · Class · Label · Class · Label
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (IATA): 	<p>Product contains environmentally hazardous substances:</p> <p>Yes</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: 	<p>Warning: Miscellaneous dangerous substances and articles</p> <p>90</p> <p>F-A,S-F</p>

(Contd. on page 11)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 10)

· <i>Stowage Category</i>	A
· <i>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</i>	Not applicable.
· <i>Transport/Additional information:</i>	
· <i>DOT</i>	
· <i>Remarks:</i>	Special marking with the symbol (fish and tree).
· <i>IMDG</i>	
· <i>Limited quantities (LQ)</i>	5L
· <i>Excepted quantities (EQ)</i>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <i>UN "Model Regulation":</i>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (HEXAMETHYLENE DIACRYLATE, 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE, ESTERS WITH ACRYLIC ACID), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

79-10-7	acrylic acid	<0.1%
110-82-7	cyclohexane	≥0.025-<0.1%
25154-52-3	nonylphenol	<0.01%

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

79-10-7	acrylic acid
---------	--------------

· Proposition 65

· Chemicals known to cause cancer:

119-61-9	benzophenone	*	2.5-<10%
----------	--------------	---	----------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 12)

Product number TJ1831
Trade name: CLEAR UV SEALER

(Contd. of page 11)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

110-82-7	cyclohexane	I	≥0.025-<0.1%
----------	-------------	---	--------------

· **TLV (Threshold Limit Value)**

79-10-7	acrylic acid	A4
---------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
 - **Date of preparation / last revision** 09/07/2022 / 65
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - Flammable Liquids 4: Flammable liquids . Category 4
 - Acute Toxicity - Oral 4: Acute toxicity . Category 4
 - Skin Irritation 2: Skin corrosion/irritation . Category 2
 - Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 - Sensitization - Skin 1: Skin sensitisation . Category 1
 - Sensitization - Skin 1B: Skin sensitisation . Category 1B
 - Carcinogenicity 2: Carcinogenicity . Category 2
 - Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3
 - Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1
 - Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2
 - Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3
 - Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3
- **Sources**
 - REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/07/2022

Version number 66

Reviewed on 09/07/2022

Product number TJ1831**Trade name: CLEAR UV SEALER**

(Contd. of page 12)

INRS Fiche Toxicologique
IARC International agency for research on cancer
*. * Data compared to the previous version altered.*

US