

Chemicals

Printing date 08/15/2022

Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

1 Identification

- · Product identifier
 - · Product number PZ338
 - Trade name: <u>BLEU TINT. PASTE</u> • Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture
 Flammable Liquids 2
 Kin Irrititation 2
 Eye Irritation 2A
 Carcinogenicity 2
 Specific Target Organ Toxicity - Single Exposure

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

xylene

n-butyl acetate

ethylbenzene 4-methylpentan-2-one

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

• Precautionary statements P210 Keep

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)



Printing date 08/15/2022

Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE			
P241	(Contd. of page 1) Use explosion-proof electrical/ventilating/lighting/equipment.		
	+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.		
P305+P351	+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P405	Store locked up.		
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.		
· Classification sys	-		
· NFPA ratings (see	cale 0 - 4)		
Fi	ealth = 2 if $e = 3$ eactivity = 0		
· HMIS-ratings (s	cale 0 - 4)		

HEALTH 2]	Health = 2
FIRE 3		Fire = 3
REACTIVITY 0]	Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

123-86-4	n-butyl acetate	15-19.99%
	 Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336 	
1330-20-7	 xylene Flammable Liquids 3, H226 Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412 	10-12.49%
108-65-6	2-methoxy-1-methylethyl acetate Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%
100-41-4	 1-4 ethylbenzene Flammable Liquids 2, H225 Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 Acute Toxicity - Inhalation 4, H332 Aquatic Chronic 3, H412 	
108-10-1	 4-methylpentan-2-one Flammable Liquids 2, H225 Carcinogenicity 2, H351 Acute Toxicity - Inhalation 4, H332; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 	2.5-4.99%

(Contd. on page 3)



Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

- · General information:
 - Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation:*
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

• After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

- For symptoms and effects caused by substances, refer to Section 11.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents:
- Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced. In case of fire, the following can be released: Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources

(Contd. on page 4)

US



Version number 117

Reviewed on 08/15/2022

Product number PZ338

Printing date 08/15/2022

Product number	· PZ338	
Trade name:	BLEU TINT. PA	4STE

Environm	c) ental precautions: Do not allow to enter sewers/ surface or ground water.	ontd. of page 3)
	and material for containment and cleaning up:	
Absorb wit Dispose co Ensure ade	h liquid-binding material (sand, diatomite, acid binders, universal binders, sav ontaminated material as waste according to Section 13. equate ventilation.	vdust).
	n 7 for information on safe handling.	
	n 8 for information on personal protection equipment.	
	n 13 for disposal information. Action Criteria for Chemicals	
· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
108-10-1	4-methylpentan-2-one	75 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
108-10-1	4-methylpentan-2-one	500 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
108-10-1	4-methylpentan-2-one	3000* ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling
 - Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
 - Prevent formation of aerosols.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool, well-ventilated area, away from heat and sources of ignition Provide solvent resistant, sealed floor. Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.



Printing date 08/15/2022

Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

(Contd. of page 4)

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

	Components with limit values that require monitoring at the	workplace:
123-	-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	. Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	0-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	. Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4	
108-	65-6 2-methoxy-1-methylethyl acetate	
WE	EL Long-term value: 50 ppm	
100-	-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3	
108-	10-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m³, 100 ppm	
REL	Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm	
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3	
	· Ingredients with biological limit values:	
1330	0-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids	
		(Contd. on page 6)
		Us

(Contd. of page 5)



Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

> 100-41-4 ethylbenzene BEI 0.15 g/g creatinine

Printing date 08/15/2022

	Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
108-	10-1 4-methylpentan-2-one
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
	 Additional information: The lists that were valid during the creation were used as basis. osure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.
	Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Breathing equipment:
- Short term filter device:



Suitable respiratory protective device recommended.

Filter A • Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)



Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

Printing date 08/15/2022

(Contd. of page 6)

Information on basic physical and o	hemical properties	
· General Information		
· Appearance:		
· Form:	Fluid	20
· Color:	According to product specification Characteristic)[]
· Odor: · Odor threshold:	Not determined.	
	Mixture is non-polar/aprotic.	
· pH-value:		
· Change in condition		
• Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	117 °C (242.6 °F)	
· Flash point:	14 °C (57.2 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	430 °C (806 °F)	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, for air/vapor mixtures are possible.	mation of explosi
· Explosion limits:		
· Lower:	1 Vol %	
· Upper:	10.8 Vol %	
· Vapor pressure at 20 °C (68 °F):	20.2 hPa (15.2 mm Hg)	
• Density (+/- 0,03) at 20 °C (68 °F):	1.052 g/cm³ (8.779 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
\cdot Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water)): Not determined.	
· Viscosity:		
• Dynamic:	Not determined.	
• <i>Kinematic at 20 •C (68 •F):</i>	55 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	39.92 %	
	420.0 g/l / 3.50 lb/gal	
· Solids content:	60.1 %	
Other information (HAPS)		
1330-20-7 xylene		10-12.49
		2.5-4.99%
100-41-4 ethylbenzene		2.0 1.00/



Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

Printing date 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

(Contd. of page 7)

· Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- Possibility of hazardous reactions
 Reacts with oxidizing agents.
 Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- Hazardous decomposition products:

in case of possible formation of combustion: Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

ATE (Acu	te Toxicit	/ Estimate)	
Dermal	LD50	9,426 mg/kg (rabbit)	
		70.6 mg/l (mouse)	
		- · · · ·	
123-86-4 I	n-butyl ac	etate	
Oral	LD50	10,760 mg/kg (mouse)	
Dermal	LD50	14,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	21.1 mg/l (mouse)	
1330-20-7	xylene		
Oral	LD50.	3,523 mg/kg (mouse)	
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)	
	LD50.	12,126 mg/kg (rabbit)	
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)	
	LC50/4h.	27.571 mg/l (mouse)	
108-65-6 2	2-methoxy	r-1-methylethyl acetate	
Oral	LD50	8,532 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (rabbit)	
Inhalative	LC50/4 h	35.7 mg/l (mouse)	
100-41-4 (ethylbenz	ene	
Oral	LD50	3,500 mg/kg (mouse)	
Dermal	LD50	15,486 mg/kg (rabbit)	
Inhalative	LC50/4 h	17.2 mg/l (mouse)	
108-10-1	4-methylp	entan-2-one	
Oral	LD50	2,080 mg/kg (mouse)	
			(Contd. on

US



Printing date 08/15/2022

Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

· Toxicity	
· Aquatic t	oxicity:
123-86-4 n-	butyl acetate
EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
1330-20-7 >	kylene kylene kara kara kara kara kara kara kara kar
EC50	2.2 mg/l (algae)
	(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/15/2022

Printing date 08/15/2022

Version number 117

Product number	PZ338
Trade name:	BLEU TINT. PASTE

		(Contd. of page 9)				
LC50 48h	1 mg/l (daphnia)					
LC50 (96h)	2.6 mg/l (Fish)					
108-65-6 2-	108-65-6 2-methoxy-1-methylethyl acetate					
EC50	1,001 mg/l (algae) (72 h)					
	501 mg/l (daphnia) (48 h)					
LC50 (96h)	134 mg/l (Fish)					
100-41-4 et	hylbenzene					
EC50	438 mg/l (algae) (72h)					
	1.8 mg/l (daphnia) (48 h)					
LC50 (96h)	12.1 mg/l (Fish)					
108-10-1 4-	methylpentan-2-one					
EC50	201 mg/l (daphnia) (48 h)					
LC50 (96h)	180 mg/l (Fish)					
· Persistence	e and degradability No further re	elevant information available.				
· Substance	es Easily biodegradable					
123-86-4	n-butyl acetate					
1330-20-7	xylene					
108-65-6	2-methoxy-1-methylethyl acetate					
100-41-4	ethylbenzene					
108-10-1	4-methylpentan-2-one					
· Bioaccun · Mobility : · Additional · General r Water ha Do not a Danger t	azard class 2 (Self-assessment): I	tion available. hazardous for water er, water course or sewage system. antities leak into the ground.				
• Waste treat • Recommo Must no sewage • Hand ove	t be disposed of together with system. er to hazardous waste disposers.	household garbage. Do not allow product to reach ordance with local state and federal regulations.				
	<i>packagings:</i> endation: Disposal must be made	according to official regulations.				

UN-Number			
· DOT, IMDG, IATA	UN1263		
· Note	Check viscosity and flash point at section 9		



Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

Printing date 08/15/2022

Product number PZ338						
Trade name:	BLEU TINT. PASTE					

UN "Model Regulation":	UN 1263 PAINT, 3, III
· Remarks:	> 30 I: 3, II
· IATA	
· Remarks:	1000 ml > 450 l: 3, ll
	Maximum net quantity per outer packaging
	Maximum net quantity per inner packaging: 3 ml
\cdot Excepted quantities (EQ)	Code: E1
\cdot Limited quantities (LQ)	5L
·IMDG	
· DOT · Remarks:	> 450 I: 3 F1, II
Transport/Additional information:	
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	r II of Not applicable.
· Stowage Category	A
• EMS Number:	<i>F-E,<u>S-E</u></i>
Special precautions for user · Hazard identification number (Keml	Warning: Flammable liquids ler code): -
· Marine pollutant:	No Morningu Elerenceble liquide
Environmental hazards:	A.L.
Packing group · DOT, IMDG, IATA	<i>III</i>
· Label	3
· Class	3 Flammable liquids
· IMDG, IATA	
· Label	3
· Class	3 Flammable liquids
· Class · Label	3 Flammable liquids 3
FLAMMARE LOUD	
·DOT	
Transport hazard class(es)	
· IMDG, IATA	PAINT
	Paint
UN proper shipping name	

(Contd. on page 12)



Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

Printing date 08/15/2022

(Contd. of page 11)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or
mixture
Requirements of Federal Register

· Various regulations

· SARA

· SAK				
	ection 355 (extremely hazardous substances):			
None of th	e ingredients is listed.			
· S	ection 313 (Specific toxic chemical listings) :			
1330-20-7	xylene		10-	12.49%
100-41-4	ethylbenzene		2.5-	4.99%
108-10-1	4-methylpentan-2-one		2.5-	4.99%
· TSC	A (Toxic Substances Control Act):			
All compor	nents have the value ACTIVE.			
· H	lazardous Air Pollutants			
1330-20-7	xylene			
100-41-4	ethylbenzene			
108-10-1	4-methylpentan-2-one			
-	osition 65			
	hemicals known to cause cancer:			
	ethylbenzene	,		-4.99%
108-10-1	4-methylpentan-2-one	,	2.5	-4.99%
· (hemicals known to cause reproductive toxicity for females:			
70657-70-4	2-methoxypropyl acetate			<0.1%
· (hemicals known to cause reproductive toxicity for males:			
None of th	e ingredients is listed.			
· (hemicals known to cause developmental toxicity:			
108-10-1	4-methylpentan-2-one		2.5	-4.99%
· Carc	inogenic categories			
	PA (Environmental Protection Agency)			
1330-20-7	xylene	1	10-	12.49%
100-41-4	ethylbenzene	D	2.5	-4.99%
108-10-1	4-methylpentan-2-one	Ι	2.5	-4.99%
· 7	LV (Threshold Limit Value)	-		
1330-20-7	xylene			A4
100-41-4	ethylbenzene			A3
· N	IOSH-Ca (National Institute for Occupational Safety and Health)			
None of th	e ingredients is listed.			

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 08/15/2022

Safety Data Sheet acc. to OSHA HCS

Version number 117

Reviewed on 08/15/2022

Product number PZ338 Trade name: BLEU TINT. PASTE

(Contd. of page 12)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 08/15/2022 / 116

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids - Category 2 Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Dermal 4: Acute toxicity - Category 4 Skin Irrititation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2 Aspiration Hazard 1: Aspiration hazard - Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site

INRS Fiche Toxicologique IARC International agency for research on cancer •* Data compared to the previous version altered.