

1 Identification

- **Product identifier**
 - *Product number* HNS703
 - *Trade name:* **CLEAR WB EXT IMPREGNATOR**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Sensitization - Skin 1 H317 May cause an allergic skin reaction.
 Aquatic Acute 2 H401 Toxic to aquatic life.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*



GHS07

- *Signal word* Warning
- *Hazard-determining components of labeling:*
2-methyl-2H-isothiazol-3-one
3-Iodo-2-propynylbutylcarbamate
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
- *Hazard statements*
H317 May cause an allergic skin reaction.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.
- *Precautionary statements*
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Product number HNS703

Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 1)

Classification system:

· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 1
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0
FIRE 1 Fire = 1
REACTIVITY 0 Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

Dangerous components:

34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	1-<5%
100-79-8	2,2-dimethyl-1,3-dioxolan-4-ylmethanol ⚠ Eye Irritation 2A, H319	2.5-4.99%
55406-53-6	3-Iodo-2-propynylbutylcarbamate ⚠ Acute Toxicity - Inhalation 3, H331 ⚠ Specific Target Organ Toxicity - Repeated Exposure 1, H372 ⚠ Eye Damage 1, H318 ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) ⚠ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.5-<1%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irritation 2A, H319	0.5-1%
	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) ⚠ Aquatic Chronic 2, H411 ⚠ Sensitization - Skin 1, H317	≥0.25-<0.5%
1336-21-6	ammonia ⚠ Skin Corrosion 1B, H314 ⚠ Aquatic Acute 1, H400	<0.25%
2682-20-4	2-methyl-2H-isothiazol-3-one ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ⚠ Sensitization - Skin 1, H317	≥0.0015-<0.01%

US

(Contd. on page 3)

Product number HNS703

Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 2)

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)

Product number HNS703

Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 3)

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· PAC-1:		
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
100-79-8	2,2-dimethyl-1,3-dioxolan-4-ylmethanol	3.9 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/m
55406-53-6	3-Iodo-2-propynylbutylcarbamate	3.3 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
1336-21-6	ammonia	61 ppm

· PAC-2:		
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
100-79-8	2,2-dimethyl-1,3-dioxolan-4-ylmethanol	43 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m
55406-53-6	3-Iodo-2-propynylbutylcarbamate	36 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
1336-21-6	ammonia	330 ppm

· PAC-3:		
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
100-79-8	2,2-dimethyl-1,3-dioxolan-4-ylmethanol	260 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m
55406-53-6	3-Iodo-2-propynylbutylcarbamate	220 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
1336-21-6	ammonia	2,300 ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** None.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

US

(Contd. on page 5)

Product number HNS703

Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³ , 100 ppm
Skin

REL Short-term value: 900 mg/m³ , 150 ppm
Long-term value: 600 mg/m³ , 100 ppm
Skin

TLV Long-term value: NIC-50 ppm
(Skin)

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10* ppm
*Inhalable fraction and vapor

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Product number **HNS703**
Trade name: **CLEAR WB EXT IMPREGNATOR**

(Contd. of page 5)

 · *Eye protection:* Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Mixture is non-polar/aprotic.

Range: 7 - 9

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

100 °C (212 °F)

· Flash point:

96 °C (204.8 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

270 °C (518 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product does not present an explosion hazard.

· Explosion limits:

· Lower:

1.1 Vol %

· Upper:

14 Vol %

· Vapor pressure at 20 °C (68 °F):

0.4 hPa (0.3 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F):

1.004 g/cm (8.378 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Fully miscible.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

21 s (ISO 4 mm)

· Oxidising properties:

N.A.

· Solvent content:

· Water:

83.9 %

· VOC content:

7.02 %

70.5 g/l / 0.59 lb/gal

· Solids content:

9.0 %

· Other information (HAPS)

112-34-5 | 2-(2-butoxyethoxy)ethanol

0.5-1%

(Contd. on page 7)

US

Product number HNS703
Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 6)

143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
----------	-------------------------------------	-------

· *Other information* No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	83.3 mg/l
------------	----------	-----------

34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)

100-79-8 2,2-dimethyl-1,3-dioxolan-4-ylmethanol

Oral	LD50	7,000 mg/kg (mouse)
Inhalative	LC50	1,001 mg/l (daphnia) (24 h) 16,700 mg/l (Fish) (96 h)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

Oral	LD50	500 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (mouse)

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Oral	LD50	5,001 mg/kg (mouse) (OECD - 401)
Dermal	LD50	2,001 mg/kg (mouse) (OECD - 402)

1336-21-6 ammonia

Oral	LD50	3,500 mg/kg (mouse)
------	------	---------------------

2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)

(Contd. on page 8)

Product number HNS703

Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 7)

Inhalative LC50/4 h 0.53 mg/l (mouse)

· **Primary irritant effect:**

· on the skin: No irritant effect.

· on the eye: No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

Irritant

May cause an allergic skin reaction.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity** Harmful to aquatic life with long lasting effects.

· **Aquatic toxicity:**

34590-94-8 (2-methoxymethylethoxy)propanol

EC50 970 mg/l (algae) (72 h)

1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50 22 mg/l (algae) (72 h)

0.16 mg/l (daphnia) (48 h)

LC50 (96h) 67 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50 1,001 mg/l (daphnia) (48 h)

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

EC50 101 mg/l (algae) (72h)

4 mg/l (daphnia) (OECD linee guida 202 parte 1)

LC50 (96h) 2.8 mg/l (Leuciscus idus melanotus) (OECD linee guida 203)

1336-21-6 ammonia

EC50 101 mg/l (daphnia) (96 h)

LC50 (96h) 0.89 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

34590-94-8 (2-methoxymethylethoxy)propanol .

112-34-5 2-(2-butoxyethoxy)ethanol .

(Contd. on page 9)

Product number HNS703
Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 8)

- **Behavior in environmental systems:**
 - *Bioaccumulative potential* No further relevant information available.
 - *Mobility in soil* No further relevant information available.
- **Ecotoxicological effects:**
 - *Remark:* Harmful to fish
- **Additional ecological information:**
 - *General notes:*
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Harmful to aquatic organisms
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - *Recommendation:*
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Hand over to hazardous waste disposers.
 - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
 - *Recommendation:* Disposal must be made according to official regulations.
 - *Recommended cleansing agent:* Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|--|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | Not applicable |
| · Note | Check viscosity and flash point at section 9 |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | Not applicable |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Not applicable |
| · Packing group | |
| · DOT, IMDG, IATA | Not applicable |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Not applicable |

US

(Contd. on page 10)

Product number HNS703
Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 9)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

55406-53-6	3-Iodo-2-propynylbutylcarbamate	≥0.5-<1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
1336-21-6	ammonia	<0.25%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone

(Contd. on page 11)

Product number HNS703
Trade name: CLEAR WB EXT IMPREGNATOR

(Contd. of page 10)

 · **Date of preparation / last revision 08/08/2022 / 9**

 · **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Acute Toxicity - Inhalation 3: Acute toxicity . Category 3

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Eye Damage 1: Serious eye damage/eye irritation . Category 1

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Skin 1: Skin sensitisation . Category 1

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) . Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

 · **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

 · *** Data compared to the previous version altered.**