

1 Identification

- **Product identifier**
 - *Product number* TX70
 - *Trade name:* **PU HARDENER**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

| | |
|---|---|
| <p>Flammable Liquids 2</p> <p>Eye Irritation 2A</p> <p>Sensitization - Skin 1</p> <p>Toxic to Reproduction 2</p> <p>Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.</p> <p>Specific Target Organ Toxicity - Repeated Exposure 2</p> | <p>H225 Highly flammable liquid and vapor.</p> <p>H319 Causes serious eye irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H361 Suspected of damaging fertility or the unborn child.</p> <p>H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.</p> |
|---|---|

· Label elements

- *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger
- *Hazard-determining components of labeling:*
Polyisocyanate HDI/TDI
ethyl acetate
toluene
n-butyl acetate
- *Hazard statements*
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

(Contd. on page 2)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

| | | |
|------------|--|-----------|
| 141-78-6 | ethyl acetate <ul style="list-style-type: none"> Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336 | 40-49.99% |
| 123-86-4 | n-butyl acetate <ul style="list-style-type: none"> Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336 | 25-29.99% |
| 26426-91-5 | Polyisocyanate HDI/TDI <ul style="list-style-type: none"> Eye Irritation 2A, H319; Sensitization - Skin 1, H317 | 20-24.99% |
| 108-65-6 | 2-methoxy-1-methylethyl acetate <ul style="list-style-type: none"> Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336 | 5-9.99% |
| 108-88-3 | toluene <ul style="list-style-type: none"> Flammable Liquids 2, H225 Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412 | 2.5-4.99% |
| 822-06-0 | hexamethylene diisocyanate <ul style="list-style-type: none"> Acute Toxicity - Inhalation 1, H330 Sensitization - Respiratory 1, H334 Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335 | <0.1% |


(Contd. on page 3)

Product number TX70
Trade name: PU HARDENER

26471-62-5 m-tolyldiene diisocyanate

(Contd. of page 2)

<0.1%


 Acute Toxicity - Inhalation 1, H330
 Sensitization - Respiratory 1, H334; Carcinogenicity 2, H351
 Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335
 Aquatic Chronic 3, H412

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

US

(Contd. on page 4)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

| | | |
|----------|---------------------------------|-----------|
| 141-78-6 | ethyl acetate | 1,200 ppm |
| 123-86-4 | n-butyl acetate | 5 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |
| 108-88-3 | toluene | 67 ppm |

- **PAC-2:**

| | | |
|----------|---------------------------------|-----------|
| 141-78-6 | ethyl acetate | 1,700 ppm |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| 108-88-3 | toluene | 560 ppm |

- **PAC-3:**

| | | |
|----------|---------------------------------|-------------|
| 141-78-6 | ethyl acetate | 10000** ppm |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 108-88-3 | toluene | 3700* ppm |

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 5)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 4)

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m , 400 ppm

REL Long-term value: 1400 mg/m , 400 ppm

TLV Long-term value: 400 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m , 150 ppm

REL Short-term value: 950 mg/m , 200 ppm

Long-term value: 710 mg/m , 150 ppm

TLV Short-term value: 150 ppm

Long-term value: 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift

REL Short-term value: 560 mg/m , 150 ppm
 Long-term value: 375 mg/m , 100 ppm

TLV Long-term value: 20 ppm
 BEI, OTO, A4

822-06-0 hexamethylene diisocyanate

REL Long-term value: 0.035 mg/m , 0.005 ppm
 Ceiling limit value: 0.14* mg/m , 0.02* ppm
 *10-min

TLV Long-term value: 0.005 ppm
 BEI

(Contd. on page 6)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 5)

26471-62-5 m-tolyldene diisocyanate

| | |
|-----|---|
| PEL | Ceiling limit value: 0.14 mg/m , 0.02 ppm |
| REL | LFC |
| TLV | Short-term value: (0.14) NIC-0.021* mg/m , (0.02) NIC-0.003* ppm Long-term value: (0.036) NIC-0.007* mg/m , (0.005) NIC-0.001* ppm *(IFV) SEN; NIC-Skin; A3 |

· **Regulatory information**

- PEL: Guide to Occupational Exposure Values (OSHA PELs)
- REL: Guide to Occupational Exposure Values (NIOSH RELs)
- TLV: Guide to Occupational Exposure Values (TLV)
- WEEL: Guide to Occupational Exposure Values (AIHA WEELS)

· **Ingredients with biological limit values:****108-88-3 toluene**

| | |
|-----|--|
| BEI | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |

822-06-0 hexamethylene diisocyanate

| | |
|-----|--|
| BEI | 15 g/g creatinine Medium: urine Time: end of shift Parameter: 1.6-Hexamethylene diamine with hydrolysis (nonspecific) |
|-----|--|

· **Regulatory information BEI:** Guide to Occupational Exposure Values (BEI)· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

(Contd. on page 7)

US

Product number TX70
Trade name: PU HARDENER

(Contd. of page 6)

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (170.6 °F)

· **Flash point:**

-4 °C (24.8 °F)

· **Flammability (solid, gaseous):**

Highly flammable.

· **Auto igniting:**

315 °C (599 °F)

· **Decomposition temperature:**

Not determined.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1.2 Vol %

· **Upper:**

11.5 Vol %

· **Vapor pressure at 20 °C (68 °F):**

97 hPa (72.8 mm Hg)

· **Vapor pressure at 50 °C (122 °F):**

360 hPa (270 mm Hg)

· **Density (+/- 0,03) at 20 °C (68 °F):**

0.973 g/cm (8.12 lbs/gal)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

(Contd. on page 8)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 7)

| | | |
|---|------------------------------------|-----------|
| · <i>Evaporation rate</i> | Not determined. | |
| · <i>Solubility in / Miscibility with</i> | Not miscible or difficult to mix. | |
| · <i>Water:</i> | | |
| · <i>Partition coefficient (n-octanol/water):</i> | Not determined. | |
| · <i>Viscosity:</i> | | |
| · <i>Dynamic:</i> | Not determined. | |
| · <i>Kinematic at 20 °C (68 °F):</i> | 29 s (ISO 3 mm) | |
| · <i>Oxidising properties:</i> | N.A. | |
| · <i>Solvent content:</i> | | |
| · <i>VOC content:</i> | 77.80 % 757.0 g/l / 6.32 lb/gal | |
| · <i>Solids content:</i> | 22.1 % | |
| · Other information (HAPS) | | |
| 108-88-3 | toluene | 2.5-4.99% |
| 822-06-0 | hexamethylene diisocyanate | <0.1% |
| 26471-62-5 | m-tolyldiene diisocyanate | <0.1% |

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**

in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

141-78-6 ethyl acetate

| | | |
|------------|-------------------|-----------------------|
| Oral | LD50 | 4,934 mg/kg (rabbit) |
| Dermal | LD50 | 20,001 mg/kg (rabbit) |
| Inhalative | LC50/4 ore/h/saat | 1,600 mg/l (mouse) |
| | LC0 | 22.6 ppm (mouse) |

123-86-4 n-butyl acetate

| | | |
|------------|-------------------|-----------------------|
| Oral | LD50 | 10,760 mg/kg (mouse) |
| Dermal | LD50 | 14,000 mg/kg (rabbit) |
| Inhalative | LC50/4 ore/h/saat | 21.1 mg/l (mouse) |

(Contd. on page 9)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 8)

| | | |
|---|-------------------|-----------------------|
| 26426-91-5 Polyisocyanate HDI/TDI | | |
| Oral | LD50 | 5,001 mg/kg (mouse) |
| 108-65-6 2-methoxy-1-methylethyl acetate | | |
| Oral | LD50 | 8,532 mg/kg (mouse) |
| Dermal | LD50 | 5,001 mg/kg (rabbit) |
| Inhalative | LC50/4 ore/h/saat | 35.7 mg/l (mouse) |
| 108-88-3 toluene | | |
| Oral | LD50 | 5,000 mg/kg (mouse) |
| Dermal | LD50 | 12,124 mg/kg (rabbit) |
| Inhalative | LC50/4 ore/h/saat | 25.7 mg/l (mouse) |
| 822-06-0 hexamethylene diisocyanate | | |
| Oral | LD50 | 738 mg/kg (mouse) |
| Dermal | LD50 | 7,001 mg/kg (rabbit) |
| Inhalative | LC50/4 ore/h/saat | 0.124 mg/l (mouse) |
| 26471-62-5 m-tolylidene diisocyanate | | |
| Oral | LD50 | 5,110 mg/kg (mouse) |
| Dermal | LD50 | 9,401 mg/kg (rabbit) |
| Inhalative | LC50/4 ore/h/saat | 0.107 mg/l (mouse) |

· **Primary irritant effect:**

· *on the skin:* No irritant effect.

· *on the eye:* Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

Irritant

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

Contains isocyanates. See information supplied by the manufacturer.

As from 24 August 2023 adequate training is required before industrial or professional use.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

| | | |
|------------|---------------------------|----|
| 26471-62-5 | m-tolylidene diisocyanate | 2B |
|------------|---------------------------|----|

· **NTP (National Toxicology Program)**

| | | |
|------------|---------------------------|-------|
| 26471-62-5 | m-tolylidene diisocyanate | <0.1% |
|------------|---------------------------|-------|

· **OSHA-Ca (Occupational Safety & Health Administration)**

| | | |
|------------------------------------|--|--|
| None of the ingredients is listed. | | |
|------------------------------------|--|--|

· **Sensitisation**

Monomers / polymers isocyanate

Particular characteristics / effects; prolonged exposure may irritate the eyes, nose, throat and respiratory tract.

Isocyanate exposure may result in the delayed appearance of respiratory disorders, cough or asthma. Sensitive individuals may show exposure symptoms to isocyanates below workplace TLV values. Prolonged skin contact may result cause irritation and dehydration.

US

(Contd. on page 10)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 9)

12 Ecological information

· Toxicity

· Aquatic toxicity:

141-78-6 ethyl acetate

| | |
|----------------------|---------------------------|
| EC50 | 165 mg/l (daphnia) (48 h) |
| LC50 (96 ore/h/saat) | 230 mg/l (Fish) |

123-86-4 n-butyl acetate

| | |
|----------------------|---|
| EC50 | 397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h) |
| LC50 (96 ore/h/saat) | 18 mg/l (Fish) |

108-65-6 2-methoxy-1-methylethyl acetate

| | |
|----------------------|--|
| EC50 | 1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h) |
| LC50 (96 ore/h/saat) | 134 mg/l (Fish) |

108-88-3 toluene

| | |
|----------------------|---|
| EC50 | 134 mg/l (algae) (96 h) 3.78 mg/l (daphnia) (48 h) |
| LC50 (96 ore/h/saat) | 5.5 mg/l (Fish) |

822-06-0 hexamethylene diisocyanate

| | |
|----------------------|--|
| EC50 | 77.5 mg/l (algae) (72 h) 89.2 mg/l (daphnia) (48 h) |
| LC50 (96 ore/h/saat) | 82.9 mg/l (Fish) |

26471-62-5 m-tolidene diisocyanate

| | |
|----------------------|-------------------------------------|
| EC50 | 12.5 mg/l (daphnia) (48h) |
| LC50 (96 ore/h/saat) | 133 mg/l (Leuciscus idus melanotus) |

· **Persistence and degradability** No further relevant information available.

· Substances Easily biodegradable

| | | |
|----------|---------------------------------|---|
| 141-78-6 | ethyl acetate | . |
| 123-86-4 | n-butyl acetate | . |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | . |
| 108-88-3 | toluene | . |

· Behavior in environmental systems:

· Bioaccumulative potential

| | | |
|----------|---------------------------------|---|
| 141-78-6 | ethyl acetate | Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 0,68 |
| 123-86-4 | n-butyl acetate | Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 2,3 |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1,2 |
| 108-88-3 | toluene | Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 2,73 |

· Mobility in soil

| | | |
|----------|---------------|--|
| 141-78-6 | ethyl acetate | Basso potenziale di adsorbimento nel suolo |
|----------|---------------|--|

(Contd. on page 11)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 10)

| | | |
|----------|---------|--|
| 108-88-3 | toluene | Coefficiente di assorbimento normalizzato del carbonio organico (Log Koc): 205 |
|----------|---------|--|

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· DOT, IMDG, IATA

UN1263

· Note

Check viscosity and flash point at section 9

· **UN proper shipping name**

· DOT

Paint

· IMDG, IATA

PAINT

· **Transport hazard class(es)**

· DOT



· Class

3 Flammable liquids

· Label

3

· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· **Packing group**

· DOT, IMDG, IATA

II

(Contd. on page 12)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 11)

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E, S-E

· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· **Various regulations**

· SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

| | | |
|------------|----------------------------|-----------|
| 108-88-3 | toluene | 2.5-4.99% |
| 822-06-0 | hexamethylene diisocyanate | <0.1% |
| 26471-62-5 | m-tolyldiene diisocyanate | <0.1% |

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

| | | |
|----------|----------------------------|--|
| 108-88-3 | toluene | |
| 822-06-0 | hexamethylene diisocyanate | |

· **Proposition 65**

· **Chemicals known to cause cancer:**

| | | | |
|------------|---------------------------|---|-------|
| 26471-62-5 | m-tolyldiene diisocyanate | * | <0.1% |
|------------|---------------------------|---|-------|

· **Chemicals known to cause reproductive toxicity for females:**

| | | | |
|------------|-------------------------|--|-------|
| 70657-70-4 | 2-methoxypropyl acetate | | <0.1% |
|------------|-------------------------|--|-------|

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

| | | | |
|----------|---------|--|-----------|
| 108-88-3 | toluene | | 2.5-4.99% |
|----------|---------|--|-----------|

(Contd. on page 13)

Product number TX70
Trade name: PU HARDENER

(Contd. of page 12)

· **Carcinogenic categories**

| · EPA (Environmental Protection Agency) | | |
|---|---------------------------|--------------|
| 108-88-3 | toluene | II 2.5-4.99% |
| · TLV (Threshold Limit Value) | | |
| 108-88-3 | toluene | A4 |
| 26471-62-5 | m-tolyldiene diisocyanate | (A4) |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | | |
| None of the ingredients is listed. | | |

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

- **Date of preparation / last revision** 02/12/2024

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Acute Toxicity - Inhalation 1: Acute toxicity . Category 1

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation . Category 1

Sensitization - Skin 1: Skin sensitisation . Category 1

Carcinogenicity 2: Carcinogenicity . Category 2

Toxic to Reproduction 2: Reproductive toxicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2

Aspiration Hazard 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

(Contd. on page 14)



Safety Data Sheet
acc. to OSHA HCS

Printing date 02/12/2024

Version number 481

Reviewed on 02/12/2024

Product number TX70
Trade name: PU HARDENER

(Contd. of page 13)

*. * Data compared to the previous version altered.*

US