

1 Identification

· **Product identifier**

- *Product number* PAS901
- *Trade name:* **WHITE PU SEALER**
 - *Application of the substance / the mixture* For professional use

· **Details of the supplier of the safety data sheet**

- *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

1.3.2 Importer

Name I.C. & S. DISTRIBUTING CO.
Address P.O. BOX 10845
LANCASTER. PA
USA
E-Mail: nelson@ics-company.com

· *Information department:*

Environmental Health and safety office
hseoffice@ivmchemicals.com

· *Emergency telephone number:*

ChemTel Expert Assistance Hotline/MSDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

- isobutyl acetate
- xylene
- 2-methoxy-1-methylethyl acetate
- ethyl acetate
- Fatty acids, tallow, oleylamine compounds

· **Hazard statements**

- H225 Highly flammable liquid and vapor.
 - H317 May cause an allergic skin reaction.
 - H351 Suspected of causing cancer.
 - H361 Suspected of damaging fertility or the unborn child.
 - H336 May cause drowsiness or dizziness.
 - H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- Route of exposure: Oral, Inhalation.

· **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

110-19-0	isobutyl acetate	10-12.49%
	Flam. Liq. 2, H225 STOT SE 3, H336	

(Contd. on page 3)

Product number PAS901
Trade name: WHITE PU SEALER

		(Contd. of page 2)
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	5-9.99%
1330-20-7	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	2.5-4.99%
141-78-6	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	2.5-4.99%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332 Aquatic Chronic 3, H412	0.5-1%
77-99-6	propylidynetrimehanol ⚠ Repr. 2, H361	≥0.1-<0.5%
	Fatty acids, tallow, oleylamine compounds ⚠ Acute Tox. 3, H301 ⚠ STOT RE 2, H373 ⚠ Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥0.1-<0.5%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

(Contd. on page 4)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:**
 Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
 During heating or in case of fire poisonous gases are produced.
 In case of fire, the following can be released:
 Nitrogen oxides (NO_x)
 Carbon monoxide (CO)
- **Advice for firefighters**
 Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
- **Protective equipment:**
 Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to Section 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
471-34-1	calcium carbonate	45 mg/m
110-19-0	isobutyl acetate	450 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
141-78-6	ethyl acetate	1,200 ppm
100-41-4	ethylbenzene	33 ppm

· PAC-2:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
471-34-1	calcium carbonate	210 mg/m
110-19-0	isobutyl acetate	1300* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
141-78-6	ethyl acetate	1,700 ppm
100-41-4	ethylbenzene	1100* ppm

(Contd. on page 5)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 4)

· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
471-34-1	calcium carbonate	1,300 mg/m
110-19-0	isobutyl acetate	7500** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
141-78-6	ethyl acetate	10000** ppm
100-41-4	ethylbenzene	1800* ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

- Store in a cool, well-ventilated area, away from heat and sources of ignition
- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
- At this time, the other constituents have no known exposure limits.

110-19-0 isobutyl acetate

PEL (USA)	Long-term value: 700 mg/m , 150 ppm
-----------	-------------------------------------

(Contd. on page 6)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 5)

REL (USA)	Long-term value: 700 mg/m , 150 ppm
TLV (USA)	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL (USA)	Long-term value: 50 ppm
1330-20-7 xylene	
PEL (USA)	Long-term value: 435 mg/m , 100 ppm
REL (USA)	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV (USA)	Short-term value: 651 mg/m , 150 ppm Long-term value: 434 mg/m , 100 ppm BEI
141-78-6 ethyl acetate	
PEL (USA)	Long-term value: 1400 mg/m , 400 ppm
REL (USA)	Long-term value: 1400 mg/m , 400 ppm
TLV (USA)	Long-term value: 1440 mg/m , 400 ppm
100-41-4 ethylbenzene	
PEL (USA)	Long-term value: 435 mg/m , 100 ppm
REL (USA)	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV (USA)	Long-term value: 87 mg/m , 20 ppm BEI

· **Ingredients with biological limit values:**

1330-20-7 xylene	
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-41-4 ethylbenzene	
BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) - Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Pregnant women should strictly avoid inhalation or skin contact.

(Contd. on page 7)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 6)

- **Breathing equipment:**
Short term filter device:
Filter AX



Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

77 °C (170.6 °F)

· Flash point:

-4 °C (24.8 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

315 °C (599 °F)

· Decomposition temperature:

Not determined.

(Contd. on page 8)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 7)

· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1.1 Vol %	
· Upper:	30 Vol %	
· Vapor pressure at 20 °C (68 °F):	97 hPa (72.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.356 g/cm (11.316 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	101 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	0.1 %	
· VOC content:	28.27 %	
	383.3 g/l / 3.20 lb/gal	
· Solids content:	71.5 %	
· Other information (HAPS)	No further relevant information available.	
1330-20-7	xylene	2.5-4.99%
100-41-4	ethylbenzene	0.5-1%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**

in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

ICS

(Contd. on page 9)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 8)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4h.	27.571 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)

77-99-6 propylidynetrimethanol

Oral	LD50	14,700 mg/kg (mouse)
Dermal	LD50	10,001 mg/kg (mouse)

· Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

Irritant

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· Carcinogenic categories

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula
 Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

(Contd. on page 10)

Product number PAS901**Trade name: WHITE PU SEALER**

(Contd. of page 9)

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	<0.1%
------------	----------------------------	-------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:****110-19-0 isobutyl acetate**

EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

1330-20-7 xylene

EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)

141-78-6 ethyl acetate

EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)

100-41-4 ethylbenzene

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

77-99-6 propylidynetrimethanol

EC50	1,001 mg/l (algae) (72h)
	13,000 mg/l (daphnia) (48h)
LC50 (96h)	1,001 mg/l (Fish)

(Contd. on page 11)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 10)

· **Persistence and degradability** Easily biodegradable

· **Substances Easily biodegradable**

110-19-0	isobutyl acetate	.
108-65-6	2-methoxy-1-methylethyl acetate	.
1330-20-7	xylene	.
141-78-6	ethyl acetate	.
100-41-4	ethylbenzene	.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

- **DOT** NA1263
- **IMDG, IATA** UN1263

· **UN proper shipping name**

- **DOT** Paint
- **IMDG, IATA** PAINT

· **Transport hazard class(es)**

· **DOT**




- **Class** 3 Flammable liquids
- **Label** 3
- **Class** 3 Flammable liquids

(Contd. on page 12)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 11)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user Warning: Flammable liquids	
· Hazard identification number (Kemler code):	-
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	2.5-4.99%
100-41-4	ethylbenzene	0.5-1%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene

(Contd. on page 13)

Product number PAS901
Trade name: WHITE PU SEALER

(Contd. of page 12)

· **Proposition 65**

- **Chemicals known to cause cancer:**
 Quartz (SiO₂) only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	15-19.99%
100-41-4	ethylbenzene	*	0.5-1%
14808-60-7	Quartz (SiO ₂)	*	<0.1%

· **Chemicals known to cause reproductive toxicity for females:**

70657-70-4	2-methoxypropyl acetate		<0.1%
------------	-------------------------	--	-------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	2.5-4.99%
100-41-4	ethylbenzene	D	0.5-1%

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	15-19.99%
14808-60-7	Quartz (SiO ₂)	<0.1%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
 · **Contact:** See emergency phone
 · **Date of preparation / last revision** 06/18/2020 / 163

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety

(Contd. on page 14)

Product number PAS901

Trade name: WHITE PU SEALER

(Contd. of page 13)

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 3: Acute toxicity . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

Skin Sens. 1A: Skin sensitisation . Category 1A

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer