

Printing date 09/14/2022 Version number 63 Reviewed on 09/14/2022

### 1 Identification

- · Product identifier
  - · Product number TW642
  - · Trade name: CLEAR WB 2K SELF-SEALER 50GL
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

001 813-248-0585

## 2 Hazard(s) identification

· Classification of the substance or mixture

Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

- · Label elements
  - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 0



Printing date 09/14/2022 Version number 63

Reviewed on 09/14/2022

**Product number TW642** 

Trade name: CLEAR WB 2K SELF-SEALER 50GL

(Contd. of page 1)

## 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	as components:	
34590-94-8	(2-methoxymethylethoxy)propanol	5-<10%
	Flammable Liquids 4, H227	
57-55-6	propane-1,2-diol	5-9.99%
108-01-0	2-dimethylaminoethanol	1-2.49%
	<ul> <li>Flammable Liquids 3, H226</li> <li>Skin Corrosion 1B, H314</li> <li>Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332</li> </ul>	

### 4 First-aid measures

### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed
    For symptoms and effects caused by substances, refer to Section 11.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

(Contd. on page 3)



Printing date 09/14/2022

Version number 63

Reviewed on 09/14/2022

**Product number TW642** 

Trade name: CLEAR WB 2K SELF-SEALER 50GL

(Contd. of page 2)

### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

### · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

### Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

· PAC-1:				
34590-94-8	4590-94-8 (2-methoxymethylethoxy)propanol		150 ppm	
57-55-6	57-55-6 propane-1,2-diol		mg/m³	
108-01-0	108-01-0 2-dimethylaminoethanol		ррт	
· PAC-2:				
34590-94-8	(2-methoxymethylethoxy)propanol	1700*	1700* ppm	
57-55-6	propane-1,2-diol	1,300	1,300 mg/m³	
108-01-0	2-dimethylaminoethanol	40 ppm		
· PAC-3:				
34590-94-8	(2-methoxymethylethoxy)propanol	9900**	9900** ppm	
<i>57-55-</i> 6	propane-1,2-diol	7,900	7,900 mg/m³	
108-01-0	2-dimethylaminoethanol	72 ppr	72 ppm	

## 7 Handling and storage

#### · Handling:

· Precautions for safe handling

No special precautions are necessary if used correctly.

Protect against electrostatic charges

No special measures required.

· Information about protection against explosions and fires: No special measures required.

### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - Requirements to be met by storerooms and receptacles:

    Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

(Contd. on page 4)



Printing date 09/14/2022 Version number 63 Reviewed on 09/14/2022

**Product number TW642** 

Trade name: CLEAR WB 2K SELF-SEALER 50GL

(Contd. of page 3)

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### 34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm

Skin

REL Short-term value: 900 mg/m³, 150 ppm

Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Long-term value: NIC-50 ppm

(Skin)

## 57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m<sup>3</sup>

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 09/14/2022 Version number 63 Reviewed on 09/14/2022

**Product number TW642** 

Trade name: CLEAR WB 2K SELF-SEALER 50GL

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

-6	al anni ant muse months a
nformation on basic physical and on General Information	cnemical properties
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic. Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	230 °C (446 °F)
$\cdot$ Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	14 Vol %
· Vapor pressure at 20 °C (68 °F):	0.6 hPa (0.5 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1 g/cm³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water	·): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	21 s (ISO 4 mm)
· Oxidising properties:	N.A.
· Solvent content:	00.0.07
· Water:	62.6 %
· VOC content:	11.19 % 111.9 g/l / 0.93 lb/gal

(Contd. on page 6)



Printing date 09/14/2022

Version number 63

Reviewed on 09/14/2022

**Product number TW642** 

Trade name: **CLEAR WB 2K SELF-SEALER 50GL** 

(Contd. of page 5)

26.2 % · Solids content: · Other information (HAPS) None of the ingredients is listed. · Other information No further relevant information available.

## 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects

· Acute to	oxicity:		
· LD/	· LD/LC50 values that are relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	115,753 mg/kg (mouse)	
Dermal	LD50	119,276 mg/kg	
Inhalative	LC50/4 h	597 mg/l (mouse)	
34590-94-	34590-94-8 (2-methoxymethylethoxy)propanol		
Oral	LD50	5,135 mg/kg (mouse)	
Dermal	LD50	19,020 mg/kg (rabbit)	
57-55-6 p	57-55-6 propane-1,2-diol		
Oral	LD50	20,000 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
108-01-0	108-01-0 2-dimethylaminoethanol		
Oral	LD50	1,183 mg/kg (mouse)	
Dermal	LD50	1,219 mg/kg (rabbit)	
Inhalative	LC50/4 h	6.1 mg/l (mouse)	
· Prin	· Primary irritant effect:		

- - · on the skin: Irritant to skin and mucous membranes.
  - · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Irritant

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 7)



Printing date 09/14/2022 Version number 63 Reviewed on 09/14/2022

**Product number TW642** 

Trade name: CLEAR WB 2K SELF-SEALER 50GL

(Contd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

· Toxicity

· Aquatic toxicity:		
34590-94-8 (2-methoxymethylethoxy)propanol		
970 mg/l (algae) (72 h)		
1,919 mg/l (daphnia) (48 h)		
1,001 mg/l (Fish)		
57-55-6 propane-1,2-diol		
19,000 mg/l (algae) (48 h)		
18,340 mg/l (daphnia) (48 h)		
40,613 mg/l (Fish)		
108-01-0 2-dimethylaminoethanol		
66.1 mg/l (algae) (72 h)		
98.4 mg/l (daphnia) (48 h)		
(		

- · Persistence and degradability No further relevant information available.
  - · Substances Easily biodegradable

34590-94-8 (2-methoxymethylethoxy)propanol . 57-55-6 propane-1,2-diol .

- Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- Additional ecological information:
  - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

### · Waste treatment methods

· Recommendation:

Smaller quantities can be disposed of with household waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 8)



Printing date 09/14/2022

Version number 63

Reviewed on 09/14/2022

**Product number TW642** 

**CLEAR WB 2K SELF-SEALER 50GL** Trade name:

(Contd. of page 7)

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	ː II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- · Various regulations

$\cdot SARA$	4		
· Se	ection 355 (extremely hazardous substances):		
None of the	e ingredients is listed.		
· Se	ection 313 (Specific toxic chemical listings) :		
111-76-2	2-butoxyethanol	<0.1%	
1344-28-1	aluminium oxide	<0.01%	
· TSCA	A (Toxic Substances Control Act):		
All compon	All components have the value ACTIVE.		
·H	lazardous Air Pollutants		
None of the	e ingredients is listed.		

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 09/14/2022 Version number 63 Reviewed on 09/14/2022

**Product number TW642** 

**CLEAR WB 2K SELF-SEALER 50GL** Trade name:

(Contd. of page 8)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcino	genic categories		
· <b>EP</b> A	(Environmental Protection Agency)		
111-76-2 2-b	utoxyethanol	NL	<0.1%
· TLV	(Threshold Limit Value)		
112945-52-5	silicon dioxide		A4
111-76-2	2-butoxyethanol		A3
1344-28-1	aluminium oxide		A4
· NIC	SH-Ca (National Institute for Occupational Safety and Health)		
None of the i	ngredients is listed.		

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 09/14/2022 / 62
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

(Contd. on page 10)

Page 10/10



# Safety Data Sheet acc. to OSHA HCS

Printing date 09/14/2022

Version number 63

Reviewed on 09/14/2022

**Product number TW642** 

Trade name: CLEAR WB 2K SELF-SEALER 50GL

(Contd. of page 9)

INRS Fiche Toxicologique
IARC International agency for research on cancer

\* Data compared to the previous version altered.

- US