## ILVA TECHNICAL DATA SHEET

PRODUCT CODE: WMM5A/SERIES

**DESCRIPTION: WB WHITE SELF-SEALER** 

USES: Furniture, architectural millwork, store fixtures. Offers the best in dry times and leveling, with very good

sanding properties and filling power.

PRODUCT PREPARATION: WMM5A series White Self-Sealer 100 parts by weight 128 parts by volume 1-6 parts by volume

Water 0-5 parts

**APPLICATION SYSTEM:** Spray

**FILM THICKNESS:** 4.4 - 5.2 wet mils

**GENERAL PROPERTIES:** Specific gravity: 1.28+/-5 gr/l

> Solid content (% by weight) 55 +/- 2 by weight Viscosity (at 20°C): 95+/-15 (iso 6)

**DRYING TIME:** All dry times are dependent upon air flow, ambient temperatures, and humidity

(at 20°C/68°F) Drying schedule at room temperature 2-3 hours

Drying time with hot air tunnel 20-30 mins 30-60 mins Dust free/time gel Dry to touch 2-3 hours Dry Hard 6-8 hours Stackable overnight

Sandable after 2-3 hours before applying 2nd coat as topcoat

**GLOSS LEVELS:** WMM5A03D 60 sheen

WMM5A032 50 sheen WMM5A033 30 sheen WMM5A034 20 sheen WMM5A036 10 sheen

SHELF LIFE: 12 Months

STORAGE: Store in a tightly closed container at room temperatures (18 -25°C/64 -75°F) and protect from moisture

and foreign material. Do not store at temperatures below 7°C (45°F)

**DATE OF ISSUANCE:** 8-14, Revised 1-15, 9-16