

Printing date 09/07/2022

Version number 84

Reviewed on 09/07/2022

1 Identification

- · Product identifier
 - · Product number TN030
 - · Trade name: KLIMA WB REGENERATING TOP-COAT
 - \cdot Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number:
- ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

- · GHS label elements
 - The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



- · Signal word Warning
- *Hazard-determining components of labeling:* 2-methyl-2H-isothiazol-3-one adipohydrazide
- Hazard statements
- H317 May cause an allergic skin reaction.
- · Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



LIS



Version number 84

Reviewed on 09/07/2022

Printing date 09/07/2022

Product number TN030 Trade name: KLIMA WB REGENERATING TOP-COAT

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous components:		
112-34-5	2-(2-butoxyethoxy)ethanol	2.5-4.99%
	🚸 Eye Irritation 2A, H319	
1071-93-8	adipohydrazide	≥0.25-<0.5%
	Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 Aquatic Acute 2, H401	
34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	<1%
2682-20-4	2-methyl-2H-isothiazol-3-one	≥0.0015-<0.01%
	 Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Skin Corrosion 1B, H314; Eye Damage 1, H318 Sensitization - Skin 1, H317 	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation:*

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.

• Special hazards arising from the substance or mixture In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

(Contd. on page 3)

US

Version number 84

Review

Reviewed on 09/07/2022

Product number TN030

Printing date 09/07/2022

Trade name: KLIMA WB REGENERATING TOP-COAT

(Contd. of page 2)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binder Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation. Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals 	rs, sawdust).
112-34-5 2-(2-butoxyethoxy)ethanol	30 ppm
34590-94-8 (2-methoxymethylethoxy)propanol	150 ppm
· PAC-2:	
112-34-5 2-(2-butoxyethoxy)ethanol	33 ppm
34590-94-8 (2-methoxymethylethoxy)propanol	1700* ppm
· PAC-3:	
112-34-5 2-(2-butoxyethoxy)ethanol	200 ppm
34590-94-8 (2-methoxymethylethoxy)propanol	9900** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

(Contd. on page 4)

ivm Chemicals

US

Version number 84

Reviewed on 09/07/2022

Printing date 09/07/2022

Product number TN030 Trade name:

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

- · Components with limit values that require monitoring at the workplace:
 - The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 - At this time, the other constituents have no known exposure limits.

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10* ppm *Inhalable fraction and vapor

34590-94-8 (2-methoxymethylethoxy)propanol

- PEL Long-term value: 600 mg/m³, 100 ppm Skin
- Short-term value: 900 mg/m³, 150 ppm REL Long-term value: 600 mg/m³, 100 ppm Skin
- TLV Long-term value: NIC-50 ppm (Skin)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - · Breathing equipment:
 - Short term filter device:



Suitable respiratory protective device recommended.

Filter A · Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

KLIMA WB REGENERATING TOP-COAT



(Contd. of page 3)

Chemicals ngs & polymers technologi

Safety Data Sheet acc. to OSHA HCS

Version number 84

Reviewed on 09/07/2022

Product number TN030

Printing date 09/07/2022

KLIMA WB REGENERATING TOP-COAT Trade name:

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

Information on basic physical and o	chemical properties
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
• Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
r	Range: 7 - 9
· Change in condition	
• Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	225 °C (437 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	0.9 Vol %
· Upper:	5.9 Vol %
· Vapor pressure at 20 °C (68 °F):	0 hPa
• Density (+/- 0,03) at 20 °C (68 °F):	1.01 g/cm³ (8.428 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
• Water:	Fully miscible.
	•
· Partition coefficient (n-octanol/water	
· Viscosity:	
· Dynamic:	Not determined.
• Kinematic at 20 •C (68 •F):	40 s (ISO 4 mm)
• Oxidising properties:	N.A.
· Solvent content:	
· Water:	81.7 %
· VOC content:	4.33 %
	43.7 g/l / 0.36 lb/gal
· Solids content:	13.7 %

Version number 84

Reviewed on 09/07/2022

Product number TN030

Trade name: KLIMA WB REGENERATING TOP-COAT

(Contd. of page 5)

2.5-4.99%

us

· Other information (HAPS)

112-34-5 2-(2-butoxyethoxy)ethanol

• Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

· Acute toxicity:

· LD/	LC50 value	s that are relevant for classification:	
112-34-5 2-(2-butoxyethoxy)ethanol			
Oral	LD50	6,600 mg/kg (mouse)	
Dermal	LD50	2,764 mg/kg (rabbit)	
1071-93-8 adipohydrazide			
Oral	LD50	2,001 mg/kg (mouse)	
34590-94-8 (2-methoxymethylethoxy)propanol			
Oral	LD50	5,135 mg/kg (mouse)	
Dermal	LD50	19,020 mg/kg (rabbit)	
2682-20-4 2-methyl-2H-isothiazol-3-one			
Oral	LD50	200 mg/kg (mouse)	
Dermal	LD50	400 mg/kg (mouse)	
Inhalative	LC50/4 h	0.53 mg/l (mouse)	
 Primary irritant effect: on the skin: No irritant effect. on the eye: No irritating effect. Sensitization: Sensitization possible through skin contact. Additional toxicological information: Irritant May cause an allergic skin reaction. 			
	cinogenic c	0	
		national Agency for Research on Cancer - Cl. 1 and 2)	
5989-27-5 (R)-p-mentha-1,8-diene			
• I	· NTP (National Toxicology Program)		
None of the ingredients is listed.			
			(Contd. on page



Printing date 09/07/2022



Version number 84

Reviewed on 09/07/2022

Product number TN030

Printing date 09/07/2022

Trade name: KLIMA WB REGENERATING TOP-COAT

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:
112-34-5 2-(2-butoxyethoxy)ethanol

EC50 1,001 mg/l (daphnia) (48 h)

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

1071-93-8	adipohydrazide
-----------	----------------

EC50	9.19 mg/l (algae) (72 h)	
	101 mg/l (daphnia) (48 h)	

LC50 (96h) 101 mg/l (Fish)

34590-94-8 (2-methoxymethylethoxy)propanol

- EC50 970 mg/l (algae) (72 h)
 - 1,919 mg/l (daphnia) (48 h)
- LC50 (96h) 1,001 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable

112-34-5 2-(2-butoxyethoxy)ethanol .

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 8)



Version number 84

Reviewed on 09/07/2022

(Contd. of page 7)

Product number TN030

Printing date 09/07/2022

Trade name: KLIMA WB REGENERATING TOP-COAT

14 Transport information · UN-Number · DOT, ADN, IMDG, IATA Not applicable Check viscosity and flash point at section 9 · Note · UN proper shipping name · DOT, ADN, IMDG, IATA Not applicable · Transport hazard class(es) · DOT, ADR, ADN, IMDG, IATA · Class Not applicable Packing group Not applicable · DOT, IMDG, IATA · Environmental hazards: · Marine pollutant: No Special precautions for user Not applicable. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations

· SARA

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings) :

112-34-5 2-(2-butoxyethoxy)ethanol

• TSCA (Toxic Substances Control Act): All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

2.5-4.99%

ivm Chemicals

Safety Data Sheet acc. to OSHA HCS

Printing date 09/07/2022

Version number 84

Reviewed on 09/07/2022

Product number TN030

Trade name: KLIMA WB REGENERATING TOP-COAT

(Contd. of page 8)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- Contact: See emergency phone
 - · Date of preparation / last revision 09/07/2022 / 83 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 3: Acute toxicity - Category 3 Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Eye Damage 1: Serious eye damage/eye irritation - Category 1 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site **INRS Fiche Toxicologique** IARC International agency for research on cancer \cdot * Data compared to the previous version altered.