

Printing date 01/07/2021

Version number 2

Reviewed on 01/05/2021

1 Identification

- · Product identifier
 - · Product number HOG5AA2A
 - · Trade name: CLEAR 2K WB TOP-C 90SH · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier: IVM Chemicals Srl Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - · Information department: Environmental Health and safety office hseoffice@ivmchemicals.com
 - · Emergency telephone number:
 - ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Lia. 4 H227 Combustible liquid. Flam. Liq. 4

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

- · GHS label elements
 - The product is classified and labeled according to the Globally Harmonized System (GHS).
 - · Hazard pictograms Not applicable
 - · Signal word Warning
 - · Hazard statements

H227 Combustible liquid. Flam. Liq. 4

H412 Harmful to aquatic life with long lasting effects.

- · Precautionary statements
- P210 Keep away from flames and hot surfaces. - No smoking.
- P273 Avoid release to the environment.
- Wear protective gloves/protective clothing/eye protection/face protection. P280
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

· Chemical characterization: Mixtures · Description: Mixture: consisting of the following components.

(Contd. on page 2)

US



Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

		(Contd. of page 2
 Dangerou 	us components:	
111-76-2	2-butoxyethanol	5-9.99%
	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-4.99%
	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 	
	 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 	
763-69-9	ethyl 3-ethoxypropionate	2.498%
	🚸 Flam. Liq. 3, H226	
34590-94-8	Dipropylene glycol monomethyl ether	<1%
	Flam. Liq. 4, H227	
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
	1 Eye Irrit. 2A, H319	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 3)

⁻US



Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

(Contd. of page 2)

• Protective	equipment:
Hardbat	with view fi

Printing date 01/07/2021

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Wear protect Ensure ade Keep away Environme Do not allow Inform respe Dilute with p Do not allow Methods al Absorb with Dispose cor Ensure ade Reference See Section	recautions, protective equipment and emergency procedures ctive equipment. Keep unprotected persons away. quate ventilation from ignition sources ntal precautions: v product to reach sewage system or any water course. ective authorities in case of seepage into water course or sewage system. olenty of water. v to enter sewers/ surface or ground water. nd material for containment and cleaning up: liquid-binding material (sand, diatomite, acid binders, universal binders, so thaminated material as waste according to Section 13. quate ventilation. to other sections of 7 for information on safe handling. of 8 for information on personal protection equipment.	
	13 for disposal information.	
	Action Criteria for Chemicals	
· PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

7 Handling and storage

· Handling:

• *Precautions for safe handling* No special precautions are necessary if used correctly. Protect against electrostatic charges

- No special measures required.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

(Contd. on page 4)

US



Safety Data Sheet acc. to OSHA HCS

Version number 2

Reviewed on 01/05/2021

	number HOG5AA2A ne: CLEAR 2K WB TOP-C 90SH
	(Contd. of pa
· Cond	itions for safe storage, including any incompatibilities
	rage:
	Requirements to be met by storerooms and receptacles:
	Observe the label precautions, the expiration date for the use, if not indicated, is f
	delivery date of goods. In cases where there is no reported expiration date, it means that the product must be u
	within 8 months.
	Take on temperature greater than 5 ° C
	Information about storage in one common storage facility: Not required.
	Further information about storage conditions: Keep receptacle tightly sealed.
· Spec	fic end use(s) Those typical of the product and the instructions in the data sheet if require
B Expo	osure controls/personal protection
-	
· Addit	ional information about design of technical systems: No further data; see item 7.
· Conti	ol parameters
	mponents with limit values that require monitoring at the workplace:
	e following constituents are the only constituents of the product which have a PEL, TL
	ner recommended exposure limit.
	this time, the remaining constituent has no known exposure limits.
	6-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm
	Skin
TLV	Long-term value: 97 mg/m³, 20 ppm
	BEI
763-6	9-9 ethyl 3-ethoxypropionate
STEL	Short-term value: 598 mg/m ³
	Long-term value: 299 mg/m³
34590	-94-8 Dipropylene glycol monomethyl ether
PEL	Long-term value: 600 mg/m³, 100 ppm
,	Skin
REL	Short-term value: 900 mg/m³, 150 ppm
	Long-term value: 600 mg/m ³ , 100 ppm
REL	Long-term value: 600 mg/m³, 100 ppm Skin
	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm
REL	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm
REL TLV	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin)
REL TLV 112-3	Long-term value: 600 mg/m ³ , 100 ppm Skin Short-term value: NIC-606 (909) mg/m ³ , NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m ³ , NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol
REL TLV	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin)
REL TLV 112-3 TLV	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor • Ingredients with biological limit values:
REL TLV 112-3 TLV 111-7	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor · Ingredients with biological limit values: 6-2 2-butoxyethanol
REL TLV 112-3 TLV 111-7 BEI 2	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor · Ingredients with biological limit values: 6-2 2-butoxyethanol 700 mg/g creatinine
REL TLV 112-3 TLV 111-7 BEI 2 N	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor • Ingredients with biological limit values: 6-2 2-butoxyethanol 00 mg/g creatinine Medium: urine
REL TLV 112-3 TLV 111-7 BEI 2	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor • Ingredients with biological limit values: 6-2 2-butoxyethanol 00 mg/g creatinine Aedium: urine Time: end of shift
REL TLV 112-3 TLV 111-7 BEI 2 I F	Long-term value: 600 mg/m³, 100 ppm Skin Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm (Skin) 4-5 2-(2-butoxyethoxy)ethanol Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor • Ingredients with biological limit values: 6-2 2-butoxyethanol 00 mg/g creatinine Medium: urine

– US



Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

(Contd. of page 4)

· Exposure controls

- · Personal protective equipment:
 - General protective and hygienic measures: Wash hands before breaks and at the end of work. • Protection of hands:

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

	chemical properties	
· General Information		
· Appearance:		
· Form:	Fluid	
· Color:	According to product specification	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
 Melting point/Melting range: 	Undetermined.	
 Boiling point/Boiling range: 	100 °C (212 °F)	
· Flash point:	85 °C (185 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
· Lower:	0.7 Vol %	
· Upper:	10.6 Vol %	
· Vapor pressure at 20 •C (68 •F):	5 hPa (3.8 mm Hg)	
• Density (+/- 0,03) at 20 °C (68 °F):	1.024 g/cm³ (8.545 lbs/gal)	
· Relative density	Not determined.	



Printing date 01/07/2021

Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

		(Contd. of page 5
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• <i>Kinematic at 20 •C (68 •F):</i>	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	44.0 %	
· VOC content:	13.60 %	
	139.3 g/l / 1.16 lb/gal	
· Solids content:	42.4 %	
· Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol	1	<0.5%
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

• <i>LD</i> /	LC50 value	es that are relevant for classification:
ATE (Acu	te Toxicit	y Estimate)
Oral	LD50	22,989 mg/kg (mouse)
Dermal	LD50	13,119 mg/kg
Inhalative	LC50/4 h	128 mg/l (mouse)
111-76-2	2-butoxye	thanol
Oral	LD50	1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)
		(Contd. on page 7)



Printing date 01/07/2021

Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

		(Contd. of page 6)
763-69-9	ethyl 3-eth	noxypropionate
Oral	LD50	5,001 mg/kg (mouse)
Dermal	LD50	4,080 mg/kg (mouse)
Inhalative	LC50/6 h	999 ppm (mouse)
34590-94-	8 Dipropy	lene glycol monomethyl ether
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
112-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
• 0 • 0 • Sens	on the eye: sitization: N	<i>t effect:</i> No irritant effect. No sensitizing effects known. ogical information:
· Care	cinogenic c	ategories
· 1	ARC (Inter	national Agency for Research on Cancer - Cl. 1 and 2)
None of th	e ingredie	nts is listed.
· 1	NTP (Natio	nal Toxicology Program)
None of th	e ingredie	nts is listed.
· (OSHA-Ca (Occupational Safety & Health Administration)
None of th	e ingredie	nts is listed.

12 Ecological information

 \cdot **Toxicity** Harmful to aquatic life with long lasting effects.

• Aquatic t	-
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
64742-95-6	Solvent naphtha (petroleum), light arom.
EC50	1 mg/l (algae) (72 h)
	1 mg/l (daphnia) (48 h)
LC50 (96h)	1 mg/l (Fish)
763-69-9 et	hyl 3-ethoxypropionate
EC50	115 mg/l (algae) (72 h)
	873 mg/l (daphnia) (48 h)
LC50 (96h)	60.9 mg/l (Fish)
34590-94-8	Dipropylene glycol monomethyl ether
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
	(Contd. on page

US

(Contd. of page 7)



Safety Data Sheet acc. to OSHA HCS

Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A

Printing date 01/07/2021

Product number	HOG5AA2A
Trade name:	CLEAR 2K WB TOP-C 90SH

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

· Persistence and degradability No fu	rther relevant information available.
· Substances Easily biodegradable	
111-76-2 2-butoxyethanol .	
· Behavior in environmental systems	:
· Bioaccumulative potential No further	r relevant information available.
 Mobility in soil No further relevant in 	nformation available.
 Ecotoxical effects: 	
• Remark: Harmful to fish	
 Additional ecological information: 	
· General notes:	
Water hazard class 1 (Self-assessr	
Do not allow undiluted product or	large quantities of it to reach ground water, water course or
seware system	

sewage system.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
· DOT, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not applicable	
Packing group		
· DOT, IMDG, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	all of	
MARPOL73/78 and the IBC Code	Not applicable.	



Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

 (Contd. of page 8)

 • Transport/Additional information:

 • DOT

 • Remarks:
 > 450 l: 3 F1, III

 • IMDG

 • Remarks:
 > 450 l: 3, III

 • UN "Model Regulation":
 Not applicable

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · · Various regulations

· SARA

• Section 355 (extremely hazardous substances):		
None of the ingredients is listed.		
· Section 313 (Specific toxic chemical listings) :		
111-76-2 2-butoxyethanol		5-9.99%
112-34-5 2-(2-butoxyethoxy)ethanol		<0.5%
· TSCA (Toxic Substances Control Act):		
All components have the value ACTIVE.		
· Hazardous Air Pollutants		
None of the ingredients is listed.		
· Proposition 65		
· Chemicals known to cause cancer:		
None of the ingredients is listed.		
• Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
• Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
111-76-2 2-butoxyethanol	NL	5-9.99%
• TLV (Threshold Limit Value established by ACGIH)		
111-76-2 2-butoxyethanol		A3
• NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		
• National regulations: The product is subject to be labeled according with the prevailing version of the	regi	ulations on

hazardous substances.

(Contd. on page 10)

US



Safety Data Sheet acc. to OSHA HCS

Version number 2

Reviewed on 01/05/2021

Product number HOG5AA2A Trade name: CLEAR 2K WB TOP-C 90SH

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl · Contact: See emergency phone · Date of preparation / last revision 01/07/2021 / 1 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Flam. Liq. 4: Flammable liquids - Category 4 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Sources REGULATION (EC) № 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site **INRS Fiche Toxicologique** IARC International agency for research on cancer \cdot * Data compared to the previous version altered. us