

Version number 85 Printing date 08/15/2022

Reviewed on 08/15/2022

1 Identification

- · Product identifier
 - · Product number PF52
 - · Trade name: UNIVERSAL DYE WARM YELLOW
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 3 H226 Flammable liquid and vapor.

Sensitization - Skin 1 H317 May cause an allergic skin reaction. Toxic to Reproduction 1B H360 May damage fertility or the unborn child. Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting

effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

1-methoxy-2-propanol

sodium 3-(p-anilinophenylazo)benzenesulphonate

2-methoxypropanol

· Hazard statements

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 2)



Printing date 08/15/2022 Version number 85 Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 1)

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 3 Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangero	ous components:	
107-98-2	1-methoxy-2-propanol	75-100%
	 Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336 	
587-98-4	sodium 3-(p-anilinophenylazo)benzenesulphonate	10-12.49%
	Toxic to Reproduction 2, H361 Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 Aquatic Acute 2, H401	
1589-47-5	2-methoxypropanol Flammable Liquids 3, H226 Toxic to Reproduction 1B, H360 Eye Damage 1, H318 Skin Irrititation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335	≥0.1-<0.5%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.

(Contd. on page 3)



Printing date 08/15/2022 Version number 85 Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 2)

· Information for doctor:

· Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
107-98-2	1-methoxy-2-propanol	100 ppm
· PAC-2:		
107-98-2	1-methoxy-2-propanol	160 ppm
	(Con	td. on page 4)



Printing date 08/15/2022 Version number 85 Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 3)

· PAC-3:

107-98-2 1-methoxy-2-propanol

660 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm

Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 100 ppm

Long-term value: 50 ppm

A4

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 5)



Printing date 08/15/2022

Version number 85

Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 4)

Store protective clothing separately.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment: Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information (on basic physic	cal and chemica	i properties

· General Information

 \cdot Appearance:

· Form: Fluid

· Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

• pH-value: Mixture is non-polar/aprotic.

· Change in condition

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 120.3 °C (248.5 °F)

• Flash point: $35 \,^{\circ}\text{C} \, (95 \,^{\circ}\text{F})$

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 270 °C (518 °F)

· Decomposition temperature: Not determined.

(Contd. on page 6)



Printing date 08/15/2022 Version number 85 Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

	(Contd. of page
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosiv air/vapor mixtures are possible.
· Explosion limits:	
·Lower:	2.3 Vol %
· Upper:	~20 Vol %
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	0.915 g/cm³ (7.636 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not determined.
· Partition coefficient (n-octanol/water	·): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	89.25 %
	816.6 g/l / 6.82 lb/gal
· Solids content:	10.8 %
Other information (HAPS)	
None of the ingredients is listed.	
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD	/LC50 valu	ues that are relevant for classification:
107-98-2	1-methox	ry-2-propanol
Oral	LD50	4,016 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)

(Contd. on page 7)



Printing date 08/15/2022 Version number 85 Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 6)

Inhalative LC50/4 h 5,001 mg/l (mouse)

- · Primary irritant effect:
 - on the skin: No irritant effect.
 - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

- · Carcinogenic categories
 - · IARC (International Agency for Research on Cancer Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity Harmful to aquatic life with long lasting effects.
 - · Aquatic toxicity:

107-98-2 1-methoxy-2-propanol

EC50 21,100 mg/l (daphnia) (48 h)

LC50 (96h) 6,812 mg/l (Fish)

- Persistence and degradability No further relevant information available.
 - · Substances Easily biodegradable

107-98-2 1-methoxy-2-propanol .

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

(Contd. on page 8)



Printing date 08/15/2022 Version number 85 Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 7)

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number · DOT, IMDG, IATA	UN1263
· Note	Check viscosity and flash point at section 9
UN proper shipping name · DOT · IMDG, IATA	Paint PAINT
Transport hazard class(es)	
· DOT	
PRAMMRIE LIDUS	
· Class	3 Flammable liquids
· Label · Class	3 3 Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
Packing group · DOT, IMDG, IATA	III
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
· Hazard identification number (K · EMS Number:	(emler code): 30 F-E,S-E
· Stowage Category	A
Transport in bulk according to Ani MARPOL73/78 and the IBC Code	nex II of Not applicable.
Transport/Additional information:	
· IMDG	
\cdot Limited quantities (LQ)	5L



Printing date 08/15/2022

Version number 85

Reviewed on 08/15/2022

Product number PF52

Trade name: UNIVERSAL DYE WARM YELLOW

(Contd. of page 8)

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- · Various regulations
 - · SARA
 - · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
 - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

1589-47-5 2-methoxypropanol

≥0.1-<0.5%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
 - · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 08/15/2022

Version number 85

Reviewed on 08/15/2022

Product number PF52

UNIVERSAL DYE WARM YELLOW Trade name:

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 08/15/2022 / 84
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Toxic to Reproduction 1B: Reproductive toxicity - Category 1B

Toxic to Reproduction 2: Reproductive toxicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* Data compared to the previous version altered.