


## 1 Identification


- **Product identifier**
  - *Product number* PI64
  - *Trade name:* **POLYALLILIC WHITE PE SEALER**
    - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
  - *Manufacturer/Supplier:*  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
  - *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.


## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2    H225 Highly flammable liquid and vapor.  
 Eye Irritation 2A        H319 Causes serious eye irritation.  
 Sensitization - Skin 1    H317 May cause an allergic skin reaction.  
 Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.
- **Label elements**
  - *GHS label elements*  
The product is classified and labeled according to the Globally Harmonized System (GHS).
  - *Hazard pictograms*

  
GHS02

  
GHS07

  
GHS08
  - *Signal word* Danger
  - *Hazard-determining components of labeling:*  
methacrylic acid, monoester with propane-1,2-diol  
maleic anhydride
  - *Hazard statements*  
H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H361 Suspected of damaging fertility or the unborn child.
  - *Precautionary statements*

P210                    Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P241                    Use explosion-proof electrical/ventilating/lighting/equipment.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P405                    Store locked up.  
 P501                    Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

**Product number PI64**

**Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 1)

**Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

27813-02-1	methacrylic acid, monoester with propane-1,2-diol ⚠ Eye Irritation 2A, H319; Sensitization - Skin 1, H317	5-9.99%
141-78-6	ethyl acetate ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%
123-86-4	n-butyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%
108-88-3	toluene ⚠ Flammable Liquids 2, H225 ⚠ Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	0.5-1%
57-55-6	propane-1,2-diol	<0.5%
67-56-1	methanol ⚠ Flammable Liquids 2, H225 ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ⚠ Specific Target Organ Toxicity - Single Exposure 1, H370	<0.5%
78-93-3	butanone ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	<0.5%
108-31-6	maleic anhydride ⚠ Sensitization - Respiratory 1, H334 ⚠ Skin Corrosion 1B, H314 ⚠ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.001-<0.1%

US

(Contd. on page 3)

**Product number PI64**

**Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 2)

#### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 3)

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
471-34-1	calcium carbonate	45 mg/m
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
141-78-6	ethyl acetate	1,200 ppm
123-86-4	n-butyl acetate	5 ppm
108-88-3	toluene	67 ppm
57-55-6	propane-1,2-diol	30 mg/m
67-56-1	methanol	530 ppm
78-93-3	butanone	200 ppm

· PAC-2:		
471-34-1	calcium carbonate	210 mg/m
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
141-78-6	ethyl acetate	1,700 ppm
123-86-4	n-butyl acetate	200 ppm
108-88-3	toluene	560 ppm
57-55-6	propane-1,2-diol	1,300 mg/m
67-56-1	methanol	2,100 ppm
78-93-3	butanone	2700* ppm

· PAC-3:		
471-34-1	calcium carbonate	1,300 mg/m
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
141-78-6	ethyl acetate	10000** ppm
123-86-4	n-butyl acetate	3000* ppm
108-88-3	toluene	3700* ppm
57-55-6	propane-1,2-diol	7,900 mg/m
67-56-1	methanol	7200* ppm
78-93-3	butanone	4000* ppm

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 4)

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

- At this time, the remaining constituent has no known exposure limits.

### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 400 ppm

### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

### 108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

### 57-55-6 propane-1,2-diol

WEEL	Long-term value: 10 mg/m
------	--------------------------

### 67-56-1 methanol

PEL	Long-term value: 260 mg/m , 200 ppm
REL	Short-term value: 325 mg/m , 250 ppm Long-term value: 260 mg/m , 200 ppm Skin

(Contd. on page 6)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 5)

TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
<b>78-93-3 butanone</b>	
PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI
<b>108-31-6 maleic anhydride</b>	
PEL	Long-term value: 1 mg/m , 0.25 ppm
REL	Long-term value: 1 mg/m , 0.25 ppm
TLV	Long-term value: 0.01* mg/m DSEN, RSEN;*inh. fraction + vapor, A4

· **Ingredients with biological limit values:**

<b>108-88-3 toluene</b>	
BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
<b>67-56-1 methanol</b>	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
<b>78-93-3 butanone</b>	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

(Contd. on page 7)

**Product number PI64**  
**Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 6)

- **Breathing equipment:**  
Short term filter device:



Suitable respiratory protective device recommended.

Filter A

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

#### · Change in condition

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (170.6 °F)

· **Flash point:**

-17 °C (1.4 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

370 °C (698 °F)

· **Decomposition temperature:**

Not determined.

(Contd. on page 8)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 7)

· <b>Auto igniting:</b>	Product is not selfigniting.	
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· <b>Explosion limits:</b>		
· <b>Lower:</b>	1.2 Vol %	
· <b>Upper:</b>	30 Vol %	
· <b>Vapor pressure at 20 °C (68 °F):</b>	97 hPa (72.8 mm Hg)	
· <b>Density (+/- 0,03) at 20 °C (68 °F):</b>	1.462 g/cm (12.2 lbs/gal)	
· <b>Relative density</b>	Not determined.	
· <b>Vapor density</b>	Not determined.	
· <b>Evaporation rate</b>	Not determined.	
· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>	Not miscible or difficult to mix.	
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.	
· <b>Viscosity:</b>		
· <b>Dynamic:</b>	Not determined.	
· <b>Kinematic at 20 °C (68 °F):</b>	101 s (ISO 6 mm)	
· <b>Oxidising properties:</b>	N.A.	
· <b>Solvent content:</b>		
· <b>VOC content:</b>	14.35 % 209.8 g/l / 1.75 lb/gal	
· <b>Solids content:</b>	85.6 %	
· <b>Other information (HAPS)</b>		
108-88-3	toluene	0.5-1%
67-56-1	methanol	<0.5%
1330-20-7	xylene	<0.1%
108-31-6	maleic anhydride	≥0.001-<0.1%
100-41-4	ethylbenzene	<0.1%
79-10-7	acrylic acid	<0.01%
· <b>Other information</b>	No further relevant information available.	

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**

in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

US

(Contd. on page 9)



**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 8)

## 11 Toxicological information

### · Information on toxicological effects

#### · Acute toxicity:

· LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

Oral	LD50	1,141,346 mg/kg
Inhalative	LC50/4 h	123,269 mg/l (mouse)

#### 27813-02-1 methacrylic acid, monoester with propane-1,2-diol

Oral	LD50	2,001 mg/kg (–)
Dermal	LD50	5,001 mg/kg (–)

#### 141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

#### 123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

#### 108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

#### 57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

#### 67-56-1 methanol

Oral	LD50	1,187 mg/kg (mouse)
Dermal	LD50	17,000 mg/kg (rabbit)
Inhalative	LC50/4 h	128.2 mg/l (mouse)

#### 78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)

#### 108-31-6 maleic anhydride

Oral	LD50	1,090 mg/kg (mouse)
Dermal	LD50	2,620 mg/kg (rabbit)

#### · Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: Irritating effect.

· Sensitization: Sensitization possible through skin contact.

#### · Additional toxicological information:

Irritant

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

(Contd. on page 10)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 9)

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- **Carcinogenic categories**

- Titanium dioxide

- IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

- Ethylbenzene

- From IARC MONOGRAPHS VOLUME 77/2000

- Human carcinogenicity data

- Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

- Evaluation

- There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

- None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

- None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

- 27813-02-1 methacrylic acid, monoester with propane-1,2-diol**

EC50	97.3 mg/l (algae) (72 h)
	131 mg/l (daphnia) (48 h)
LC50 48h	493 mg/l (Fish)

- 141-78-6 ethyl acetate**

EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)

- 123-86-4 n-butyl acetate**

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

- 108-88-3 toluene**

EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)

(Contd. on page 11)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 10)

LC50 (96h)	5.5 mg/l (Fish)
<b>57-55-6 propane-1,2-diol</b>	
EC50	19,000 mg/l (algae) (48 h) 18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)
<b>67-56-1 methanol</b>	
EC50	8,000 mg/l (algae) (72 h) 24,500 mg/l (daphnia) (48 h)
LC50 (96h)	15,400 mg/l (Fish)
<b>78-93-3 butanone</b>	
EC50	2,029 mg/l (algae) (96 h) 308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)
<b>108-31-6 maleic anhydride</b>	
EC50	29 mg/l (algae) (72 h) 42.8 mg/l (daphnia) (48 h)
LC50 (96h)	75 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

141-78-6	ethyl acetate	.
123-86-4	n-butyl acetate	.
108-88-3	toluene	.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.



US

(Contd. on page 12)

**Product number PI64**  
**Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 11)

## 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· DOT, IMDG, IATA</li> <li>· Note</li> </ul>	UN1263  Check viscosity and flash point at section 9
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· DOT</li> <li>· IMDG, IATA</li> </ul>	Paint PAINT
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· DOT</li> </ul>	 <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> <li>· Class</li> <li>· Label</li> </ul>
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	 <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· DOT, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· Marine pollutant:</li> </ul>	No
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· Hazard identification number (Kemler code):</li> <li>· EMS Number:</li> <li>· Stowage Category</li> </ul>	Warning: Flammable liquids - F-E, S-E A
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· DOT</li> <li>· Remarks:</li> </ul>	> 450 l: 3 F1, II
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> <li>· Remarks:</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml > 450 l: 3, II

(Contd. on page 13)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 12)

· IATA

· Remarks:

&gt; 30 l: 3, II

· UN "Model Regulation":

UN 1263 PAINT, 3, III

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· Various regulations

· SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

108-88-3	toluene	0.5-1%
67-56-1	methanol	<0.5%
1330-20-7	xylene	<0.1%
108-31-6	maleic anhydride	≥0.001-<0.1%
100-41-4	ethylbenzene	<0.1%
79-10-7	acrylic acid	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

108-88-3	toluene	
67-56-1	methanol	
1330-20-7	xylene	
108-31-6	maleic anhydride	
100-41-4	ethylbenzene	
79-10-7	acrylic acid	

· **Proposition 65**· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	5-9.99%
100-41-4	ethylbenzene	*	<0.1%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	0.5-1%
67-56-1	methanol	<0.5%

(Contd. on page 14)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 13)

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II	0.5-1%
78-93-3	butanone	I	<0.5%
1330-20-7	xylene	I	<0.1%
100-41-4	ethylbenzene	D	<0.1%

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
112945-52-5	silicon dioxide	A4
108-88-3	toluene	A4
1330-20-7	xylene	A4
108-31-6	maleic anhydride	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	5-9.99%
------------	---	---------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 08/15/2022 / 137

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flammable Liquids 2: Flammable liquids . Category 2  
 Flammable Liquids 3: Flammable liquids . Category 3  
 Acute Toxicity - Oral 3: Acute toxicity . Category 3  
 Acute Toxicity - Oral 4: Acute toxicity . Category 4  
 Skin Corrosion 1B: Skin corrosion/irritation . Category 1B  
 Skin Irritation 2: Skin corrosion/irritation . Category 2  
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A  
 Sensitization - Respiratory 1: Respiratory sensitisation . Category 1  
 Sensitization - Skin 1: Skin sensitisation . Category 1  
 Toxic to Reproduction 2: Reproductive toxicity . Category 2  
 Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) . Category 1

(Contd. on page 15)

**Product number PI64****Trade name: POLYALLILIC WHITE PE SEALER**

(Contd. of page 14)

*Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3*

*Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2*

*Aspiration Hazard 1: Aspiration hazard . Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3*

**• Sources**

**REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments**

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

**• \* Data compared to the previous version altered.**

US