

ILVA TECHNICAL DATA SHEET

PRODUCT SERIES: KLIMA SERIES

PRODUCT CODE: TN030

DESCRIPTION: Klima Regenerator Clear Coat

USES: Used as a field maintenance product. Typically used once a year, or when necessary, on windows, doors, shutters or furniture. Product helps to maintain original performance.

APPLICATION SYSTEM: Clean with water and neutral detergents to remove dust and rain spots. Cleaning products containing acids or ammonia must be absolutely avoided, as they would attack the coating and damage it. If after the cleaning operations, the coating film appears to be in good condition (no cracking), we suggest proceeding with the application of TN030 Regenerator, wiping a cloth soaked in the TN030 on the entire surface.

FILM THICKNESS: 0.8-1.6 mils wet

COATS: One

GENERAL PROPERTIES:	Specific Gravity, gr/cc	1.013+/- .03
	Viscosity as supplied (EN ISO 2431) ISO 3 cup	26 +/-2
	Solids, % by weight:	14+/-2
	Thinner:	Water
	% of dilution:	0-5%

DRYING TIME: At 20°C with ventilation, dry to handle:
(at 20°C/68°F)

Dust Free:	2 hours
Dry to touch:	12 hour
Full dried:	24 hours

(Drying times may vary according to temperature, ventiation and relative humidity)

WARNINGS: KEEP FROM FREEZING

SHELF LIFE: 12 months

STORAGE: Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture and foreign material. Do not store at temperatures below 7°C (45°F)

DATE OF ISSUANCE: 2-18

IC & S, P.O. BOX 10845, LANCASTER, PA 17605
(800) 220-4035

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL, INCLUDING FOR EXAMPLE, THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.