

Printing date 09/23/2022 Version number 212

Reviewed on 09/23/2022

#### 1 Identification

- · Product identifier
  - · Product number PN31
  - · Trade name: WB IMPREGN. FAIR WALNUT
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

#### · Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

Aguatic Chronic 3 H412 Harmful to aguatic life with long lasting effects.

#### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

2-methyl-2H-isothiazol-3-one

3-lodo-2-propynylbutylcarbamate

· Hazard statements

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

(Contd. on page 2)



Printing date 09/23/2022

Version number 212

Reviewed on 09/23/2022

**Product number PN31** 

WB IMPREGN. FAIR WALNUT Trade name:

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

	us components:	
111-76-2	2-butoxyethanol  Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319	2.5-4.99%
	Flammable Liquids 4, H227	
55406-53-6	3-lodo-2-propynylbutylcarbamate  Acute Toxicity - Inhalation 3, H331  Specific Target Organ Toxicity - Repeated Exposure 1, H372  Eye Damage 1, H318  Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1)  ↑ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.5-<1%
<i>57-55-</i> 6	propane-1,2-diol	<0.5%
107-21-1	ethanediol  Oral 4, H302	<0.5%
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol  Eye Damage 1, H318  Sensitization - Skin 1B, H317  Flammable Liquids 4, H227; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥0.1-<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one  ♠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ♠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ♠ Sensitization - Skin 1, H317	≥0.0015-<0.01
	pyridine-2-thiol 1-oxide, sodium salt Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10) Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319	<0.0025%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)  ♠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330  ♠ Skin Corrosion 1B, H314; Eye Damage 1, H318  ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)  ♠ Sensitization - Skin 1A, H317	<0.00025%



Printing date 09/23/2022 Version nu

Version number 212 Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 2)

### 4 First-aid measures

#### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

#### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

#### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

### 6 Accidental release measures

#### · Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)



Printing date 09/23/2022

Version number 212

Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 3)

Ensure adequate ventilation.

#### · Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

· PAC-1:			
111-76-2	2-butoxyethanol	60 ppm	
55406-53-6	3-lodo-2-propynylbutylcarbamate	3.3 mg/m <sup>3</sup>	
57-55-6	propane-1,2-diol		
577-11-7	7-11-7 docusate sodium		
107-21-1	ethanediol	30 ppm	
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	30 mg/m³	
· PAC-2:			
111-76-2	2-butoxyethanol	120 ppm	
55406-53-6	3-lodo-2-propynylbutylcarbamate	36 mg/m³	
<i>57-55</i> -6	propane-1,2-diol	1,300 mg/n	
577-11-7	docusate sodium	63 mg/m³	
107-21-1	ethanediol	150 ppm	
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	330 mg/m³	
· PAC-3:			
111-76-2	2-butoxyethanol	700 ppm	
55406-53-6	3-lodo-2-propynylbutylcarbamate	220 mg/m³	
<i>57-55</i> -6	propane-1,2-diol	7,900 mg/m	
577-11-7	docusate sodium	380 mg/m³	
107-21-1	ethanediol	900 ppm	
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	2,000 mg/m	

## 7 Handling and storage

#### · Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

#### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

(Contd. on page 5)



Printing date 09/23/2022 Version number 212 Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 4)

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111 7	S 2.2 hutevusthenel
111-70	6-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3
57-55-	6 propane-1,2-diol
WEEL	Long-term value: 10 mg/m³
107-21	1-1 ethanediol
TLV	Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only, A4
WEEL	I (2)

### · Ingredients with biological limit values:

#### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves



Printing date 09/23/2022 Version number 212 Review

Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

## 9 Physical and chemical properties

· Information on basic physical and o	chemical properties
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
P-2 · ········	Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
• • • • • • • • • • • • • • • • • • • •	· · · · · · · · · · · · · · · · · · ·
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	10.6 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1.004 g/cm³ (8.378 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water	·); Not determined.
· Viscosity:	
Dynamic:	Not determined.



Printing date 09/23/2022 Version number 212 Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

			(Contd. of page
· Kinemat	ic at 20 °C (68 °F):	29 s (ISO 3 mm)	
· Oxidising p		N.A.	
· Solvent con	tent:		
· Water:		81.8 %	
· VOC content:		4.86 %	
		48.7 g/l / 0.41 lb/gal	
· Solids co	ontent:	13.2 %	
Other informa	ation (HAPS)		
107-21-1 eth			<0.5%
111-90-0 Die	ethylene glycol monoe	ethyl ether	<0.1%
1330-20-7 xyl	ene		<0.1%
98-82-8 cui	mene		<0.01%
112-34-5 2-(	2-butoxyethoxy)ethan	nol	<0.01%
110-80-5 2-6	ethoxyethanol		<0.01%
· Other information		No further relevant information ava	ailable.

## 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects

$\cdot$ $LD_{\ell}$	LC50 value	s that are relevant for classification:	
ATE (Acı	ıte Toxicit	y Estimate)	
Oral	LD50	37,175 mg/kg	
Dermal	LD50	34,077 mg/kg	
Inhalative	LC50/4 h	50.7 mg/l	
111-76-2	2-butoxye	thanol	
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (mouse)	
Dermal	LD50	1,100 mg/kg (rab)	
Inhalative	LC50/4 h	11 mg/l (mouse)	
55406-53	-6 3-lodo-2	-propynylbutylcarbamate	
Oral	LD50	500 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (mouse)	
	1		(Contd. on pag



Printing date 09/23/2022

Version number 212

Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

		(Contd. of page
57-55-6 p	ropane-1,2	2-diol
Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
577-11-7	docusate	sodium
Oral	LD50	3,001 mg/kg (mouse)
Dermal	LD50	2,525 mg/kg (rabbit)
107-21-1	ethanedio	I
Oral	LD50	301 mg/kg (mouse)
	LD50.	7,712 mg/kg (mouse)
Dermal	LD50	3,501 mg/kg (mouse)
		9,530 mg/kg (rabbit)
Inhalative	LC50/6 h	2.6 ppm (mouse)
126-86-3	2,4,7,9-teti	ramethyldec-5-yne-4,7-diol
Oral	LD50	4,600 mg/kg (mouse)
2682-20-4	2-methyl-	-2H-isothiazol-3-one
Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)
3811-73-2	pyridine-	2-thiol 1-oxide, sodium salt
Oral	LD50	1,208 mg/kg (mouse)
Dermal	LD50	1,800 mg/kg (mouse)
Inhalative	LC50/4 h	1.66 mg/l (mouse)

- · Primary irritant effect:
  - on the skin: No irritant effect.
  - · on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

May cause an allergic skin reaction.

· Carcinogenic categories

Carbon Black

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to carbon black but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as paint."

· <b>I</b> .	ARC (International Agency for Research on Cancer - Cl. 1 and 2)	
1333-86-4	Carbon black	2B
98-82-8	cumene	2B
$\cdot N$	TP (National Toxicology Program)	
98-82-8 сเ	ımene	<0.01%
.0	SHA-Ca (Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

110



Printing date 09/23/2022 Version number 212

n number 212 Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 8)

## 12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

· TOXICILY TIE	infinition advance line with long lasting effects.
· Aquatic t	oxicity:
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
55406-53-6	3-lodo-2-propynylbutylcarbamate
EC50	22 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	67 mg/l (Fish)
57-55-6 pro	pane-1,2-diol
EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)
577-11-7 do	ocusate sodium
EC50	82.5 mg/l (algae) (72 h)
	15.2 mg/l (daphnia) (48 h)
LC50 (96h)	49 mg/l (Fish)
107-21-1 et	hanediol
EC50	101 mg/l (daphnia) (48h)
LC50 (96h)	72,860 mg/l (Fish)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
2000	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)
2000 (0011)	o. To man (Fight

- Persistence and degradability No further relevant information available.
  - · Substances Easily biodegradable

111-76-2 2-butoxyethanol .

- Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- Ecotoxical effects:
  - · Remark: Harmful to fish
- · Additional ecological information:
  - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

HS



Printing date 09/23/2022 Version number 212 Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 9)

## 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Smaller quantities can be disposed of with household waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- · Various regulations
  - · SARA

	511101		
	· Sec	ction 355 (extremely hazardous substances):	
	None of the	ingredients is listed.	
	· Sec	ction 313 (Specific toxic chemical listings) :	
Ī	111-76-2	2-butoxyethanol	2.5-4.99%
	55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0.5-<1%

(Contd. on page 11)



Printing date 09/23/2022

Version number 212

Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

107-21-1	ethanediol	(Co	ntd. of pag	je '
	1,2,4-trimethylbenzene		<0.1%	
	Diethylene glycol monoethyl ether		<0.1%	
1330-20-7	, ,		<0.1%	_
	cumene		<0.01%	<u>_</u>
	2-(2-butoxyethoxy)ethanol		<0.01%	
	aluminium oxide		<0.01%	
			<0.01%	-
	(Toxic Substances Control Act):			
	ents have the value ACTIVE.			
•	zardous Air Pollutants			
107-21-1				
1330-20-7	- kylene			
98-82-8	cumene			
· CI Ca	sition 65 semicals known to cause cancer: arbon black only in bound form		* 0	4.0
	Carbon black		* <0.	
98-82-8	cumene		* <0.0	119
	emicals known to cause reproductive toxicity for females:			
None of the	ingredients is listed.			
· Cl	emicals known to cause reproductive toxicity for males:			
110-80-5 2	ethoxyethanol		<0.0	19
· CI	emicals known to cause developmental toxicity:			
107-21-1 e	hanediol		<0.5	%
110-80-5 2	ethoxyethanol		<0.0	19
· Carci	nogenic categories		_	
	PA (Environmental Protection Agency)			_
111-76-2	2-butoxyethanol	NL	2.5-4.9	9
	1,2,4-trimethylbenzene	II .	<0.1	%
95-63-6		I	<0.1	%
95-63-6 1330-20-7	kylene	,		%
		D, CBD	<0.01	_
1330-20-7 98-82-8		-	<0.01 <0.01	%
1330-20-7 98-82-8 526-73-8	cumene	D, CBD		%
1330-20-7 98-82-8 526-73-8	cumene 1,2,3-trimethylbenzene	D, CBD		
1330-20-7 98-82-8 526-73-8 • TI 111-76-	cumene 1,2,3-trimethylbenzene V (Threshold Limit Value)	D, CBD		A A
1330-20-7 98-82-8 526-73-8 • TI 111-76- 107-21-	Cumene  1,2,3-trimethylbenzene  IV (Threshold Limit Value)  2 2-butoxyethanol	D, CBD		A A
1330-20-7 98-82-8 526-73-8 • TI 111-76- 107-21- 112945-52-	Cumene 1,2,3-trimethylbenzene  IV (Threshold Limit Value) 2 2-butoxyethanol 1 ethanediol	D, CBD		A A
1330-20-7 98-82-8 526-73-8 • TI 111-76- 107-21- 112945-52-	Cumene 1,2,3-trimethylbenzene  IV (Threshold Limit Value) 2 2-butoxyethanol 1 ethanediol 5 silicon dioxide 4 Carbon black	D, CBD		Α

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.



Printing date 09/23/2022

Version number 212

Reviewed on 09/23/2022

**Product number PN31** 

Trade name: WB IMPREGN. FAIR WALNUT

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - · Date of preparation / last revision 09/23/2022 / 211
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 2: Acute toxicity - Category 2 Acute Toxicity - Inhalation 3: Acute toxicity - Category 3

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Corrosion 1B: Skin corrosion/irritation – Category Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

·Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* \* Data compared to the previous version altered.