

Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

1 Identification

- · Product identifier
 - · Product number PD601
 - · Trade name: PASTEL WHITE
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aguatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling:

a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

2-methyl-2H-isothiazol-3-one

· Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 2)



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Υ

Product number PD601

Trade name: PASTEL WHITE

(Contd. of page 1)

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 2 Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: Mixture: consisting of the following components.

· Dangerou	us components:	
67-63-0	propan-2-ol Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	12.5-15%
95-63-6	1,2,4-trimethylbenzene Flammable Liquids 3, H226 Aquatic Chronic 2, H411 Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	<0.25%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 Skin Corrosion 1B, H314; Eye Damage 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Sensitization - Skin 1A, H317	≥0.0025-<0.01%
2682-20-4	2-methyl-2H-isothiazol-3-one ♦ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ♦ Skin Corrosion 1B, H314; Eye Damage 1, H318 ↑ Sensitization - Skin 1, H317	≥0.0015-<0.01%

4 First-aid measures

- · Description of first aid measures
 - · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Product number PD601

Trade name: **PASTEL WHITE** Y

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist . consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

67-63-0 propan-2-ol

400 ppm

(Contd. on page 4)



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Product number PD601

Trade name: PASTEL WHITE Y

		(Contd. of page 3)
577-11-7	docusate sodium	5.7 mg/m³
95-63-6	1,2,4-trimethylbenzene	140 ppm
· PAC-2	:	
67-63-0	propan-2-ol	2000* ppm
577-11-7	docusate sodium	63 mg/m³
95-63-6	1,2,4-trimethylbenzene	360 ppm
· PAC-3	:	
67-63-0	propan-2-ol	12000** ppm
577-11-7	docusate sodium	380 mg/m³
95-63-6	1,2,4-trimethylbenzene	480 ppm

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

, ,	t the time, the ether condition have no known expected innie.
67-6	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
95-6	3-6 1,2,4-trimethylbenzene
REL	Long-term value: 125 mg/m³, 25 ppm
	(Contd. on page 5)



Printing date 08/15/2022

Version number 289

Reviewed on 07/06/2022

Product number PD601

Trade name: **PASTEL WHITE** Y

(Contd. of page 4)

TLV Long-term value: (25) NIC-10 ppm

NIC-A4

· Ingredients with biological limit values:

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Product number PD601

Trade name: PASTEL WHITE Y

(Contd. of page 5)

Information on basic physical and of	chemical properties	
· General Information · Appearance:		
· Form:	Fluid	
· Color:	According to product specification	
· Odor:	Strong	
· Odor threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic. Range: 7 - 9	
· Change in condition		
· Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	82 °C (179.6 °F)	
· Flash point:	100 °C (212 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	425 °C (797 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
· Lower:	2 Vol %	
· Upper:	12 Vol %	
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	0.983 g/cm³ (8.203 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	59.9 %	
· VOC content:	14.74 %	
	144.9 g/l / 1.21 lb/gal	
· Solids content:	25.4 %	
Other information (HAPS)		.0.4
67-56-1 methanol		<0.1
1330-20-7 xylene		< 0.1



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Product number PD601

Trade name: PASTEL WHITE Y

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

neme n		
· <i>LD</i> /.	LC50 value	es that are relevant for classification:
67-63-0 pi	ropan-2-o	I
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
577-11-7	docusate	sodium
Oral	LD50	3,001 mg/kg (mouse)
Dermal	LD50	2,525 mg/kg (rabbit)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)
95-63-6 1,	2,4-trimet	hylbenzene
Oral	LD50	5,000 mg/kg (mouse)
Inhalative	LC50/4 h	11 mg/l (mouse)
2682-20-4	2-methyl-	-2H-isothiazol-3-one
Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)
Duin	narv irritan	t affect.

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye:

Irritating effect.

Causes serious eye irritation.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

Causes serious eye irritation.

May cause an allergic skin reaction.

(Contd. on page 8)



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Product number PD601

Trade name: PASTEL WHITE Y

(Contd. of page 7)

· Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer - Cl. 1 and 2)	
98-82-8 cumene	2B
· NTP (National Toxicology Program)	
98-82-8 cumene	<0.1%
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

· Aquatic t	armiul to aquatic life with long lasting effects.
67-63-0 pro	<u> </u>
EC50	
LC30	1,001 mg/l (algae) (72 h)
1050 (001)	10,000 mg/l (daphnia) (24 h)
, ,	9,640 mg/l (Fish)
577-11-7 do	ocusate sodium
EC50	100 mg/l (algae) (48 h)
	6.6 mg/l (daphnia) (48 h)
LC50 (96h)	17.3 mg/l (Fish)
64742-95-6	Solvent naphtha (petroleum), light arom.
EC50	1 mg/l (algae) (72 h)
	1 mg/l (daphnia) (48 h)
LC50 (96h)	1 mg/l (Fish)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)

- · Persistence and degradability No further relevant information available.
- · Substances Easily biodegradable

67-63-0 propan-2-ol .

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.



Printing date 08/15/2022 Version number 289 Reviewed on 07/06/2022

Product number PD601

Trade name: PASTEL WHITE Y

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
	Not applicable
· DOT, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.

15 Regulatory information

· UN "Model Regulation":

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable.

Not applicable

Requirements of Federal Register

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

- · Various regulations
 - · SARA

$\cdot S$	ection 355 (extremely hazardous substances):	
None of the	e ingredients is listed.	
$\cdot S$	ection 313 (Specific toxic chemical listings) :	
67-63-0	propan-2-ol	12.5-15%
95-63-6	1,2,4-trimethylbenzene	<0.25%
67-56-1	methanol	<0.1%
	(Con-	td on nage 10)

(Contd. on page 10)



Printing date 08/15/2022

Version number 289

Reviewed on 07/06/2022

Product number PD601

Trade name: PASTEL WHITE Y

			d. of page
1330-20-7			0.1%
98-82-8	cumene	<	0.1%
52-51-7	bronopol (INN)	<	0.01%
	A (Toxic Substances Control Act):		
All compor	nents have the value ACTIVE.		
· H	lazardous Air Pollutants		
67-56-1	methanol		
1330-20-7	xylene		
98-82-8	cumene		
_	osition 65		
	Chemicals known to cause cancer:		
98-82-8 cu	umene		* <0.19
. (Chemicals known to cause reproductive toxicity for females:		
None of th	e ingredients is listed.		
٠ (Chemicals known to cause reproductive toxicity for males:		
None of th	e ingredients is listed.		
٠ (Chemicals known to cause developmental toxicity:		
67-56-1 m	nethanol		<0.19
· Carc	inogenic categories		
· E	EPA (Environmental Protection Agency)		
95-63-6	1,2,4-trimethylbenzene	ll .	<0.25
1330-20-7	xylene	I	<0.19
98-82-8	cumene	D, CBD	<0.19
526-73-8	1,2,3-trimethylbenzene	II .	<0.1%
· 1	LV (Threshold Limit Value)		
67-63-0	propan-2-ol		Α
1330-20-7	xylene		Α
· N	IIOSH-Ca (National Institute for Occupational Safety and Health)		<u> </u>
None of the	e ingredients is listed.		

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 08/15/2022 / 288
 - · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 11)



Printing date 08/15/2022

Version number 289

Y

Reviewed on 07/06/2022

Product number PD601

PASTEL WHITE Trade name:

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2 Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Acute Toxicity - Dermal 2: Acute toxicity - Category 2 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* * Data compared to the previous version altered.