

Printing date 08/08/2022

Version number 91

Reviewed on 08/08/2022

1 Identification

- · Product identifier
 - · Product number HNS710
 - Trade name: IMPREGN WB EXT NEUT
 - \cdot Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number:
- ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2

H401 Toxic to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling:
- 2-methyl-2H-isothiazol-3-one
- 3-lodo-2-propynylbutylcarbamate
- · Hazard statements

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

- P273 Avoid release to the environment.
- P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- P363 Wash contaminated clothing before reuse.
- *P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.*
- · Classification system:

· NFPA ratings (scale 0 - 4)



(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/08/2022

Printing date 08/08/2022

Version number 91

Product number	[•] HNS710
Trade name:	IMPREGN WB EXT NEUT

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)		(Contd. of page 1	
HEALTH FIRE REACTIVIT	 Health = *0 Fire = 1 Reactivity = 0 		
3 Composi	tion/information on ingredients		
	haracterization: Mixtures on: Mixture: consisting of the following components.		
· Dangerou	is components:		
•	2-butoxyethanol	2.5-4.99%	
111102	 Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227 	2.0 1.0070	
34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%	
	Flammable Liquids 4, H227		
55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0.5-<1%	
	 Acute Toxicity - Inhalation 3, H331 Specific Target Organ Toxicity - Repeated Exposure 1, H372 Eye Damage 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317 		
57-55-6	propane-1,2-diol	0.5-1%	
	ethanediol	<0.5%	
	🚯 Acute Toxicity - Oral 4, H302		
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol Eye Damage 1, H318 Sensitization - Skin 1B, H317 Flammable Liquids 4, H227; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥0.1-<0.5%	
2682-20-4	2-methyl-2H-isothiazol-3-one	≥0.0015-<0.01%	
	 Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Skin Corrosion 1B, H314; Eye Damage 1, H318 Sensitization - Skin 1, H317 		
3811-73-2	 pyridine-2-thiol 1-oxide, sodium salt Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10) Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 	<0.0025%	
55965-84-9	 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ♦ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ♦ Skin Corrosion 1B, H314; Eye Damage 1, H318 ♦ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) 1 Sensitization - Skin 1A, H317 	<0.00025%	

(Contd. on page 3)

US



Version number 91

Reviewe

Reviewed on 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

(Contd. of page 2)

4 First-aid measures

Printing date 08/08/2022

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation:*

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed Allergic reactions
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.

• Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources
 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)

US



Printing date 08/08/2022

Product number HNS710

Version number 91

Reviewed on 08/08/2022

uate ventilation.	(Contd. of page 3)
Action Criteria for Chemicals	
2-butoxyethanol	60 ppm
(2-methoxymethylethoxy)propanol	150 ppm
3-lodo-2-propynylbutylcarbamate	3.3 mg/m ³
docusate sodium	5.7 mg/m ³
propane-1,2-diol	30 mg/m ³
ethanediol	30 ppm
2,4,7,9-tetramethyldec-5-yne-4,7-diol	30 mg/m ³
2-butoxyethanol	120 ppm
(2-methoxymethylethoxy)propanol	1700* ppm
	36 mg/m³
docusate sodium	63 mg/m³
propane-1,2-diol	1,300 mg/m³
	150 ppm
2,4,7,9-tetramethyldec-5-yne-4,7-diol	330 mg/m³
2-butoxyethanol	700 ppm
	9900** ppm
	220 mg/m³
docusate sodium	380 mg/m³
	7,900 mg/m³
	900 ppm
2,4,7,9-tetramethyldec-5-yne-4,7-diol	2,000 mg/m³
	b other sections is substances are released. 7 for information on safe handling. 8 for information on personal protection equipment. 13 for disposal information. Action Criteria for Chemicals 2-butoxyethanol (2-methoxymethylethoxy)propanol 3-lodo-2-propynylbutylcarbamate docusate sodium propane-1,2-diol ethanediol 2,4,7,9-tetramethyldec-5-yne-4,7-diol 2-butoxyethanol (2-methoxymethylethoxy)propanol 3-lodo-2-propynylbutylcarbamate docusate sodium propane-1,2-diol ethanediol 2,4,7,9-tetramethyldec-5-yne-4,7-diol 2-butoxyethanol (2-methoxymethylethoxy)propanol 3-lodo-2-propynylbutylcarbamate docusate sodium propane-1,2-diol ethanediol 2,4,7,9-tetramethyldec-5-yne-4,7-diol 2-butoxyethanol (2-methoxymethylethoxy)propanol 3-lodo-2-propynylbutylcarbamate docusate sodium 2-butoxyethanol (2-methoxymethylethoxy)propanol 3-lodo-2-propynylbutylcarbamate docus

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- Storage:
 - · Requirements to be met by storerooms and receptacles:
 - Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
 - In cases where there is no reported expiration date , it means that the product must be used within 8 months.
 - Take on temperature greater than 5 ° C
 - · Information about storage in one common storage facility: Not required.

(Contd. on page 5)

(Contd. of page 4)



Safety Data Sheet acc. to OSHA HCS

Version number 91

Reviewed on 08/08/2022

Printing date 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

· Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-	76-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3
3459	0-94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)
57-5	5-6 propane-1,2-diol
WEE	L Long-term value: 10 mg/m ³
107-2	21-1 ethanediol
TLV	Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only, A4
WEE	EL 1 (2)
	· Ingredients with biological limit values:
111-	76-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
	• Additional information: The lists that were valid during the creation were used as basis.
	osure controls ersonal protective equipment: · General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

(Contd. on page 6)

US



Version number 91

Reviewed on 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

Printing date 08/08/2022

(Contd. of page 5)

· Breathing equipment: Short term filter device: Suitable respiratory protective device recommended. Filter A · Protection of hands: Protective gloves Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product . · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eve protection: Goggles recommended during refilling. 9 Physical and chemical properties Information on basic physical and chemical properties · General Information · Appearance: · Form: Fluid · Color: According to product specification · Odor: Characteristic Not determined. · Odor threshold: Mixture is non-polar/aprotic. · pH-value: Range: 7 - 9 · Change in condition · Melting point/Melting range: Undetermined. · Boiling point/Boiling range: 100 °C (212 °F) 96 °C (204.8 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. 240 °C (464 °F) · Ignition temperature: · Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: 1.1 Vol % · Lower: (Contd. on page 7)



Printing date 08/08/2022

Version number 91

Reviewed on 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

		(Contd. of page
· Upper:	14 Vol %	
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.003 g/cm³ (8.37 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
• Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:	/-/	
• Water:	80.4 %	
· VOC content:	8.01 %	
	80.3 g/l / 0.67 lb/gal	
· Solids content:	11.6 %	
Other information (HAPS)		
107-21-1 ethanediol		<0.5%
112-34-5 2-(2-butoxyethoxy)ethanol		<0.1%
111-90-0 Diethylene glycol monoeth	yl ether	<0.1%
1330-20-7 xylene		<0.1%
98-82-8 cumene		<0.1%
143-22-6 2-[2-(2-butoxyethoxy)ethox	ky]ethanol	<0.01%
110-80-5 2-ethoxyethanol		<0.01%
· Other information	No further relevant information avail	lable.

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- \cdot Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 31,571 mg/kg

(Contd. on page 8)

US



Reviewed on 08/08/2022

Printing date 08/08/2022

Version number 91

Product number	HNS710
Trade name:	IMPREGN WB EXT NEUT

Dermal	LD50	28,940 mg/kg	(Contd. of pa
Inhalative		56 mg/l	
	2-butoxye		
Oral	LD50	1,200 mg/kg (ATE)	
Dormol		1,480 mg/kg (mouse)	
Dermal	LD50	1,100 mg/kg (rab)	
		11 mg/l (mouse)	
	LD50	oxymethylethoxy)propanol	
Oral Domocol		5,135 mg/kg (mouse)	
Dermal	LD50	19,020 mg/kg (rabbit)	
		2-propynylbutylcarbamate	
Oral	LD50	500 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (mouse)	
	docusate	-	
Oral	LD50	3,001 mg/kg (mouse)	
Dermal	LD50	2,525 mg/kg (rabbit)	
	ropane-1,2		
Oral	LD50	20,000 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
	-	y-2,2,6,6-tetramethylpiperidinoxyl	
Oral	LD50	1,053 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
0ral	ethanedio LD50		
Ulai	LD50 LD50.	301 mg/kg (mouse)	
Dermal	LD50. LD50	7,712 mg/kg (mouse) 3,501 mg/kg (mouse)	
Dennai	LDSU	9,530 mg/kg (rabbit)	
Inholotivo	I CEO/C h		
		2.6 ppm (mouse) ramethyldec-5-yne-4,7-diol	
	LD50		
Oral		4,600 mg/kg (mouse)	
04742-95- Oral	LD50	naphtha (petroleum), light arom. 6,801 mg/kg (mouse)	
Dermal	LD50 LD50	3,401 mg/kg (rab)	
		20.1 mg/l (mouse)	
		-2H-isothiazol-3-one	
2002-20-4 Oral	LD50		
Dermal	LD50 LD50	200 mg/kg (mouse) 400 mg/kg (mouse)	
		0.53 mg/l (mouse) 2-thiol 1-oxide, sodium salt	
	LD50	1,208 mg/kg (mouse)	
Oral		1,800 mg/kg (mouse)	
Oral Dermal	1 D.50		
Dermal	LD50 LC50/4 h	1.66 mg/l (mouse)	

(Contd. on page 9)



Version number 91

Reviewed on 08/08/2022

Printing date 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

(Contd. of page 8)

<0.1%

· Sensiti · Additiona Irritant	the eye: No irritating effect. ization: Sensitization possible through skin contact. I toxicological information: se an allergic skin reaction.	Contd. of page 8)
Titani IARC exper huma signifi	<i>togenic categories</i> um dioxide 's Monograph No. 93 reports there is sufficient evidence of carcin imental rats exposed to titanium dioxide but inadequate evidence for carc ns and has assigned a Group 2B rating. In addition, the IARC summary co icant exposure to titanium dioxide is thought to occur during the use o titanium is bound to other materials, such as paint."	inogenicity in Includes, "No
· IA	RC (International Agency for Research on Cancer - Cl. 1 and 2)	
2226-96-2	4-hydroxy-2,2,6,6-tetramethylpiperidinoxyl	3
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
98-82-8	cumene	2B
· N7	P (National Toxicology Program)	

98-82-8 cumene

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

• Aquatic 111-76-2 2	2-butoxyethanol	
EC50	101 mg/l (daphnia) (24 h)	
LC50 (96h) 101 mg/l (Fish)	
34590-94-	8 (2-methoxymethylethoxy)propanol	
EC50	970 mg/l (algae) (72 h)	
	1,919 mg/l (daphnia) (48 h)	
LC50 (96h) 1,001 mg/l (Fish)	
55406-53-	6 3-lodo-2-propynylbutylcarbamate	
EC50	22 mg/l (algae) (72 h)	
	0.16 mg/l (daphnia) (48 h)	
LC50 (96h) 67 mg/l (Fish)	
577-11-7 c	locusate sodium	
EC50	100 mg/l (algae) (48 h)	
	6.6 mg/l (daphnia) (48 h)	
LC50 (96h) 17.3 mg/l (Fish)	
57-55-6 pr	opane-1,2-diol	
EC50	19,000 mg/l (algae) (48 h)	
	18,340 mg/l (daphnia) (48 h)	
LC50 (96h) 40,613 mg/l (Fish)	
2226-96-2	4-hydroxy-2,2,6,6-tetramethylpiperidinoxyl	
EC50	1,038 mg/l (algae) (72 h)	
		(Contd. on page



Printing date 08/08/2022

Version number 91

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

	(Contd. of page 9)
	54 mg/l (daphnia) (48 h)
, ,	545 mg/l (Fish)
107-21-1 et	hanediol
EC50	101 mg/l (daphnia) (48h)
, ,	72,860 mg/l (Fish)
	Solvent naphtha (petroleum), light arom.
EC50	1 mg/l (algae) (72 h)
	1 mg/l (daphnia) (48 h)
	1 mg/l (Fish)
	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2- methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)
· Persistence	e and degradability No further relevant information available.
· Substance	es Easily biodegradable
111-76-2	2-butoxyethanol .
34590-94-8	(2-methoxymethylethoxy)propanol .
57-55-6	propane-1,2-diol .
• Additional • General r Water ha Do not a Danger t Harmful	Harmful to fish ecological information: notes: azard class 2 (Self-assessment): hazardous for water llow product to reach ground water, water course or sewage system. o drinking water if even small quantities leak into the ground. to aquatic organisms rse effects No further relevant information available.
• Waste treat • Recomme Must no sewage Hand ov Dispose • Uncleaned	t be disposed of together with household garbage. Do not allow product to reach system. er to hazardous waste disposers. of contents and container in accordance with local state and federal regulations. packagings:
	endation: Disposal must be made according to official regulations. ended cleansing agent: Water, if necessary with cleansing agents. (Contd. on page 11

(Contd. of page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/08/2022

Version number 91

Reviewed on 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

14 Transport information · UN-Number · DOT, ADN, IMDG, IATA Not applicable Check viscosity and flash point at section 9 · Note · UN proper shipping name · DOT, ADN, IMDG, IATA Not applicable Transport hazard class(es) · DOT, ADR, ADN, IMDG, IATA · Class Not applicable · Packing group · DOT, IMDG, IATA Not applicable · Environmental hazards: No • Marine pollutant: · Special precautions for user Not applicable. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations

· SARA

· Se	ction 313 (Specific toxic chemical listings) :	
111-76-2	2-butoxyethanol	2.5-4.99%
55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0. 5- <1%
107-21-1	ethanediol	<0.5%
95-63-6	1,2,4-trimethylbenzene	<0.1%
112-34-5	2-(2-butoxyethoxy)ethanol	<0.1%
111-90-0	Diethylene glycol monoethyl ether	<0.1%
1330-20-7	xylene	<0.1%
98-82-8	cumene	<0.1%
1336-21-6	ammonia	<0.01%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.01%
1344-28-1	aluminium oxide	<0.01%
110-80-5	2-ethoxyethanol	<0.01%
· TSCA	(Toxic Substances Control Act):	



Printing date 08/08/2022

Version number 91

Reviewed on 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

		(Co	ntd. of pag	ge 11
	lazardous Air Pollutants			
	ethanediol			
1330-20-7	xylene			
98-82-8	cumene			
. (osition 65 Themicals known to cause cancer: Titanium dioxide only in bound form			
13463-67-	7 Titanium dioxide C.I. 77891 Pigment white 6	only for D	ust <0.	.1%
98-82-	B cumene	*	<0.	.1%
· (hemicals known to cause reproductive toxicity for females:	-		
None of th	e ingredients is listed.			
· (hemicals known to cause reproductive toxicity for males:			
110-80-5	5 2-ethoxyethanol		<0.0	1%
· (hemicals known to cause developmental toxicity:			
107-21-1	1 ethanediol <		<0.5	%
110-80-5	5 2-ethoxyethanol <			1%
· Carc	inogenic categories			
· E	PA (Environmental Protection Agency)			
111-76-2	2-butoxyethanol	NL	2.5-4.9	9%
95-63-6	1,2,4-trimethylbenzene	11	<0.19	%
1330-20-7	xylene	1	<0.19	%
98-82-8	cumene	D, CBD	<0.19	%
526-73-8	1,2,3-trimethylbenzene	11	<0.19	%
· 7	LV (Threshold Limit Value)			
111-76	-2 2-butoxyethanol			AЗ
107-21	-1 ethanediol			A4
112945-52	-5 silicon dioxide			A4
13463-67	7 Titanium dioxide C.I. 77891 Pigment white 6			A4
1330-20	-7 xylene			Α4
· N	IOSH-Ca (National Institute for Occupational Safety and Health)			
13463-67-	7 Titanium dioxide C.I. 77891 Pigment white 6		<0.	1%

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

· Date of preparation / last revision 08/08/2022 / 90

• Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 13)

US

coatings & polymers technologies

Printing date 08/08/2022

Safety Data Sheet acc. to OSHA HCS

Version number 91

Reviewed on 08/08/2022

Product number HNS710 Trade name: IMPREGN WB EXT NEUT

	(Contd. of page
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 4: Flammable liquids – Category 4	
Acute Toxicity - Oral 4: Acute toxicity – Category 4	
Acute Toxicity - Dermal 2: Acute toxicity – Category 2	
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3	
Skin Corrosion 1B: Skin corrosion/irritation – Category 1B	
Skin Irrititation 2: Skin corrosion/irritation – Category 2	
Eye Damage 1: Serious eye damage/eye irritation – Category 1	
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A	
Sensitization - Skin 1: Skin sensitisation – Category 1	
Sensitization - Skin 1A: Skin sensitisation – Category 1A	
Sensitization - Skin 1B: Skin sensitisation – Category 1B	
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure	re) – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	, <u></u> , , , ,
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2	
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
Sources	
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT	
COUNCIL and following amendments	
Agency ECHA web site	
INRS Fiche Toxicologique	
IARC International agency for research on cancer	
* Data compared to the previous version altered.	
- •	