

1 Identification

- **Product identifier**
 - *Product number* TX90
 - *Trade name:* **NON-YELLOWING PU HARDENER**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

<p>Flammable Liquids 2</p> <p>Skin Irritation 2</p> <p>Eye Irritation 2A</p> <p>Sensitization - Skin 1</p> <p>Carcinogenicity 2</p> <p>Toxic to Reproduction 2</p> <p>Specific Target Organ Toxicity - Single Exposure 3H335-H336</p> <p>Specific Target Organ Toxicity - Repeated Exposure 2</p> <p>Aspiration Hazard 1</p>	<p>H225</p> <p>H315</p> <p>H319</p> <p>H317</p> <p>H351</p> <p>H361</p> <p>H335-H336</p> <p>H373</p> <p>H304</p>	<p>Highly flammable liquid and vapor.</p> <p>Causes skin irritation.</p> <p>Causes serious eye irritation.</p> <p>May cause an allergic skin reaction.</p> <p>Suspected of causing cancer.</p> <p>Suspected of damaging fertility or the unborn child.</p> <p>May cause respiratory irritation. May cause drowsiness or dizziness.</p> <p>May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.</p> <p>May be fatal if swallowed and enters airways.</p>
--	--	--

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger

- *Hazard-determining components of labeling:*

HDI Homopolymer
toluene
ethylbenzene
butanone

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 1)

· Hazard statements

- H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H361 Suspected of damaging fertility or the unborn child.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.
 H304 May be fatal if swallowed and enters airways.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P321 Specific treatment (see on this label).
 P331 Do NOT induce vomiting.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:**· NFPA ratings (scale 0 - 4)****· HMIS-ratings (scale 0 - 4)**







HEALTH	2	Health = 2
FIRE	4	Fire = 4
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

· Dangerous components:

28182-81-2	HDI Homopolymer  Acute Toxicity - Inhalation 4, H332; Sensitization - Skin 1, H317;  Specific Target Organ Toxicity - Single Exposure 3, H335	25-29.99%
78-93-3	butanone  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	25-29.99%
123-86-4	n-butyl acetate  Flammable Liquids 3, H226  Specific Target Organ Toxicity - Single Exposure 3, H336	20-24.99%

(Contd. on page 3)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

		(Contd. of page 2)
108-88-3	toluene ⚠ Flammable Liquids 2, H225 ⚠ Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	12.5-15%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%
1330-20-7	xylene ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	2.5-4.99%
100-41-4	ethylbenzene ⚠ Flammable Liquids 2, H225 ⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Inhalation 4, H332 Aquatic Chronic 3, H412	0.5-1%
822-06-0	hexamethylene diisocyanate ⚠ Acute Toxicity - Inhalation 1, H330 ⚠ Sensitization - Respiratory 1, H334 ⚠ Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	<0.1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

(Contd. on page 4)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 3)

· Information for doctor:

- **Most important symptoms and effects, both acute and delayed**
Allergic reactions
For symptoms and effects caused by substances, refer to Section 11.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

- **Suitable extinguishing agents:**
Alcohol resistant foam
Alcohol resistant foam, CO, powder, water spray/mist.
- **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-I:**

28182-81-2	HDI Homopolymer	7.8 mg/m
78-93-3	butanone	200 ppm
123-86-4	n-butyl acetate	5 ppm
108-88-3	toluene	67 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm

(Contd. on page 5)

Product number TX90

Trade name: NON-YELLOWING PU HARDENER

(Contd. of page 4)

1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
· PAC-2:		
28182-81-2	HDI Homopolymer	86 mg/m
78-93-3	butanone	2700* ppm
123-86-4	n-butyl acetate	200 ppm
108-88-3	toluene	560 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
· PAC-3:		
28182-81-2	HDI Homopolymer	510 mg/m
78-93-3	butanone	4000* ppm
123-86-4	n-butyl acetate	3000* ppm
108-88-3	toluene	3700* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

US

(Contd. on page 6)

Product number TX90
Trade name: NON-YELLOWING PU HARDENER

(Contd. of page 5)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the remaining constituent has no known exposure limits.

78-93-3 butanone

PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: NIC-150 (300) ppm Long-term value: NIC-75 (200) ppm BEI, NIC-Skin

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

1330-20-7 xylene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

822-06-0 hexamethylene diisocyanate

REL	Long-term value: 0.035 mg/m , 0.005 ppm Ceiling limit value: 0.14* mg/m , 0.02* ppm *10-min
-----	---

(Contd. on page 7)

Product number TX90
Trade name: NON-YELLOWING PU HARDENER

(Contd. of page 6)

TLV	Long-term value: 0.005 ppm BEI
-----	-----------------------------------

- **Regulatory information**
PEL: Guide to Occupational Exposure Values (OSHA PELs)
REL: Guide to Occupational Exposure Values (NIOSH RELs)
TLV: Guide to Occupational Exposure Values (TLV)
WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

· **Ingredients with biological limit values:**

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
-----	---

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

822-06-0 hexamethylene diisocyanate

BEI	15 g/g creatinine Medium: urine Time: end of shift Parameter: 1.6-Hexamethylene diamine with hydrolysis (nonspecific)
-----	--

- **Regulatory information** BEI: Guide to Occupational Exposure Values (BEI)
- **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.

(Contd. on page 8)

Product number TX90

Trade name: NON-YELLOWING PU HARDENER

(Contd. of page 7)

- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.
- **Breathing equipment:**
Short term filter device:



Suitable respiratory protective device recommended.

Filter A

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

· **pH-value:** Mixture is non-polar/aprotic.

· Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 79-80.5 °C (174.2-176.9 °F)

· **Flash point:** -4 °C (24.8 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Auto igniting:** 315 °C (599 °F)

- **Decomposition temperature:** Not determined.

(Contd. on page 9)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 8)

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1.1 Vol %	
· Upper:	11.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	105 hPa (78.8 mm Hg)	
· Vapor pressure at 50 °C (122 °F):	124 hPa (93 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	0.95 g/cm (7.928 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	70.08 % 665.8 g/l / 5.56 lb/gal	
· Solids content:	29.9 %	
· Other information (HAPS)		
108-88-3	toluene	12.5-15%
1330-20-7	xylene	2.5-4.99%
100-41-4	ethylbenzene	0.5-1%
822-06-0	hexamethylene diisocyanate	<0.1%

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Reacts with oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**

in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

US

(Contd. on page 10)

Product number TX90
Trade name: NON-YELLOWING PU HARDENER

(Contd. of page 9)

11 Toxicological information

· Information on toxicological effects

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal	LD50	27,160 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	32.4 mg/l

28182-81-2 HDI Homopolymer

Oral	LD50	2,501 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)

78-93-3 butanone

Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	21 mg/l (mouse)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	21.1 mg/l (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	25.7 mg/l (mouse)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	35.7 mg/l (mouse)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	11 mg/l (mouse) (ATE value)
	LC50/4 ore/h/saat.	27.571 mg/l (mouse)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	17.2 mg/l (mouse)

822-06-0 hexamethylene diisocyanate

Oral	LD50	738 mg/kg (mouse)
Dermal	LD50	7,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	0.124 mg/l (mouse)

(Contd. on page 11)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 10)

- **Primary irritant effect:**

- **on the skin:**

- Irritant to skin and mucous membranes.

- Causes skin irritation.

- May cause an allergic skin reaction.

- **on the eye:**

- Irritating effect.

- Causes serious eye irritation.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

- Irritant

- Causes skin irritation.

- Causes serious eye irritation.

- May cause an allergic skin reaction.

- Suspected of causing cancer.

- Suspected of damaging fertility or the unborn child.

- May cause respiratory irritation.

- May cause drowsiness or dizziness.

- May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

- May be fatal if swallowed and enters airways.

- Contains isocyanates. See information supplied by the manufacturer.

- May cause drowsiness or dizziness.

- May cause respiratory irritation.

- **Carcinogenic categories**

- Ethylbenzene

- From IARC MONOGRAPHS VOLUME 77/2000

- Human carcinogenicity data

- Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

- Evaluation

- There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

100-41-4 ethylbenzene	2B
-----------------------	----

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Sensitisation**

- Monomers / polymers isocyanate

- Particular characteristics / effects; prolonged exposure may irritate the eyes, nose, throat and respiratory tract.

- Isocyanate exposure may result in the delayed appearance of respiratory disorders, cough or asthma. Sensitive individuals may show exposure symptoms to isocyanates below workplace TLV values. Prolonged skin contact may result cause irritation and dehydration.

US

(Contd. on page 12)

Product number TX90
Trade name: NON-YELLOWING PU HARDENER

(Contd. of page 11)

12 Ecological information

· Toxicity

· Aquatic toxicity:

28182-81-2 HDI Homopolymer

EC50	1,001 mg/l (algae) (72 h) 127 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	100 mg/l (Fish)

78-93-3 butanone

EC50	2,029 mg/l (algae) (96 h) 308 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	2,993 mg/l (Fish)

123-86-4 n-butyl acetate

EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	18 mg/l (Fish)

108-88-3 toluene

EC50	134 mg/l (algae) (96 h) 3.78 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	5.5 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50	1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	134 mg/l (Fish)

1330-20-7 xylene

EC50	2.2 mg/l (algae)
LC50 (48 ore/h/saat)	1 mg/l (daphnia)
LC50 (96 ore/h/saat)	2.6 mg/l (Fish)

100-41-4 ethylbenzene

EC50	438 mg/l (algae) (72h) 1.8 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	12.1 mg/l (Fish)

822-06-0 hexamethylene diisocyanate

EC50	77.5 mg/l (algae) (72 h) 89.2 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	82.9 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable

78-93-3	butanone	.
123-86-4	n-butyl acetate	.
108-88-3	toluene	.
108-65-6	2-methoxy-1-methylethyl acetate	.
1330-20-7	xylene	.
100-41-4	ethylbenzene	.

(Contd. on page 13)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 12)

· Behavior in environmental systems:**· Bioaccumulative potential**

78-93-3	butanone	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 0,3
123-86-4	n-butyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 2,3
108-88-3	toluene	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 2,73
108-65-6	2-methoxy-1-methylethyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1,2
1330-20-7	xylene	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 3,12

· Mobility in soil

78-93-3	butanone	Evapora rapidamente.
108-88-3	toluene	Coefficiente di assorbimento normalizzato del carbonio organico (Log Koc): 205
1330-20-7	xylene	Koc = 246 . 540

· Additional ecological information:**· General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.**13 Disposal considerations****· Waste treatment methods****· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:**· Recommendation:** Disposal must be made according to official regulations.**14 Transport information****· UN-Number****· DOT, IMDG, IATA**

UN1263

· Note

Check viscosity and flash point at section 9

· UN proper shipping name**· DOT**

Paint

· IMDG, IATA

PAINT

(Contd. on page 14)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 13)

· **Transport hazard class(es)**· **DOT**

- **Class** 3 Flammable liquids
- **Label** 3
- **Class** 3 Flammable liquids
- **Label** 3

· **IMDG, IATA**

- **Class** 3 Flammable liquids
- **Label** 3

· **Packing group**

- **DOT, IMDG, IATA** II

· **Environmental hazards:**

- **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

- **Hazard identification number (Kemler code):** 33
- **EMS Number:** F-E, S-E
- **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **IMDG**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- **Various regulations**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 15)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 14)

· **Section 313 (Specific toxic chemical listings) :**

108-88-3	toluene	12.5-15%
1330-20-7	xylene	2.5-4.99%
100-41-4	ethylbenzene	0.5-1%
822-06-0	hexamethylene diisocyanate	<0.1%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

108-88-3	toluene
1330-20-7	xylene
100-41-4	ethylbenzene
822-06-0	hexamethylene diisocyanate

· **Proposition 65**· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	0.5-1%
----------	--------------	---	--------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	12.5-15%
----------	---------	----------

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

78-93-3	butanone	I	25-29.99%
108-88-3	toluene	II	12.5-15%
1330-20-7	xylene	I	2.5-4.99%
100-41-4	ethylbenzene	D	0.5-1%

· **TLV (Threshold Limit Value)**

108-88-3	toluene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl· **Contact:** See emergency phone· **Date of preparation / last revision** 02/12/2024

(Contd. on page 16)

Product number TX90**Trade name: NON-YELLOWING PU HARDENER**

(Contd. of page 15)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 2: Flammable liquids . Category 2
 Flammable Liquids 3: Flammable liquids . Category 3
 Acute Toxicity - Inhalation 1: Acute toxicity . Category 1
 Acute Toxicity - Inhalation 4: Acute toxicity . Category 4
 Skin Irritation 2: Skin corrosion/irritation . Category 2
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 Sensitization - Respiratory 1: Respiratory sensitisation . Category 1
 Sensitization - Skin 1: Skin sensitisation . Category 1
 Carcinogenicity 2: Carcinogenicity . Category 2
 Toxic to Reproduction 2: Reproductive toxicity . Category 2
 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3
 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2
 Aspiration Hazard 1: Aspiration hazard . Category 1
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· * Data compared to the previous version altered.

US