

ILVA TECHNICAL DATA SHEET

PRODUCT CODE: PD4/90

DESCRIPTION: WB GLAZE & STAIN VEHICLE

USES: Vehicle for glazes by spray and wipe. Suitable for chestnut, oak, etc. woods. Excellent smoothing action. Can be used on various types of furniture.

APPLICATION SYSTEM: By spray and wipe

GENERAL PROPERTIES:

Specific gravity:	1.05 +/-0.02 gr/m;
Solid content:	25% +/- 1% by weight
Viscosity (at 20°C):	55 +/-5 (DIN 53211 CUP 0 mm.4)

DRYING TIME: Air (minnum 4 hours)
(at 20°C/68°F)

SUGGESTED COATING CYCLES:

Substrate:	Different kinds of wood
Stain:	PD4/90 + PC3/series + water = 100/10/50
Drying:	4 hr
Base coat:	TT PUR WB base coats
Topcoat:	TW PUR WB topcoats

SHELF LIFE: 12 Months

STORAGE: Store in a tightly closed container at room temperatures (18-25°C/64-75°F) and protect from moisture and foreign material. Do not store at temperatures below 7°C (45°F)

DATE OF ISSUANCE: 09-10

**IC & S, P.O. BOX 10845, LANCASTER, PA 17605
(800) 220-4035**

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL, INCLUDING FOR EXAMPLE, THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.