

1 Identification

- **Product identifier**
 - *Product number* WUM5AB76
 - *Trade name:* **WB UV TOP-C WHITE 10SH**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Sensitization - Skin 1 H317 May cause an allergic skin reaction.
Carcinogenicity 2 H351 Suspected of causing cancer.
Aquatic Acute 2 H401 Toxic to aquatic life.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*



GHS07 GHS08 GHS09

- *Signal word* Warning
- *Hazard-determining components of labeling:*
2,2-bis(acryloyloxymethyl)butyl acrylate
2-methyl-2H-isothiazol-3-one
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
- *Hazard statements*
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H401 Toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
- *Precautionary statements*
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 1)

Classification system:

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture: consisting of the following components.

Dangerous components:

15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate 	5-9.99%
7473-98-5	2-hydroxy-2-methylpropiophenone 	<2.5%
5131-66-8	3-butoxypropan-2-ol 	1-2.49%
111-90-0	Diethylene glycol monoethyl ether 	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol 	0.5-1%
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide 	≥0.1-<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one 	≥0.0015-<0.01%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) 	≥0.00025-<0.0015%

US

(Contd. on page 3)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 2)

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)

Product number WUM5AB76**Trade name: WB UV TOP-C WHITE 10SH**

(Contd. of page 3)

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
111-90-0	Diethylene glycol monoethyl ether	75 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m

· PAC-2:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
111-90-0	Diethylene glycol monoethyl ether	100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m

· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
111-90-0	Diethylene glycol monoethyl ether	450 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Keep respiratory protective device available.

- **Information about protection against explosions and fires:**

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- **Information about storage in one common storage facility: Not required.**

- **Further information about storage conditions: Keep receptacle tightly sealed.**

(Contd. on page 5)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 4)

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate	
WEEL	Long-term value: 1 mg/m Skin
111-90-0 Diethylene glycol monoethyl ether	
WEEL	Long-term value: 25 ppm
112-34-5 2-(2-butoxyethoxy)ethanol	
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 5)

· *Eye protection:* Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Mixture is non-polar/aprotic.

Range: 7 - 9

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

100 °C (212 °F)

· Flash point:

100 °C (212 °F)

· Flammability (solid, gaseous):

Not applicable.

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product does not present an explosion hazard.

· Explosion limits:

· Lower:

1.1 Vol %

· Upper:

8.4 Vol %

· Vapor pressure at 20 °C (68 °F):

1.3 hPa (1 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F):

1.164 g/cm (9.714 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Fully miscible.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

60 s (ISO 6 mm)

· Oxidising properties:

N.A.

· Solvent content:

· Water:

49.0 %

· VOC content:

2.99 %

34.9 g/l / 0.29 lb/gal

· Solids content:

48.0 %

· Other information (HAPS)

111-90-0 Diethylene glycol monoethyl ether

0.5-1%

112-34-5 2-(2-butoxyethoxy)ethanol

0.5-1%

(Contd. on page 7)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 6)

121-44-8	triethylamine	<0.1%
110-80-5	2-ethoxyethanol	<0.01%

 · **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

 · **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	109,290 mg/kg (mouse)
------	------	-----------------------

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate

Oral	LD50	5,001 mg/kg (mouse)
------	------	---------------------

Dermal	LD50	5,001 mg/kg (mouse)
--------	------	---------------------

7473-98-5 2-hydroxy-2-methylpropiophenone

Oral	LD50	1,694 mg/kg (mouse)
------	------	---------------------

Dermal	LD50	6,929 mg/kg (mouse)
--------	------	---------------------

5131-66-8 3-butoxypropan-2-ol

Oral	LD50	3,300 mg/kg (mouse)
------	------	---------------------

Dermal	LD50	8,001 mg/kg (mouse)
--------	------	---------------------

111-90-0 Diethylene glycol monoethyl ether

Oral	LD50	6,031 mg/kg (mouse)
------	------	---------------------

Dermal	LD50	9,143 mg/kg (rabbit)
--------	------	----------------------

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	6,600 mg/kg (mouse)
------	------	---------------------

Dermal	LD50	2,764 mg/kg (rabbit)
--------	------	----------------------

162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Oral	LD50	2,001 mg/kg (mouse)
------	------	---------------------

Dermal	LD50	2,001 mg/kg (mouse)
--------	------	---------------------

2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	200 mg/kg (mouse)
------	------	-------------------

Dermal	LD50	400 mg/kg (mouse)
--------	------	-------------------

Inhalative	LC50/4 h	0.53 mg/l (mouse)
------------	----------	-------------------

(Contd. on page 8)

Product number WUM5AB76**Trade name: WB UV TOP-C WHITE 10SH**

(Contd. of page 7)

- **Primary irritant effect:**
 - *on the skin:* No irritant effect.
 - *on the eye:* No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 - Irritant
 - May cause an allergic skin reaction.
 - Suspected of causing cancer.
 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- **Carcinogenic categories**
 - Titanium dioxide
 - IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

 · **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	2B

 · **NTP (National Toxicology Program)**

None of the ingredients is listed.

 · **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity** Toxic to aquatic life with long lasting effects.

 · **Aquatic toxicity:**
15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate

EC50	4.9 mg/l (algae) (72 h)
	19.9 mg/l (daphnia) (48 h)
LC50 (96h)	2.1 mg/l (Fish)

7473-98-5 2-hydroxy-2-methylpropiophenone

EC50	119 mg/l (daphnia) (48h)
LC50 (96h)	160 mg/l (Fish)

5131-66-8 3-butoxypropan-2-ol

EC50	1,001 mg/l (algae) (96 h)
	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,000 mg/l (Fish)

111-90-0 Diethylene glycol monoethyl ether

LC50 48h	1,982 mg/l (daphnia)
LC50 (96h)	101 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)

(Contd. on page 9)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 8)

162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

EC50 1,175 mg/l (daphnia)
 48h

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50 0.027 mg/l (algae) (72 h)
 0.16 mg/l (daphnia) (48 h)
 LC50 (96h) 0.19 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	.
5131-66-8	3-butoxypropan-2-ol	.
111-90-0	Diethylene glycol monoethyl ether	.
112-34-5	2-(2-butoxyethoxy)ethanol	.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.
 · **Mobility in soil** No further relevant information available.

· **Ecotoxic effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Hand over to hazardous waste disposers.
 Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.
 · **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN3082

· **Note**

Check viscosity and flash point at section 9

(Contd. on page 10)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 9)

· UN proper shipping name

· DOT

Environmentally hazardous substance, liquid, n.o.s. (2,2-bis(acryloyloxymethyl)butyl acrylate)

· IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate), MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-bis(acryloyloxymethyl)butyl acrylate)

· Transport hazard class(es)

· DOT, IMDG, IATA



· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· Packing group

· DOT, IMDG, IATA

III

· Environmental hazards:

Product contains environmentally hazardous substances: 2,2-bis(acryloyloxymethyl)butyl acrylate

· Marine pollutant:

Yes

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

· Special precautions for user

Warning: Miscellaneous dangerous substances and articles

· Hazard identification number (Kemler code): 90

· EMS Number:

F-A,S-F

· Stowage Category

A

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Remarks:

Special marking with the symbol (fish and tree).

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-

(Contd. on page 11)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 10)

BIS(ACRYLOYLOXYMETHYL)BUTYL ACRYLATE),
 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

- Various regulations
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

111-90-0	Diethylene glycol monoethyl ether	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
121-44-8	triethylamine	<0.1%
110-80-5	2-ethoxyethanol	<0.01%

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

121-44-8	triethylamine
----------	---------------

· Proposition 65

- Chemicals known to cause cancer:
Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	12.5-15%
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	*	5-9.99%

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

110-80-5	2-ethoxyethanol	<0.01%
----------	-----------------	--------

· Chemicals known to cause developmental toxicity:

110-80-5	2-ethoxyethanol	<0.01%
----------	-----------------	--------

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
121-44-8	triethylamine	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	12.5-15%
------------	---	----------

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 12)

Product number WUM5AB76
Trade name: WB UV TOP-C WHITE 10SH

(Contd. of page 11)

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone

- **Date of preparation / last revision** 09/14/2022 / 3

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids . Category 4

Acute Toxicity - Oral 3: Acute toxicity . Category 3

Acute Toxicity - Oral 4: Acute toxicity . Category 4

Acute Toxicity - Dermal 2: Acute toxicity . Category 2

Skin Corrosion 1B: Skin corrosion/irritation . Category 1B

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Damage 1: Serious eye damage/eye irritation . Category 1

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Skin 1: Skin sensitisation . Category 1

Sensitization - Skin 1A: Skin sensitisation . Category 1A

Carcinogenicity 2: Carcinogenicity . Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard . Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard . Category 4

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- *** Data compared to the previous version altered.**