

Printing date 08/15/2022

Version number 187

Reviewed on 08/15/2022

1 Identification

- · Product identifier
 - · Product number PN6B
 - Trade name: WB EXT CONV WHITE 30SH • Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:* IVM Chemicals Srl Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number:
- ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling:
- 2-methyl-2H-isothiazol-3-one
- · Hazard statements
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- · Precautionary statements
 - P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P308+P313 IF exposed or concerned: Get medical advice/attention.
 - P363 Wash contaminated clothing before reuse.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.
- · Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



us



Version number 187

Reviewed on 08/15/2022

Product number PN6B Trade name: WB EXT CONV WHITE 30SH

Printing date 08/15/2022

(Contd. of page 1)

•••	haracterization: Mixtures on: Mixture: consisting of the following components.	
· Dangeroi	as components:	
34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	1-<5%
57-55-6	propane-1,2-diol	1-2.49%
77-99-6	propylidynetrimethanol	≥0.1-<0.5%
2682-20-4	 2-methyl-2H-isothiazol-3-one Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Skin Corrosion 1B, H314; Eye Damage 1, H318 Sensitization - Skin 1, H317 	≥0.0015-<0.01%
	 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ♦ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ♦ Skin Corrosion 1B, H314; Eye Damage 1, H318 ♦ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ♦ Sensitization - Skin 1A, H317 	
55965-84-9	 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 Skin Corrosion 1B, H314 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Sensitization - Skin 1A, H317 	<0.00025%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · *After inhalation:*

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.

• Information for doctor:

• Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

(Contd. on page 3)

⁻US



Version number 187

Reviewed on 08/15/2022

Product number PN6B

Printing date 08/15/2022

Trade name: WB EXT CONV WHITE 30SH

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents:
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
 Keep away from ignition sources
 Environmental precautions:
 Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:
 Absorb with liquid-binding material (cand. diatomite, acid binders, universal binders)

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation.

- Reference to other sections
 No dangerous substances are released.
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:			
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		30 mg/m³
34590-94-8	(2-methoxymethylethoxy)propanol		150 ppm
57-55-6	propane-1,2-diol		30 mg/m ³
25322-69-4	Propane-1,2-diol, propoxylated		30 mg/m ³
7631-86-9	silicon dioxide, chemically prepared		18 mg/m³
· PAC-2:			
	Titanium dioxide C.I. 77891 Pigment white 6	3	30 mg/m³
34590-94-8	(2-methoxymethylethoxy)propanol	1	700* ppm
57-55-6	propane-1,2-diol	1	,300 mg/m³
		(C	ontd. on page 4)



Reviewed on 08/15/2022

Printing date 08/15/2022

Version number 187

Product number PN6B Trade name: WB EXT CONV WHITE 30SH

	Propane-1,2-diol, propoxylated silicon dioxide, chemically prepared	(Contd. of page 3) 330 mg/m ³ 740 mg/m ³
· PAC-3:		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m ³
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
57-55-6	propane-1,2-diol	7,900 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Keep respiratory protective device available.
- Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 (2-methoxymethylethoxy)propanol

	Long-term value: 600 mg/m³, 100 ppm Skin
	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)
57-55-0	6 propane-1 2-diol

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m³

(Contd. on page 5)

US

Safety Data Sheet acc. to OSHA HCS

Version number 187

Reviewed on 08/15/2022



N Chemicals

Printing date 08/15/2022

coatings & polymers technologies

· Additional information: The lists	(Contd. of page 4) s that were valid during the creation were used as basis.
·	5
• Exposure controls	
 Personal protective equipment: General protective and hygienic i 	M 0 (51) 80 C +
Keep away from foodstuffs, be	
Immediately remove all soiled a	
Wash hands before breaks and	
Store protective clothing separa	
	v avoid inhalation or skin contact.
· Breathing equipment:	
Short term filter device:	
Suitable respiratory p	protective device recommended.
Filter A	
• Protection of hands:	
Protective gloves	
	mendation to the glove material can be given for the product. I on consideration of the penetration times, rates of diffusion
The glove material has to be in	npermeable and resistant to the product .
Material of gloves The selection of the suitab	le gloves does not only depend on the material, but also on
further marks of quality and a preparation of several su	varies from manufacturer to manufacturer. As the product is ubstances, the resistance of the glove material can not be
	as therefore to be checked prior to the application.
• Penetration time of glove mat	
gloves and has to be observ	ne has to be found out by the manufacturer of the protective
· Eye protection: Goggles recomm	
Lyc protection. Coggico rocom	
9 Physical and chemical prope	rties
· Information on basic physical and	chemical properties
· General Information	enemieu properties
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
	Range: 7 - 9
· Change in condition	
• Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
	(Contd. on page 6)



Version number 187

Reviewed on 08/15/2022

Product number PN6B

Printing date 08/15/2022

i louuct number	I NOD
Trade name:	WB EXT CONV WHITE 30SH

	(C	ontd. of page
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	270 °C (518 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
- Lower:	1.1 Vol %	
· Upper:	14 Vol %	
· Vapor pressure at 20 °C (68 °F):	0.4 hPa (0.3 mm Hg)	
• Density (+/- 0,03) at 20 °C (68 °F):	1.19 g/cm³ (9.931 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water	·): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
• <i>Kinematic at 20</i> • <i>C</i> (68 • <i>F</i>):	29 s (ISO 3 mm)	
• Oxidising properties:	N.A.	
· Solvent content:		
· Water:	50.6 %	
· VOC content:	5.03 %	
	59.9 g/l / 0.50 lb/gal	
· Solids content:	44.3 %	
· Other information (HAPS)		
143-22-6 2-[2-(2-butoxyethoxy)ethoxy	/]ethanol	<0.1%
50-00-0 formaldehyde		<0.01%
Other information	No further relevant information available.	· ·

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

 \cdot Conditions to avoid No further relevant information available.

· Incompatible materials: Acids, alkalis and oxidizing agents

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US



Version number 187

Product number PN6B

Printing date 08/15/2022

Trade name: WB EXT CONV WHITE 30SH

Toxicol	ogical in	formation	
Information · Acute to		cological effects	
	-	s that are relevant for classification:	
		oxymethylethoxy)propanol	
Oral	LD50	5,135 mg/kg (mouse)	
Dermal	LD50	19,020 mg/kg (rabbit)	
57-55-6 p			
Oral	LD50	20,000 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
		etrimethanol	
Oral	LD50	14,700 mg/kg (mouse)	
Dermal	LD50	10,001 mg/kg (mouse)	
2682-20-4		2H-isothiazol-3-one	
Oral	LD50	200 mg/kg (mouse)	
Dermal	LD50	400 mg/kg (mouse)	
Inhalative	LC50/4 h	0.53 mg/l (mouse)	
Addition Irritant May ca Suspec Product and us Warnin mist. Care	nal toxicolo use an alle ted of dan t contains: e according g! Hazardo cinogenic c		-
IAR exp hun sigr whie	erimental i nans and h nificant exp ch titanium	de graph No. 93 reports there is sufficient evidence of ca ats exposed to titanium dioxide but inadequate evidence for o as assigned a Group 2B rating. In addition, the IARC summar posure to titanium dioxide is thought to occur during the us is bound to other materials, such as paint." mational Agency for Research on Cancer - Cl. 1 and 2)	arcinogenicity y concludes, "N
		n dioxide C.I. 77891 Pigment white 6	2B - DUST
		Ū Ū	20-0001
		nal Toxicology Program)	
		nts is listed.	
	OSHA-Ca (ormaldehyd	Occupational Safety & Health Administration)	
			<0.01%

(Contd. on page 8)

(Contd. of page 7)



Safety Data Sheet acc. to OSHA HCS

Printing date 08/15/2022

Version number 187

Reviewed on 08/15/2022

Product number PN6B Trade name: WB EXT CONV WHITE 30SH

· Toxicity		
· Aquatic t	oxicity:	
34590-94-8	(2-methoxymethylethoxy)propan	nol
EC50	970 mg/l (algae) (72 h)	
	1,919 mg/l (daphnia) (48 h)	
LC50 (96h)	1,001 mg/l (Fish)	
57-55-6 pro	pane-1,2-diol	
EC50	19,000 mg/l (algae) (48 h)	
	18,340 mg/l (daphnia) (48 h)	
LC50 (96h)	40,613 mg/l (Fish)	
77-99-6 pro	pylidynetrimethanol	
EC50	1,001 mg/l (algae) (72h)	
	13,000 mg/l (daphnia) (48h)	
LC50 (96h)	1,001 mg/l (Fish)	
55965-84-9	a mixture of: 5-chloro-2-methyl- methyl-2 H -isothiazol-3-one [EC	2 H -isothiazol-3-one [EC No 247-500-7] and 2- No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)	
	0.16 mg/l (daphnia) (48 h)	
LC50 (96h)	0.19 mg/l (Fish)	
55965-84-9	a mixture of: 5-chloro-2-methyl-	0.11 is a (his set 0 and 150 his 0.17 500 71 and 0
	methyl-2 H -isothiazol-3-one [EC	
EC50		2 H -isothiazol-3-one [EC No 247-500-7] and 2- No 220-239-6] (3:1)
	methyl-2 H -isothiazol-3-one [EC	
EC50	methyl-2 H -isothiazol-3-one [ÉC 0.027 mg/l (algae) (72 h)	
EC50 LC50 (96h)	methyl-2 H -isothiazol-3-one [ÉC 0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h)	No 220-239-6] (3:1)
EC50 LC50 (96h) • Persistence	methyl-2 H -isothiazol-3-one [ĔC 0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h) 0.19 mg/l (Fish)	No 220-239-6] (3:1)
EC50 LC50 (96h) • Persistence • Substanc	methyl-2 H -isothiazol-3-one [ĔC 0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h) 0.19 mg/l (Fish) e and degradability No further rele	No 220-239-6] (3:1)
EC50 LC50 (96h) • Persistence • Substanc 34590-94-8 57-55-6	methyl-2 H -isothiazol-3-one [ÉC 0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h) 0.19 mg/l (Fish) e and degradability No further rele es Easily biodegradable (2-methoxymethylethoxy)propanol propane-1,2-diol	No 220-239-6] (3:1)
EC50 LC50 (96h) • Persistence • Substance 34590-94-8 57-55-6 • Behavior in • Bioaccum • Mobility • Additional • General n Water has Do not a sewage	methyl-2 H -isothiazol-3-one [ÉC 0.027 mg/l (algae) (72 h) 0.16 mg/l (daphnia) (48 h) 0.19 mg/l (Fish) e and degradability No further rele es Easily biodegradable (2-methoxymethylethoxy)propanol propane-1,2-diol n environmental systems: nulative potential No further relevant in soil No further relevant informatio ecological information: notes: azard class 1 (Self-assessment): slig illow undiluted product or large qua	No 220-239-6] (3:1)

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

(Contd. on page 9)



Version number 187

Reviewed on 08/15/2022

Printing date 08/15/2022

Product number PN6B Trade name: WB EXT CONV WHITE 30SH

(Contd. of page 8)

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
• UN proper shipping name • DOT, ADN, IMDG, IATA	Not applicable
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA · Class	Not applicable
• Packing group • DOT, IMDG, IATA	Not applicable
• Environmental hazards: • Marine pollutant:	No
· Special precautions for user	Not applicable.
 Transport in bulk according to Annex II MARPOL73/78 and the IBC Code 	of Not applicable.
· UN "Model Regulation":	Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations

· SARA

· S	ection 355 (extremely hazardous substances):	
50-00-0 fc	rmaldehyde	<0.01%
· S	ection 313 (Specific toxic chemical listings) :	
1336-21-6	ammonia	<0.1%
111-76-2	2-butoxyethanol	<0.1%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
71-36-3	butan-1-ol	<0.01%
50-00-0	formaldehyde	<0.01%
· TSC	A (Toxic Substances Control Act):	
(2-methoxy	/methylethoxy)propanol	ACTIVE
propane-1,	2-diol	ACTIVE
propylidyne	etrimethanol	ACTIVE
		(Contd. on page 10



Printing date 08/15/2022

Version number 187

Product number PN6B Trade name: WB EXT CONV WHITE 30SH

0 11 10		(Con	td. of page
2-methyl-2	2H-isothiazol-3-one		ACTIVE
	Hazardous Air Pollutants		
50-00-0 fa	ormaldehyde		
· (position 65 Chemicals known to cause cancer: Titanium dioxide only in bound form		
13463-67-	7 Titanium dioxide C.I. 77891 Pigment white 6 only for De	ust	12.5-159
· (Chemicals known to cause reproductive toxicity for females:		
None of th	ne ingredients is listed.		
· (Chemicals known to cause reproductive toxicity for males:		
None of th	ne ingredients is listed.		
· (Chemicals known to cause developmental toxicity:		
None of th	a increasion to listed		
	ne ingredients is listed.		
	cinogenic categories		
· Care			
· Carc · I	cinogenic categories	NL	<0.1%
· Carc · I	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol	NL 1	
· Caro · E 111-76-2 67-64-1	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol	_	<0.019
· Carc · E 111-76-2 67-64-1 71-36-3	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol acetone	1	<0.019 <0.019
· Carc · H 111-76-2 67-64-1 71-36-3 50-00-0	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol acetone butan-1-ol	l D	<0.01%
· Carc · E 111-76-2 67-64-1 71-36-3 50-00-0 · T	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol acetone butan-1-ol formaldehyde	l D	<0.1% <0.01% <0.01% <0.019
· Carc · I 111-76-2 67-64-1 71-36-3 50-00-0 · 1 13463-67-	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol acetone butan-1-ol formaldehyde TLV (Threshold Limit Value)	l D	<0.019 <0.019 <0.019
· Carc · E 111-76-2 67-64-1 71-36-3 50-00-0 · E 13463-67- 111-76-	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol acetone butan-1-ol formaldehyde ILV (Threshold Limit Value) 7 Titanium dioxide C.I. 77891 Pigment white 6	l D	<0.019 <0.019 <0.019 A
· Carc · H 111-76-2 67-64-1 71-36-3 50-00-0 · H 13463-67- 111-76- 67-64-	cinogenic categories EPA (Environmental Protection Agency) 2-butoxyethanol acetone butan-1-ol formaldehyde TLV (Threshold Limit Value) 7 Titanium dioxide C.I. 77891 Pigment white 6 2 2-butoxyethanol	l D	<0.019 <0.019 <0.019 <0.019 A

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 08/15/2022 / 186
 Abbreviations and acronyms:
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal concentration, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health

coatings & polymers technologies

Printing date 08/15/2022

Safety Data Sheet acc. to OSHA HCS

Version number 187

Reviewed on 08/15/2022

Product number PN6B Trade name: WB EXT CONV WHITE 30SH

(Contd. of page 10)

US

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 3: Acute toxicity - Category 3 Acute Toxicity - Dermal 2: Acute toxicity - Category 2 Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Eye Damage 1: Serious eye damage/eye irritation - Category 1 Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1A: Skin sensitisation - Category 1A Toxic to Reproduction 2: Reproductive toxicity – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 · Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site **INRS** Fiche Toxicologique IARC International agency for research on cancer \cdot * Data compared to the previous version altered.