

Printing date 09/07/2022 Version number 293

Reviewed on 09/07/2022

1 Identification

- · Product identifier
 - · Product number TN0/600
 - · Trade name: KLIMA WAX IMPR. COLORLESS
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

Aguatic Chronic 3 H412 Harmful to aguatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

2-methyl-2H-isothiazol-3-one

3-lodo-2-propynylbutylcarbamate

· Hazard statements

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangeroi	is components:	
111-76-2	2-butoxyethanol ↑ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	2.5-4.99%
57-55-6	propane-1,2-diol	2.5-4.99%
55406-53-6	3-lodo-2-propynylbutylcarbamate Acute Toxicity - Inhalation 3, H331 Specific Target Organ Toxicity - Repeated Exposure 1, H372 Eye Damage 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	≥0.5-<1%
107-21-1	ethanediol	<0.5%
	♦ Acute Toxicity - Oral 4, H302	
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol Eye Damage 1, H318 Sensitization - Skin 1B, H317 Flammable Liquids 4, H227; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥0.1-<0.5%
112-34-5	2-(2-butoxyethoxy)ethanol © Eye Irritation 2A, H319	<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one ♦ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ♦ Skin Corrosion 1B, H314; Eye Damage 1, H318 ♦ Sensitization - Skin 1, H317	≥0.0015-<0.01%

(Contd. on page 3)



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

		(Contd. of page 2)
3811-73-2	pyridine-2-thiol 1-oxide, sodium salt	<0.0025%
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10)	
	Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	 Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 Skin Corrosion 1B, H314; Eye Damage 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 	
	(M=100) ◆ Sensitization - Skin 1A, H317	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

(Contd. of page 3)

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

1 100000110	Total of Contains	
· PAC-1:		
111-76-2 2-butoxyethanol		60 ppm
57-55-6 propane-1,2-diol		30 mg/m³
55406-53-6	3-lodo-2-propynylbutylcarbamate	3.3 mg/m
577-11-7	docusate sodium	5.7 mg/m
107-21-1	ethanediol	30 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	30 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
<i>57-55-</i> 6	propane-1,2-diol	1,300 mg/m
55406-53-6	3-lodo-2-propynylbutylcarbamate	36 mg/m³
577-11-7	docusate sodium	63 mg/m³
107-21-1	ethanediol	150 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	330 mg/m³
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
· PAC-3:		·
111-76-2	2-butoxyethanol	700 ppm
<i>57-55-6</i>	propane-1,2-diol	7,900 mg/m
55406-53-6	3-lodo-2-propynylbutylcarbamate	220 mg/m³
577-11-7	docusate sodium	380 mg/m³
107-21-1	ethanediol	900 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	2,000 mg/m
		(Contd. on page



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

 (Contd. of page 4)

 112-34-5
 2-(2-butoxyethoxy)ethanol
 200 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-76	G-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin	
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 20 ppm BEI, A3	
<i>57-55-</i>	6 propane-1,2-diol	
WEEL	Long-term value: 10 mg/m³	
107-21	-1 ethanediol	
TLV	Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only, A4	
WEEL	<i>I</i> (2)	
112-34-5 2-(2-butoxyethoxy)ethanol		
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor	
	(Contd. on page 6)	

Contd. on page 6



Printing date 09/07/2022 Reviewed on 09/07/2022 Version number 293

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

(Contd. of page 5)

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine

Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment: Short term filter device:

Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

· Color: According to product specification

Characteristic · Odor Not determined. · Odor threshold:

Mixture is non-polar/aprotic. · pH-value:

Range: 7 - 9

Fluid

(Contd. on page 7)



Printing date 09/07/2022 Version number 293 Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

		(C	contd. of page
· Melt	in condition ing point/Melting range: ing point/Boiling range:	Undetermined. 100°C (212°F)	
· Flash po	oint:	101 °C (213.8 °F)	
· Flammability (solid, gaseous):		Not applicable.	
· Ignition	temperature:	240 °C (464 °F)	
· Deca	omposition temperature:	Not determined.	
· Auto igr	niting:	Product is not selfigniting.	
· Danger	of explosion:	Product does not present an explosion hazard.	
· Explosio · Lowe · Uppe	er:	1.1 Vol % 12.6 Vol %	
· Vapor p	ressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)	
· Rela · Vapo	(+/- 0,03) at 20 °C (68 °F): tive density or density poration rate	1.01 g/cm³ (8.428 lbs/gal) Not determined. Not determined. Not determined.	
· Solubili · Wate	ty in / Miscibility with er:	Fully miscible.	
· Partition	n coefficient (n-octanol/water	r): Not determined.	
		Not determined. 40 s (ISO 4 mm) N.A.	
· Solvent · Wate · VOC		66.1 % 7.87 % 79.5 g/l / 0.66 lb/gal	
· Solia	ls content:	26.1 %	
	rmation (HAPS)		
	ethanediol		<0.5%
	2-(2-butoxyethoxy)ethanol		<0.5%
	Diethylene glycol monoeth	yı etner	<0.1%
1330-20-7	,		<0.1%
	cumene		<0.019
143-22-6	2-[2-(2-butoxyethoxy)ethox	ky]ethanol	< 0.019
	2-ethoxyethanol		< 0.019

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- Chemical stability The product is stable in normal conditions of storage and use recommended (Contd. on page 8)



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

(Contd. of page 7)

- Thermal decomposition / conditions to be avoided:
 No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

ATE (Acute Toxicity Estimate)		
Oral	LD50	30,042 mg/kg
Dermal	LD50	27,538 mg/kg
	LC50/4 h	
111-76-2 2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
o rai	2500	1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
		11 mg/l (mouse)
	ropane-1,2	,
0ral	LD50	20,000 mg/kg (mouse)
Orai Dermal	LD50 LD50	2,001 mg/kg (mouse)
		2-propynylbutylcarbamate
	LD50	
Oral Dormol		500 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (mouse)
	docusate :	
Oral	LD50	3,001 mg/kg (mouse)
Dermal	LD50	2,525 mg/kg (rabbit)
	ethanedio	
Oral	LD50	301 mg/kg (mouse)
	LD50.	7,712 mg/kg (mouse)
Dermal	LD50	3,501 mg/kg (mouse)
		9,530 mg/kg (rabbit)
Inhalative	LC50/6 h	2.6 ppm (mouse)
126-86-3 2	2,4,7,9-teti	ramethyldec-5-yne-4,7-diol
Oral	LD50	4,600 mg/kg (mouse)
69011-36-	5 Poly(ox	y-1,2-ethanediyl),-tridecyl-hydroxy-, branched
Oral	LD50	2,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalativo	1 C50/4 h	20.1 mg/l (mouse)

(Contd. on page 9)



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

442 24 5 1	2 /2 hutav	(Contd. of page 8)
	•	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
2682-20-4	2-methyl-	-2H-isothiazol-3-one
Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)
3811-73-2	3811-73-2 pyridine-2-thiol 1-oxide, sodium salt	
Oral	LD50	1,208 mg/kg (mouse)
Dermal	LD50	1,800 mg/kg (mouse)
Inhalative	LC50/4 h	1.66 mg/l (mouse)

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

May cause an allergic skin reaction.

· Carcinogenic categories

	· IARC (International Agency for Research on Cancer - Cl. 1 and 2)			
98-82-8	cumene	2B		
	· NTP (National Toxicology Program)			
98-82-8	cumene	<0.01%		
	· OSHA-Ca (Occupational Safety & Health Administration)			
None of	None of the ingredients is listed.			

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

· Aquatic t	oxicity:
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
57-55-6 pro	pane-1,2-diol
EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)
55406-53-6	3-lodo-2-propynylbutylcarbamate
EC50	22 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	67 mg/l (Fish)
577-11-7 do	ocusate sodium
EC50	82.5 mg/l (algae) (72 h)
	15.2 mg/l (daphnia) (48 h)
LC50 (96h)	49 mg/l (Fish)
	(Contd. on page



Printing date 09/07/2022 Version number 293 Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

	(Contd. of page 9		
107-21-1 ethanediol			
EC50	101 mg/l (daphnia) (48h)		
LC50 (96h)	72,860 mg/l (Fish)		
69011-36-5	Poly(oxy-1,2-ethanediyl),-tridecyl-hydroxy-, branched		
EC50	10 mg/l (algae) (72 h)		
LC50 48h	10 mg/l (daphnia)		
LC50 (96h)	10 mg/l (Fish)		
64742-95-6	Solvent naphtha (petroleum), light arom.		
EC50	1 mg/l (algae) (72 h)		
	1 mg/l (daphnia) (48 h)		
LC50 (96h)	1 mg/l (Fish)		
112-34-5 2-	(2-butoxyethoxy)ethanol		
EC50	1,001 mg/l (daphnia) (48 h)		
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)		
55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2- methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)			
EC50	0.027 mg/l (algae) (72 h)		
	0.16 mg/l (daphnia) (48 h)		
LC50 (96h)	0.19 mg/l (Fish)		

· Persistence and degradability No further relevant information available.

Substances Easily biodegradable 111-76-2 | 2-butoxyethanol | . 57-55-6 | propane-1,2-diol | .

Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Smaller quantities can be disposed of with household waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

(Contd. on page 11)



Printing date 09/07/2022 Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

(Contd. of page 10)

· Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	r II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- · Various regulations
 - · SARA

· Se	ction 355 (extremely hazardous substances):	
None of the	ingredients is listed.	
· Se	ction 313 (Specific toxic chemical listings) :	
111-76-2	2-butoxyethanol	2.5-4.99%
55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0.5-<1%
107-21-1	ethanediol	<0.5%
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
111-90-0	Diethylene glycol monoethyl ether	<0.1%
95-63-6	1,2,4-trimethylbenzene	<0.1%
1330-20-7	xylene	<0.1%
98-82-8	cumene	<0.01%
1336-21-6	ammonia	<0.01%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.01%
110-80-5	2-ethoxyethanol	<0.01%
		(Contd. on page 12



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

· TSC	A (Toxic Substances Control Act):	(00	ntd. of pa	gc
	nents have the value ACTIVE.			
	Hazardous Air Pollutants			
	ethanediol			
1330-20-7				
	cumene			
	position 65			
	Chemicals known to cause cancer:			
98-82-8 c			* <0.0	ງ1
			νο.	_
	Chemicals known to cause reproductive toxicity for females:			
	e ingredients is listed.			
	Chemicals known to cause reproductive toxicity for males:			
110-80-5	2-ethoxyethanol		<0.0)1
٠ (Chemicals known to cause developmental toxicity:			
107-21-1	ethanediol ·		<0.5	5%
110-80-5	2-ethoxyethanol		<0.0)1
· Caro	cinogenic categories			
· <i>E</i>	EPA (Environmental Protection Agency)			
111-76-2	2-butoxyethanol	NL	2.5-4.9	99
95-63-6	1,2,4-trimethylbenzene	11	<0.1	%
1330-20-7	xylene	1	<0.1	%
98-82-8	cumene	D, CBD	<0.0	1%
526-73-8	1,2,3-trimethylbenzene	ll e	<0.0	1%
· 7	TLV (Threshold Limit Value)			_
111-76-2	2-butoxyethanol			Α
107-21-1	ethanediol			А
1330-20-7	xylene			Α
	NIOSH-Ca (National Institute for Occupational Safety and Health			<u>—</u>

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 09/07/2022 / 292
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)



Printing date 09/07/2022

Version number 293

Reviewed on 09/07/2022

Product number TN0/600

Trade name: KLIMA WAX IMPR. COLORLESS

(Contd. of page 12)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4
Acute Toxicity - Oral 4: Acute toxicity – Category 4
Acute Toxicity - Dermal 2: Acute toxicity – Category 2
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3
Skin Corrosion 1B: Skin corrosion/irritation – Category 1B
Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1A: Skin sensitisation - Category 1A Sensitization - Skin 1B: Skin sensitisation - Category 1B

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site
INRS Fiche Toxicologique
IARC International agency for research on cancer
* Data compared to the previous version altered.

- 115