

Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

1 Identification

- · Product identifier
 - · Product number PF5T06
 - · Trade name: SB STAIN RED MAHOGANY
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 3 H226 Flammable liquid and vapor.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Carcinogenicity 2 H351 Suspected of causing cancer.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life. Aquatic Acute 3

H412 Harmful to aquatic life with long lasting Aquatic Chronic 3

effects.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

1-methoxy-2-propanol

C.I. Acid Yellow 151

2-methoxypropanol

C.I. ACID BLACK 194

· Hazard statements

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210

(Contd. on page 2)



Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 1)

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

107-98-2	1-methoxy-2-propanol	75-100%
	Flammable Liquids 3, H226Specific Target Organ Toxicity - Single Exposure 3, H336	
72275-69-5	C.I. ACID ORANGE 139	5-9.99%
	Aquatic Chronic 2, H411 Aquatic Acute 2, H401	
112-34-5	2-(2-butoxyethoxy)ethanol	2.5-4.99%
	💠 Eye Irritation 2A, H319	
72496-88-9	C.I. Acid Yellow 151	1-2.49%
	 Carcinogenicity 2, H351 Sensitization - Skin 1B, H317 Aquatic Acute 3, H402; Aquatic Chronic 3, H412 	
57693-14-8	C.I. ACID BLACK 194	≥0.5-<1%
	Aquatic Chronic 2, H411 Eye Irritation 2A, H319; Sensitization - Skin 1, H317 Aquatic Acute 2, H401	
34590-94-8	(2-methoxymethylethoxy)propanol	<1%
	Flammable Liquids 4, H227	
1589-47-5	2-methoxypropanol	≥0.1-<0.5%
	Flammable Liquids 3, H226 Toxic to Reproduction 1B, H360	
	 Eye Damage 1, H318 Skin Irrititation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335 	

- US



Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 08/15/2022

Version number 80

Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
107-98-2	1-methoxy-2-propanol	100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
· PAC-2:		
107-98-2	1-methoxy-2-propanol	160 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
· PAC-3:		
107-98-2	1-methoxy-2-propanol	660 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage.
 - · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.



Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 4)

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10* ppm
*Inhalable fraction and vapor

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm

Skin

REL Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Long-term value: NIC-50 ppm

(Skin)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

(Contd. on page 6)



Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 5)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties				
· General Information	• •			
· Appearance:				
· Form:	Fluid			
· Color:	According to product specification			
· Odor:	Characteristic			
· Odor threshold:	Not determined.			
· pH-value:	Mixture is non-polar/aprotic.			
· Change in condition				
· Melting point/Melting range:	Undetermined.			
· Boiling point/Boiling range:	120.3 °C (248.5 °F)			
· Flash point:	35 °C (95 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	225 °C (437 °F)			
· Decomposition temperature:	Not determined.			
\cdot Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.			
· Explosion limits:				
· Lower:	0.9 Vol %			
· Upper:	~20 Vol %			
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)			
· Density (+/- 0,03) at 20 °C (68 °F):	0.912 g/cm³ (7.611 lbs/gal)			
· Relative density	Not determined.			
· Vapor density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
· Water:	Not determined.			
· Partition coefficient (n-octanol/water): Not determined.			

(Contd. on page 7)



Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

		(Contd. of page 6
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	40 s (ISO 4 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	92.54 %	
	844.0 g/l / 7.04 lb/gal	
· Solids content:	7.5 %	
· Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		2.5-4.99%
· Other information	No further relevant information available.	'

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

·Acute to	michy.	
· <i>LD</i> /.	LC50 value	es that are relevant for classification:
107-98-2 ·	1-methoxy	/-2-propanol
Oral	LD50	4,016 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	5,001 mg/l (mouse)
72275-69-	5 C.I. ACI	D ORANGE 139
Oral	LD50	5,001 mg/kg (mouse)
112-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
72496-88-	9 C.I. Acid	d Yellow 151
Oral	LD50	5,001 mg/kg (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
. Dvin	narv irritan	t offeet.

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.

(Contd. on page 8)



Printing date 08/15/2022

Version number 80

Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 7)

· Additional toxicological information:

Irritant

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

72496-88-9 C.I. Acid Yellow 151

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

•	,
· Aquatic t	oxicity:
107-98-2 1-	methoxy-2-propanol
EC50	21,100 mg/l (daphnia) (48 h)
LC50 (96h)	6,812 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable		
107-98-2	1-methoxy-2-propanol	
112-34-5	2-(2-butoxyethoxy)ethanol	

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.



Printing date 08/15/2022 Version number 80 Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleansing agent: Water, if necessary with cleansing agents.

				•	48
1 <i>4</i> I	rane	nort	ınt	orma	tion
		\mathbf{v}	шш	OHIHA	UUII

	IA.		A I	I		L	
u	IN	_	N	u	m	D	er

· DOT, IMDG, IATA

UN1263

· Note

Check viscosity and flash point at section 9

· UN proper shipping name

 $\cdot DOT$

Paint

· IMDG, IATA

PAINT

· Transport hazard class(es)

 $\cdot DOT$



· Class

3 Flammable liquids

· Label

3

· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class · Label 3 Flammable liquids

3

· Packing group

· DOT, IMDG, IATA

III

· Environmental hazards:

· Marine pollutant:

No

· Special precautions for user

Warning: Flammable liquids

Hazard identification number (Kemler code):

· EMS Number:

F-E,<u>S-E</u>

· Stowage Category

Α

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 10)



Printing date 08/15/2022

Version number 80

Reviewed on 08/15/2022

Product number PF5T06

Trade name: SB STAIN RED MAHOGANY

(Contd. of page 9)

	Trans	port/A	dditional	' inform	ation:
--	-------	--------	-----------	----------	--------

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30

m

5L

Maximum net quantity per outer packaging:

1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- · Various regulations
 - · SARA

· Section 355 (extremely hazardous substances).	· Section 35.	5 (extremely	hazardous	substances):
---	---------------	--------------	-----------	------------	----

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

112-34-5 2-(2-butoxyethoxy)ethanol

2.5-4.99%

72496-88-9 C.I. Acid Yellow 151

1-2.49%

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

72496-88-9 C.I. Acid Yellow 151

- · Proposition 65
 - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

1589-47-5 2-methoxypropanol

≥0.1-<0.5%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
 - · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)



Printing date 08/15/2022

Version number 80

Reviewed on 08/15/2022

Product number PF5T06

SB STAIN RED MAHOGANY Trade name:

(Contd. of page 10)

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 08/15/2022 / 79
 - · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids - Category 3

Flammable Liquids 4: Flammable liquids - Category 4

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Carcinogenicity 2: Carcinogenicity - Category 2

Toxic to Reproduction 1B: Reproductive toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* * Data compared to the previous version altered.