

Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

1 Identification

· Product identifier

- · Product number HUM5AC46
- · Trade name: CLEAR WB UV TOP-C 10SH
 - · Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aguatic Acute 3 H402 Harmful to aquatic life.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

2 propenoic acid, reaction products with dipentaerythritol

PHENYL ETHYL PHOSPHATE

· Hazard statements

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

(Contd. on page 2)



Printing date 10/11/2022 Ve

Version number 1

Reviewed on 10/11/2022

Product number HUM5AC46

Trade name: CLEAR WB UV TOP-C 10SH

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous o	<u> </u>	
1384855-91-7	2 propenoic acid, reaction products with dipentaerythritol	
	Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1A, H317	
	Aquatic Acute 3, H402; Aquatic Chronic 3, H412	
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
	💠 Eye Irritation 2A, H319	
84434-11-7	PHENYL ETHYL PHOSPHATE	1-2.49%
	Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Sensitization - Skin 1B, H317	
5131-66-8	3-butoxypropan-2-ol	0.5-1%
	Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	
34590-94-8	(2-methoxymethylethoxy)propanol	<1%
	Flammable Liquids 4, H227	
68439-49-6	c16-18 alcohols ethoxylated	<0.5%
	Acute Toxicity - Oral 3, H301 Eye Damage 1, H318	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

Trade name: CLEAR WB UV TOP-C 10SH

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
7631-86-9	silicon dioxide, chemically prepared	18 mg/m³
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m³
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m³
· PAC-2:		
7631-86-9	silicon dioxide, chemically prepared	740 mg/m³
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
108-01-0	2-dimethylaminoethanol	40 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
	•	(Contd. on page 4



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

Trade name: CLEAR WB UV TOP-C 10SH

68439-49-6	c16-18 alcohols ethoxylated	(Contd. of page 3) 42 mg/m ³
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m³
· PAC-3:		
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m³
	2-(2-butoxyethoxy)ethanol	200 ppm
108-01-0	2-dimethylaminoethanol	72 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m³
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m³

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

112-	34-5 2-(2-butoxyethoxy)ethanol
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
3459	0-94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

Trade name: **CLEAR WB UV TOP-C 10SH**

(Contd. of page 4)

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
 - · Breathing equipment: Short term filter device:



Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection: Goggles recommended during refilling.

9 Physical and chemical properties

Information on basic physical and	chemical properties	
· General Information		
· Appearance:		
· Form:	Fluid	
· Color:	According to product specification	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic.	
•	Range: 7 - 9	
· Change in condition		
· Melting point/Melting range:	Undetermined.	
· Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	100 °C (212 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	225 °C (437 °F)	
· Decomposition temperature:	Not determined.	



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

Trade name: CLEAR WB UV TOP-C 10SH

	(Control	d. of page
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	0.9 Vol %	
\cdot Upper:	8.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	1.3 hPa (1 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.03 g/cm³ (8.595 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	62.1 %	
· VOC content:	2.93 %	
	30.2 g/l / 0.25 lb/gal	
· Solids content:	34.9 %	
Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		1-2.499
121-44-8 triethylamine		<0.1%
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

- LD/LC50 v	values that	are rei	levant for	classification:

ATE (Acute Toxicity Estimate)

Oral LD50 85,570 mg/kg

(Contd. on page 7)



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

CLEAR WB UV TOP-C 10SH Trade name:

		(Contd. of page
1384855-9	91-7 2 pro _l	penoic acid, reaction products with dipentaerythritol
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
112-34-5 2	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
5131-66-8	3-butoxy	propan-2-ol
Oral	LD50	3,300 mg/kg (mouse)
Dermal	LD50	8,001 mg/kg (mouse)
108-01-0 2	2-dimethy	laminoethanol
Oral	LD50	1,183 mg/kg (mouse)
Dermal	LD50	1,219 mg/kg (rabbit)
Inhalative	LC50/4 h	6.1 mg/l (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
169117-72	2-0 2,5,8,1	1 Tetramethyl 6 dodecyn-Produktname : 5,8 Diol Ethoxylate
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- $\cdot Additional\ toxicological\ information:$

Irritant

May cause an allergic skin reaction.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

TOXICITY	
· Aquatic t	oxicity:
1384855-91	-7 2 propenoic acid, reaction products with dipentaerythritol
	101 mg/l (algae) (72 h)
	35 mg/l (daphnia) (48 h)
LC50 (96h)	13 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
	(Contd. on page 8)

(Contd. on page 8)



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

CLEAR WB UV TOP-C 10SH Trade name:

	(Contd. of page 7)
<i>5131-66-8 3</i>	-butoxypropan-2-ol
EC50	1,001 mg/l (algae) (96 h)
	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,000 mg/l (Fish)
108-01-0 2-	dimethylaminoethanol
EC50	66.1 mg/l (algae) (72 h)
	98.4 mg/l (daphnia) (48 h)
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
D ' - 1	and daggedability. No further relevant information evollable

Persistence and degradability No further relevant information available.

	· Substances Easily biodegradable		
	2-(2-butoxyethoxy)ethanol		
5131-66-8	3-butoxypropan-2-ol		

Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, IMDG, IATA	Not applicable



Printing date 10/11/2022 Version number 1 Reviewed on 10/11/2022

Product number HUM5AC46

Trade name: **CLEAR WB UV TOP-C 10SH**

(Contd. of page 8)

 Transport 	hazard	class	(es)
-------------------------------	--------	-------	------

· DOT, ADR, ADN, IMDG, IATA

Not applicable · Class

· Packing group

· DOT, IMDG, IATA Not applicable

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": Not applicable

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Various regulations

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

112-34-5 2-(2-butoxyethoxy)ethanol 1-2.49% <0.1%

121-44-8 triethylamine

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants 121-44-8 triethylamine

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

1589-47-5 2-methoxypropanol

<0.01%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

121-44-8 triethylamine

A4

(Contd. on page 10)



Printing date 10/11/2022

Version number 1

Reviewed on 10/11/2022

Product number HUM5AC46

CLEAR WB UV TOP-C 10SH Trade name:

(Contd. of page 9)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 10/11/2022
 - · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer