

1 Identification

- **Product identifier**
 - *Product number* TF25
 - *Trade name:* **POLYURETHANE INSULATOR**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

<p>Flammable Liquids 2</p> <p>Skin Irritation 2</p> <p>Eye Irritation 2A</p> <p>Sensitization - Respiratory 1</p> <p>Sensitization - Skin 1</p> <p>Carcinogenicity 2</p> <p>Toxic to Reproduction 2</p> <p>Specific Target Organ Toxicity - Single Exposure 3</p> <p>Specific Target Organ Toxicity - Repeated Exposure 2</p> <p>Aspiration Hazard 1</p>	<p>H225 Highly flammable liquid and vapor.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H351 Suspected of causing cancer.</p> <p>H361 Suspected of damaging fertility or the unborn child.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to the central nervous system, the hearing organs and the respiratory tract through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.</p> <p>H304 May be fatal if swallowed and enters airways.</p>
--	---

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

toluene
ethyl acetate
4,4'-methylenediphenyl diisocyanate
Aromatic polyisocyanate

Product number TF25**Trade name: POLYURETHANE INSULATOR**

(Contd. of page 1)

4-isocyanatesulphonyltoluene

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system, the hearing organs and the respiratory tract through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:**· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = *2

Fire = 3

Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture: consisting of the following components.

(Contd. on page 3)

US

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 2)

· Dangerous components:		
141-78-6	ethyl acetate ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	30-39.99%
108-88-3	toluene ⚠ Flammable Liquids 2, H225 ⚠ Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	20-24.99%
110-19-0	isobutyl acetate ⚠ Flammable Liquids 2, H225 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	12.5-15%
53317-61-6	Aromatic polyisocyanate ⚠ Eye Irritation 2A, H319; Sensitization - Skin 1, H317	2.5-4.99%
101-68-8	4,4'-methylenediphenyl diisocyanate ⚠ Sensitization - Respiratory 1, H334; Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373 ⚠ Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	2.5-4.99%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	2.5-4.99%
78-93-3	butanone ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	2.5-4.99%
4083-64-1	4-isocyanatesulphonyltoluene ⚠ Sensitization - Respiratory 1, H334 ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	≥0.1-<0.5%
26471-62-5	m-tolyldiene diisocyanate ⚠ Acute Toxicity - Inhalation 1, H330 ⚠ Sensitization - Respiratory 1, H334; Carcinogenicity 2, H351 ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Chronic 3, H412	<0.1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

Product number TF25**Trade name: POLYURETHANE INSULATOR**

(Contd. of page 3)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Take off immediately all contaminated clothing, include underwear and shoes (if necessary).
Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
Allergic reactions
For symptoms and effects caused by substances, refer to Section 11.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
Alcohol resistant foam
Alcohol resistant foam, CO, powder, water spray/mist.
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
In case of fire, the following can be released:
Nitrogen oxides (NOx)
Carbon monoxide (CO)
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 5)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 4)

· Protective Action Criteria for Chemicals

· PAC-1:		
141-78-6	ethyl acetate	1,200 ppm
108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
78-93-3	butanone	200 ppm
· PAC-2:		
141-78-6	ethyl acetate	1,700 ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
78-93-3	butanone	2700* ppm
· PAC-3:		
141-78-6	ethyl acetate	10000** ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
78-93-3	butanone	4000* ppm

7 Handling and storage

· Handling:
· Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

- Store in a cool, well-ventilated area, away from heat and sources of ignition
- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.
· Further information about storage conditions:

- Keep receptacle tightly sealed.

(Contd. on page 6)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 5)

- Store in cool, dry conditions in well sealed receptacles.
 · **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 400 ppm

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m , 0.02 ppm
REL	Long-term value: 0.05 mg/m , 0.005 ppm Ceiling limit value: 0.2* mg/m , 0.02* ppm *10-min
TLV	Long-term value: 0.005 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

78-93-3 butanone

PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

26471-62-5 m-tolyldene diisocyanate

PEL	Ceiling limit value: 0.14 mg/m , 0.02 ppm
-----	---

(Contd. on page 7)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 6)

REL	LFC
TLV	Short-term value: (0.14) NIC-0.021* mg/m , (0.02) NIC-0.003* ppm Long-term value: (0.036) NIC-0.007* mg/m , (0.005) NIC-0.001* ppm *(IFV) SEN; NIC-Skin; A3

· Ingredients with biological limit values:

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
-----	---

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

(Contd. on page 8)

Product number TF25**Trade name: POLYURETHANE INSULATOR**

(Contd. of page 7)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

77 °C (170.6 °F)

- **Flash point:**

-4 °C (24.8 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

315 °C (599 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

- **Lower:**

1.2 Vol %

- **Upper:**

11.5 Vol %

- **Vapor pressure at 20 °C (68 °F):**

105 hPa (78.8 mm Hg)

- **Density (+/- 0,03) at 20 °C (68 °F):**

0.932 g/cm (7.778 lbs/gal)

- **Relative density**

Not determined.

- **Vapor density**

Not determined.

- **Evaporation rate**

Not determined.

- **Solubility in / Miscibility with**

- **Water:**

Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 9)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 8)

- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic at 20 °C (68 °F):** 40 s (ISO 4 mm)
- **Oxidising properties:** N.A.
- **Solvent content:**
 - **VOC content:** 77.92 %
726.2 g/l / 6.06 lb/gal
- **Solids content:** 22.1 %

- **Other information (HAPS)**

108-88-3	toluene	20-24.99%
101-68-8	4,4'-methylenediphenyl diisocyanate	2.5-4.99%
26471-62-5	m-tolyldiene diisocyanate	<0.1%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**

in case of possible formation of combustion:
 Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	34.3 mg/l
------------	----------	-----------

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (mouse)
------	------	----------------------

(Contd. on page 10)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 9)

Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
53317-61-6 Aromatic polyisocyanate		
Oral	LD50	5,001 mg/kg (mouse)
101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	9,401 mg/kg (rabbit)
Inhalative	LC50/4h.	0.368 mg/l (mouse)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)
78-93-3 butanone		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	21 mg/l (mouse)
26471-62-5 m-tolidene diisocyanate		
Oral	LD50	5,110 mg/kg (mouse)
Dermal	LD50	9,401 mg/kg (rabbit)
Inhalative	LC50/4 h	0.107 mg/l (mouse)

· **Primary irritant effect:**

- *on the skin:* Irritant to skin and mucous membranes.
- *on the eye:* Irritating effect.

· **Sensitization:**

- Sensitization possible through inhalation.
- Sensitization possible through skin contact.

· **Additional toxicological information:**

Harmful

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the central nervous system, the hearing organs and the respiratory tract through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

May be fatal if swallowed and enters airways.

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
26471-62-5	m-tolidene diisocyanate	2B
98-88-4	benzoyl chloride	2A

· NTP (National Toxicology Program)		
26471-62-5	m-tolidene diisocyanate	<0.1%

(Contd. on page 11)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 10)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Sensitisation**

Monomers / polymers isocyanate

Particular characteristics / effects; prolonged exposure may irritate the eyes, nose, throat and respiratory tract.

Isocyanate exposure may result in the delayed appearance of respiratory disorders, cough or asthma. Sensitive individuals may show exposure symptoms to isocyanates below workplace TLV values. Prolonged skin contact may result cause irritation and dehydration.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

141-78-6 ethyl acetate

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

108-88-3 toluene

EC50 134 mg/l (algae) (96 h)

3.78 mg/l (daphnia) (48 h)

LC50 (96h) 5.5 mg/l (Fish)

110-19-0 isobutyl acetate

EC50 370 mg/l (algae) (72 h)

25 mg/l (daphnia)

LC50 (96h) 17 mg/l (Fish)

101-68-8 4,4'-methylenediphenyl diisocyanate

EC50 1,001 mg/l (daphnia) (24 h)

LC50 (96h) 1,001 mg/l (Fish) (96 h)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 1,001 mg/l (algae) (72 h)

501 mg/l (daphnia) (48 h)

LC50 (96h) 134 mg/l (Fish)

78-93-3 butanone

EC50 2,029 mg/l (algae) (96 h)

308 mg/l (daphnia) (48 h)

LC50 (96h) 2,993 mg/l (Fish)

26471-62-5 m-tolylidene diisocyanate

EC50 12.5 mg/l (daphnia) (48h)

LC50 (96h) 133 mg/l (Leuciscus idus melanotus)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

141-78-6 ethyl acetate

108-88-3 toluene

110-19-0 isobutyl acetate

108-65-6 2-methoxy-1-methylethyl acetate

(Contd. on page 12)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 11)

78-93-3 butanone

- **Behavior in environmental systems:**
 - *Bioaccumulative potential* No further relevant information available.
 - *Mobility in soil* No further relevant information available.
- **Additional ecological information:**
 - *General notes:*
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - *Recommendation:*
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Hand over to hazardous waste disposers.
 - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
 - *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
 - *DOT, IMDG, IATA* UN1263
 - *Note* Check viscosity and flash point at section 9

- **UN proper shipping name**
 - *DOT* Paint
 - *IMDG, IATA* PAINT

- **Transport hazard class(es)**

- *DOT*



- *Class* 3 Flammable liquids
- *Label* 3
- *Class* 3 Flammable liquids
- *Label* 3

- *IMDG, IATA*



- *Class* 3 Flammable liquids
- *Label* 3

(Contd. on page 13)

Product number TF25
Trade name: POLYURETHANE INSULATOR

(Contd. of page 12)

· Packing group · DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids 33 F-E, S-E B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· Various regulations

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3	toluene	20-24.99%
101-68-8	4,4'-methylenediphenyl diisocyanate	2.5-4.99%
26471-62-5	m-tolyldiene diisocyanate	<0.1%
98-88-4	benzoyl chloride	<0.01%

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

108-88-3	toluene	
101-68-8	4,4'-methylenediphenyl diisocyanate	

· Proposition 65

· Chemicals known to cause cancer:

26471-62-5	m-tolyldiene diisocyanate	*	<0.1%
------------	---------------------------	---	-------

· Chemicals known to cause reproductive toxicity for females:

70657-70-4	2-methoxypropyl acetate		<0.1%
------------	-------------------------	--	-------

(Contd. on page 14)

Product number TF25**Trade name: POLYURETHANE INSULATOR**

(Contd. of page 13)

 · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

 · **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	20-24.99%
----------	---------	-----------

 · **Carcinogenic categories**

 · **EPA (Environmental Protection Agency)**

108-88-3	toluene	II	20-24.99%
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD	2.5-4.99%
78-93-3	butanone	I	2.5-4.99%

 · **TLV (Threshold Limit Value)**

108-88-3	toluene	A4
26471-62-5	m-tolyldiene diisocyanate	(A4)
98-88-4	benzoyl chloride	A4

 · **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

 · **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 09/07/2022 / 117

 · **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 2: Flammable liquids . Category 2
 Flammable Liquids 3: Flammable liquids . Category 3
 Acute Toxicity - Inhalation 1: Acute toxicity . Category 1
 Acute Toxicity - Inhalation 4: Acute toxicity . Category 4
 Skin Irritation 2: Skin corrosion/irritation . Category 2
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 Sensitization - Respiratory 1: Respiratory sensitisation . Category 1
 Sensitization - Skin 1: Skin sensitisation . Category 1
 Carcinogenicity 2: Carcinogenicity . Category 2
 Toxic to Reproduction 2: Reproductive toxicity . Category 2
 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

(Contd. on page 15)

Product number TF25

Trade name: POLYURETHANE INSULATOR

(Contd. of page 14)

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2

Aspiration Hazard 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• *** Data compared to the previous version altered.**

US