

Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

#### 1 Identification

- · Product identifier
  - · Product number PD12Y15
  - · Trade name: SB PATINA SILVER
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

#### · Classification of the substance or mixture

Flammable Liquids 2 H225 Highly flammable liquid and vapor.

Skin Irrititation 2 H315 Causes skin irritation.

Eve Irritation 2A H319 Causes serious eve irritation. Carcinogenicity 2 H351 Suspected of causing cancer.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the

unborn child.

Specific Target Organ Toxicity - Single Exposure 3H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated

Exposure 2

H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

H304 May be fatal if swallowed and enters airways.

#### · Label elements

Aspiration Hazard 1

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 · Signal word Danger

· Hazard-determining components of labeling:

toluene xylene

acetone

ethylbenzene

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H351 Suspected of causing cancer.

(Contd. on page 2)



Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 1)

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	· Dangerous components:		
64-17-5	ethanol	40-49.99%	
	<ul><li>Flammable Liquids 2, H225</li><li>Eye Irritation 2A, H319</li></ul>		
67-64-1	acetone	15-19.99%	
	Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336		

(Contd. on page 3)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

400.00.0		Contd. of page 2
108-88-3	toluene	10-12.49%
1330-20-7	<ul> <li>Flammable Liquids 3, H226</li> <li>Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304</li> <li>Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335</li> <li>Aquatic Acute 3, H402; Aquatic Chronic 3, H412</li> </ul>	5-9.99%
78-93-3	butanone  Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	2.5-4.99%
100-41-4	<ul> <li>ethylbenzene</li> <li>Flammable Liquids 2, H225</li> <li>Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304</li> <li>Acute Toxicity - Inhalation 4, H332</li> <li>Aquatic Chronic 3, H412</li> </ul>	1-2.49%
64742-48-9	Naphtha (petroleum), hydrotreated heavy  Aspiration Hazard 1, H304 Flammable Liquids 4, H227	1-2.49%
64742-95-6	Solvent naphtha (petroleum), light arom.  Flammable Liquids 3, H226 Aspiration Hazard 1, H304 Specific Target Organ Toxicity - Single Exposure 3, H335-H336	1-2.49%
110-19-0	isobutyl acetate  Flammable Liquids 2, H225 Specific Target Organ Toxicity - Single Exposure 3, H336	1-2.49%
	Salt of polyamine amide (72243/00 / 2008.0023, Germany)  Skin Irrititation 2, H315	1-2.49%
67-63-0	propan-2-ol  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	<0.5%
	Octadecanoic acid, 12-hydroxy-, reaction products with hexamethylenediamine (E96096)  Specific Target Organ Toxicity - Repeated Exposure 2, H373 Sensitization - Skin 1B, H317 Aquatic Chronic 4, H413	≥0. <del>1-&lt;</del> 0.5%
108-94-1	cyclohexanone  Flammable Liquids 3, H226  Eye Damage 1, H318  Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312;  Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315	<0.5%



Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 3)

## 4 First-aid measures

#### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - Most important symptoms and effects, both acute and delayed
    For symptoms and effects caused by substances, refer to Section 11.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

#### · Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

 $\cdot \textit{For safety reasons unsuitable extinguishing agents:} \\$ 

Do not use a jet water stream as it may scatter and spread fire.

#### Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

#### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

(Contd. on page 5)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 4)

## · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

## · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

## · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

64-17-5	ethanol	1,800 ppm
67-64-1	7-64-1 acetone	
108-88-3	toluene	200 ppm 67 ppm
1330-20-7	xylene	130 ppm
78-93-3	butanone	200 ppm
100-41-4	ethylbenzene	33 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m <sup>2</sup>
110-19-0	isobutyl acetate	450 ppm
67-63-0	propan-2-ol	400 ppm
108-94-1	cyclohexanone	60 ppm
· PAC-2:		<u>'</u>
64-17-5	ethanol	3300* ppm
67-64-1	acetone	3200* ppm
108-88-3	toluene	560 ppm
1330-20-7	xylene	920* ppm
78-93-3	butanone	2700* ppm
100-41-4	-4 ethylbenzene	
64742-48-9	-9 Naphtha (petroleum), hydrotreated heavy	
110-19-0	<ul><li>9 Naphtha (petroleum), hydrotreated heavy</li><li>1,</li><li>0 isobutyl acetate</li><li>13</li></ul>	
67-63-0	-0 propan-2-ol 20	
108-94-1	cyclohexanone 83	
· PAC-3:		
64-17-5	ethanol	15000* ppm
67-64-1	acetone	5700* ppm
108-88-3	3 toluene 37	
1330-20-7		
78-93-3	3 butanone 4000	
100-41-4	-4 ethylbenzene 1800	
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m <sup>-</sup>
110-19-0	isobutyl acetate 7500**	
67-63-0	propan-2-ol	12000** ppm



Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

108-94-1 cyclohexanone

(Contd. of page 5)

5000\* ppm

# 7 Handling and storage

#### · Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

#### Conditions for safe storage, including any incompatibilities

- · Storage:
  - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

A4, BEI

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

A	this time, the other constituents have no known exposure limits.	
64-17	7-5 ethanol	
PEL	Long-term value: 1900 mg/m³, 1000 ppm	
REL	Long-term value: 1900 mg/m³, 1000 ppm	
TLV	Short-term value: 1000 ppm A3	
67-64-1 acetone		
PEL	Long-term value: 2400 mg/m³, 1000 ppm	
REL	Long-term value: 590 mg/m³, 250 ppm	
TLV	Short-term value: 500 ppm Long-term value: 250 ppm	

(Contd. on page 7)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

SB PATINA SILVER Trade name:

400	00.2 toluene	(Contd. of p
	88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, OTO, A4	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4	
<b>78-9</b> .	3-3 butanone	
PEL	Long-term value: 590 mg/m³, 200 ppm	
REL	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm	
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI	
100-	41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3	
110-	19-0 isobutyl acetate	
PEL	Long-term value: 700 mg/m³, 150 ppm	
REL	Long-term value: 700 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
67-6	3-0 propan-2-ol	
PEL	Long-term value: 980 mg/m³, 400 ppm	
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4	
108-	94-1 cyclohexanone	
PEL	Long-term value: 200 mg/m³, 50 ppm	
REL	Long-term value: 100 mg/m³, 25 ppm Skin	
TLV	Short-term value: 50 ppm Long-term value: 20 ppm	



Printing date 08/15/2022 Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 7)

# · Ingredients with biological limit values:

## 67-64-1 acetone

BEI 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

#### 108-88-3 toluene

#### BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

## 1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

#### 78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift

Parameter: Methyl ethyl ketone (nonspecific)

### 100-41-4 ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

#### 67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

## 108-94-1 cyclohexanone

BEI 80 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 1.2-Cyclohexanediol (with hydrolysis, nonspecific, nonquantitative)

8 mg/L

Medium: urine Time: end of shift

Parameter: Cyclohexanol (with hydrolysis, nonspecific, nonquantitative)

(Contd. on page 9)



Printing date 08/15/2022 Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 8)

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

Short term filter device:

Filter AX



Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
  - · General Information
    - · Appearance:

· Form: Fluid

· Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

• pH-value: Mixture is non-polar/aprotic.

(Contd. on page 10)



Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

		(Contd. of page
· Change in condition	Undatarminad	
· Melting point/Melting range: · Boiling point/Boiling range:	Undetermined. 56 °C (132.8 °F)	
	-17 °C (1.4 °F)	
· Flash point:	, ,	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.		
· Explosion limits:		
· Lower:	0.6 Vol %	
· Upper:	15 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	0.858 g/cm³ (7.16 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with	Not determined	
· Water:	Not determined.	
· Partition coefficient (n-octanol/water	): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm) N.A.	
· Oxidising properties:	N.A.	
· Solvent content: · Water:	0.0 %	
· water: · VOC content:	74.29 %	
100 comem.	637.4 g/l / 5.32 lb/gal	
· Solids content:	8.7 %	
Other information (HAPS)	- ··-	
108-88-3 toluene		10-12.499
1330-20-7 xylene		5-9.99%
100-41-4 ethylbenzene		1-2.49%
Other information	No further relevant information ava	ilable.

# 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with oxidizing agents.

Vapours may form explosive mixtures with air

(Contd. on page 11)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

SB PATINA SILVER Trade name:

(Contd. of page 10)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

4 4	LOVICO		ormation
		Total Parel	

· LD/LC50 values that are relevant for classification:			
ATE (Acu	te Toxicit	y Estimate)	
Dermal	LD50	11,317 mg/kg	
Inhalative	LC50/4 h	97.7 mg/l (mouse)	
64-17-5 et	hanol		
Oral	LD50	10,470 mg/kg (mouse)	
Dermal	LD50	20,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	124.7 mg/l (mouse)	
67-64-1 ad	cetone		
Oral	LD50	5,800 mg/kg (mouse)	
Dermal	LD50	20,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	76 mg/l (mouse)	
108-88-3 1	oluene		
Oral	LD50	5,000 mg/kg (mouse)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	25.7 mg/l (mouse)	
1330-20-7	xylene		
Oral	LD50.	3,523 mg/kg (mouse)	
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)	
	LD50.	12,126 mg/kg (rabbit)	
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)	
	LC50/4h.	27.571 mg/l (mouse)	
78-93-3 bi	utanone		
Oral	LD50	2,001 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (rabbit)	
		21 mg/l (mouse)	
100-41-4 <del>(</del>	-	ene	
Oral	LD50	3,500 mg/kg (mouse)	
Dermal	LD50	15,486 mg/kg (rabbit)	
		17.2 mg/l (mouse)	
64742-48-	-	a (petroleum), hydrotreated heavy	
Oral	LD50	>5,000 mg/kg (mouse)	

(Contd. on page 12)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

		(Contd. of page 11
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	6,801 mg/kg (mouse)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (mouse)
110-19-0 i	sobutyl a	cetate
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
67-63-0 p	ropan-2-o	I
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
Octadeca	noic acid,	12-hydroxy-, reaction products with hexamethylenediamine (E96096)
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
108-94-1	cyclohexa	none
Oral	LD50	1,890 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit)
Inhalative	LC50/4 h	6.3 mg/l (mouse)

- · Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- $\cdot Additional\ toxicological\ information:$

Irritant

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

May be fatal if swallowed and enters airways.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

#### · Carcinogenic categories

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

## Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

(Contd. on page 13)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

SB PATINA SILVER Trade name:

		(Contd. of page 12)	
	IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
64-17-5	ethanol	1 in alcoholic beverages	
100-41-4	ethylbenzene	2B	
	· NTP (National Toxicology Program)		
None of t	None of the ingredients is listed.		
	· OSHA-Ca (Occupational Safety & Health Administration)		
None of t	None of the ingredients is listed.		

# 12 Ecological information

## Toxicity

· Toxicity	
· Aquatic	
64-17-5 ethanol	
EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)
67-64-1 ac	etone
EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)
108-88-3 to	luene
EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
1330-20-7	xylene
EC50	2.2 mg/l (algae)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
78-93-3 bu	tanone
EC50	2,029 mg/l (algae) (96 h)
	308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)
100-41-4 e	thylbenzene
EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
110-19-0 is	sobutyl acetate
EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
, ,	yamine amide (72243/00 / 2008.0023, Germany)
EC50	31 mg/l (daphnia) (48 h)
LC50 (96h)	49 mg/l (Fish)
67-63-0 pro	ppan-2-ol
EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
	(Contd. on page



Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

	(Contd. of page 13)
LC50 (96h)	9,640 mg/l (Fish)
Octadecan	oic acid, 12-hydroxy-, reaction products with hexamethylenediamine (E96096)
EC50	101 mg/l (algae) (72 h)
	101 mg/l (daphnia) (48 h)
LC50 (96h)	101 mg/l (Fish)
108-94-1 cy	vclohexanone
EC50	101 mg/l (algae) (72 h)
	101 mg/l (daphnia)
LC50 (96h)	527 mg/l (Fish)

Persistence and degradability No further relevant information available.

· Substances Easily biodegradable		
64-17-5	ethanol	
67-64-1	acetone	
108-88-3	toluene	
1330-20-7	xylene	
<i>7</i> 8-93-3	butanone	
100-41-4	ethylbenzene	
110-19-0	isobutyl acetate	

### · Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

## · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.

# 13 Disposal considerations

#### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

#### Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

· UN-Number

UN1263 · DOT, IMDG, IATA

Check viscosity and flash point at section 9 · Note

(Contd. on page 15)



Printing date 08/15/2022 Version number 78 Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 14)

· UN proper shipping name

Paint · IMDG, IATA PAINT

· Transport hazard class(es)

 $\cdot DOT$ 



· Class 3 Flammable liquids

· Label

· Class 3 Flammable liquids

· Label

· IMDG, IATA



3 Flammable liquids · Class 3

· Label

· Packing group

11 · DOT, IMDG, IATA

· Environmental hazards:

No · Marine pollutant:

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33

F-E,S-E · EMS Number:

· Stowage Category В

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· IMDG

5L · Limited quantities (LQ)

Code: E2 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging:

500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

(Contd. on page 16)



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

Trade name: SB PATINA SILVER

(Contd. of page 15) · Various regulations · SARA · Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings): 108-88-3 toluene 10-12.49% 1330-20-7 xylene 5-9.99% 7429-90-5 aluminium powder (stabilised) 5-9.99% 100-41-4 ethylbenzene 1-2.49% 67-63-0 propan-2-ol <0.5% · TSCA (Toxic Substances Control Act): All components have the value ACTIVE. · Hazardous Air Pollutants 108-88-3 toluene 1330-20-7 xylene 100-41-4 ethylbenzene · Proposition 65 · Chemicals known to cause cancer: 100-41-4 ethylbenzene 1-2.49% · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene 10-12.49% · Carcinogenic categories · EPA (Environmental Protection Agency) 67-64-1 acetone 15-19.99% 108-88-3 toluene 11 10-12.49% 1330-20-7 xylene Ι 5-9.99% 78-93-3 butanone 1 2.5-4.99% 100-41-4 ethylbenzene D 1-2.49% · TLV (Threshold Limit Value) 64-17-5 ethanol *A*3 67-64-1 acetone A4 108-88-3 toluene Α4 1330-20-7 xylene A4 7429-90-5 aluminium powder (stabilised) A4 А3 100-41-4 ethylbenzene 67-63-0 propan-2-ol A4 108-94-1 cyclohexanone *A*3 · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.



Printing date 08/15/2022

Version number 78

Reviewed on 08/15/2022

**Product number PD12Y15** 

SB PATINA SILVER Trade name:

(Contd. of page 16)

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 08/15/2022 / 77
  - · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Flammable Liquids 3: Flammable liquids - Category 3

Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Dermal 4: Acute toxicity - Category 4

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1B: Skin sensitisation - Category 1B

Carcinogenicity 2: Carcinogenicity - Category 2

Toxic to Reproduction 2: Reproductive toxicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard - Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* Data compared to the previous version altered.