

Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

### 1 Identification

- · Product identifier
  - · Product number HTMB06B
  - · Trade name: KLIMA UNICO CLEAR 80SH S/SEAL
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

1.3.2 Importer

Name I.C.& S. DISTRIBUTING CO. Address P.O.BOX 10845 LANCASTER. PA USA

E-Mail: nelson@ics-company.com

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

001 813-248-0585

### 2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Aguatic Acute 3 H402 Harmful to aguatic life.

- · Label elements
  - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

adipohydrazide

3-lodo-2-propynylbutylcarbamate

· Hazard statements

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves.

(Contd. on page 2)



Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

**Product number HTMB06B** 

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 1)

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 1Reactivity = 0

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%	
	Flammable Liquids 4, H227		
111-76-2	2-butoxyethanol	0.5-1%	
	Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227		
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%	
	💠 Eye Irritation 2A, H319		
	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	≥0.25-<0.5%	
	Aquatic Chronic 2, H411 Sensitization - Skin 1, H317		
1071-93-8	adipohydrazide	≥ <i>0.</i> 25-< <i>0.</i> 5%	
	Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 Aquatic Acute 2, H401		

(Contd. on page 3)



Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

		(Contd. of page 2
55406-53-6	3-lodo-2-propynylbutylcarbamate	≥0.1-<0.25%
	<ul> <li>Acute Toxicity - Inhalation 3, H331</li> <li>Specific Target Organ Toxicity - Repeated Exposure 1, H372</li> </ul>	
	A Eye Damage 1, H318	
	Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1)	
	♠ Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.00159
	<ul> <li>Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330</li> <li>Skin Corrosion 1B, H314; Eye Damage 1, H318</li> </ul>	
	<ul> <li>Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)</li> <li>Sensitization - Skin 1A, H317</li> </ul>	

### 4 First-aid measures

### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

### · Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

#### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)



Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 3)

#### · Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

### 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

### Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

· PAC-1:			
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm	
25265-77-4	65-77-4 2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)		
111-76-2	2-butoxyethanol	60 ppm	
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm	
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m³	
55406-53-6	3-lodo-2-propynylbutylcarbamate	3.3 mg/m³	
· PAC-2:		·	
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm	
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m³	
111-76-2	2-butoxyethanol	120 ppm	
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm	
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m³	
55406-53-6	3-lodo-2-propynylbutylcarbamate	36 mg/m³	
· PAC-3:			
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm	
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m³	
111-76-2	2-butoxyethanol	700 ppm	
112-34-5	5 2-(2-butoxyethoxy)ethanol 2		
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m³	
55406-53-6	3-lodo-2-propynylbutylcarbamate	220 mg/m³	



Printing date 08/08/2022 Version number 26 Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 4)

### 7 Handling and storage

- · Handling:
  - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

### 34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm

Skin

REL Short-term value: 900 mg/m³, 150 ppm

Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Long-term value: NIC-50 ppm

(Skin)

### 111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 20 ppm

BEI, A3

### 112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 10\* ppm
\*Inhalable fraction and vapor

### · Ingredients with biological limit values:

### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

(Contd. on page 6)



Printing date 08/08/2022 Version number 26

Reviewed on 07/15/2022

**Product number HTMB06B** 

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 5)

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Not required.

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

9 Physical and chemical properties

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

# Information on basic physical and chemical properties General Information Appearance: Form: Color: Odor: Fluid According to product specification Characteristic

• Odor threshold: Characteristic Not determined.

· pH-value: Mixture is non-polar/aprotic.

Range: 7 - 9

· Change in condition

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 100 °C (212 °F)

• Flash point: 96 °C (204.8 °F)

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 7)



Printing date 08/08/2022 Version number 26 Reviewed on 07/15/2022

**Product number HTMB06B** 

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

	(Cc	ontd. of page
$\cdot$ Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
· Lower:	1.1 Vol %	
$\cdot$ Upper:	14 Vol %	
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.022 g/cm³ (8.529 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water	·): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	30 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	65.1 %	
· VOC content:	4.37 %	
	44.7 g/l / 0.37 lb/gal	
· Solids content:	30.5 %	
Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		0.5-19
143-22-6 2-[2-(2-butoxyethoxy)ethoxy	-	<0.1%
Other information	No further relevant information available.	•

### 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

- 115



Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 7)

### 11 Toxicological information

- · Information on toxicological effects
  - · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral LD50		120,000 mg/kg (ATE)
Dermal	LD50	110,000 mg/kg (rab)
Inhalative	LC50/4 h	222 mg/l

		1.19,000 1119,119 (1.6.5)		
Inhalative	LC50/4 h	222 mg/l		
34590-94-8 (2-methoxymethylethoxy)propanol				
Oral	LD50	5,135 mg/kg (mouse)		
Dermal	LD50	19,020 mg/kg (rabbit)		
111-76-2 2	2-butoxye	thanol		
Oral	LD50	1,200 mg/kg (ATE)		
		1,480 mg/kg (mouse)		
Dermal	LD50	1,100 mg/kg (rab)		
Inhalative	LC50/4 h	11 mg/l (mouse)		
112-34-5 2	2-(2-butox	yethoxy)ethanol		
Oral	LD50	6,600 mg/kg (mouse)		
Dermal	LD50	2,764 mg/kg (rabbit)		
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)				
Oral	LD50	5,001 mg/kg (mouse) (OECD - 401)		
Dermal	LD50	2,001 mg/kg (mouse) (OECD - 402)		
1071-93-8 adipohydrazide				
Oral	LD50	2,001 mg/kg (mouse)		
		The state of the s		

### 55406-53-6 3-lodo-2-propynylbutylcarbamate

Oral	LD50	500 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (mouse)

- Primary irritant effect:
  - · on the skin: No irritant effect.
  - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

May cause an allergic skin reaction. Safety data sheet available on request.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 9)



Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

**Product number HTMB06B** 

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

### · Toxicity

· Aqı	iatic	toxi	city:	

### 34590-94-8 (2-methoxymethylethoxy)propanol

EC50 970 mg/l (algae) (72 h) 1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

### 111-76-2 2-butoxyethanol

EC50 101 mg/l (daphnia) (24 h)

LC50 (96h) 101 mg/l (Fish)

### 112-34-5 2-(2-butoxyethoxy)ethanol

EC50 1,001 mg/l (daphnia) (48 h)

LC50 (96h) 1,300 mg/l (Leuciscus idus melanotus)

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

EC50 101 mg/l (algae) (72h)

4 --- --- (algae) (1211)

4 mg/l (daphnia) (OECD linee guida 202 parte 1)

LC50 (96h) 2.8 mg/l (Leuciscus idus melanotus) (OECD linee guida 203)

### 1071-93-8 adipohydrazide

EC50 9.19 mg/l (algae) (72 h)

101 mg/l (daphnia) (48 h)

LC50 (96h) 101 mg/l (Fish)

### 55406-53-6 3-lodo-2-propynylbutylcarbamate

EC50 22 mg/l (algae) (72 h)

0.16 mg/l (daphnia) (48 h)

LC50 (96h) 67 mg/l (Fish)

### 55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

EC50 0.027 mg/l (algae) (72 h)

0.16 mg/l (daphnia) (48 h)

LC50 (96h) 0.19 mg/l (Fish)

### · Persistence and degradability No further relevant information available.

### · Substances Easily biodegradable

34590-94-8 (2-methoxymethylethoxy)propanol

111-76-2 2-butoxyethanol

112-34-5 2-(2-butoxyethoxy)ethanol

### Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 10)



Printing date 08/08/2022 Version number 26 Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 9)

### · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	ll of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

(Contd. on page 11)



Printing date 08/08/2022 Version number 26

Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 10)

### · Various regulations

· SARA

· Section 355 (extremely hazardous substances):				
None of the ingredients is listed.				
· Section 313 (Specific toxic chemical listings):				
111-76-2 2-butoxyethanol		0.5-1%		
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%		
<i>55406-53-6</i>	3-lodo-2-propynylbutylcarbamate	≥0.1-<0.25%		
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%		

#### · TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

#### · Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
  - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EI	PA (Environmental Protection Agency)		
111-76-2 2	-butoxyethanol	NL	0.5-1%

· TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

*A*3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 08/08/2022 / 25
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 12)



Printing date 08/08/2022

Version number 26

Reviewed on 07/15/2022

Product number HTMB06B

Trade name: KLIMA UNICO CLEAR 80SH S/SEAL

(Contd. of page 11)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4
Acute Toxicity - Oral 4: Acute toxicity – Category 4
Acute Toxicity - Dermal 2: Acute toxicity – Category 2
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3
Skin Corrosion 1B: Skin corrosion/irritation – Category 1B
Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1A: Skin sensitisation - Category 1A

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site
INRS Fiche Toxicologique
IARC International agency for research on cancer
\* Data compared to the previous version altered.

US