

Printing date 09/28/2023

Version number 73

Reviewed on 09/18/2023

1 Identification

- · Product identifier
 - · Product number WBS4A01
 - · Trade name: WB SEALER WHITE
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling: adipohydrazide
- · Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Classification system:
 - · NFPA ratings (scale 0 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 1Reactivity = 0



Printing date 09/28/2023

Version number 73

Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangeroi	us components:		
111-76-2	2-butoxyethanol	2.5-4.99%	
	Acute Toxicity - Oral 4, H302; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227		
57-55-6	propane-1,2-diol	0.5-1%	
34590-94-8	(2-methoxymethylethoxy)propanol	<1%	
	Flammable Liquids 4, H227		
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%	
	💠 Eye Irritation 2A, H319		
1071-93-8	adipohydrazide	≥0.1-<0.25%	
	Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 Aquatic Acute 2, H401		

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

(Contd. on page 3)



Printing date 09/28/2023

Version number 73

Reviewed on 09/18/2023

Product number WBS4A01

Trade name: **WB SEALER WHITE**

(Contd. of page 2)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:				
471-34-1	calcium carbonate		45 mg/m³	
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		30 mg/m³	
111-76-2	2-butoxyethanol		60 ppm	
57-55-6	propane-1,2-diol		30 mg/m³	
34590-94-8	(2-methoxymethylethoxy)propanol		150 ppm	
112-34-5	2-(2-butoxyethoxy)ethanol		30 ppm	
· PAC-2:				
471-34-1	calcium carbonate	21	0 mg/m³	
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	33	0 mg/m³	
111-76-2	2-butoxyethanol	12	120 ppm	
57-55-6	propane-1,2-diol	1,300 mg/m ³		
34590-94-8	(2-methoxymethylethoxy)propanol	17	00* ppm	
112-34-5	2-(2-butoxyethoxy)ethanol 33		ррт	
· PAC-3:				
471-34-1	calcium carbonate	1,3	300 mg/m ³	
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,0	000 mg/m ³	
111-76-2	2-butoxyethanol	70	0 ррт	
57-55-6	propane-1,2-diol	7,9	900 mg/m ³	
34590-94-8	(2-methoxymethylethoxy)propanol	99	00** ppm	
112-34-5	2-(2-butoxyethoxy)ethanol	20	0 ppm	



Printing date 09/28/2023 Version number 73 Reviewed on 09/18/2023

Product number WBS4A01

Trade name: **WB SEALER WHITE**

(Contd. of page 3)

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

	nis time, the remaining constituent has no known exposure limits.
111-76	-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3
57-55-0	6 propane-1,2-diol
WEEL	Long-term value: 10 mg/m³
34590-	94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: 50 ppm
112-34	-5 2-(2-butoxyethoxy)ethanol
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
	· Regulatory information

PEL: Guide to Occupational Exposure Values (OSHA PELs) REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

(Contd. on page 5)



Printing date 09/28/2023 Version number 73 Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

(Contd. of page 4)

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine
Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

- · Regulatory information BEI: Guide to Occupational Exposure Values (BEI)
- · Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Not required.

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Color: According to product specification

Odor: Characteristic

Odor: CharacteristicOdor threshold: Not determined.

• pH-value: Mixture is non-polar/aprotic.

Range: 7 - 9

(Contd. on page 6)



Printing date 09/28/2023 Version number 73 Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

CI 1.	(Contd. of
· Change in condition	Undetermined.
· Melting point/Melting range: · Boiling point/Boiling range:	100 °C (212 °F)
01 0 0	, ,
· Flash point:	100 °C (212 °F)
Flammability (solid, gaseous):	Not applicable.
· Auto igniting:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	10.6 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
· Vapor pressure at 50 °C (122 °F):	5.3 hPa (4 mm Hg)
Density (+/- 0,03) at 20 °C (68 °F):	1.61 g/cm³ (13.435 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water	·); Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	30 s (ISO 3 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	31.4 %
· VOC content:	3.84 %
	61.8 g/l / 0.52 lb/gal
· Solids content:	64.8 %
ther information (HAPS)	
12-34-5 2-(2-butoxyethoxy)ethanol	<

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.



Printing date 09/28/2023 Version number 73 Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· Acute to	охииу.	
· LD/	LC50 value	es that are relevant for classification:
ATE (Acu	te Toxicit	y Estimate)
Oral	LD50	48,000 mg/kg (ATE)
Inhalative	LC50/4 h	440 mg/l (mouse)
111-76-2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,414 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)
57-55-6 p	ropane-1,2	2-diol
Oral	LD50	20,000 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)
34590-94-	8 (2-meth	oxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)
112-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
1071-93-8	adipohyo	Irazide
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

- Primary irritant effect:
 - on the skin: No irritant effect. • on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- $\cdot Additional\ toxicological\ information:$

Irritant

May cause an allergic skin reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· Carcinogenic categories

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6

2B - DUST



Printing date 09/28/2023 Version

Version number 73

Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

14808-60-7	Quartz (SiO2)	(Contd. of page 7)
$\cdot N'$	TP (National Toxicology Program)	
14808-60-7	Quartz (SiO2)	<0.1%
· O.	SHA-Ca (Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

· Toxicity

· Aquatic to	· Aquatic toxicity:			
111-76-2 2-	111-76-2 2-butoxyethanol			
EC50	1,840 mg/l (algae) (72h)			
	1,550 mg/l (daphnia) (48h)			
LC50 (96h)	1,474 mg/l (Fish)			
57-55-6 pro	pane-1,2-diol			
EC50	19,000 mg/l (algae) (48 h)			
	18,340 mg/l (daphnia) (48 h)			
LC50 (96h)	40,613 mg/l (Fish)			
34590-94-8	(2-methoxymethylethoxy)propanol			
EC50	970 mg/l (algae) (72 h)			
	1,919 mg/l (daphnia) (48 h)			
LC50 (96h)	1,001 mg/l (Fish)			
112-34-5 2-	(2-butoxyethoxy)ethanol			
EC50	1,001 mg/l (daphnia) (48 h)			
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)			
1071-93-8 a	1071-93-8 adipohydrazide			
EC50	9.19 mg/l (algae) (72 h)			
	101 mg/l (daphnia) (48 h)			
LC50 (96h)	101 mg/l (Fish)			

- Persistence and degradability No further relevant information available.
 - · Substances Easily biodegradable

111-76-2 2-butoxyethanol .

57-55-6 propane-1,2-diol .

Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or

Do not allow undiluted product or large quantities of it to reach ground water, water course of sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



Printing date 09/28/2023 Version number 73 Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

(Contd. of page 8)

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	Natarrila
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR/RID, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex I	l of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Various regulations
 - · SARA

· SA	KA	
	Section 355 (extremely hazardous substances):	
None of t	the ingredients is listed.	
	Section 313 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	2.5-4.99%
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
· TS	CA (Toxic Substances Control Act):	
All compo	onents have the value ACTIVE.	
	Hazardous Air Pollutants	
None of t	the ingredients is listed.	

- · Proposition 65
 - · Chemicals known to cause cancer: Titanium dioxide only in bound form Quartz (SiO2) only in bound form

(Contd. on page 10)



Printing date 09/28/2023

Version number 73

Reviewed on 09/18/2023

Product number WBS4A01

Trade name: **WB SEALER WHITE**

		(Co	ntd. of page 9)
13463-6	7-7 Titanium dioxide C.I. 77891 Pigment white 6	only for Dus	t 5-9.99%
14808-6	0-7 Quartz (SiO2)	*	<0.1%
	Chemicals known to cause reproductive toxicity for females:	•	
None of	he ingredients is listed.		
	Chemicals known to cause reproductive toxicity for males:		
None of	he ingredients is listed.		
	Chemicals known to cause developmental toxicity:		
None of	he ingredients is listed.		
· Ca	rcinogenic categories		
	EPA (Environmental Protection Agency)		
111-76-2	2-butoxyethanol	NL	2.5-4.99%

·EF	A (Environmental Protection Agency)		
111-76-2 2	butoxyethanol	NL	2.5-4.99%
· TI	V (Threshold Limit Value)		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		A4
14807-96-6	Talc (Mg3H2(SiO3)4)		A4
111-76-2	2-butoxyethanol		A3
14808-60-7	Quartz (SiO2)		A2
· NI	OSH-Ca (National Institute for Occupational Safety and Health)		

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	5-9.99%
1 <i>4</i> 808-60-7	Quartz (SiO2)	<0.1%

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 09/28/2023
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

(Contd. on page 11)



Printing date 09/28/2023

Version number 73

Reviewed on 09/18/2023

Product number WBS4A01

Trade name: WB SEALER WHITE

(Contd. of page 10)

Sensitization - Skin 1: Skin sensitisation - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

·Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site
INRS Fiche Toxicologique
IARC International agency for research on cancer

* Data compared to the previous version altered.

- 110