

## 1 Identification

- **Product identifier**
  - *Product number* TX1939
  - *Trade name:* **PU HARDENER**
    - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
  - *Manufacturer/Supplier:*  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
  - *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.  
001 813-248-0585

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225	Highly flammable liquid and vapor.
Eye Irritation 2A	H319	Causes serious eye irritation.
Sensitization - Skin 1	H317	May cause an allergic skin reaction.
Specific Target Organ Toxicity - Single Exposure 3H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.		

### · Label elements

- *GHS label elements*  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS07

- *Signal word* Danger
- *Hazard-determining components of labeling:*  
Homopolymers of HDI  
ethyl acetate  
n-butyl acetate  
2-methoxy-1-methylethyl acetate
- *Hazard statements*  
H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- *Precautionary statements*  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 1)

P405  
P501

Store locked up.  
Dispose of contents/container in accordance with local/regional/national/  
international regulations.

**Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

**Dangerous components:**

141-78-6	ethyl acetate ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	40-49.99%
28182-81-2	Homopolymers of HDI ⚠ Acute Toxicity - Inhalation 4, H332; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	30-39.99%
123-86-4	n-butyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	20-24.99%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	2.5-4.99%
822-06-0	hexamethylene diisocyanate ⚠ Acute Toxicity - Inhalation 1, H330 ⚠ Sensitization - Respiratory 1, H334 ⚠ Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	<0.1%

**4 First-aid measures**

**Description of first aid measures**

**General information:**

Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
personal protective equipment for first aid responders is recommended. (please see section 8)

**After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 2)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
  - **Most important symptoms and effects, both acute and delayed**  
Allergic reactions  
For symptoms and effects caused by substances, refer to Section 11.
  - **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
  - **Suitable extinguishing agents:**  
Alcohol resistant foam  
Alcohol resistant foam, CO, powder, water spray/mist.
  - **For safety reasons unsuitable extinguishing agents:**  
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)
- **Advice for firefighters**  
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
  - **Protective equipment:**  
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to Section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
141-78-6	ethyl acetate	1,200 ppm
28182-81-2	Homopolymers of HDI	7.8 mg/m
123-86-4	n-butyl acetate	5 ppm

(Contd. on page 4)

**Product number TX1939**  
**Trade name: PU HARDENER**

		(Contd. of page 3)
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
· PAC-2:		
141-78-6	ethyl acetate	1,700 ppm
28182-81-2	Homopolymers of HDI	86 mg/m
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
· PAC-3:		
141-78-6	ethyl acetate	10000** ppm
28182-81-2	Homopolymers of HDI	510 mg/m
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

## 7 Handling and storage

### · Handling:

#### · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### · Conditions for safe storage, including any incompatibilities

#### · Storage:

##### · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

##### · Information about storage in one common storage facility: Not required.

##### · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

### · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

### · Additional information about design of technical systems: No further data; see section 7.

### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
-----	--------------------------------------

(Contd. on page 5)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 4)

REL Long-term value: 1400 mg/m , 400 ppm  
 TLV Long-term value: 400 ppm

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m , 150 ppm  
 REL Short-term value: 950 mg/m , 200 ppm  
 Long-term value: 710 mg/m , 150 ppm  
 TLV Short-term value: 150 ppm  
 Long-term value: 50 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL Long-term value: 50 ppm

**822-06-0 hexamethylene diisocyanate**

REL Long-term value: 0.035 mg/m , 0.005 ppm  
 Ceiling limit value: 0.14\* mg/m , 0.02\* ppm  
 \*10-min  
 TLV Long-term value: 0.005 ppm  
 BEI

· **Regulatory information**

PEL: Guide to Occupational Exposure Values (OSHA PELs)  
 REL: Guide to Occupational Exposure Values (NIOSH RELs)  
 TLV: Guide to Occupational Exposure Values (TLV)  
 WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

· **Ingredients with biological limit values:****822-06-0 hexamethylene diisocyanate**

BEI 15 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: 1.6-Hexamethylene diamine with hydrolysis (nonspecific)

· **Regulatory information BEI:** Guide to Occupational Exposure Values (BEI)· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· **Protection of hands:**

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

(Contd. on page 6)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (170.6 °F)

· **Flash point:**

-4 °C (24.8 °F)

· **Flammability (solid, gaseous):**

Highly flammable.

· **Auto igniting:**

315 °C (599 °F)

· **Decomposition temperature:**

Not determined.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1.2 Vol %

· **Upper:**

11.5 Vol %

· **Vapor pressure at 20 °C (68 °F):**

97 hPa (72.8 mm Hg)

· **Vapor pressure at 50 °C (122 °F):**

360 hPa (270 mm Hg)

· **Density (+/- 0,03) at 20 °C (68 °F):**

0.951 g/cm (7.936 lbs/gal)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

· **Water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 7)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 6)

· <b>Viscosity:</b>	
· <b>Dynamic:</b>	Not determined.
· <b>Kinematic at 20 °C (68 °F):</b>	29 s (ISO 3 mm)
· <b>Oxidising properties:</b>	N.A.
· <b>Solvent content:</b>	
· <b>VOC content:</b>	68.60 % 652.4 g/l / 5.44 lb/gal
· <b>Solids content:</b>	
31.4 %	
· <b>Other information (HAPS)</b>	
822-06-0	hexamethylene diisocyanate <0.1%

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimate)</b>		
Inhalative	LC50/4 ore/h/saat	35 mg/l
<b>141-78-6 ethyl acetate</b>		
Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)
<b>28182-81-2 Homopolymers of HDI</b>		
Oral	LD50	2,501 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (rabbit)
<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	21.1 mg/l (mouse)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8,532 mg/kg (mouse)

(Contd. on page 8)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 7)

Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	35.7 mg/l (mouse)
<b>822-06-0 hexamethylene diisocyanate</b>		
Oral	LD50	738 mg/kg (mouse)
Dermal	LD50	7,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	0.124 mg/l (mouse)

- **Primary irritant effect:**

- *on the skin:* No irritant effect.

- *on the eye:* Irritating effect.

- *Sensitization:* Sensitization possible through skin contact.

- **Additional toxicological information:**

*Irritant*

*Causes serious eye irritation.*

*May cause an allergic skin reaction.*

*May cause respiratory irritation.*

*May cause drowsiness or dizziness.*

*Contains isocyanates. See information supplied by the manufacturer.*

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Sensitisation**

*Monomers / polymers isocyanate*

*Particular characteristics / effects; prolonged exposure may irritate the eyes, nose, throat and respiratory tract.*

*Isocyanate exposure may result in the delayed appearance of respiratory disorders, cough or asthma. Sensitive individuals may show exposure symptoms to isocyanates below workplace TLV values. Prolonged skin contact may result cause irritation and dehydration.*

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

- **141-78-6 ethyl acetate**

EC50 165 mg/l (daphnia) (48 h)

LC50 (96 ore/h/saat) 230 mg/l (Fish)

- **28182-81-2 Homopolymers of HDI**

EC50 1,001 mg/l (algae) (72 h)

127 mg/l (daphnia) (48 h)

LC50 (96 ore/h/saat) 100 mg/l (Fish)

- **123-86-4 n-butyl acetate**

EC50 397 mg/l (algae) (72 h)

44 mg/l (daphnia) (48 h)

LC50 (96 ore/h/saat) 18 mg/l (Fish)

(Contd. on page 9)



**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 8)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50	1,001 mg/l (algae) (72 h) 501 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	134 mg/l (Fish)

**822-06-0 hexamethylene diisocyanate**

EC50	77.5 mg/l (algae) (72 h) 89.2 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	82.9 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· *Substances Easily biodegradable*

141-78-6	ethyl acetate	.
123-86-4	n-butyl acetate	.
108-65-6	2-methoxy-1-methylethyl acetate	.

· **Behavior in environmental systems:**

· *Bioaccumulative potential*

141-78-6	ethyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 0,68
123-86-4	n-butyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 2,3
108-65-6	2-methoxy-1-methylethyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1,2

· *Mobility in soil*

141-78-6	ethyl acetate	Basso potenziale di adsorbimento nel suolo
----------	---------------	--

· **Additional ecological information:**

· *General notes:*

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· *Recommendation:*

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· *Recommendation:* Disposal must be made according to official regulations.

### 14 Transport information

· **UN-Number**

· DOT, IMDG, IATA

UN1263

· *Note*

Check viscosity and flash point at section 9

(Contd. on page 10)

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 9)

**· UN proper shipping name**

· DOT Paint  
 · IMDG, IATA PAINT

**· Transport hazard class(es)**

· DOT



· Class 3 Flammable liquids  
 · Label 3  
 · Class 3 Flammable liquids  
 · Label 3

· IMDG, IATA



· Class 3 Flammable liquids  
 · Label 3

**· Packing group**

· DOT, IMDG, IATA II

**· Environmental hazards:**

· Marine pollutant: No

**· Special precautions for user**

Warning: Flammable liquids

· Hazard identification number (Kemler code): 33  
 · EMS Number: F-E, S-E  
 · Stowage Category B

**· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**· Transport/Additional information:**

· IMDG

· Limited quantities (LQ) 5L  
 · Excepted quantities (EQ) Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, II

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture  
 Requirements of Federal Register

(Contd. on page 11)

US

**Product number TX1939**  
**Trade name: PU HARDENER**

(Contd. of page 10)

- **Various regulations**

- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings) :**

822-06-0	hexamethylene diisocyanate	<0.1%
----------	----------------------------	-------

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

822-06-0	hexamethylene diisocyanate
----------	----------------------------

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

70657-70-4	2-methoxypropyl acetate	<0.01%
------------	-------------------------	--------

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
  - **Date of preparation / last revision** 02/12/2024
- **Abbreviations and acronyms:**
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMIS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent

(Contd. on page 12)

**Product number TX1939**
**Trade name: PU HARDENER**

(Contd. of page 11)

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Acute Toxicity - Inhalation 1: Acute toxicity . Category 1

Acute Toxicity - Inhalation 4: Acute toxicity . Category 4

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation . Category 1

Sensitization - Skin 1: Skin sensitisation . Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

 • **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

 • \* **Data compared to the previous version altered.**