

## 1 Identification

- **Product identifier**
  - Product number PA70
  - Trade name: **WHITE GEN PURPOSE PU SEALER**
    - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
IVM Chemicals Srl  
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
  - **Information department:**  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - **Emergency telephone number:**  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

- **Label elements**

- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

xylene  
ethylbenzene

- **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H373 May cause damage to the hearing organs through prolonged or repeated exposure.  
Route of exposure: Oral, Inhalation.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

**Product number PA70**  
**Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 1)

P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

**Dangerous components:**

1330-20-7	xylene <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 3, H226</li> <li>⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304</li> <li>⚠ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335</li> <li>⚠ Aquatic Acute 3, H402; Aquatic Chronic 3, H412</li> </ul>	10-12.49%
110-19-0	isobutyl acetate <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 2, H225</li> <li>⚠ Specific Target Organ Toxicity - Single Exposure 3, H336</li> </ul>	5-9.99%
141-78-6	ethyl acetate <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 2, H225</li> <li>⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336</li> </ul>	5-9.99%
108-65-6	2-methoxy-1-methylethyl acetate <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 3, H226</li> <li>⚠ Specific Target Organ Toxicity - Single Exposure 3, H336</li> </ul>	2.5-4.99%
100-41-4	ethylbenzene <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 2, H225</li> <li>⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304</li> <li>⚠ Acute Toxicity - Inhalation 4, H332</li> <li>⚠ Aquatic Chronic 3, H412</li> </ul>	2.5-4.99%
123-86-4	n-butyl acetate <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 3, H226</li> <li>⚠ Specific Target Organ Toxicity - Single Exposure 3, H336</li> </ul>	<0.5%
64-17-5	ethanol <ul style="list-style-type: none"> <li>⚠ Flammable Liquids 2, H225</li> <li>⚠ Eye Irritation 2A, H319</li> </ul>	<0.5%

US

(Contd. on page 3)

**Product number PA70**

**Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 2)

#### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

(Contd. on page 4)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 3)

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to Section 13.  
 Ensure adequate ventilation.
- **Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
471-34-1	calcium carbonate	45 mg/m
1330-20-7	xylene	130 ppm
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
110-19-0	isobutyl acetate	450 ppm
141-78-6	ethyl acetate	1,200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
123-86-4	n-butyl acetate	5 ppm
64-17-5	ethanol	1,800 ppm
· PAC-2:		
471-34-1	calcium carbonate	210 mg/m
1330-20-7	xylene	920* ppm
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
110-19-0	isobutyl acetate	1300* ppm
141-78-6	ethyl acetate	1,700 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
123-86-4	n-butyl acetate	200 ppm
64-17-5	ethanol	3300* ppm
· PAC-3:		
471-34-1	calcium carbonate	1,300 mg/m
1330-20-7	xylene	2500* ppm
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
110-19-0	isobutyl acetate	7500** ppm
141-78-6	ethyl acetate	10000** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
123-86-4	n-butyl acetate	3000* ppm
64-17-5	ethanol	15000* ppm

## 7 Handling and storage

- **Handling:**
  - **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.

(Contd. on page 5)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 4)

- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- **Information about protection against explosions and fires:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

### 110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 400 ppm

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

### 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
-----	-------------------------------------

(Contd. on page 6)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 5)

REL Short-term value: 545 mg/m , 125 ppm  
 Long-term value: 435 mg/m , 100 ppm

TLV Long-term value: 20 ppm  
 OTO, BEI, A3

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m , 150 ppm

REL Short-term value: 950 mg/m , 200 ppm  
 Long-term value: 710 mg/m , 150 ppm

TLV Short-term value: 150 ppm  
 Long-term value: 50 ppm

**64-17-5 ethanol**

PEL Long-term value: 1900 mg/m , 1000 ppm

REL Long-term value: 1900 mg/m , 1000 ppm

TLV Short-term value: 1000 ppm  
 A3

- **Regulatory information**

- PEL: Guide to Occupational Exposure Values (OSHA PELs)

- REL: Guide to Occupational Exposure Values (NIOSH RELs)

- TLV: Guide to Occupational Exposure Values (TLV)

- WEEL: Guide to Occupational Exposure Values (AIHA WEELs)

- **Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

**100-41-4 ethylbenzene**

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Regulatory information BEI:** Guide to Occupational Exposure Values (BEI)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing.

- Wash hands before breaks and at the end of work.

- Store protective clothing separately.

- Avoid contact with the eyes and skin.

- **Breathing equipment:**

- Short term filter device:



Suitable respiratory protective device recommended.

Filter A

(Contd. on page 7)

US

**Product number PA70**  
**Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 6)

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Mixture is non-polar/aprotic.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (170.6 °F)

· **Flash point:**

-4 °C (24.8 °F)

· **Flammability (solid, gaseous):**

Highly flammable.

· **Auto igniting:**

315 °C (599 °F)

· **Decomposition temperature:**

Not determined.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1 Vol %

· **Upper:**

30 Vol %

· **Vapor pressure at 20 °C (68 °F):**

97 hPa (72.8 mm Hg)

· **Density (+/- 0,03) at 20 °C (68 °F):**

1.373 g/cm (11.458 lbs/gal)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

(Contd. on page 8)

**Product number PA70**  
**Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 7)

· <i>Evaporation rate</i>	Not determined.	
· <i>Solubility in / Miscibility with</i>	Not miscible or difficult to mix.	
· <i>Water:</i>		
· <i>Partition coefficient (n-octanol/water):</i>	Not determined.	
· <i>Viscosity:</i>		
· <i>Dynamic:</i>	Not determined.	
· <i>Kinematic at 20 °C (68 °F):</i>	101 s (ISO 6 mm)	
· <i>Oxidising properties:</i>	N.A.	
· <i>Solvent content:</i>		
· <i>Water:</i>	0.0 %	
· <i>VOC content:</i>	29.63 %	
	406.8 g/l / 3.39 lb/gal	
· <i>Solids content:</i>	70.4 %	
· <b>Other information (HAPS)</b>		
1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	2.5-4.99%

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### ATE (Acute Toxicity Estimate)

Dermal	LD50	10,183 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	88.5 mg/l (mouse)

### 1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	11 mg/l (mouse) (ATE value)

(Contd. on page 9)



**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 8)

	LC50/4 ore/h/saat.	27.571 mg/l (mouse)
<b>110-19-0 isobutyl acetate</b>		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	31 mg/l (mouse)
<b>141-78-6 ethyl acetate</b>		
Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	35.7 mg/l (mouse)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	17.2 mg/l (mouse)
<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	21.1 mg/l (mouse)
<b>64-17-5 ethanol</b>		
Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 ore/h/saat	124.7 mg/l (mouse)

- **Primary irritant effect:**

- *on the skin:* Irritant to skin and mucous membranes.
- *on the eye:* Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- **Carcinogenic categories**

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

(Contd. on page 10)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 9)

*Ethylbenzene*

From IARC MONOGRAPHS VOLUME 77/2000

*Human carcinogenicity data*

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

*Evaluation*

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· *IARC (International Agency for Research on Cancer - Cl. 1 and 2)*

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1 in alcoholic beverages
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· *NTP (National Toxicology Program)*

14808-60-7	Quartz (SiO <sub>2</sub> )	<0.1%
------------	----------------------------	-------

· *OSHA-Ca (Occupational Safety & Health Administration)*

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**· *Aquatic toxicity:*

<b>1330-20-7 xylene</b>	
EC50	2.2 mg/l (algae)
LC50 (48 ore/h/saat)	1 mg/l (daphnia)
LC50 (96 ore/h/saat)	2.6 mg/l (Fish)
<b>110-19-0 isobutyl acetate</b>	
EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96 ore/h/saat)	17 mg/l (Fish)
<b>141-78-6 ethyl acetate</b>	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	230 mg/l (Fish)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	134 mg/l (Fish)
<b>100-41-4 ethylbenzene</b>	
EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	12.1 mg/l (Fish)

(Contd. on page 11)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 10)

**123-86-4 n-butyl acetate**

EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	18 mg/l (Fish)

**64-17-5 ethanol**

EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96 ore/h/saat)	15.3 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

1330-20-7	xylene	.
110-19-0	isobutyl acetate	.
141-78-6	ethyl acetate	.
108-65-6	2-methoxy-1-methylethyl acetate	.
100-41-4	ethylbenzene	.

- **Behavior in environmental systems:**

- **Bioaccumulative potential**

1330-20-7	xylene	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 3,12
110-19-0	isobutyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 2,3
141-78-6	ethyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 0,68
108-65-6	2-methoxy-1-methylethyl acetate	Coefficiente di ripartizione n-ottanolo/acqua (Log Kow): 1,2

- **Mobility in soil**

1330-20-7	xylene	Koc = 246 . 540
110-19-0	isobutyl acetate	Adsorbimento/desorbimento log Koc: 1,19
141-78-6	ethyl acetate	Basso potenziale di adsorbimento nel suolo

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
 Hand over to hazardous waste disposers.  
 Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 12)

**Product number PA70**  
**Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 11)

- **Uncleaned packagings:**
- *Recommendation: Disposal must be made according to official regulations.*

## 14 Transport information

- **UN-Number**
- *DOT, IMDG, IATA* UN1263
- *Note* Check viscosity and flash point at section 9

- **UN proper shipping name**
- *DOT* Paint
- *IMDG, IATA* PAINT

- **Transport hazard class(es)**
- *DOT*
- 
- *Class* 3 Flammable liquids
- *Label* 3
- *Class* 3 Flammable liquids
- *Label* 3

- *IMDG, IATA*
- 
- *Class* 3 Flammable liquids
- *Label* 3

- **Packing group**
- *DOT, IMDG, IATA* III

- **Environmental hazards:**
- *Marine pollutant:* No

- **Special precautions for user** Warning: Flammable liquids
- *Hazard identification number (Kemler code):* -
- *EMS Number:* F-E, S-E
- *Stowage Category* A

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**
- *DOT*
- *Remarks:* > 450 l: 3 F1, II
- *IMDG*
- *Limited quantities (LQ)* 5L
- *Excepted quantities (EQ)* Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging:

(Contd. on page 13)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 12)

· <b>Remarks:</b>	1000 ml > 450 l: 3, II
· <b>IATA</b>	
· <b>Remarks:</b>	> 30 l: 3, II
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

### · Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

- Various regulations
- SARA

#### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

#### · Section 313 (Specific toxic chemical listings) :

1330-20-7	xylene	10-12.49%
100-41-4	ethylbenzene	2.5-4.99%
67-63-0	propan-2-ol	<0.01%

#### · TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

#### · Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene

#### · Proposition 65

##### · Chemicals known to cause cancer:

Titanium dioxide only in bound form  
 Quartz (SiO<sub>2</sub>) only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	5-9.99%
100-41-4	ethylbenzene	*	2.5-4.99%
14808-60-7	Quartz (SiO <sub>2</sub> )	*	<0.1%

##### · Chemicals known to cause reproductive toxicity for females:

70657-70-4	2-methoxypropyl acetate	<0.01%
------------	-------------------------	--------

##### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

##### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

##### · EPA (Environmental Protection Agency)

1330-20-7	xylene	I	10-12.49%
100-41-4	ethylbenzene	D	2.5-4.99%
78-93-3	butanone	I	<0.01%

##### · TLV (Threshold Limit Value)

1330-20-7	xylene	A4
-----------	--------	----

(Contd. on page 14)

**Product number PA70****Trade name: WHITE GEN PURPOSE PU SEALER**

(Contd. of page 13)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	5-9.99%
14808-60-7	Quartz (SiO <sub>2</sub> )	<0.1%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

- **Date of preparation / last revision** 02/13/2024

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Acute Toxicity - Dermal 4: Acute toxicity . Category 4

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Carcinogenicity 2: Carcinogenicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2

Aspiration Hazard 1: Aspiration hazard . Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- **\* Data compared to the previous version altered.**