

Printing date 09/07/2022

Version number 92

Reviewed on 08/05/2022

1 Identification

- · Product identifier
 - · Product number TN931/00
 - Trade name: <u>KLIMA WB MATT TOP-COAT</u> • Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals Srl
 Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

- · GHS label elements
 - The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labeling:

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)

- · Hazard statements
- H317 May cause an allergic skin reaction.
- · Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



(Contd. on page 2)

US



Reviewed on 08/05/2022

Printing date 09/07/2022

Version number 92

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4) HEALTH 0 FIRE 1 REACTIVITY 0

Health = 0Fire = 1Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

 Dangerou 	us components:	
34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%
440.04.5	Flammable Liquids 4, H227	4.0.400/
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
	🚸 Eye Irritation 2A, H319	
	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyloxypoly(oxyethylene)	≥0.25-<0.5%
	 Aquatic Chronic 2, H411 Sensitization - Skin 1, H317 	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	 Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 Skin Corrosion 1B, H314; Eye Damage 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Sensitization - Skin 1A, H317 	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8) · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

(Contd. on page 3)

US



Version number 92

Reviewed on 08/05/2022

Product number TN931/00

Printing date 09/07/2022

Trade name: KLIMA WB MATT TOP-COAT

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents:
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture In case of fire, the following can be released: Nitrogen oxides (NOx)

Carbon monoxide (CO)

Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
 Keep away from ignition sources
 Environmental precautions:
 Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation.

- Reference to other sections
 No dangerous substances are released.
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
9002-84-0	Polytetrafluoroethylene	12 mg/m ³
· PAC-2:		
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
9002-84-0	Polytetrafluoroethylene	130 mg/m³
	·	(Contd. on page 4)



Version number 92

Reviewed on 08/05/2022

Printing date 09/07/2022

Product number TN931/00 Trade name: KLIMA WB MATT TOP-COAT

		(Contd. of page 3)
· PAC-3:		
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
9002-84-0	Polytetrafluoroethylene	790 mg/m³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

- Take on temperature greater than 5 ° C
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

34590-94-8 (2-methoxymethylethoxy)propanol

- PEL Long-term value: 600 mg/m³, 100 ppm Skin REL Short-term value: 900 mg/m³, 150 ppm
- Long-term value: 600 mg/m³, 100 ppm Skin
- TLV Long-term value: NIC-50 ppm (Skin)

112-34-5 2-(2-butoxyethoxy)ethanol

- TLV Long-term value: 10* ppm
 - *Inhalable fraction and vapor

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

US

iVM Chemicals

Printing date 09/07/2022

· Auto igniting:

· Danger of explosion:

Safety Data Sheet acc. to OSHA HCS

Version number 92

Reviewed on 08/05/2022

Product number TN931/00 Trade name: KLIMA WB MATT TOP-COAT

Wash hands before breaks and at the end of work.

(Contd. of page 4)

· Breathing equipment: Short term filter device: Suitable respiratory protective device recommended. Filter A · Protection of hands: Protective gloves Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product . · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective aloves and has to be observed. · Eve protection: Goggles recommended during refilling. 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: · Form: Fluid · Color: According to product specification Characteristic · Odor: Not determined. · Odor threshold: Mixture is non-polar/aprotic. · pH-value: Range: 7 - 9 · Change in condition • Melting point/Melting range: Undetermined. · Boiling point/Boiling range: 100 °C (212 °F) 100 °C (212 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. 225 °C (437 °F) · Ignition temperature: Not determined. · Decomposition temperature:

Product is not selfigniting.

Product does not present an explosion hazard.

(Contd. on page 6)



Printing date 09/07/2022

Version number 92

Reviewed on 08/05/2022

Product number TN931/00 Trade name: KLIMA WB MATT TOP-COAT

		(Contd. of page
· Explosion limits:		
· Lower:	0.9 Vol %	
· Upper:	14 Vol %	
· Vapor pressure at 20 °C (68 °F):	0.4 hPa (0.3 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	1.05 g/cm³ (8.762 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Fully miscible.	
· Partition coefficient (n-octanol/water	·): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
• <i>Kinematic at 20</i> • <i>C</i> (68 • <i>F</i>):	29 s (ISO 3 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
• Water:	56.5 %	
· VOC content:	4.64 %	
	48.7 g/l / 0.41 lb/gal	
· Solids content:	38.8 %	
Other information (HAPS)		
112-34-5 2-(2-butoxyethoxy)ethanol		1-2.49%
143-22-6 2-[2-(2-butoxyethoxy)ethoxy	r]ethanol	<0.1%
• Other information	No further relevant information avail	lable.

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

• **Chemical stability** The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:

- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

\cdot LD/LC50 values that are	relevant for classification	:
---------------------------------	-----------------------------	---

34590-94-8 (2-methoxymethylethoxy)propanol

Oral LD50 5,135 mg/kg (mouse)

Dermal LD50 19,020 mg/kg (rabbit)

112-34-5 2-(2-butoxyethoxy)ethanol

Oral LD50 6,600 mg/kg (mouse)

(Contd. on page 7)

⁻US



Version number 92

Reviewed on 08/05/2022

Printing date 09/07/2022

Product number TN931/00 Trade name: KLIMA WB MATT TOP-COAT

	(Contd. of page 6)
Dermal LD50 2,764 mg/kg (rabbit)	
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox	
hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-	
hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tel	't-butyl-4-hydroxyphenyl)
propionyloxypoly(oxyethylene)	
Oral LD50 5,001 mg/kg (mouse) (OECD - 401)	
Dermal LD50 2,001 mg/kg (mouse) (OECD - 402)	
73296-89-6 Sulfuric acid, mono-C12-16-alkyl esters, sodium salts	
Oral LD50 2,001 mg/kg (mouse)	
Dermal LD50 2,001 mg/kg (rabbit)	
Primary irritant effect:	
• on the skin: No irritant effect.	
• on the eye: No irritating effect.	
 Sensitization: Sensitization possible through skin contact. 	
• Additional toxicological information:	
Irritant	
May cause an allergic skin reaction.	
· Carcinogenic categories	
· IARC (International Agency for Research on Cancer - Cl. 1 and	12)
None of the ingredients is listed.	
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed	

None of the ingredients is listed.

12 Ecological information

 Toxicity

• Ачиши и	oxicity:
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
hydroxypo hydroxyph	alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega- ly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- enyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) xypoly(oxyethylene)
hydroxypo hydroxyph propionylo	ly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- enyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
hydroxypo hydroxyph propionylo	lý(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-bútyl-4- enyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) xypoly(oxyethylene)
hydroxypo hydroxyph propionylo EC50	lý(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-bútyl-4- enyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) xypoly(oxyethylene) 101 mg/l (algae) (72h)
hydroxypo hydroxyph propionylo EC50 LC50 (96h)	lý(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-bútyl-4- enyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) xypoly(oxyethylene) 101 mg/l (algae) (72h) 4 mg/l (daphnia) (OECD linee guida 202 parte 1)
hydroxypo hydroxyph propionylo EC50 LC50 (96h)	ly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- enyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) xypoly(oxyethylene) 101 mg/l (algae) (72h) 4 mg/l (daphnia) (OECD linee guida 202 parte 1) 2.8 mg/l (Leuciscus idus melanotus) (OECD linee guida 203)



Version number 92

Reviewed on 08/05/2022

Printing date 09/07/2022

Product number TN931/00 Trade name: KLIMA WB MATT TOP-COAT

LC50 48h	3.6 mg/l (Fish) (Contd. of page 7
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2- methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)
· Persistence	e and degradability No further relevant information available.
· Substanc	es Easily biodegradable
34590-94-8	(2-methoxymethylethoxy)propanol.
112-34-5	2-(2-butoxyethoxy)ethanol .
• Bioaccun • Mobility • Additional • General n Water ha Do not a sewage	azard class 1 (Self-assessment): slightly hazardous for water llow undiluted product or large quantities of it to reach ground water, water course o
13 Disposal	considerations
	tment methods endation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No

1-2.49%

<0.1%

<0.1%



Safety Data Sheet acc. to OSHA HCS

Version number 92

Reviewed on 08/05/2022

Printing date 09/07/2022

Product number TN931/00

Trade name: KLIMA WB MATT TOP-COAT			
		(Contd. of page 8)	
· Special precautions for user	Not applicable.		
 Transport in bulk according to Anne MARPOL73/78 and the IBC Code 	x II of Not applicable.		
· UN "Model Regulation":	Not applicable		

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture Requirements of Federal Register

· Various regulations

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

112-34-5 2-(2-butoxyethoxy)ethanol

1336-21-6 ammonia 143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 10)



Printing date 09/07/2022

Safety Data Sheet acc. to OSHA HCS

Version number 92

Reviewed on 08/05/2022

Product number TN931/00 Trade name: KLIMA WB MATT TOP-COAT

(Contd. of page 9)

us

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl · Contact: See emergency phone · Date of preparation / last revision 09/07/2022 / 91 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity - Oral 3: Acute toxicity - Category 3 Acute Toxicity - Dermal 2: Acute toxicity - Category 2 Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Eye Damage 1: Serious eye damage/eye irritation - Category 1 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1A: Skin sensitisation - Category 1A Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments Agency ECHA web site **INRS Fiche Toxicologique** IARC International agency for research on cancer \cdot * Data compared to the previous version altered.