

Printing date 09/14/2022 Version number 1 Reviewed on 09/14/2022

1 Identification

- · Product identifier
 - · Product number WUM5A06J
 - · Trade name: UV WB WHITE SELF-S 8 GLOSS
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV) Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Carcinogenicity 2 H351 Suspected of causing cancer.

Aquatic Acute 2 H401 Toxic to aquatic life.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS07 GHS08 GHS09

- · Signal word Warning
- · Hazard-determining components of labeling:

2,2-bis(acryloyloxymethyl)butyl acrylate

2-methyl-2H-isothiazol-3-one

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

· Hazard statements

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)



Printing date 09/14/2022

Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 1)

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

-	components:	
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate Carcinogenicity 2, H351 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrititation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	5-9.99%
7473-98-5	2-hydroxy-2-methylpropiophenone	<2.5%
5131-66-8	3-butoxypropan-2-ol 1 Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	
111-90-0	Diethylene glycol monoethyl ether Flammable Liquids 4, H227	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol © Eye Irritation 2A, H319	0.5-1%
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide Sensitization - Skin 1A, H317 Aquatic Chronic 4, H413	≥0.1-<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 Skin Corrosion 1B, H314; Eye Damage 1, H318 Sensitization - Skin 1, H317	≥0.0015-<0.01%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) ♠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330 ♠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ♠ Sensitization - Skin 1A, H317	≥0.00025-<0.00159



Printing date 09/14/2022

Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

(Contd. on page 4)



Printing date 09/14/2022 Version number 1 Re

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 3)

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:			
13463-67-7	7 Titanium dioxide C.I. 77891 Pigment white 6 30 m		30 mg/m³
7631-86-9	silicon dioxide, chemically prepared		18 mg/m³
111-90-0	Diethylene glycol monoethyl ether		75 ppm
112-34-5	2-(2-butoxyethoxy)ethanol		30 ppm
68439-49-6	c16-18 alcohols ethoxylated		3.8 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated		30 mg/m³
· PAC-2:			
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		330 mg/m³
7631-86-9	silicon dioxide, chemically prepared		740 mg/m³
111-90-0	Diethylene glycol monoethyl ether		100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol		33 ppm
68439-49-6	c16-18 alcohols ethoxylated 42 mg		42 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated 330 mg		330 mg/m³
· PAC-3:			
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,	.000 mg/m³
7631-86-9	silicon dioxide, chemically prepared	4,	.500 mg/m³
111-90-0	Diethylene glycol monoethyl ether	4:	50 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	20	00 ppm
68439-49-6	c16-18 alcohols ethoxylated	2:	50 mg/m³
25322-69-4	Propane-1,2-diol, propoxylated	2,	.000 mg/m³
	I .		

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Keep respiratory protective device available.

· Information about protection against explosions and fires:

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)



Printing date 09/14/2022

Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

UV WB WHITE SELF-S 8 GLOSS Trade name:

(Contd. of page 4)

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

,	ine time, the ether denetice have no mile in expectate in the
15625-	89-5 2,2-bis(acryloyloxymethyl)butyl acrylate
WEEL	Long-term value: 1 mg/m³ Skin
111-90	-0 Diethylene glycol monoethyl ether
WEEL	Long-term value: 25 ppm
112-34	-5 2-(2-butoxyethoxy)ethanol
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

Not required.

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Printing date 09/14/2022 Version number 1 Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

nformation on basic physical and o	chemical properties
· General Information	
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
	Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	190 °C (374 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
\cdot $Upper:$	8.4 Vol %
· Vapor pressure at 20 °C (68 °F):	1.3 hPa (1 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1.153 g/cm³ (9.622 lbs/gal)
· Relative density	Not determined.
Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water	e): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	48.7 %
· VOC content:	3.15 %
	36.3 g/l / 0.30 lb/gal



Printing date 09/14/2022

Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

		(Contd. of page 6)
· Other inf	formation (HAPS)	
111-90-0	Diethylene glycol monoethyl ether	0.5-1%
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%
121-44-8	triethylamine	<0.1%
110-80-5	2-ethoxyethanol	<0.01%
· Other i	information No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
 - Thermal decomposition / conditions to be avoided:

 No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

	ioxicuy:		
		ues that are relevant for classification:	
ATE (Ac	ute Toxic	ity Estimate)	
Oral	LD50	106,207 mg/kg (mouse)	
15625-89)-5 2,2-bis	(acryloyloxymethyl)butyl acrylate	
Oral	LD50	5,001 mg/kg (mouse)	
Dermal	LD50	5,001 mg/kg (mouse)	
7473-98-	5 2-hydro	xy-2-methylpropiophenone	
Oral	LD50	1,694 mg/kg (mouse)	
Dermal	LD50	6,929 mg/kg (mouse)	
5131-66-	8 3-butox	ypropan-2-ol	
Oral	LD50	3,300 mg/kg (mouse)	
Dermal	LD50	8,001 mg/kg (mouse)	
111-90-0	Diethyler	ne glycol monoethyl ether	
Oral	LD50	6,031 mg/kg (mouse)	
Dermal	LD50	9,143 mg/kg (rabbit)	
112-34-5	2-(2-buto	xyethoxy)ethanol	
Oral	LD50	6,600 mg/kg (mouse)	
Dermal	LD50	2,764 mg/kg (rabbit)	
162881-2	26-7 phen	yl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	
Oral	LD50	2,001 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
			(Contd. on page



Printing date 09/14/2022

Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

		(Contd. of page 7)
2682-20-4	2-methyl-	-2H-isothiazol-3-one
Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)

- · Primary irritant effect:
 - · on the skin: No irritant effect. · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- $\cdot Additional\ toxicological\ information:$

Irritant

May cause an allergic skin reaction.

Suspected of causing cancer.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· Carcinogenic categories

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

· IA	RC (International Agency for Research on Cancer - Cl. 1 and 2)	
13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6		2B - DUST
15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate 2B		2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the	ingredients is listed.	

12 Ecological information

· Toxicity Toxic to aquatic life with long lasting effects.

· Aquatic t	toxicity:	
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	
EC50	4.9 mg/l (algae) (72 h)	
	19.9 mg/l (daphnia) (48 h)	
LC50 (96h)	2.1 mg/l (Fish)	
7473-98-5 2	2-hydroxy-2-methylpropiophenone	
EC50	119 mg/l (daphnia) (48h)	
LC50 (96h)	160 mg/l (Fish)	
5131-66-8 3	3-butoxypropan-2-ol	
EC50	1,001 mg/l (algae) (96 h)	
	1,001 mg/l (daphnia) (48 h)	
LC50 (96h)	1,000 mg/l (Fish)	
111-90-0 Di	iethylene glycol monoethyl ether	
LC50 48h	1,982 mg/l (daphnia)	
	(Contd. on pag	e 9



Printing date 09/14/2022 Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

	(Contd. of page 8)
LC50 (96h)	101 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	
EC50	1,175 mg/l (daphnia) 48h
	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
, ,	0.19 mg/l (Fish)

· Persistence and degradability No further relevant information available.

· Fersistence and degradability No further relevant information available.			
· Substances Easily biodegradable			
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate		
5131-66-8	3-butoxypropan-2-ol		
111-90-0	Diethylene glycol monoethyl ether		
112-34-5	2-(2-butoxyethoxy)ethanol		

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

US



Printing date 09/14/2022 Version number 1 Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 9)

UN-Number	
· DOT, IMDG, IATA	UN3082
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
$\cdot DOT$	Environmentally hazardous substance, liqu
· IMDG	n.o.s. (2,2-bis(acryloyloxymethyl)butyl acrylate) ENVIRONMENTALLY HAZARDOL SUBSTANCE, LIQUID, N.O.S. (2, bis(acryloyloxymethyl)butyl acrylate), MARII POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOL SUBSTANCE, LIQUID, N.O.S. (2, bis(acryloyloxymethyl)butyl acrylate)
Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	9 Miscellaneous dangerous substances a articles
· Label · Class	9 0 Missallanasus dangaraus substanass s
· Class	9 Miscellaneous dangerous substances a articles
\cdot Label	9
Packing group · DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardo substances: 2,2-bis(acryloyloxymethyl)butyl acryla
· Marine pollutant:	Yes
Special marking (IATA).	Symbol (fish and tree) Symbol (fish and tree)
Special marking (IATA):	· · · · · · · · · · · · · · · · · · ·
Special precautions for user	Warning: Miscellaneous dangerous substances a articles
· Hazard identification number (Keml	
· EMS Number: · Stowage Category	F-A,S-F A
	··
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
\cdot DOT	
· Remarks:	Special marking with the symbol (fish a tree).
· IMDG	
· Limited quantities (LQ)	5L Codo: E1
\cdot Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging:



Printing date 09/14/2022 Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 10)

Maximum net quantity per outer packaging: 1000 ml

UN 3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (2,2-BIS(ACRYLOYLOXYMETHYL)BUTYL ACRYLATE), 9. III

15 Regulatory information

UN "Model Regulation":

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Various regulations
 - · SARA

· SAI	KA				
• ,	Section 355 (extremely hazardous substances):				
None of t	he ingredients is listed.				
	Section 313 (Specific toxic chemical listings) :				
111-90-0	Diethylene glycol monoethyl ether	0.5-1%			
112-34-5	2-(2-butoxyethoxy)ethanol	0.5-1%			
121- 44 -8	triethylamine	<0.1%			
110-80-5	2-ethoxyethanol	<0.01%			
· TSO	CA (Toxic Substances Control Act):	·			
All compo	All components have the value ACTIVE.				
	· Hazardous Air Pollutants				
121-44-8	121-44-8 triethylamine				

- · Proposition 65
 - · Chemicals known to cause cancer:

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	10-12.49%		
15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate	*	5-9.99%		
· Chemicals known to cause reproductive toxicity for females:					
None of the ingredients is listed.					
· Chemicals known to cause reproductive toxicity for males:					
110-80-5 2	-ethoxyethanol		<0.01%		
· Chemicals known to cause developmental toxicity:					
110-80-5 2	-ethoxyethanol		<0.01%		

· Carci	nogenic categories				
· EF	PA (Environmental Protection Agency)				
None of the	ingredients is listed.				
· TLV (Threshold Limit Value)					
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4			
121-44-8	triethylamine	A4			
· NIOSH-Ca (National Institute for Occupational Safety and Health)					
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	10-12.49%			
	(Co	ntd. on page 12			



Printing date 09/14/2022

Version number 1

Reviewed on 09/14/2022

Product number WUM5A06J

Trade name: UV WB WHITE SELF-S 8 GLOSS

(Contd. of page 11)

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 09/14/2022 / -
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Acute Toxicity - Oral 4: Acute toxicity - Category 4 Acute Toxicity - Dermal 2: Acute toxicity - Category 2

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Carcinogenicity 2: Carcinogenicity - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* * Data compared to the previous version altered.