

Printing date 07/18/2019 Version number 65 Reviews

Reviewed on 07/18/2019

### 1 Identification

### · Product identifier

·!Product number PF5K18

·!Trade name: STAIN CONCENTRATE WENGHE

· Application of the substance / the mixture For professional use

#### · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

1.3.2 Importer

Name I.C.& S. DISTRIBUTING CO.

Address P.O.BOX 10845

LANCASTER. PA

USA

E-Mail: nelson@ics-company.com

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated

exposure.



#### GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Printing date 07/18/2019 Version number 65 Reviewed on 07/18/2019

**Product number PF5K18** 

STAIN CONCENTRATE WENGHE Trade name:

(Contd. of page 1)

### · Hazard pictograms







GHS02

GHS07

### · Signal word Danger

### · Hazard-determining components of labeling:

1-methoxy-2-propanol C.I. ACID BLACK 194 xvlene

C.I. Acid Yellow 151

hydrogenbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)] chromate(1-)

#### · Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/ P501

international regulations.

### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
  - · Description: Mixture: consisting of the following components.

(Contd. on page 3)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

		(Contd. of page 2			
Ü	us components:	15-19.99%			
107-98-2	1-methoxy-2-propanol  ♠ Flam. Liq. 3, H226 ♠ STOT SE 3, H336				
123-86-4	n-butyl acetate  ♦ Flam. Liq. 3, H226  ♦ STOT SE 3, H336	15-19.99%			
67-64-1	acetone 10- <b>♦</b> Flam. Liq. 2, H225 <b>♦</b> Eye Irrit. 2A, H319; STOT SE 3, H336				
108-65-6	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226 STOT SE 3, H336	10-12.49%			
1330-20-7	xylene     Flam. Liq. 3, H226     STOT RE 2, H373; Asp. Tox. 1, H304     Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	5-9.99%			
112-34-5	2-(2-butoxyethoxy)ethanol   © Eye Irrit. 2A, H319	5-9.99%			
111-76-2	2-butoxyethanol  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319  Flam. Liq. 4, H227	5-9.99%			
57693-14-8	C.I. ACID BLACK 194  Aquatic Chronic 2, H411  Eye Irrit. 2A, H319; Skin Sens. 1, H317  Aquatic Acute 2, H401	2.5-4.99%			
67-63-0	propan-2-ol <b>♦</b> Flam. Liq. 2, H225 <b>♦</b> Eye Irrit. 2A, H319; STOT SE 3, H336	2.5-4.99%			
72496-88-9	9 C.I. Acid Yellow 151 1-2.  Carc. 2, H351 Skin Sens. 1, H317 Aquatic Acute 3, H402; Aquatic Chronic 3, H412				
100-41-4	ethylbenzene  Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	1-2.49%			
5601-29-6	hydrogenbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl) azo]benzoato(2-)]chromate(1-)  © Eye Irrit. 2A, H319; Skin Sens. 1A, H317 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥0.1-<0.5%			

### 4 First-aid measures

- · Description of first aid measures
  - · General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 4)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 3)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - Most important symptoms and effects, both acute and delayed
    For symptoms and effects caused by substances, refer to Section 11.
    No further relevant information available.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
  - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
  - · For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

### 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 4)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### · Protective Action Criteria for Chemicals

· PAC-1:				
107-98-2	1-methoxy-2-propanol		100 ppm	
123-86-4	n-butyl acetate		5 ppm	
67-64-1	acetone		200 ppm	
108-65-6	2-methoxy-1-methylethyl acetate		50 ppm	
1330-20-7	xylene		130 ppn	
112-34-5	2-(2-butoxyethoxy)ethanol		30 ppm	
67-63-0	propan-2-ol		400 ppm	
100-41-4	ethylbenzene		33 ppm	
· PAC-2:				
107-98-2	1-methoxy-2-propanol		160 ppm	
123-86-4 n-butyl acetate			200 ppm	
67-64-1 acetone			3200* ppn	
108-65-6	108-65-6 2-methoxy-1-methylethyl acetate		1,000 ppm	
1330-20-7	0-20-7 xylene		920* ppm	
112-34-5	2-(2-butoxyethoxy)ethanol		33 ppm	
67-63-0	propan-2-ol		2000* ppn	
100-41-4	ethylbenzene		1100* ppm	
· PAC-3:				
107-98-2	1-methoxy-2-propanol	660 ppm		
123-86-4	n-butyl acetate	30	3000* ppm	
67-64-1	acetone	5700* ppm		
108-65-6	2-methoxy-1-methylethyl acetate	50	5000* ppm	
1330-20-7	xylene	25	2500* ppm	
112-34-5	2-(2-butoxyethoxy)ethanol	20	200 ppm	
67-63-0	propan-2-ol	12	2000** ppn	
100-41-4	ethylbenzene	18	300* ppm	

### 7 Handling and storage

### · Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)



Printing date 07/18/2019 Version number 65 Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 5)

### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

### · Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

	and unio, the other conductorite have no known expedito inities.
107-98	3-2 1-methoxy-2-propanol
REL	Short-term value: 540 mg/m³, 150 ppm
	Long-term value: 360 mg/m³, 100 ppm
TLV	Short-term value: 369 mg/m³, 100 ppm
	Long-term value: 184 mg/m³, 50 ppm
123-80	6-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm
	Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m³, 150 ppm
	Long-term value: 238 mg/m³, 50 ppm
67-64-	1 acetone
PEL	Long-term value: 2400 mg/m³, 1000 ppm
REL	Long-term value: 590 mg/m³, 250 ppm
TLV	Short-term value: 1187 mg/m³, 500 ppm
	Long-term value: 594 mg/m³, 250 ppm
	BEI
	5-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
112-34	1-5 2-(2-butoxyethoxy)ethanol
TLV	Long-term value: 67.5* mg/m³, 10* ppm
	*Inhalable fraction and vapor
67-63-	0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
	I .

(Contd. on page 7)



Printing date 07/18/2019 Version number 65 Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

	(Contd. of pa
REL	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm
	Long-term value: 492 mg/m³, 200 ppm
100 4	BEI I1-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	
KEL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm
1 L V	BEI
	· Ingredients with biological limit values:
67-64	I-1 acetone
BEI !	50 mg/L
1	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)
	-20-7 xylene
	1.5 g/g creatinine
	Medium: urine
	Time: end of shift Parameter: Methylhippuric acids
	76-2 2-butoxyethanol
	200 mg/g creatinine
	Medium: urine
-	Time: end of shift
1	Parameter: Butoxyacetic acid with hydrolysis
	3-0 propan-2-ol
	40 mg/L
	Medium: urine Time: end of shift at end of workweek
	Parameter: Acetone (background, nonspecific)
	I1-4 ethylbenzene
	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
1	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative
-	
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

### · Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 8)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 7)

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



#### Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

  The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties		
· Information on basic physical and chemical properties		

· General Information · Appearance:

· Form: Fluid

· Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

· Flammability (solid, gaseous):

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 56 °C (132.8 °F)

• Flash point: -17 °C (1.4 °F)

1 tush point:

· Ignition temperature: 225 °C (437 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive

Not applicable.

air/vapor mixtures are possible.

(Contd. on page 9)



Printing date 07/18/2019 Version number 65 Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

		(Contd. of page
· Explosion limits:		
· Lower:	0.9 Vol %	
· Upper:	~20 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
· Density (+/- 0,03) at 20 °C (68 °F):	0.929 g/cm³ (7.753 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water	·); Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	0.6 %	
· VOC content:	75.79 %	
	704.1 g/l / 5.88 lb/gal	
· Solids content:	12.6 %	
Other information (HAPS)		
1330-20-7 xylene		5-9.99
112-34-5 2-(2-butoxyethoxy)ethanol		5-9.99
100-41-4 ethylbenzene		1-2.49
Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
  - · Chemical stability The product is stable in normal conditions of storage and use recommended
    - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

HS



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

Product number PF5K18

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 9)

formatic	on on toy	icological effects
· Acute to		icological effects
		es that are relevant for classification:
07-98-2	1-methoxy	r-2-propanol
Oral	LD50	4,016 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
nhalative	LC50/4 h	5,001 mg/l (mouse)
23-86-4 ı	n-butyl ac	etate
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
nhalative	LC50/4 h	21.1 mg/l (mouse)
7-64-1 ad	cetone	
)ral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
nhalative	LC50/4 h	76 mg/l (mouse)
08-65-6 2	2-methoxy	v-1-methylethyl acetate
)ral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
nhalative	LC50/4 h	35.7 mg/l (mouse)
330-20-7	xylene	
Dral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
nhalative	LC50/4h.	27.571 mg/l (mouse)
12-34-5	2-(2-butox	yethoxy)ethanol
Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)
11-76-2	2-butoxye	thanol
Dral	LD50	1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
7-63-0 pi	ropan-2-o	I
)ral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
	LC50/4 h	
2496-88-	9 C.I. Acid	d Yellow 151
Oral	LD50	5,001 mg/kg (mouse)
	ethylbenz	
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
		17.2 mg/l (mouse)
601-29-6		nbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl) o(2-)]chromate(1-)
)ral	LD50	8,290 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (_)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 10)

- · Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· Carcinogenic categories

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

#### Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IA	RC (International Agency for Research on Cancer - Cl. 1 and 2)			
72496-88-9	C.I. Acid Yellow 151	2B		
100-41-4	ethylbenzene	2B		
· N7	TP (National Toxicology Program)			
None of the	None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

### 12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects

· TOXICILY FIRE	armui to aquatic line with long lasting effects.				
· Aquatic t	oxicity:				
107-98-2 1-	methoxy-2-propanol				
EC50	21,100 mg/l (daphnia) (48 h)				
LC50 (96h)	6,812 mg/l (Fish)				
123-86-4 n-	123-86-4 n-butyl acetate				
EC50	397 mg/l (algae) (72 h)				
	44 mg/l (daphnia) (48 h)				
LC50 (96h)	18 mg/l (Fish)				
67-64-1 ace	etone				
EC50	8,800 mg/l (daphnia)				
LC50 (96h)	5,540 mg/l (Fish)				
108-65-6 2-	methoxy-1-methylethyl acetate				
EC50	1,001 mg/l (algae) (72 h)				
	501 mg/l (daphnia) (48 h)				
	(Contd. on page 12)				



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

	(Contd. of page 11
LC50 (96h)	134 mg/l (Fish)
1330-20-7 x	ylene
EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
112-34-5 2-	(2-butoxyethoxy)ethanol
EC50	1,001 mg/l (daphnia) (48 h)
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)
111-76-2 2-	butoxyethanol
EC50	1,840 mg/l (algae) (72 h)
	1,550 mg/l (daphnia) (48 h)
LC50 (96h)	1,474 mg/l (Fish)
67-63-0 pro	pan-2-ol
EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)
100-41-4 et	hylbenzene
EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
	hydrogenbis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo] penzoato(2-)]chromate(1-)
LC50 48h	75 mg/l (daphnia)
Davaiatama	a and dagradahility. No further relevant information available

· Persistence and degradability No further relevant information available.

· Substances Easily biodegradable			
107-98-2	1-methoxy-2-propanol		
123-86-4	n-butyl acetate		
67-64-1	acetone		
108-65-6	2-methoxy-1-methylethyl acetate		
1330-20-7	xylene		
112-34-5	2-(2-butoxyethoxy)ethanol		
111-76-2	2-butoxyethanol		
67-63-0	propan-2-ol		
100-41-4	ethylbenzene		

### Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

### Ecotoxical effects:

· Remark: Harmful to fish

### · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 13)



Printing date 07/18/2019 Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 12)

· Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.

9 / 1	ronc	nort II	ntorm	2tion
	10113	port ii		GUIOII

U	N-	Nı	um	he	r

*· DOT* NA 1263 *· IMDG, IATA* UN1263

### · UN proper shipping name

· DOT Paint · IMDG, IATA PAINT

### · Transport hazard class(es)

 $\cdot DOT$ 



· Class 3 Flammable liquids

· Label

· Class 3 Flammable liquids

· Label

### · IMDG, IATA



· Class 3 Flammable liquids

· Label 3

### · Packing group

· DOT, IMDG, IATA

### · Environmental hazards:

· Marine pollutant: No

### · Special precautions for user Warning: Flammable liquids

Danger code (Kemler):
 EMS Number:
 F-E,S-E

· Stowage Category B

(Contd. on page 14)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

Trade name: STAIN CONCENTRATE WENGHE

(Contd. of page 13)

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

1L

Code: E2

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging:

500 ml

UN 1263 PAINT, 3, II · UN "Model Regulation":

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):			
None of the ingredients is listed.			
· Section 313 (Specific toxic chemical listings) :			
1330-20-7	xylene	5-9.99%	
112-34-5	2-(2-butoxyethoxy)ethanol	5-9.99%	
111-76-2	2-butoxyethanol	5-9.99%	
67-63-0	propan-2-ol	2.5-4.99%	
72496-88-9	C.I. Acid Yellow 151	1-2.49%	
100-41-4	ethylbenzene	1-2.49%	
· TSCA (Toxic Substances Control Act):			

All components have the value ACTIVE.

· Hazar	dous Air Pollutants
1330-20-7	
	C.I. Acid Yellow 151
100-41-4	ethylbenzene

· Proposition 65

· Chemicals known to cause cancer:		
100-41-4 ethylbenzene	*	1-2.49%

·Chemi	cals known to cause reproductive toxicity for females:	
1589-47-5	2-methoxypropanol	<0.1%
70657-70-4	2-methoxypropyl acetate	<0.1%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 15)



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

STAIN CONCENTRATE WENGHE Trade name:

(Contd. of page 14)

#### · Carcinogenic categories

· ·	genic cuiegories		
· EPA	(Environmental Protection Agency)		
67-64-1	acetone	1	10-12.49%
1330-20-7	xylene	1	5-9.99%
111-76-2	2-butoxyethanol	NL	5-9.99%
100-41-4	ethylbenzene	D	1-2.49%
· TLV	(Threshold Limit Value established by ACGIH)		
67-64-1	acetone		A4
1330-20-7	xylene		A4
111-76-2	2-butoxyethanol		A3
67-63-0	propan-2-ol		A4
100-41-4	ethylbenzene		A3
· NIO	SH-Ca (National Institute for Occupational Safety and Health)		
None of the	e ingredients is listed.		

#### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 07/18/2019 / 64
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2



Printing date 07/18/2019

Version number 65

Reviewed on 07/18/2019

**Product number PF5K18** 

STAIN CONCENTRATE WENGHE Trade name:

(Contd. of page 15)

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard — Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer \* \* Data compared to the previous version altered.