

1 Identification

- **Product identifier**
 - Product number TZ33
 - Trade name: **MEDIUM PU THINNER**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - **Information department:**
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - **Emergency telephone number:**
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3H336	May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· Label elements

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

 - **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
toluene
butanone
n-butyl acetate
acetone
- **Hazard statements**
H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Product number TZ33**Trade name: MEDIUM PU THINNER**

(Contd. of page 1)

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	4	Fire = 4
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients**Chemical characterization: Mixtures****Description:**

Mixture: consisting of the following components.

Solvent mixture

Dangerous components:

108-88-3	toluene	40-49.99%
	Flammable Liquids 2, H225 Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336 Aquatic Chronic 3, H412	
78-93-3	butanone	30-39.99%
	Flammable Liquids 2, H225 Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	
123-86-4	n-butyl acetate	12.5-15%
	Flammable Liquids 3, H226 Specific Target Organ Toxicity - Single Exposure 3, H336	

(Contd. on page 3)

Product number TZ33
Trade name: MEDIUM PU THINNER

		(Contd. of page 2)
67-64-1	acetone ⚠ Flammable Liquids 2, H225 ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	2.5-4.99%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

Alcohol resistant foam

Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 4)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 3)

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· PAC-1:		
108-88-3	toluene	67 ppm
78-93-3	butanone	200 ppm
123-86-4	n-butyl acetate	5 ppm
67-64-1	acetone	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
· PAC-2:		
108-88-3	toluene	560 ppm
78-93-3	butanone	2700* ppm
123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
· PAC-3:		
108-88-3	toluene	3700* ppm
78-93-3	butanone	4000* ppm
123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 5)

Product number TZ33**Trade name: MEDIUM PU THINNER**

(Contd. of page 4)

- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

78-93-3 butanone

PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

(Contd. on page 6)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 5)

67-64-1 acetone

PEL	Long-term value: 2400 mg/m , 1000 ppm
REL	Long-term value: 590 mg/m , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

· **Ingredients with biological limit values:****108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
-----	---

67-64-1 acetone

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

- Short term filter device:
Filter AX



Suitable respiratory protective device recommended.

(Contd. on page 7)

Product number TZ33**Trade name: MEDIUM PU THINNER**

(Contd. of page 6)

- **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Fluid

- **Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Mixture is non-polar/aprotic.

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

56 °C (132.8 °F)

- **Flash point:**

-17 °C (1.4 °F)

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

315 °C (599 °F)

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not selfigniting.

- **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

- **Lower:**

1.2 Vol %

- **Upper:**

13 Vol %

- **Vapor pressure at 20 °C (68 °F):**

233 hPa (174.8 mm Hg)

(Contd. on page 8)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 7)

· Density (+/- 0,03) at 20 °C (68 °F):	0.881 g/cm (7.352 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	95.00 % 836.9 g/l / 6.98 lb/gal
· Solids content:	0.0 %
· Other information (HAPS)	
108-88-3 toluene	40-49.99%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**
in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
78-93-3 butanone		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)

(Contd. on page 9)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 8)

Inhalative	LC50/4 h	21 mg/l (mouse)
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
67-64-1 acetone		
Oral	LD50	5,800 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (mouse)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

· **Primary irritant effect:**

· *on the skin:* Irritant to skin and mucous membranes.

· *on the eye:*

Irritating effect.

Causes serious eye irritation.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Oral and Inhalation.

May be fatal if swallowed and enters airways.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

May cause drowsiness or dizziness.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity** Harmful to aquatic life with long lasting effects.

· **Aquatic toxicity:**

108-88-3 toluene

EC50 134 mg/l (algae) (96 h)

3.78 mg/l (daphnia) (48 h)

LC50 (96h) 5.5 mg/l (Fish)

(Contd. on page 10)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 9)

78-93-3 butanone

EC50	2,029 mg/l (algae) (96 h)
	308 mg/l (daphnia) (48 h)
LC50 (96h)	2,993 mg/l (Fish)

123-86-4 n-butyl acetate

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

67-64-1 acetone

EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Substances Easily biodegradable**

108-88-3	toluene	.
78-93-3	butanone	.
123-86-4	n-butyl acetate	.
67-64-1	acetone	.
108-65-6	2-methoxy-1-methylethyl acetate	.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Hand over to hazardous waste disposers.
 Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.



US

(Contd. on page 11)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 10)

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA · Note 	UN1263 Check viscosity and flash point at section 9
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA 	Paint related material PAINT RELATED MATERIAL
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	 <ul style="list-style-type: none"> · Class · Label · Class · Label
<ul style="list-style-type: none"> · IMDG, IATA 	 <ul style="list-style-type: none"> · Class · Label
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	II
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Flammable liquids 33 F-E, S-E B
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT RELATED MATERIAL, 3, II

US

(Contd. on page 12)

Product number TZ33
Trade name: MEDIUM PU THINNER

(Contd. of page 11)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- *Various regulations*
- SARA

- *Section 355 (extremely hazardous substances):*

None of the ingredients is listed.

- *Section 313 (Specific toxic chemical listings) :*

108-88-3	toluene	40-49.99%
----------	---------	-----------

- *TSCA (Toxic Substances Control Act):*

All components have the value ACTIVE.

- *Hazardous Air Pollutants*

108-88-3	toluene
----------	---------

- *Proposition 65*

- *Chemicals known to cause cancer:*

None of the ingredients is listed.

- *Chemicals known to cause reproductive toxicity for females:*

70657-70-4	2-methoxypropyl acetate	<0.1%
------------	-------------------------	-------

- *Chemicals known to cause reproductive toxicity for males:*

None of the ingredients is listed.

- *Chemicals known to cause developmental toxicity:*

108-88-3	toluene	40-49.99%
----------	---------	-----------

- *Carcinogenic categories*

- *EPA (Environmental Protection Agency)*

108-88-3	toluene	II	40-49.99%
78-93-3	butanone	I	30-39.99%
67-64-1	acetone	I	5-9.99%

- *TLV (Threshold Limit Value)*

108-88-3	toluene	A4
67-64-1	acetone	A4

- *NIOSH-Ca (National Institute for Occupational Safety and Health)*

None of the ingredients is listed.

- *National regulations:*

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone

(Contd. on page 13)

Product number TZ33**Trade name: MEDIUM PU THINNER**

(Contd. of page 12)

- **Date of preparation / last revision** 09/14/2022 / 253

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids . Category 2

Flammable Liquids 3: Flammable liquids . Category 3

Skin Irritation 2: Skin corrosion/irritation . Category 2

Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A

Toxic to Reproduction 2: Reproductive toxicity . Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) . Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) . Category 2

Aspiration Hazard 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

- **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

- *** Data compared to the previous version altered.**