

1 Identification

- **Product identifier**
 - *Product number* WMM5A033
 - *Trade name:* **WB WHITE SELF-SEALER 30 SH**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals Srl
Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
- **Label elements**
 - *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - *Hazard pictograms*



GHS07

- *Signal word* Warning
- *Hazard-determining components of labeling:*
2-methyl-2H-isothiazol-3-one
- *Hazard statements*
H317 May cause an allergic skin reaction.
- *Precautionary statements*
 - P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 - P280 Wear protective gloves.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P321 Specific treatment (see on this label).
 - P363 Wash contaminated clothing before reuse.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
 - *NFPA ratings (scale 0 - 4)*



Health = 0
 Fire = 1
 Reactivity = 0

- *HMIS-ratings (scale 0 - 4)*



Health = 0
 Fire = 1
 Reactivity = 0

Product number WMM5A033
Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

 · *Description:* Mixture: consisting of the following components.

· Dangerous components:

111-76-2	2-butoxyethanol ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	1-2.49%
34590-94-8	(2-methoxymethylethoxy)propanol Flammable Liquids 4, H227	1-<5%
112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye Irritation 2A, H319	<0.5%
2682-20-4	2-methyl-2H-isothiazol-3-one ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318 ⚠ Sensitization - Skin 1, H317	≥0.0015-<0.01%

4 First-aid measures

· Description of first aid measures
· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:
· Most important symptoms and effects, both acute and delayed

Allergic reactions

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media
· Suitable extinguishing agents:

 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

 Nitrogen oxides (NO_x)

Carbon monoxide (CO)

(Contd. on page 3)

Product number WMM5A033**Trade name: WB WHITE SELF-SEALER 30 SH**

(Contd. of page 2)

- **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

- **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30 mg/m
111-76-2	2-butoxyethanol	60 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	13 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm

- **PAC-2:**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330 mg/m
111-76-2	2-butoxyethanol	120 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	140 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm

- **PAC-3:**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,000 mg/m
111-76-2	2-butoxyethanol	700 ppm
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
25265-77-4	2,2,4-Trimethyl-1,3-pentanediolmono(2-methylpropanoate)	840 mg/m
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

US

(Contd. on page 4)

Product number WMM5A033
Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 3)

7 Handling and storage

· **Handling:**

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

- **Requirements to be met by storerooms and receptacles:**
Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
In cases where there is no reported expiration date, it means that the product must be used within 8 months.
Take on temperature greater than 5 ° C
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m , 50 ppm Skin
REL	Long-term value: 24 mg/m , 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3

34590-94-8 (2-methoxymethylethoxy)propanol

PEL	Long-term value: 600 mg/m , 100 ppm Skin
REL	Short-term value: 900 mg/m , 150 ppm Long-term value: 600 mg/m , 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)

112-34-5 2-(2-butoxyethoxy)ethanol

TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
-----	---

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----	--

(Contd. on page 5)

Product number WMM5A033
Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 4)

· *Additional information:* The lists that were valid during the creation were used as basis.

· **Exposure controls**

· *Personal protective equipment:*

· *General protective and hygienic measures:*

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· *Breathing equipment:*

Not required.

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· *Protection of hands:*



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· *Penetration time of glove material*

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· *Eye protection:* Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· *General Information*

· *Appearance:*

· *Form:*

Fluid

· *Color:*

According to product specification

· *Odor:*

Characteristic

· *Odor threshold:*

Not determined.

· *pH-value:*

Mixture is non-polar/aprotic.

Range: 7 - 9

· *Change in condition*

· *Melting point/Melting range:*

Undetermined.

· *Boiling point/Boiling range:*

100 °C (212 °F)

· *Flash point:*

100 °C (212 °F)

· *Flammability (solid, gaseous):*

Not applicable.

(Contd. on page 6)

Product number WMM5A033
Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 5)

· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	0.6 Vol %
· Upper:	20.4 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1.249 g/cm (10.423 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	45 s (ISO 6 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	46.8 %
· VOC content:	4.72 %
	58.9 g/l / 0.49 lb/gal
· Solids content:	48.5 %
· Other information (HAPS)	
112-34-5 2-(2-butoxyethoxy)ethanol	<0.5%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Product number WMM5A033

Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 6)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	66,007 mg/kg
Dermal	LD50	60,506 mg/kg (rab)
Inhalative	LC50/4 h	605 mg/l (mouse)

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (mouse)

34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	5,135 mg/kg (mouse)
Dermal	LD50	19,020 mg/kg (rabbit)

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	6,600 mg/kg (mouse)
Dermal	LD50	2,764 mg/kg (rabbit)

2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (mouse)
Inhalative	LC50/4 h	0.53 mg/l (mouse)

· Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

Irritant

May cause an allergic skin reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· Carcinogenic categories

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Quartz

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
14808-60-7	Quartz (SiO ₂)	1

(Contd. on page 8)

Product number WMM5A033
Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 7)

 · *NTP (National Toxicology Program)*

14808-60-7	Quartz (SiO ₂)	<0.1%
------------	----------------------------	-------

 · *OSHA-Ca (Occupational Safety & Health Administration)*

None of the ingredients is listed.

12 Ecological information

· Toxicity

 · *Aquatic toxicity:*

111-76-2 2-butoxyethanol

EC50 101 mg/l (daphnia) (24 h)

LC50 (96h) 101 mg/l (Fish)

34590-94-8 (2-methoxymethylethoxy)propanol

EC50 970 mg/l (algae) (72 h)

1,919 mg/l (daphnia) (48 h)

LC50 (96h) 1,001 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50 1,001 mg/l (daphnia) (48 h)

 LC50 (96h) 1,300 mg/l (*Leuciscus idus melanotus*)

 · **Persistence and degradability** No further relevant information available.

 · *Substances Easily biodegradable*

111-76-2 2-butoxyethanol .

34590-94-8 (2-methoxymethylethoxy)propanol .

 · **Behavior in environmental systems:**

 · *Bioaccumulative potential* No further relevant information available.

 · *Mobility in soil* No further relevant information available.

 · **Additional ecological information:**

 · *General notes:*

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

 · **Other adverse effects** No further relevant information available.

13 Disposal considerations

 · **Waste treatment methods**

 · *Recommendation:*

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

 · **Uncleaned packagings:**

 · *Recommendation:* Disposal must be made according to official regulations.

 · *Recommended cleansing agent:* Water, if necessary with cleansing agents.

US

(Contd. on page 9)

Product number WMM5A033

Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 8)

14 Transport information

· UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
· UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
· Packing group	
· DOT, IMDG, IATA	Not applicable
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Not applicable

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

- Various regulations
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

111-76-2	2-butoxyethanol	1-2.49%
112-34-5	2-(2-butoxyethoxy)ethanol	<0.5%
1336-21-6	ammonia	<0.01%

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

- **Chemicals known to cause cancer:**
- Titanium dioxide only in bound form
- Quartz (SiO₂) only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	20-24.99%
14808-60-7	Quartz (SiO ₂)	*	<0.1%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 10)

Product number WMM5A033**Trade name: WB WHITE SELF-SEALER 30 SH**

(Contd. of page 9)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL	1-2.49%
----------	-----------------	----	---------

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
111-76-2	2-butoxyethanol	A3
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	20-24.99%
14808-60-7	Quartz (SiO ₂)	<0.1%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl
- **Contact:** See emergency phone
- **Date of preparation / last revision** 09/14/2022 / 17

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 4: Flammable liquids . Category 4
 Acute Toxicity - Oral 3: Acute toxicity . Category 3
 Acute Toxicity - Oral 4: Acute toxicity . Category 4
 Skin Corrosion 1B: Skin corrosion/irritation . Category 1B
 Skin Irritation 2: Skin corrosion/irritation . Category 2
 Eye Damage 1: Serious eye damage/eye irritation . Category 1
 Eye Irritation 2A: Serious eye damage/eye irritation . Category 2A
 Sensitization - Skin 1: Skin sensitisation . Category 1

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

(Contd. on page 11)



Safety Data Sheet
acc. to OSHA HCS

Printing date 09/14/2022

Version number 18

Reviewed on 09/14/2022

Product number WMM5A033

Trade name: WB WHITE SELF-SEALER 30 SH

(Contd. of page 10)

Agency ECHA web site
INRS Fiche Toxicologique
IARC International agency for research on cancer
· * *Data compared to the previous version altered.*

US