

Printing date 08/15/2022

Version number 16

Reviewed on 08/15/2022

#### 1 Identification

- · Product identifier
  - · Product number PT410
  - · Trade name: WB SEALER WHITE
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals Srl

Viale della Stazione 3 -27020 Parona (PV)Italy -Tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
  - · GHS label elements Not applicable
    - · Hazard pictograms Not applicable
    - · Signal word Not applicable
    - · Hazard statements Not applicable
- · Classification system:
  - · NFPA ratings (scale 0 4)



Health = 0

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0

Fire = 1

Reactivity = 0

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

111-76-2	2-butoxyethanol	2.5-4.99%
	Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Eye Irritation 2A, H319 Flammable Liquids 4, H227	
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
	💠 Eye Irritation 2A, H319	
57-55-6	propane-1,2-diol	0.5-1%

US



Printing date 08/15/2022 Version number 16 Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

		(Contd. of page 1)
34590-94-8	(2-methoxymethylethoxy)propanol	<1%
	Flammable Liquids 4, H227	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)	≥0.00025-<0.0015%
	<ul> <li>Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 2, H310; Acute Toxicity - Inhalation 2, H330</li> <li>Skin Corrosion 1B, H314; Eye Damage 1, H318</li> <li>Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)</li> <li>Sensitization - Skin 1A, H317</li> </ul>	

### 4 First-aid measures

- · Description of first aid measures
  - · General information:

No special measures required.

personal protective equipment for first aid responders is recommended. (please see section 8)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
  - Most important symptoms and effects, both acute and delayed
    For symptoms and effects caused by substances, refer to Section 11.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
  - · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Printing date 08/15/2022 Version number 16

Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 2)

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

· PAC-1:			
471-34-1 calcium carbonate		4	15 mg/m³
13463-67-7 Titanium dioxide C.I. 77891 Pigment white 6		(	30 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	$\epsilon$	60 ppm
112-34-5	2-(2-butoxyethoxy)ethanol		30 ppm
57-55-6	propane-1,2-diol	(	30 mg/m <sup>3</sup>
34590-94-8	(2-methoxymethylethoxy)propanol		150 ppm
· PAC-2:			
471-34-1	calcium carbonate	210	mg/m³
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	330	mg/m³
111-76-2	2-butoxyethanol	120	ррт
112-34-5	2-(2-butoxyethoxy)ethanol	33 µ	ррт
57-55-6	propane-1,2-diol	1,30	00 mg/m
34590-94-8	8 (2-methoxymethylethoxy)propanol 1		0* ppm
· PAC-3:		•	
471-34-1	calcium carbonate	1,30	00 mg/m <sup>2</sup>
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2,00	00 mg/m
111-76-2	2-butoxyethanol	700	ррт
112-34-5	2-(2-butoxyethoxy)ethanol	200	ррт
57-55-6	propane-1,2-diol	7,90	00 mg/m <sup>2</sup>
34590-94-8	(2-methoxymethylethoxy)propanol	990	0** ppm

## 7 Handling and storage

#### · Handling:

- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.

#### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.



Printing date 08/15/2022 Version number 16 Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 3)

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

111-76	6-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3
112-34	-5 2-(2-butoxyethoxy)ethanol
TLV	Long-term value: 10* ppm *Inhalable fraction and vapor
57-55-	6 propane-1,2-diol
WEEL	Long-term value: 10 mg/m³
34590-	94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)

## · Ingredients with biological limit values:

#### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
  - $\cdot \ General \ protective \ and \ hygienic \ measures:$

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Printing date 08/15/2022 Version number 16 Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

nformation on basic physical and o	chemical properties
· General Information	
$\cdot$ Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
	Range: 7 - 9
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	100 °C (212 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	225 °C (437 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	0.9 Vol %
· Upper:	30 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (0.9 mm Hg)
· Density (+/- 0,03) at 20 °C (68 °F):	1.371 g/cm³ (11.441 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water	e): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	37.8 %
· VOC content:	5.65 %
	77.4 g/l / 0.65 lb/gal



Printing date 08/15/2022 Version number 16 Reviewed on 08/15/2022

**Product number PT410** 

Trade name: **WB SEALER WHITE** 

(Contd. of page 5)

· Other inf	· Other information (HAPS)		
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%	
121-44-8	triethylamine	<0.1%	
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%	
· Other i	· Other information No further relevant information available.		

# 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
- · Chemical stability The product is stable in normal conditions of storage and use recommended
  - · Thermal decomposition / conditions to be avoided:
    - No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Acids, alkalis and oxidizing agents
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects

· Acute to	· Acute toxicity:		
· <i>LD</i> /	· LD/LC50 values that are relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	36,210 mg/kg (ATE)	
Dermal	LD50	33,193 mg/kg	
Inhalative	LC50/4 h	332 mg/l (mouse)	
111-76-2	2-butoxye	thanol	
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (mouse)	
Dermal	LD50	1,100 mg/kg (rab)	
Inhalative	LC50/4 h	11 mg/l (mouse)	
112-34-5	2-(2-butox	yethoxy)ethanol	
Oral	LD50	6,600 mg/kg (mouse)	
Dermal	LD50	2,764 mg/kg (rabbit)	
57-55-6 p	ropane-1,2	2-diol	
Oral	LD50	20,000 mg/kg (mouse)	
Dermal	LD50	2,001 mg/kg (mouse)	
34590-94-	34590-94-8 (2-methoxymethylethoxy)propanol		
Oral	LD50	5,135 mg/kg (mouse)	
Dermal	LD50	19,020 mg/kg (rabbit)	
	•		

- · Primary irritant effect:
  - · on the skin: No irritant effect.
  - on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 7)



Printing date 08/15/2022 Version number 16 Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 6)

#### · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### · Carcinogenic categories

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)				
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - L	DUST	
14808-60-7	Quartz (SiO2)	1		
· NTP (National Toxicology Program)				
14808-60-7	Quartz (SiO2)	<	:0.1%	
· OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

## 12 Ecological information

### · Toxicity

· Aquatic toxicity:		
	butoxyethanol	
EC50	101 mg/l (daphnia) (24 h)	
LC50 (96h)	101 mg/l (Fish)	
112-34-5 2-	(2-butoxyethoxy)ethanol	
EC50	1,001 mg/l (daphnia) (48 h)	
LC50 (96h)	1,300 mg/l (Leuciscus idus melanotus)	
57-55-6 pro	pane-1,2-diol	
EC50	19,000 mg/l (algae) (48 h)	
	18,340 mg/l (daphnia) (48 h)	
LC50 (96h)	40,613 mg/l (Fish)	
34590-94-8 (2-methoxymethylethoxy)propanol		
EC50	970 mg/l (algae) (72 h)	
	1,919 mg/l (daphnia) (48 h)	
LC50 (96h)	1,001 mg/l (Fish)	
55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2- methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)		
EC50	0.027 mg/l (algae) (72 h)	
	(Contd. on page 8)	



Printing date 08/15/2022 Version number 16 Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 7)

0.16 mg/l (daphnia) (48 h)

LC50 (96h) 0.19 mg/l (Fish)

Persistence and degradability No further relevant information available.

	· Substances Easily biodegradable		
111-76-2	2-butoxyethanol		
112-34-5	2-(2-butoxyethoxy)ethanol		
57-55-6	propane-1,2-diol		

#### · Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

#### · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
· DOT, ADN, IMDG, IATA	Not applicable
· Note	Check viscosity and flash point at section 9
UN proper shipping name	
· DOT, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not applicable
Packing group	
· DOT, IMDG, IATA	Not applicable
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)



Printing date 08/15/2022

Version number 16

Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 8)

· UN "Model Regulation":

Not applicable

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
  - · Various regulations
    - SARA

· SAI	(A	
-	Section 355 (extremely hazardous substances):	
None of t	he ingredients is listed.	
•	Section 313 (Specific toxic chemical listings) :	
111-76-2	2-butoxyethanol	2.5-4.99%
112-34-5	2-(2-butoxyethoxy)ethanol	1-2.49%
121-44-8	triethylamine	<0.1%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	<0.1%
· TSO	CA (Toxic Substances Control Act):	
All compo	nents have the value ACTIVE.	
•	Hazardous Air Pollutants	
121-44-8	triethylamine	

· Proposition 65

· Chemicals known to cause cancer:

Titanium dioxide only in bound form Quartz (SiO2) only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	10-12.49%
14808-60-7	Quartz (SiO2)	*	<0.1%

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· Carcu	iogenic categories			
·EF	PA (Environmental Protection Agency)			
111-76-2 2-butoxyethanol		NL	L 2.5-4.99%	
· TL	V (Threshold Limit Value)			
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	F		
111-76-2	2-butoxyethanol			A3
14807-96-6	Talc (Mg3H2(SiO3)4)			A4
121-44-8	triethylamine			A4
14808-60-7	Quartz (SiO2)			A2
· NI	OSH-Ca (National Institute for Occupational Safety and Health)			
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		10-12.49%	
14808-60-7	Quartz (SiO2)		<0.1%	
		(Con	ntd. on pa	ge 10)



Printing date 08/15/2022

Version number 16

Reviewed on 08/15/2022

**Product number PT410** 

Trade name: WB SEALER WHITE

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - · Date of preparation / last revision 08/15/2022 / 15
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 2: Acute toxicity - Category 2

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Irrititation 2: Skin corrosion/irritation – Category 2
Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

·Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* Data compared to the previous version altered.